

CompTIA

Exam Questions N10-009

CompTIA Network+ Exam



NEW QUESTION 1

- (Exam Topic 1)

A network technician is installing new software on a Windows-based server in a different geographical location. Which of the following would be BEST for the technician to use to perform this task?

- A. RDP
- B. SSH
- C. FTP
- D. DNS

Answer: A

Explanation:

RDP (Remote Desktop Protocol) is the best option for a network technician to use when installing new software on a Windows-based server in a different geographical location. This protocol allows the technician to connect to the server remotely and control it as if they were physically present.

References:

> Network+ N10-007 Certification Exam Objectives, Objective 2.2: Given a scenario, implement the appropriate network-based security and troubleshoot common connectivity issues.

NEW QUESTION 2

- (Exam Topic 1)

Which of the following TCP ports is used by the Windows OS for file sharing?

- A. 53
- B. 389
- C. 445
- D. 1433

Answer: C

Explanation:

TCP port 445 is used by the Windows OS for file sharing. It is also known as SMB (Server Message Block) or CIFS (Common Internet File System) and allows users to access files, printers, and other shared resources on a network. References:

<https://docs.microsoft.com/en-us/windows-server/storage/file-server/troubleshoot/detect-enable-and-disable-smb>

NEW QUESTION 3

- (Exam Topic 1)

An administrator is writing a script to periodically log the IPv6 and MAC addresses of all the devices on a network segment. Which of the following switch features will MOST likely be used to assist with this task?

- A. Spanning Tree Protocol
- B. Neighbor Discovery Protocol
- C. Link Aggregation Control Protocol
- D. Address Resolution Protocol

Answer: B

Explanation:

Short explanation

The switch feature that is most likely to be used to assist with logging IPv6 and MAC addresses of devices on a network segment is Neighbor Discovery Protocol (NDP). NDP is used by IPv6 to discover and maintain information about other nodes on the network, including their IPv6 and MAC addresses. By periodically querying NDP, the administrator can log this information for auditing purposes.

References:

> CompTIA Network+ Certification Study Guide, Exam N10-007, Fourth Edition, Chapter 2: The OSI Model and Networking Protocols, Objective 2.1: Compare and contrast TCP and UDP ports, protocols, and their purposes.

NEW QUESTION 4

- (Exam Topic 1)

Which of the following devices would be used to manage a corporate WLAN?

- A. A wireless NAS
- B. A wireless bridge
- C. A wireless router
- D. A wireless controller

Answer: D

Explanation:

A wireless controller is used to manage a corporate WLAN, providing centralized management and configuration of access points. References: CompTIA Network+ Certification Study Guide, Chapter 8: Wireless Networks.

NEW QUESTION 5

- (Exam Topic 1)

A technician is installing a high-density wireless network and wants to use an available frequency that supports the maximum number of channels to reduce interference. Which of the following standard 802.11 frequency ranges should the technician look for while reviewing WAP specifications?

- A. 2.4GHz
- B. 5GHz
- C. 6GHz
- D. 900MHz

Answer: B

Explanation:

* 802.11 a/b/g/n/ac wireless networks operate in two frequency ranges: 2.4 GHz and 5 GHz. The 5 GHz frequency range supports more channels than the 2.4 GHz frequency range, making it a better choice for high-density wireless networks.

References: CompTIA Network+ Certification Study Guide, Sixth Edition by Glen E. Clarke

NEW QUESTION 6

- (Exam Topic 1)

Wireless users are reporting intermittent internet connectivity. Connectivity is restored when the users disconnect and reconnect, utilizing the web authentication process each time. The network administrator can see the devices connected to the APs at all times. Which of the following steps will MOST likely determine the cause of the issue?

- A. Verify the session time-out configuration on the captive portal settings
- B. Check for encryption protocol mismatch on the client's wireless settings
- C. Confirm that a valid passphrase is being used during the web authentication
- D. Investigate for a client's disassociation caused by an evil twin AP

Answer: A

Explanation:

A captive portal is a web page that requires users to authenticate before they can access the internet. If the session time-out configuration is too short, users may experience intermittent internet connectivity and have to reconnect using the web authentication process each time. The network administrator can verify the session time-out configuration on the captive portal settings and adjust it if needed. References: CompTIA Network+ Certification Exam Objectives Version 2.0 (Exam Number: N10-006), Domain 1.0 Network Architecture, Objective 1.8 Explain the purposes and use cases for advanced networking devices.

NEW QUESTION 7

- (Exam Topic 1)

An attacker is attempting to find the password to a network by inputting common words and phrases in plaintext to the password prompt. Which of the following attack types BEST describes this action?

- A. Pass-the-hash attack
- B. Rainbow table attack
- C. Brute-force attack
- D. Dictionary attack

Answer: D

Explanation:

The attacker attempting to find the password to a network by inputting common words and phrases in plaintext to the password prompt is using a dictionary attack. References: CompTIA Network+ Certification Study Guide, Chapter 6: Network Attacks and Mitigation.

NEW QUESTION 8

- (Exam Topic 1)

Which of the following DNS records works as an alias to another record?

- A. AAAA
- B. CNAME
- C. MX
- D. SOA

Answer: B

Explanation:

The DNS record that works as an alias to another record is called CNAME (Canonical Name). CNAME records are used to create an alias for a domain name that points to another domain name.

References:

➤ CompTIA Network+ Certification Study Guide, Exam N10-007, Fourth Edition, Chapter 2: The OSI Model and Networking Protocols, Objective 2.3: Given a scenario, implement and configure the appropriate addressing schema.

NEW QUESTION 9

- (Exam Topic 1)

A network administrator discovers that users in an adjacent building are connecting to the company's guest wireless network to download inappropriate material. Which of the following can the administrator do to MOST easily mitigate this issue?

- A. Reduce the wireless power levels
- B. Adjust the wireless channels
- C. Enable wireless client isolation
- D. Enable wireless port security

Answer: A

Explanation:

Reducing the wireless power levels can limit the range of the guest wireless network and prevent users in an adjacent building from connecting to it. Adjusting the wireless channels or enabling wireless client isolation will not affect the signal strength or coverage of the guest network. Enabling wireless port security will not work on a guest network that does not use authentication or MAC address filtering. References: CompTIA Network+ Certification Exam Objectives Version 2.0 (Exam Number: N10-006), Domain 2.0 Network Operations, Objective 2.5 Given a scenario, implement appropriate wireless configuration settings; Guest WiFi Security - Cisco Umbrella

NEW QUESTION 10

- (Exam Topic 1)

Access to a datacenter should be individually recorded by a card reader even when multiple employees enter the facility at the same time. Which of the following allows the enforcement of this policy?

- A. Motion detection
- B. Access control vestibules
- C. Smart lockers
- D. Cameras

Answer: B

Explanation:

The most effective security mechanism against physical intrusions due to stolen credentials would likely be a combination of several of these options. However, of the options provided, the most effective security mechanism would probably be an access control vestibule. An access control vestibule is a secure area that is located between the outer perimeter of a facility and the inner secure area. It is designed to provide an additional layer of security by requiring that individuals pass through a series of security checks before being allowed access to the secure area. This could include biometric authentication, access card readers, and motion detection cameras.

Access control vestibules allow the enforcement of the policy that access to a datacenter should be individually recorded by a card reader even when multiple employees enter the facility at the same time. An access control vestibule is a physical security device that consists of two doors with an interlocking mechanism. Only one door can be opened at a time, and only one person can pass through each door. This prevents tailgating or piggybacking, where unauthorized persons follow authorized persons into a secure area. An access control vestibule can also be integrated with a card reader or other authentication system to record each individual's access. References: <https://www.boonedam.us/blog/what-are-access-control-vestibules>

NEW QUESTION 10

- (Exam Topic 1)

Given the following information:

Protocol	Local address	Foreign address	State
TCP	127.0.0.1:57779	Desktop-Open:57780	Established
TCP	127.0.0.1:57780	Desktop-Open:57779	Established

Which of the following command-line tools would generate this output?

- A. netstat
- B. arp
- C. dig
- D. tracert

Answer: D

Explanation:

Tracert is a command-line tool that traces the route of a packet from a source to a destination and displays the number of hops and the round-trip time for each hop. The output shown in the question is an example of a tracert output, which shows five hops with their IP addresses and hostnames (if available) and three latency measurements for each hop in milliseconds. References:

[https://partners.comptia.org/docs/default-source/resources/comptia-network-n10-008-exam-objectives-\(2-0\)](https://partners.comptia.org/docs/default-source/resources/comptia-network-n10-008-exam-objectives-(2-0)), <https://www.lumen.com/help/en-us/network/traceroute/understanding-the-traceroute-output.html>

NEW QUESTION 12

- (Exam Topic 1)

A store owner would like to have secure wireless access available for both business equipment and patron use. Which of the following features should be configured to allow different wireless access through the same equipment?

- A. MIMO
- B. TKIP
- C. LTE
- D. SSID

Answer: D

Explanation:

SSID (Service Set Identifier) is a feature that should be configured to allow different wireless access through the same equipment. SSID is the name of a wireless network that identifies it from other networks in the same area. A wireless access point (AP) can support multiple SSIDs with different security settings and network policies. For example, a store owner can create one SSID for business equipment and another SSID for patron use, and assign different passwords, VLANs, and QoS levels for each SSID. References: <https://www.cisco.com/c/en/us/support/docs/wireless-mobility/wireless-lan-wlan/70931-multiple-ssid.html>

NEW QUESTION 13

- (Exam Topic 1)

A network administrator is configuring a load balancer for two systems. Which of the following must the administrator configure to ensure connectivity during a failover?

- A. VIP
- B. NAT
- C. APIPA
- D. IPv6 tunneling
- E. Broadcast IP

Answer: A

Explanation:

A virtual IP (VIP) address must be configured to ensure connectivity during a failover. A VIP address is a single IP address that is assigned to a group of servers or network devices. When one device fails, traffic is automatically rerouted to the remaining devices, and the VIP address is reassigned to the backup device, allowing clients to continue to access the service without interruption.

References:

➤ CompTIA Network+ Certification Study Guide, Exam N10-007, Fourth Edition, Chapter 6: Network Servers, p. 300

NEW QUESTION 14

- (Exam Topic 1)

Which of the following types of devices can provide content filtering and threat protection, and manage multiple IPSec site-to-site connections?

- A. Layer 3 switch
- B. VPN headend
- C. Next-generation firewall
- D. Proxy server
- E. Intrusion prevention

Answer: C

Explanation:

Next-generation firewalls can provide content filtering and threat protection, and can manage multiple IPSec site-to-site connections. References: CompTIA Network+ Certification Study Guide, Chapter 5: Network Security.

NEW QUESTION 15

- (Exam Topic 1)

A user tries to ping 192.168.1.100 from the command prompt on the 192.168.2.101 network but gets the following response: U.U.U.U. Which of the following needs to be configured for these networks to reach each other?

- A. Network address translation
- B. Default gateway
- C. Loopback
- D. Routing protocol

Answer: B

Explanation:

A default gateway is a device that routes traffic from one network to another network, such as the Internet. A default gateway is usually configured on each host device to specify the IP address of the router that connects the host's network to other networks. In this case, the user's device and the destination device are on different networks (192.168.1.0/24 and 192.168.2.0/24), so the user needs to configure a default gateway on their device to reach the destination device.

References:

[https://partners.comptia.org/docs/default-source/resources/comptia-network-n10-008-exam-objectives-\(2-0\)](https://partners.comptia.org/docs/default-source/resources/comptia-network-n10-008-exam-objectives-(2-0)), <https://www.techopedia.com/definition/25761/default-gateway>

NEW QUESTION 19

- (Exam Topic 1)

Which of the following can be used to centrally manage credentials for various types of administrative privileges on configured network devices?

- A. SSO
- B. TACACS+
- C. Zero Trust
- D. Separation of duties
- E. Multifactor authentication

Answer: B

Explanation:

TACACS+ (Terminal Access Controller Access Control System Plus) can be used to centrally manage credentials for various types of administrative privileges on configured network devices. This protocol separates authentication, authorization, and accounting (AAA) functions, providing more granular control over access to network resources.

References:

➤ Network+ N10-007 Certification Exam Objectives, Objective 4.2: Given a scenario, implement secure network administration principles.

NEW QUESTION 21

- (Exam Topic 1)

After the A record of a public website was updated, some visitors were unable to access the website. Which of the following should be adjusted to address the issue?

- A. TTL
- B. MX
- C. TXT

D. SOA

Answer: A

Explanation:

TTL (Time To Live) should be adjusted to address the issue of some visitors being unable to access the website after the A record was updated. TTL is a value that specifies how long a DNS record should be cached by DNS servers and clients before it expires and needs to be refreshed. If the TTL is too high, some DNS servers and clients may still use the old A record that points to the previous IP address of the website, resulting in connection failures. By lowering the TTL, the DNS servers and clients will update their cache more frequently and use the new A record that points to the current IP address of the website. References: <https://www.cloudflare.com/learning/dns/dns-records/dns-ttl/>

NEW QUESTION 23

- (Exam Topic 1)

A new cabling certification is being requested every time a network technician rebuilds one end of a Cat 6 (vendor-certified) cable to create a crossover connection that is used to connect switches. Which of the following would address this issue by allowing the use of the original cable?

- A. CSMA/CD
- B. LACP
- C. PoE+
- D. MDIX

Answer: D

Explanation:

MDIX (medium-dependent interface crossover) is a feature that allows network devices to automatically detect and configure the appropriate cabling type, eliminating the need for crossover cables. By enabling MDIX on the switches, a technician can use the original Cat 6 cable to create a crossover connection. References: CompTIA Network+ Certification Study Guide, Sixth Edition by Glen E. Clarke

NEW QUESTION 25

- (Exam Topic 1)

According to troubleshooting methodology, which of the following should the technician do NEXT after determining the most likely probable cause of an issue?

- A. Establish a plan of action to resolve the issue and identify potential effects
- B. Verify full system functionality and, if applicable, implement preventive measures
- C. Implement the solution or escalate as necessary
- D. Test the theory to determine the cause

Answer: A

Explanation:

According to troubleshooting methodology, after determining the most likely probable cause of an issue, the next step is to establish a plan of action to resolve the issue and identify potential effects. This step involves defining the steps needed to implement a solution, considering the possible consequences of each step, and obtaining approval from relevant stakeholders if necessary. References: [https://partners.comptia.org/docs/default-source/resources/comptia-network-n10-008-exam-objectives-\(2-0\)](https://partners.comptia.org/docs/default-source/resources/comptia-network-n10-008-exam-objectives-(2-0)), <https://www.comptia.org/blog/the-comptia-guide-to-it-troubleshooting>

NEW QUESTION 30

- (Exam Topic 1)

A network engineer is investigating reports of poor network performance. Upon reviewing a device configuration, the engineer finds that duplex settings are mismatched on both ends. Which of the following would be the MOST likely result of this finding?

- A. Increased CRC errors
- B. Increased giants and runts
- C. Increased switching loops
- D. Increased device temperature

Answer: A

Explanation:

Mismatched duplex settings can cause an increase in CRC errors, which are errors in data transmission that can result in corrupted data. References: CompTIA Network+ Certification Study Guide, Chapter 4: Infrastructure.

NEW QUESTION 32

- (Exam Topic 1)

A technician is deploying a new switch model and would like to add it to the existing network monitoring software. The technician wants to know what metrics can be gathered from a given switch. Which of the following should the technician utilize for the switch?

- A. MIB
- B. Trap
- C. Syslog
- D. Audit log

Answer: A

Explanation:

To determine what metrics can be gathered from a given switch, a technician should utilize the Management Information Base (MIB). The MIB is a database of network management information that is used to manage and monitor network devices. It contains information about device configuration, status, and performance. References: Network+ Certification Study Guide, Chapter 5: Network Security

NEW QUESTION 33

- (Exam Topic 1)

Which of the following ports is commonly used by VoIP phones?

- A. 20
- B. 143
- C. 445
- D. 5060

Answer: D

Explanation:

TCP/UDP port 5060 is commonly used by VoIP phones. It is the default port for SIP (Session Initiation Protocol), which is a signaling protocol that establishes, modifies, and terminates multimedia sessions over IP networks. SIP is widely used for VoIP applications such as voice and video calls. References: <https://www.voip-info.org/session-initiation-protocol/>

NEW QUESTION 38

- (Exam Topic 1)

A network administrator is designing a new datacenter in a different region that will need to communicate to the old datacenter with a secure connection. Which of the following access methods would provide the BEST security for this new datacenter?

- A. Virtual network computing
- B. Secure Socket Shell
- C. In-band connection
- D. Site-to-site VPN

Answer: D

Explanation:

Site-to-site VPN provides the best security for connecting a new datacenter to an old one because it creates a secure tunnel between the two locations, protecting data in transit. References: CompTIA Network+ Certification Study Guide, Chapter 5: Network Security.

NEW QUESTION 42

- (Exam Topic 1)

A technician needs to configure a Linux computer for network monitoring. The technician has the following information:

Linux computer details:

Interface	IP address	MAC address
eth0	10.1.2.24	A1:B2:C3:F4:E5:D6

Switch mirror port details:

Interface	IP address	MAC address
eth1	10.1.2.3	A1:B2:C3:D4:E5:F6

After connecting the Linux computer to the mirror port on the switch, which of the following commands should the technician run on the Linux computer?

- A. `ifconfig eth0 promisc`
- B. `ifconfig eth1 up`
- C. `ifconfig eth0 10.1.2.3`
- D. `ifconfig eth1 hw ether A1:B2:C3:D4:E5:F6`

Answer: A

Explanation:

The `ifconfig eth0 promisc` command should be run on the Linux computer to enable promiscuous mode, which allows the computer to capture all network traffic passing through the switch mirror port. References: CompTIA Network+ Certification Study Guide, Chapter 7: Network Devices.

NEW QUESTION 43

- (Exam Topic 1)

A network device is configured to send critical events to a syslog server; however, the following alerts are not being received:

Severity 5 LINK-UPDOWN: Interface 1/1, changed state to down Severity 5 LINK-UPDOWN: Interface 1/3, changed state to down

Which of the following describes the reason why the events are not being received?

- A. The network device is not configured to log that level to the syslog server
- B. The network device was down and could not send the event
- C. The syslog server is not compatible with the network device
- D. The syslog server did not have the correct MIB loaded to receive the message

Answer: A

Explanation:

The reason why the alerts are not being received is that the network device is not configured to log that level to the syslog server. The severity level for the events may need to be adjusted in order for them to be sent to the syslog server. References: Network+ Certification Study Guide, Chapter 8: Network Troubleshooting

NEW QUESTION 46

- (Exam Topic 1)

The network administrator is informed that a user's email password is frequently hacked by brute-force programs. Which of the following policies should the

network administrator implements to BEST mitigate this issue? (Choose two.)

- A. Captive portal
- B. Two-factor authentication
- C. Complex passwords
- D. Geofencing
- E. Role-based access
- F. Explicit deny

Answer: BC

Explanation:

Two-factor authentication (2FA) is a method of verifying a user's identity by requiring two pieces of evidence, such as something the user knows (e.g., a password) and something the user has (e.g., a token or a smartphone). 2FA adds an extra layer of security that makes it harder for hackers to access a user's account by brute-force programs. Complex passwords are passwords that are long, random, and use a combination of uppercase and lowercase letters, numbers, and symbols. Complex passwords are more resistant to brute-force attacks than simple or common passwords. References: [https://partners.comptia.org/docs/default-source/resources/comptia-network-n10-008-exam-objectives-\(2-0\)](https://partners.comptia.org/docs/default-source/resources/comptia-network-n10-008-exam-objectives-(2-0)), <https://www.csoonline.com/article/3225913/what-is-two-factor-authentication-2fa-how-to-enable-it-and-why-yo> <https://www.howtogeek.com/195430/how-to-create-a-strong-password-and-remember-it/>

NEW QUESTION 50

- (Exam Topic 1)

A company hired a technician to find all the devices connected within a network. Which of the following software tools would BEST assist the technician in completing this task?

- A. IP scanner
- B. Terminal emulator
- C. NetFlow analyzer
- D. Port scanner

Answer: A

Explanation:

To find all devices connected within a network, a technician can use an IP scanner. An IP scanner sends a ping request to all IP addresses within a specified range and then identifies the active devices that respond to the request.

NEW QUESTION 54

- (Exam Topic 1)

SIMULATION


You have been tasked with setting up a wireless network in an office. The network will consist of 3 Access Points and a single switch. The network must meet the following parameters:

The SSIDs need to be configured as CorpNet with a key of S3cr3t! The wireless signals should not interfere with each other

The subnet the Access Points and switch are on should only support 30 devices maximum The Access Points should be configured to only support TKIP clients at a maximum speed INSTRUCTIONS

Click on the wireless devices and review their information and adjust the settings of the access points to meet the given requirements.

If at any time you would like to bring back the initial state of the simulation, please click the Reset All button.



AP1 Configuration

https://ap1.setup.do

Basic Configuration

Access Point Name: AP1

IP Address: /

Gateway: 192.168.1.1

SSID:

SSID Broadcast: Yes No

Wireless

Mode:
 B
 G

Channel:

Wired

Speed: Auto 100 1000

Duplex: Auto Half Full

Security Configuration

Security Settings: None WEP WPA WPA2 WPA2 - Enterprise

Key or Passphrase:

Reset to Default Save Close

AP2 Configuration

https://ap2.setup.do

Basic Configuration

Access Point Name: AP2

IP Address: /

Gateway: 192.168.1.1

SSID:

SSID Broadcast: Yes No

Wireless

Mode:
 B
 G

Channel:
 1
 2
 3
 4
 5
 6
 7
 8
 9
 10
 11

Wired

Speed: Auto 100 1000


Duplex: Auto Half Full

Security Configuration

Security Settings: None WEP WPA WPA2 WPA2 - Enterprise

Key or Passphrase:

Reset to Default Save Close




- A. Mastered
- B. Not Mastered


Answer: A

Explanation:


On the first exhibit, the layout should be as follows




Graphical user interface, text, application, chat or text message Description automatically generated



Graphical user interface Description automatically generated



Graphical user interface, text, application, chat or text message Description automatically generated



Graphical user interface Description automatically generated






Exhibit 2 as follows Access Point Name AP2
Graphical user interface Description automatically generated



Graphical user interface, text, application, chat or text message Description automatically generated



Graphical user interface Description automatically generated







Exhibit 3 as follows Access Point Name AP3
Graphical user interface Description automatically generated



Graphical user interface, text, application, chat or text message Description automatically generated



Graphical user interface Description automatically generated



NEW QUESTION 59

- (Exam Topic 1)

Which of the following routing protocols is used to exchange route information between public autonomous systems?

- A. OSPF
- B. BGP
- C. EGRIP
- D. RIP

Answer: B

Explanation:

BGP (Border Gateway Protocol) is a routing protocol used to exchange route information between public autonomous systems (AS). OSPF (Open Shortest Path First), EGRIP (Enhanced Interior Gateway Routing Protocol), and RIP (Routing Information Protocol) are all used for internal routing within a single AS. Therefore, BGP is the correct option to choose for this question.

References:

- > Network+ N10-007 Certification Exam Objectives, Objective 3.3: Given a scenario, configure and apply the appropriate routing protocol.
- > Cisco: Border Gateway Protocol (BGP) Overview

NEW QUESTION 61

- (Exam Topic 1)

Which of the following factors should be considered when evaluating a firewall to protect a datacenter's east-west traffic?

- A. Replication traffic between an on-premises server and a remote backup facility
- B. Traffic between VMs running on different hosts
- C. Concurrent connections generated by Internet DDoS attacks
- D. VPN traffic from remote offices to the datacenter's VMs

Answer: B

Explanation:

When evaluating a firewall to protect a datacenter's east-west traffic, it is important to consider traffic between VMs running on different hosts. This type of traffic is referred to as east-west traffic and is often protected by internal firewalls. By implementing firewalls, an organization can protect their internal network against threats such as lateral movement, which can be caused by attackers who have breached a perimeter firewall. References: Network+ Certification Study Guide, Chapter 5: Network Security

NEW QUESTION 63

- (Exam Topic 1)

A technician is assisting a user who cannot connect to a network resource. The technician first checks for a link light. According to troubleshooting methodology, this is an example of:

- A. using a bottom-to-top approach.
- B. establishing a plan of action.
- C. documenting a finding.
- D. questioning the obvious.

Answer: A

Explanation:

Using a bottom-to-top approach means starting from the physical layer and moving up the OSI model to troubleshoot a network problem. Checking for a link light is a physical layer check that verifies the connectivity of the network cable and device. References: <https://www.professormesser.com/network-plus/n10-007/troubleshooting-methodologies-2/>

NEW QUESTION 64

- (Exam Topic 1)

A systems administrator needs to improve WiFi performance in a densely populated office tower and use the latest standard. There is a mix of devices that use 2.4 GHz and 5 GHz. Which of the following should the systems administrator select to meet this requirement?

- A. 802.11ac
- B. 802.11ax
- C. 802.11g
- D. 802.11n

Answer: B

Explanation:

* 802.11 ax is the latest WiFi standard that improves WiFi performance in densely populated environments and supports both 2.4 GHz and 5 GHz bands. 802.11ac is the previous standard that only supports 5 GHz band. 802.11g and 802.11n are older standards that support 2.4 GHz band only or both bands respectively.

References:

[https://partners.comptia.org/docs/default-source/resources/comptia-network-n10-008-exam-objectives-\(2-0\)](https://partners.comptia.org/docs/default-source/resources/comptia-network-n10-008-exam-objectives-(2-0)),

<https://www.techtarget.com/searchnetworking/tip/Whats-the-difference-between-80211ax-vs-80211ac>

NEW QUESTION 69

- (Exam Topic 1)

Which of the following is MOST likely to generate significant East-West traffic in a datacenter?

- A. A backup of a large video presentation to cloud storage for archival purposes
- B. A duplication of a hosted virtual server to another physical server for redundancy
- C. A download of navigation data to a portable device for offline access
- D. A query from an IoT device to a cloud-hosted server for a firmware update

Answer: B

Explanation:

East-West traffic refers to data flows between servers or devices within the same datacenter. When a hosted virtual server is duplicated to another physical server for redundancy, it generates significant East-West traffic as the data is replicated between the two servers. References:

> Network+ N10-008 Objectives: 3.3 Given a scenario, implement secure network architecture concepts.

NEW QUESTION 74

- (Exam Topic 1)

A network engineer configured new firewalls with the correct configuration to be deployed to each remote branch. Unneeded services were disabled, and all firewall rules were applied successfully. Which of the following should the network engineer perform NEXT to ensure all the firewalls are hardened successfully?

- A. Ensure an implicit permit rule is enabled
- B. Configure the log settings on the firewalls to the central syslog server
- C. Update the firewalls with current firmware and software

D. Use the same complex passwords on all firewalls

Answer: C

Explanation:

Updating the firewalls with current firmware and software is an important step to ensure all the firewalls are hardened successfully, as it can fix any known vulnerabilities or bugs and provide new features or enhancements. Enabling an implicit permit rule is not a good practice for firewall hardening, as it can allow unwanted traffic to pass through the firewall. Configuring the log settings on the firewalls to the central syslog server is a good practice for monitoring and auditing purposes, but it does not harden the firewalls themselves. Using the same complex passwords on all firewalls is not a good practice for password security, as it can increase the risk of compromise if one firewall is breached. References: CompTIA Network+ Certification Exam Objectives Version 2.0 (Exam Number: N10-006), Domain 3.0 Network Security, Objective 3.3 Given a scenario, implement network hardening techniques.

NEW QUESTION 77

- (Exam Topic 1)

Which of the following would MOST likely be used to review previous upgrades to a system?

- A. Business continuity plan
- B. Change management
- C. System life cycle
- D. Standard operating procedures

Answer: B

Explanation:

Change management is the process of reviewing previous upgrades to a system. It is a systematic approach to managing changes to an organization's IT systems and infrastructure. Change management involves the assessment of potential risks associated with a change, as well as the identification of any necessary resources required to implement the change. References: Network+ Certification Study Guide, Chapter 8: Network Troubleshooting

NEW QUESTION 78

- (Exam Topic 1)

A network administrator needs to query the NSs for a remote application. Which of the following commands would BEST help the administrator accomplish this task?

- A. dig
- B. arp
- C. show interface
- D. hostname

Answer: A

Explanation:

The dig command is used to query the NSs for a remote application. It is a command-line tool that is commonly used to troubleshoot DNS issues. When used with specific options, dig can be used to obtain information about domain names, IP addresses, and DNS records. References: Network+ Certification Study Guide, Chapter 3: Network Infrastructure

NEW QUESTION 79

- (Exam Topic 2)

Which of the following uses the destination IP address to forward packets?

- A. A bridge
- B. A Layer 2 switch
- C. A router
- D. A repeater

Answer: C

Explanation:

A router is a device that uses the destination IP address to forward packets between different networks. A bridge and a Layer 2 switch operate at the data link layer and use MAC addresses to forward frames within the same network. A repeater is a device that amplifies or regenerates signals at the physical layer.

NEW QUESTION 80

- (Exam Topic 2)

A network technician needs to correlate security events to analyze a suspected intrusion. Which of the following should the technician use?

- A. SNMP
- B. Log review
- C. Vulnerability scanning
- D. SIEM

Answer: D

Explanation:

SIEM stands for Security Information and Event Management, which is a tool that collects, analyzes, and correlates data from various network devices and sources to provide alerts and reports on security incidents and events. A network technician can use SIEM to correlate security events to analyze a suspected intrusion, as SIEM can help identify the source, target, method, and impact of an attack, as well as provide recommendations for remediation. References: <https://www.comptia.org/blog/what-is-siem>

NEW QUESTION 82

- (Exam Topic 2)

Which of the following services can provide data storage, hardware options, and scalability to a third-party company that cannot afford new devices?

- A. SaaS
- B. IaaS
- C. PaaS
- D. DaaS

Answer: B

Explanation:

IaaS stands for Infrastructure as a Service, which is a cloud computing model that provides virtualized computing resources such as servers, storage, and networking over the Internet. IaaS can provide data storage, hardware options, and scalability to a third-party company that cannot afford new devices by allowing them to rent or lease the infrastructure they need from a cloud provider. The company can pay only for what they use and scale up or down as needed.

References: <https://www.comptia.org/blog/what-is-iaas>

NEW QUESTION 83

- (Exam Topic 2)

A SaaS provider has decided to leave an unpatched VM available via a public DMZ port. With which of the following concepts is this technique MOST closely associated?

- A. Insider threat
- B. War driving
- C. Evil twin
- D. Honeypot

Answer: D

Explanation:

A honeypot is a decoy system that is intentionally left vulnerable or exposed to attract attackers and divert them from the real targets. A honeypot can also be used to collect information about the attackers' techniques and motives. In the scenario, the SaaS provider has left an unpatched VM available via a public DMZ port, which could be a honeypot technique to lure attackers and monitor their activities. References: <https://www.comptia.org/blog/what-is-a-honey-pot>

NEW QUESTION 86

- (Exam Topic 2)

A business is using the local cable company to provide Internet access. Which of the following types of cabling will the cable company MOST likely use from the demarcation point back to the central office?

- A. Multimode
- B. Cat 5e
- C. RG-6
- D. Cat 6
- E. 100BASE-T

Answer: C

Explanation:

RG-6 is a type of coaxial cable that is commonly used by cable companies to provide Internet access from the demarcation point back to the central office. It has a thicker conductor and better shielding than RG-59, which is another type of coaxial cable. Multimode and Cat 5e are types of fiber optic and twisted pair cables respectively, which are not typically used by cable companies. Cat 6 and 100BASE-T are standards for twisted pair cables, not types of cabling.

NEW QUESTION 91

- (Exam Topic 2)

A technician is troubleshooting a previously encountered issue. Which of the following should the technician reference to find what solution was implemented to resolve the issue?

- A. Standard operating procedures
- B. Configuration baseline documents
- C. Work instructions
- D. Change management documentation

Answer: D

Explanation:

Change management documentation is a record of the changes that have been made to a system or process, including the reason, date, time, and impact of each change. A technician can reference this documentation to find what solution was implemented to resolve a previously encountered issue, as well as any potential side effects or dependencies of the change. References: <https://www.comptia.org/blog/what-is-change-management>

NEW QUESTION 95

- (Exam Topic 2)

A network technician is reviewing an upcoming project's requirements to implement IaaS. Which of the following should the technician consider?

- A. Software installation processes
- B. Type of database to be installed
- C. Operating system maintenance
- D. Server hardware requirements

Answer:

D

Explanation:

IaaS stands for Infrastructure as a Service, which is a cloud computing model that provides virtualized computing resources such as servers, storage, and networking over the Internet. When implementing IaaS, the network technician should consider the server hardware requirements, such as CPU, RAM, disk space, and network bandwidth, that are needed to run the applications and services on the cloud. The other options are not relevant to IaaS, as they are either handled by the cloud provider or by the end-user. References: <https://www.comptia.org/blog/what-is-iaas>

NEW QUESTION 99

- (Exam Topic 2)

A network administrator wants to analyze attacks directed toward the company's network. Which of the following must the network administrator implement to assist in this goal?

- A. A honeypot
- B. Network segmentation
- C. Antivirus
- D. A screened subnet

Answer: A

Explanation:

A honeypot is a decoy system that is intentionally left vulnerable or exposed to attract attackers and divert them from the real targets. A honeypot can also be used to collect information about the attackers' techniques and motives. A network administrator can implement a honeypot to analyze attacks directed toward the company's network, as a honeypot can help identify the source, target, method, and impact of an attack, as well as provide recommendations for remediation.

References:

<https://www.comptia.org/blog/what-is-a-honeypot>

NEW QUESTION 101

- (Exam Topic 2)

Which of the following is used to provide networking capability for VMs at Layer 2 of the OSI model?

- A. VPN
- B. VRRP
- C. vSwitch
- D. VIP

Answer: C

Explanation:

A vSwitch (virtual switch) is a software-based switch that provides networking capability for VMs (virtual machines) at Layer 2 of the OSI model. It connects the VMs to each other or to external networks using virtual NICs (network interface cards). A VPN (virtual private network) is a technology that creates a secure tunnel over a public network for remote access or site-to-site connectivity. VRRP (Virtual Router Redundancy Protocol) is a protocol that provides high availability for routers by creating a virtual router with multiple physical routers. A VIP (virtual IP) is an IP address that can be shared by multiple servers or devices for load balancing or failover purposes.

NEW QUESTION 104

- (Exam Topic 2)

There are two managed legacy switches running that cannot be replaced or upgraded. These switches do not support cryptographic functions, but they are password protected. Which of the following should a network administrator configure to BEST prevent unauthorized access?

- A. Enable a management access list
- B. Disable access to unnecessary services.
- C. Configure a stronger password for access
- D. Disable access to remote management
- E. Use an out-of-band access method.

Answer: E

Explanation:

Using an out-of-band access method is the best way to prevent unauthorized access to the legacy switches that do not support cryptographic functions. Out-of-band access is a method of accessing a network device through a dedicated channel that is separate from the main network traffic. Out-of-band access can use physical connections such as serial console ports or dial-up modems, or logical connections such as VPNs or firewalls. Out-of-band access provides more security and reliability than in-band access, which uses the same network as the data traffic and may be vulnerable to attacks or failures. References:

<https://www.cisco.com/c/en/us/td/docs/ios-xml/ios/fundamentals/configuration/15mt/fundamentals-15-mt-book/>

NEW QUESTION 106

- (Exam Topic 2)

A technician wants to install a WAP in the center of a room that provides service in a radius surrounding a radio. Which of the following antenna types should the AP utilize?

- A. Omni
- B. Directional
- C. Yagi
- D. Parabolic

Answer: A

Explanation:

An omni antenna should be used by the AP to provide service in a radius surrounding a radio. An omni antenna is a type of antenna that has a 360-degree

horizontal radiation pattern. It can provide wireless coverage in all directions from the antenna with varying degrees of vertical coverage. It is suitable for indoor environments where users are located around the AP1. References: <https://www.cisco.com/c/en/us/support/docs/wireless-mobility/wireless-lan-wlan/82068-omni-vs-direct.html> 1

NEW QUESTION 110

- (Exam Topic 2)

A wireless network was installed in a warehouse for employees to scan crates with a wireless handheld scanner. The wireless network was placed in the corner of the building near the ceiling for maximum coverage. However, users in the offices adjacent to the warehouse have noticed a large amount of signal overlap from the new network. Additionally, warehouse employees report difficulty connecting to the wireless network from the other side of the building; however, they have no issues when they are near the antenna. Which of the following is MOST likely the cause?

- A. The wireless signal is being refracted by the warehouse's windows
- B. The antenna's power level was set too high and is overlapping
- C. An omnidirectional antenna was used instead of a unidirectional antenna
- D. The wireless access points are using channels from the 5GHz spectrum

Answer: C

Explanation:

An omnidirectional antenna was used instead of a unidirectional antenna, which is most likely the cause of the wireless network issues. An omnidirectional antenna provides wireless coverage in all directions from the antenna, which can cause signal overlap with adjacent offices and interference with other wireless networks. A unidirectional antenna, on the other hand, provides wireless coverage in a specific direction from the antenna, which can reduce signal overlap and interference and increase signal range and quality. A unidirectional antenna would be more suitable for a warehouse environment where users are located on one side of the building. References:

<https://www.cisco.com/c/en/us/support/docs/wireless-mobility/wireless-lan-wlan/82068-omni-vs-direct.html> 1

NEW QUESTION 114

- (Exam Topic 2)

An organization wants to implement a method of centrally managing logins to network services. Which of the following protocols should the organization use to allow for authentication, authorization, and auditing?

- A. MS-CHAP
- B. RADIUS
- C. LDAPS
- D. RSTP

Answer: B

Explanation:

RADIUS (Remote Authentication Dial-In User Service) is a protocol that should be used by the organization to allow for authentication, authorization, and auditing of network services. RADIUS is an AAA (Authentication, Authorization, and Accounting) protocol that manages network access by verifying user credentials, granting access permissions, and logging user activities. RADIUS uses a client-server model where a RADIUS client (such as a router, switch, or VPN server) sends user information to a RADIUS server (such as an authentication server) for verification and authorization. The RADIUS server can also send accounting information to another server for billing or reporting purposes. References:

<https://www.cisco.com/c/en/us/support/docs/security-vpn/remote-authentication-dial-user-service-radius/13838>

NEW QUESTION 117

- (Exam Topic 2)

An ARP request is broadcasted and sends the following request: "Who is 192.168.1.200? Tell 192.168.1.55"

At which of the following layers of the OSI model does this request operate?

- A. Application
- B. Data link
- C. Transport
- D. Network
- E. Session

Answer: B

Explanation:

An ARP request operates at the data link layer of the OSI model. ARP (Address Resolution Protocol) is a protocol that maps IP addresses to MAC addresses on a local area network. It allows devices to communicate with each other without knowing their MAC addresses beforehand. ARP operates at the data link layer (layer 2) of the OSI model, which is responsible for framing and addressing data packets on a physical medium.

References: <https://www.cisco.com/c/en/us/support/docs/ip/routing-information-protocol-rip/13788-3.html>

NEW QUESTION 120

- (Exam Topic 2)

Which of the following security devices would be BEST to use to provide mechanical access control to the MDF/IDF?

- A. A smart card
- B. A key fob
- C. An employee badge
- D. A door lock

Answer: D

Explanation:

A door lock would be the best security device to use to provide mechanical access control to the MDF/IDF. A door lock is a device that prevents unauthorized

access to a physical area by requiring a key, a code, a card, a biometric scan, or a combination of these factors to open it. A door lock can provide mechanical access control to the MDF/IDF, which are rooms that house network equipment such as switches, routers, servers, or patch panels. A door lock can prevent unauthorized persons from tampering with or stealing the network equipment or data. References:
https://www.cisco.com/c/en/us/td/docs/solutions/Enterprise/Data_Center/DC_Infra2_5/DCInfra_6.html

NEW QUESTION 121

- (Exam Topic 2)

Which of the following protocols will a security appliance that is correlating network events from multiple devices MOST likely rely on to receive event messages?

- A. Syslog
- B. Session Initiation Protocol
- C. Secure File Transfer Protocol
- D. Server Message Block

Answer: A

Explanation:

Syslog is a protocol that provides a standard way for network devices and applications to send event messages to a logging server or a security appliance. Syslog messages can contain information about security incidents, errors, warnings, system status, configuration changes, and other events. A security appliance that is correlating network events from multiple devices can rely on Syslog to receive event messages from different sources and formats. References:
<https://www.comptia.org/blog/what-is-syslog>

NEW QUESTION 126

- (Exam Topic 2)

A local firm has hired a consulting company to clean up its IT infrastructure. The consulting company notices remote printing is accomplished by port forwarding via publicly accessible IPs through the firm's firewall. Which of the following would be the MOST appropriate way to enable secure remote printing?

- A. SSH
- B. VPN
- C. Telnet
- D. SSL

Answer: B

Explanation:

VPN (Virtual Private Network) is the most appropriate way to enable secure remote printing. VPN is a technology that creates a secure and encrypted tunnel over a public network such as the Internet. It allows remote users or sites to access a private network as if they were directly connected to it. VPN can be used for various purposes such as accessing corporate resources, bypassing geo-restrictions, or enhancing privacy and security. VPN can also be used for remote printing by allowing users to connect to a printer on the private network and send print jobs securely over the VPN tunnel. References:
<https://www.cisco.com/c/en/us/support/docs/security-vpn/ipsec-negotiation-ike-protocols/14106-how-vpn-work>

NEW QUESTION 129

- (Exam Topic 2)

A company is being acquired by a large corporation. As part of the acquisition process, the company's address should now redirect clients to the corporate organization page. Which of the following DNS records needs to be created?

- A. SOA
- B. NS
- C. CNAME
- D. TXT

Answer: C

Explanation:

Reference:

<https://www.namecheap.com/support/knowledgebase/article.aspx/9604/2237/types-of-domain-redirects-301-302>

CNAME (Canonical Name) is a type of DNS record that maps an alias name to another name, which can be either another alias or the canonical name of a host or domain. A CNAME record can be used to redirect clients from one domain name to another domain name, such as from the company's address to the corporate organization page. SOA (Start of Authority) is a type of DNS record that specifies authoritative information about a DNS zone, such as the primary name server, contact email address, serial number, refresh interval, etc., which does not redirect clients to another domain name. NS (Name Server) is a type of DNS record that specifies which name server is authoritative for a domain or subdomain, which does not redirect clients to another domain name. TXT (Text) is a type of DNS record that provides arbitrary text information about a domain or subdomain, such as SPF (Sender Policy Framework) records or DKIM (DomainKeys Identified Mail) records, which does not redirect clients to another domain name.

NEW QUESTION 133

- (Exam Topic 2)

An IDS was installed behind the edge firewall after a network was breached. The network was then breached again even though the IDS logged the attack. Which of the following should be used in place of these devices to prevent future attacks?

- A. A network tap
- B. A proxy server
- C. A UTM appliance
- D. A content filter

Answer: C

Explanation:

A UTM appliance stands for Unified Threat Management appliance, which is a device that combines multiple security functions into one solution. A UTM appliance can provide firewall, IDS/IPS, antivirus, VPN, web filtering, and other security features. A network technician can use a UTM appliance in place of an edge firewall

and an IDS to prevent future attacks, as a UTM appliance can block malicious traffic and detect and respond to intrusions more effectively. References: <https://www.comptia.org/blog/what-is-utm>

NEW QUESTION 138

- (Exam Topic 2)

A network administrator is required to ensure that auditors have read-only access to the system logs, while systems administrators have read and write access to the system logs, and operators have no access to the system logs. The network administrator has configured security groups for each of these functional categories. Which of the following security capabilities will allow the network administrator to maintain these permissions with the LEAST administrative effort?

- A. Mandatory access control
- B. User-based permissions
- C. Role-based access
- D. Least privilege

Answer: C

Explanation:

Role-based access is a security capability that assigns permissions to users based on their roles or functions within an organization. It allows the network administrator to maintain these permissions with the least administrative effort, as they only need to configure the security groups for each role once and then assign users to those groups. Mandatory access control is a security capability that assigns permissions based on security labels or classifications, which requires more administrative effort to maintain. User-based permissions are a security capability that assigns permissions to individual users, which is not scalable or efficient for large organizations. Least privilege is a security principle that states that users should only have the minimum level of access required to perform their tasks, which is not a security capability by itself.

NEW QUESTION 139

- (Exam Topic 2)

A network administrator wants to improve the security of the management console on the company's switches and ensure configuration changes made can be correlated to the administrator who conformed them Which of the following should the network administrator implement?

- A. Port security
- B. Local authentication
- C. TACACS+
- D. Access control list

Answer: C

Explanation:

TACACS+ is a protocol that provides centralized authentication, authorization, and accounting (AAA) for network devices and users. TACACS+ can help improve the security of the management console on the company's switches by verifying the identity and credentials of the administrators, enforcing granular access policies and permissions, and logging the configuration changes made by each administrator. This way, the network administrator can ensure only authorized and authenticated users can access and modify the switch settings, and also track and correlate the changes made by each user. References: <https://www.comptia.org/blog/what-is-tacacs>

NEW QUESTION 143

- (Exam Topic 2)

A company requires a disaster recovery site to have equipment ready to go in the event of a disaster at its main datacenter. The company does not have the budget to mirror all the live data to the disaster recovery site. Which of the following concepts should the company select?

- A. Cold site
- B. Hot site
- C. Warm site
- D. Cloud site

Answer: C

Explanation:

A warm site is a type of disaster recovery site that has equipment ready to go in the event of a disaster at the main datacenter, but does not have live data or applications. A warm site requires some time and effort to restore the data and services from backups, but it is less expensive than a hot site that has live data and applications. A cold site is a disaster recovery site that has no equipment or data, and requires a lot of time and money to set up after a disaster. A cloud site is a disaster recovery site that uses cloud computing resources to provide data and services, but it may have issues with bandwidth, latency, security, and cost. References: <https://www.comptia.org/blog/what-is-a-warm-site>

NEW QUESTION 146

- (Exam Topic 2)

A network administrator has been directed to present the network alerts from the past week to the company's executive staff. Which of the following will provide the BEST collection and presentation of this data?

- A. A port scan printout
- B. A consolidated report of various network devices
- C. A report from the SIEM tool
- D. A report from a vulnerability scan done yesterday

Answer: C

Explanation:

SIEM stands for Security Information and Event Management, which is a tool that collects, analyzes, and correlates data from various network devices and sources to provide alerts and reports on security incidents and events. A report from the SIEM tool can provide a comprehensive overview of the network alerts from the past week to the executive staff, highlighting any potential threats, vulnerabilities, or anomalies. References: <https://www.comptia.org/blog/what-is-siem>

NEW QUESTION 150

- (Exam Topic 2)

The following instructions were published about the proper network configuration for a videoconferencing device:

"Configure a valid static RFC1918 address for your network. Check the option to use a connection over NAT." Which of the following is a valid IP address configuration for the device?

- A. FE80::1
- B. 100.64.0.1
- C. 169.254.1.2
- D. 172.19.0.2
- E. 224.0.0.12

Answer: D

Explanation:

* 172.19.0.2 is a valid IP address configuration for the device that uses a static RFC1918 address for the network and allows for a connection over NAT (Network Address Translation). RFC1918 addresses are private IP addresses that are not routable on the public Internet and are used for internal networks. The RFC1918 address ranges are 10.0.0.0/8, 172.16.0.0/12, and 192.168.0.0/16. NAT is a technique that translates private IP addresses to public IP addresses when communicating with external networks, such as the Internet. FE80::1 is an IPv6 link-local address that is not a static RFC1918 address and does not allow for a connection over NAT. 100.64.1.1 is an IPv4 address that belongs to the shared address space range (100.64.0.0/10) that is used for carrier-grade NAT (CGN) between service providers and subscribers, which is not a static RFC1918 address and does not allow for a connection over NAT. 169.254.1.2 is an IPv4 link-local address that is automatically assigned by a device when it cannot obtain an IP address from a DHCP server or manual configuration, which is not a static RFC1918 address and does not allow for a connection over NAT. 224.0.0.12 is an IPv4 multicast address that is used for VRRP (Virtual Router Redundancy Protocol), which is not a static RFC1918 address and does not allow for a connection over NAT.

NEW QUESTION 153

- (Exam Topic 2)

A network requirement calls for segmenting departments into different networks. The campus network is set up with users of each department in multiple buildings. Which of the following should be configured to keep the design simple and efficient?

- A. MDIX
- B. Jumbo frames
- C. Port tagging
- D. Flow control

Answer: C

Explanation:

Port tagging is a technique that involves adding a tag or identifier to the frames or packets that belong to a certain VLAN. A VLAN is a logical segment of a network that isolates traffic between different groups of devices. Port tagging allows devices on different physical ports or switches to communicate with each other as if they were on the same port or switch. Port tagging can help keep the design simple and efficient by reducing the number of physical ports and switches needed to segment departments into different networks. References: <https://www.comptia.org/blog/what-is-port-tagging>

NEW QUESTION 157

- (Exam Topic 2)

Which of the following OSI model layers is where conversations between applications are established, coordinated, and terminated?

- A. Session
- B. Physical
- C. Presentation
- D. Data link

Answer: A

Explanation:

Reference: <https://www.techtarget.com/searchnetworking/definition/OSI#:~:text=The%20session%20layer,and%20termina>

The session layer is where conversations between applications are established, coordinated, and terminated. It is responsible for creating, maintaining, and ending sessions between different devices or processes. The physical layer deals with the transmission of bits over a medium. The presentation layer formats and translates data for different applications. The data link layer provides reliable and error-free delivery of frames within a network.

NEW QUESTION 159

- (Exam Topic 2)

A network administrator needs to implement an HDMI over IP solution. Which of the following will the network administrator MOST likely use to ensure smooth video delivery?

- A. Link aggregation control
- B. Port tagging
- C. Jumbo frames
- D. Media access control

Answer: C

Explanation:

Giants are packets that exceed the configured MTU (Maximum Transmission Unit) of a switchport or interface, which causes them to be dropped or fragmented by the switch or router. The MTU is the maximum size of a packet that can be transmitted without fragmentation on a given medium or protocol. Giants can indicate misconfiguration or mismatch of MTU values between devices or interfaces on a network, which can cause performance issues or errors. CRC errors are errors that occur when the cyclic redundancy check (CRC) value of a packet does not match the calculated CRC value at the destination, which indicates corruption or alteration of data during transmission due to noise, interference, faulty cabling, etc., but not necessarily exceeding MTU values. Runts are packets that are smaller than the minimum size allowed by the medium or protocol, which causes them to be dropped or ignored by the switch or router. Flooding is a technique where a switch sends packets to all ports except the source port when it does not have an entry for the destination MAC address in its MAC address table, which can cause

congestion or broadcast storms on a network.

NEW QUESTION 162

- (Exam Topic 2)

During the security audit of a financial firm the Chief Executive Officer (CEO) questions why there are three employees who perform very distinct functions on the server. There is an administrator for creating users another for assigning the users to groups and a third who is the only administrator to perform file rights assignment Which of the following mitigation techniques is being applied'

- A. Privileged user accounts
- B. Role separation
- C. Container administration
- D. Job rotation

Answer: B

Explanation:

Role separation is a security principle that involves dividing the tasks and privileges for a specific business process among multiple users. This reduces the risk of fraud and errors, as no one user has complete control over the process. In the scenario, there are three employees who perform very distinct functions on the server, which is an example of role separation. References: <https://hyperproof.io/resource/segregation-of-duties/>

NEW QUESTION 163

- (Exam Topic 2)

A client moving into a new office wants the IP network set up to accommodate 412 network-connected devices that are all on the same subnet. The subnet needs to be as small as possible. Which of the following subnet masks should be used to achieve the required result?

- A. 255.255.0.0
- B. 255.255.252.0
- C. 255.255.254.0
- D. 255.255.255.0

Answer: B

Explanation:

* 255.255.252.1 is a subnet mask that allows for 1022 network-connected devices on the same subnet, which is the smallest subnet that can accommodate 412 devices. The subnet mask determines how many bits are used for the network portion and how many bits are used for the host portion of an IP address. A smaller subnet mask means more bits are used for the network portion and less bits are used for the host portion, which reduces the number of available hosts on the subnet. 255.255.0.0 allows for 65534 hosts on the same subnet, which is too large. 255.255.254.0 allows for 510 hosts on the same subnet, which is also too large. 255.255.255.0 allows for 254 hosts on the same subnet, which is too small.

NEW QUESTION 164

- (Exam Topic 2)

A network administrator is configuring a database server and would like to ensure the database engine is listening on a certain port. Which of the following commands should the administrator use to accomplish this goal?

- A. nslookup
- B. netstat -a
- C. ipconfig /a
- D. arp -a

Answer: B

Explanation:

netstat -a is a command that displays information about active TCP connections and listening ports on a system. A network administrator can use netstat -a to check if the database engine is listening on a certain port, as well as verify if there are any connections established to or from that port. References: <https://www.comptia.org/blog/what-is-netstat>

NEW QUESTION 168

- (Exam Topic 2)

A city has hired a new employee who needs to be able to work when traveling at home and at the municipal sourcing of a neighboring city that shares services. The employee is issued a laptop, and a technician needs to train the employee on the appropriate solutions for secure access to the network from all the possible locations On which of the following solutions would the technician MOST likely train the employee?

- A. Site-to-site VPNs between the two city locations and client-to-site software on the employee's laptop for all other remote access
- B. Client-to-site VPNs between the travel locations and site-to-site software on the employee's laptop for all other remote access
- C. Client-to-site VPNs between the two city locations and site-to-site software on the employee's laptop for all other remote access
- D. Site-to-site VPNs between the home and city locations and site-to-site software on the employee's laptop for all other remote access

Answer: A

Explanation:

The technician would most likely train the employee on using site-to-site VPNs between the two city locations and client-to-site software on the employee's laptop for all other remote access. A VPN (Virtual Private Network) is a technology that creates a secure and encrypted tunnel over a public network such as the Internet. It allows remote users or sites to access a private network as if they were directly connected to it. A site-to-site VPN connects two or more networks, such as branch offices or data centers, using a VPN gateway device at each site. A client-to-site VPN connects individual users, such as mobile workers or telecommuters, using a VPN client software on their devices. In this scenario, the employee needs to access the network from different locations, such as home, travel, or another city. Therefore, the technician would train the employee on how to use site-to-site VPNs to connect to the network from another city location that shares services, and how to use client-to-site software to connect to the network from home or travel locations. References: <https://www.cisco.com/c/en/us/support/docs/security-vpn/ipsec-negotiation-ike-protocols/14106-how-vpn-work>

NEW QUESTION 172

- (Exam Topic 2)

A company wants to implement a large number of WAPs throughout its building and allow users to be able to move around the building without dropping their connections. Which of the following pieces of equipment would be able to handle this requirement?

- A. A VPN concentrator
- B. A load balancer
- C. A wireless controller
- D. A RADIUS server

Answer: C

Explanation:

A wireless controller would be able to handle the requirement of implementing a large number of WAPs throughout the building and allowing users to move around without dropping their connections. A wireless controller is a device that centrally manages and configures multiple wireless access points (WAPs) on a network. It can provide features such as load balancing, roaming, security, QoS, and monitoring for the wireless network. A wireless controller can also support wireless mesh networks, where some WAPs act as relays for other WAPs to extend the wireless coverage. References: <https://www.cisco.com/c/en/us/products/wireless/wireless-lan-controller/index.html>

NEW QUESTION 176

- (Exam Topic 3)

A network administrator views a network pcap and sees a packet containing the following:

```
community: public
request-id: 13438
get-response 1.3.6.1.2.1.1.3.0 Value:206801150
```

Which of the following are the BEST ways for the administrator to secure this type of traffic? (Select TWO).

- A. Migrate the network to IPv6.
- B. Implement 802.1 X authentication
- C. Set a private community string
- D. Use SNMPv3.
- E. Incorporate SSL encryption
- F. Utilize IPsec tunneling.

Answer: CD

Explanation:

The packet shown in the image is an SNMP (Simple Network Management Protocol) packet, which is used to monitor and manage network devices. SNMP uses community strings to authenticate requests and responses between SNMP agents and managers. However, community strings are sent in clear text and can be easily intercepted by attackers. Therefore, one way to secure SNMP traffic is to set a private community string that is not the default or well-known value. Another way to secure SNMP traffic is to use SNMPv3, which is the latest version of the protocol that supports encryption and authentication of SNMP messages. References: CompTIA Network+ Certification Exam Objectives Version 7.0 (N10-007), Objective 2.5: Given a scenario, use remote access methods.

NEW QUESTION 178

- (Exam Topic 3)

Which of the following network devices can perform routing between VLANs?

- A. Layer 2 switch
- B. Layer 3 switch
- C. Load balancer
- D. Bridge

Answer: B

Explanation:

<https://www.practicalnetworking.net/stand-alone/routing-between-vlans/#:~:text=A%20router%20will%20perfo>

NEW QUESTION 180

- (Exam Topic 3)

A network technician needs to ensure the company's external mail server can pass reverse lookup checks. Which of the following records would the technician MOST likely configure? (Choose Correct option and give explanation directly from CompTIA Network+ Study guide or documents)

- A. PTR
- B. AAAA
- C. SPF
- D. CNAME

Answer: A

Explanation:

A PTR (Pointer) record is used to map an IP address to a domain name, which is necessary for reverse lookup checks. Reverse lookup checks are performed by external mail servers to verify the identity of the sender of the email. By configuring a PTR record, the network technician can ensure that the company's external mail server can pass these checks. According to the CompTIA Network+ Study Guide, "A PTR record is used to map an IP address to a domain name, and it is often used for email authentication."

NEW QUESTION 181

- (Exam Topic 3)

Which of the following devices have the capability to allow communication between two different subnetworks? (Select TWO).

- A. IDS
- B. Access point
- C. Layer 2 switch
- D. Layer 3 switch
- E. Router
- F. Media converter

Answer: DE

NEW QUESTION 186

- (Exam Topic 3)

Which of the following has the capability to centrally manage configuration, logging, and firmware versioning for distributed devices?

- A. WLAN controller
- B. Load balancer
- C. SIEM solution
- D. Syslog server

Answer: A

Explanation:

A WLAN controller is a device that manages and controls multiple wireless access points (WAPs) in a wireless LAN (WLAN). A WLAN controller has the capability to centrally manage configuration, logging, and firmware versioning for distributed WAPs. A WLAN controller can also provide load balancing, security, and quality of service (QoS) for the WLAN.

References: Network+ Study Guide Objective 3.1: Explain the purposes and use cases for advanced networking devices.

NEW QUESTION 187

- (Exam Topic 3)

A technician performed a manual reconfiguration of a firewall, and network connectivity was reestablished. Some connection events that were previously sent to a syslog server are no longer being generated by the firewall. Which of the following should the technician perform to fix the issue?

- A. Adjust the proper logging level on the new firewall.
- B. Tune the filter for logging the severity level on the syslog server.
- C. Activate NetFlow traffic between the syslog server and the firewall.
- D. Restart the SNMP service running on the syslog server.

Answer: A

Explanation:

Logging level is a setting that determines what types of events are recorded by a device and sent to a syslog server. Different logging levels have different severity levels, ranging from emergency to debug. If the technician performed a manual reconfiguration of the firewall, it is possible that the logging level was changed or reset to a lower level that does not include the connection events that were previously sent to the syslog server. To fix the issue, the technician should adjust the proper logging level on the new firewall to match the desired level of detail and severity for the connection events. References: Network+ Study Guide Objective 3.4: Explain common scanning, monitoring and patching processes and summarize their expected outputs. Subobjective: Syslog.

NEW QUESTION 189

- (Exam Topic 3)

A network device needs to discover a server that can provide it with an IPv4 address. Which of the following does the device need to send the request to?

- A. Default gateway
- B. Broadcast address
- C. Unicast address
- D. Link local address

Answer: B

Explanation:

The DHCP client sends broadcast request packets to the network; the DHCP servers respond with broadcast packets that offer IP parameters, such as an IP address for the client. After the client chooses the IP parameters, communication between the client and server is by unicast packets.

"When a DHCP client boots up, it automatically sends out a DHCP Discover UDP datagram to the broadcast address, 255.255.255.255. This DHCP Discover message asks "Are there any DHCP servers out there?" The client can't send unicast traffic yet, as it doesn't have a valid IP address that can be used."

NEW QUESTION 190

- (Exam Topic 3)

Several employees have expressed concerns about the company monitoring their internet activity when they are working from home. The company wants to mitigate this issue and reassure employees that their private internet activity is not being monitored. Which of the following would satisfy company and employee needs?

- A. Split tunnel
- B. Full tunnel
- C. Site-to-site tunnel
- D. Virtual desktop

Answer: A

Explanation:

Split tunnel is a configuration that allows a remote user to access both the local network and the Internet at the same time. In a split tunnel configuration, only traffic destined for the corporate network is sent through the VPN tunnel, while all other traffic is sent directly to the Internet. This allows the remote user to access the Internet without the company's VPN server being able to monitor or intercept their traffic. Using a split tunnel configuration can help the company to mitigate

employee concerns about internet activity being monitored and reassure employees that their private internet activity is not being monitored.

NEW QUESTION 191

- (Exam Topic 3)

During a recent security audit, a contracted penetration tester discovered the organization uses a number of insecure protocols. Which of the following ports should be disallowed so only encrypted protocols are allowed? (Select TWO).

- A. 22
- B. 23
- C. 69
- D. 443
- E. 587
- F. 8080

Answer: BC

NEW QUESTION 193

- (Exam Topic 3)

A network technician needs to ensure that all files on a company's network can be moved in a safe and protected manner without interception from someone who is not the intended recipient. Which of the following would allow the network technician to meet these requirements?

- A. FTP
- B. TFTP
- C. SMTP
- D. SFTP

Answer: D

NEW QUESTION 195

- (Exam Topic 3)

Which of the following layers of the OSI model has new protocols activated when a user moves from a wireless to a wired connection?

- A. Data link
- B. Network
- C. Transport
- D. Session

Answer: A

Explanation:

"The Data Link layer also determines how data is placed on the wire by using an access method. The wired access method, carrier-sense multiple access with collision detection (CSMA/CD), was once used by all wired Ethernet networks, but is automatically disabled on switched full-duplex links, which have been the norm for decades. Carrier-sense multiple access with collision avoidance (CSMA/CA) is used by wireless networks, in a similar fashion."

NEW QUESTION 198

- (Exam Topic 3)

A non-employee was able to enter a server room. Which of the following could have prevented this from happening?

- A. A security camera
- B. A biometric reader
- C. OTP key fob
- D. Employee training

Answer: B

Explanation:

A biometric reader is a device that scans a person's physical characteristics, such as fingerprints, iris, or face, and compares them to a database of authorized users. A biometric reader can be used to restrict access to a server room and prevent unauthorized entry. A biometric reader provides a high level of security and cannot be easily bypassed or duplicated.

References: Network+ Study Guide Objective 5.1: Summarize the importance of physical security controls.

NEW QUESTION 199

- (Exam Topic 3)

Which of the following devices would be used to extend the range of a wireless network?

- A. A repeater
- B. A media converter
- C. A router
- D. A switch

Answer: A

Explanation:

A repeater is a device used to extend the range of a wireless network by receiving, amplifying, and retransmitting wireless signals. It is typically used to extend the range of a wireless network in a large area, such as an office building or a campus. Repeaters can also be used to connect multiple wireless networks together, allowing users to move seamlessly between networks. As stated in the CompTIA Network+ Study Manual, "a wireless repeater is used to extend the range of a wireless network by repeating the signal from one access point to another."

NEW QUESTION 203

- (Exam Topic 3)

A security vendor needs to add a note to the DNS to validate the ownership of a company domain before services begin. Which of the following records did the security company MOST likely ask the company to configure?

- A. TXT
- B. AAAA
- C. CNAME
- D. SRV

Answer: A

Explanation:

TXT stands for Text and is a type of DNS record that can store arbitrary text data associated with a domain name. TXT records can be used for various purposes, such as verifying the ownership of a domain, providing information about a domain, or implementing security mechanisms such as SPF (Sender Policy Framework) or DKIM (DomainKeys Identified Mail). In this scenario, the security company most likely asked the company to configure a TXT record with a specific value that can prove the ownership of the domain. AAAA stands for IPv6 Address and is a type of DNS record that maps a domain name to an IPv6 address. CNAME stands for Canonical Name and is a type of DNS record that maps an alias name to another name. SRV stands for Service and is a type of DNS record that specifies the location of a service on a network.

References: CompTIA Network+ Certification Exam Objectives Version 7.0 (N10-007), Objective 1.8: Explain the purposes and use cases for advanced networking devices.

NEW QUESTION 208

- (Exam Topic 3)

Which of the following is an example of on-demand scalable hardware that is typically housed in the vendor's data center?

- A. DaaS
- B. IaaS
- C. PaaS
- D. SaaS

Answer: B

NEW QUESTION 211

- (Exam Topic 3)

A large number of PCs are obtaining an APIPA IP address, and a number of new computers were added to the network. Which of the following is MOST likely causing the PCs to obtain an APIPA address?

- A. Rogue DHCP server
- B. Network collision
- C. Incorrect DNS settings
- D. DHCP scope exhaustion

Answer: D

Explanation:

DHCP scope exhaustion means that there are no more available IP addresses in the DHCP server's pool of addresses to assign to new devices on the network. When this happens, the devices will use APIPA (Automatic Private IP Addressing) to self-configure an IP address in the range of 169.254.0.1 to 169.254.255.254. These addresses are not routable and can only communicate with other devices on the same local network.

A rogue DHCP server (A) is an unauthorized DHCP server that can cause IP address conflicts or security issues by assigning IP addresses to devices on the network. A network collision (B) is a situation where two or more devices try to send data on the same network segment at the same time, causing interference and data loss. Incorrect DNS settings © can prevent devices from resolving domain names to IP addresses, but they do not affect the DHCP process.

NEW QUESTION 216

- (Exam Topic 3)

A technician installed an 8-port switch in a user's office. The user needs to add a second computer in the office, so the technician connects both PCs to the switch and connects the switch to the wall jack. However, the new PC cannot connect to network resources. The technician then observes the following:

- The new computer does not get an IP address on the client's VLAN.
- Both computers have a link light on their NICs.
- The new PC appears to be operating normally except for the network issue.
- The existing computer operates normally.

Which of the following should the technician do NEXT to address the situation?

- A. Contact the network team to resolve the port security issue.
- B. Contact the server team to have a record created in DNS for the new PC.
- C. Contact the security team to review the logs on the company's SIEM.
- D. Contact the application team to check NetFlow data from the connected switch.

Answer: A

NEW QUESTION 221

- (Exam Topic 3)

An administrator is attempting to add a new system to monitoring but is unsuccessful. The administrator notices the system is similar to another one on the network; however, the new one has an updated OS version. Which of the following should the administrator consider updating?

- A. Management information bases
- B. System baseline
- C. Network device logs
- D. SNMP traps

Answer: A

NEW QUESTION 225

- (Exam Topic 3)

Several end users viewing a training video report seeing pixelated images while watching. A network administrator reviews the core switch and is unable to find an immediate cause. Which of the following BEST explains what is occurring?

- A. Jitter
- B. Bandwidth
- C. Latency
- D. Giants

Answer: A

Explanation:

"Jitter is the loss of packets due to an overworked WAP. Jitter shows up as choppy conversations over a video call, strange jumps in the middle of an online game—pretty much anything that feels like the network has missed some data. Latency is when data stops moving for a moment due to a WAP being unable to do the work. This manifests as a Word document that stops loading, for example, or an online file that stops downloading."

NEW QUESTION 226

- (Exam Topic 3)

Due to a surge in business, a company is onboarding an unusually high number of salespeople. The salespeople are assigned desktops that are wired to the network. The last few salespeople to be onboarded are able to access corporate materials on the network but not sales-specific resources. Which of the following is MOST likely the cause?

- A. The switch was configured with port security.
- B. Newly added machines are running into DHCP conflicts.
- C. The IPS was not configured to recognize the new users.
- D. Recently added users were assigned to the wrong VLAN

Answer: D

NEW QUESTION 230

- (Exam Topic 3)

Which of the following can be used to limit the ability of devices to perform only HTTPS connections to an internet update server without exposing the devices to the public internet?

- A. Allow connections only to an internal proxy server.
- B. Deploy an IDS system and place it in line with the traffic.
- C. Create a screened network and move the devices to it.
- D. Use a host-based network firewall on each device.

Answer: A

Explanation:

An internal proxy server is a server that acts as an intermediary between internal devices and external servers on the internet. An internal proxy server can be used to limit the ability of devices to perform only HTTPS connections to an internet update server by filtering and forwarding the requests and responses based on predefined rules or policies. An internal proxy server can also prevent the devices from being exposed to the public internet by hiding their IP addresses and providing a layer of security and privacy.

NEW QUESTION 232

- (Exam Topic 3)

An administrator needs to connect two laptops directly to each other using 802.11ac but does not have an AP available. Which of the following describes this configuration?

- A. Basic service set
- B. Extended service set
- C. Independent basic service set
- D. MU-MIMO

Answer: C

NEW QUESTION 237

- (Exam Topic 3)

During a risk assessment which of the following should be considered when planning to mitigate high CPU utilization of a firewall?

- A. Recovery time objective
- B. Uninterruptible power supply
- C. NIC teaming
- D. Load balancing

Answer: D

Explanation:

The recovery time objective (RTO) is the maximum tolerable length of time that a computer, system, network or application can be down after a failure or disaster occurs. This does nothing to help with CPU utilization. Load balancing does this.

NEW QUESTION 238

- (Exam Topic 3)

A technician wants to monitor and provide traffic segmentation across the network. The technician would like to assign each department a specific identifier. Which of the following will the technician MOST likely use?

- A. Flow control
- B. Traffic shaping
- C. VLAN tagging
- D. Network performance baselines

Answer: C

Explanation:

To monitor and provide traffic segmentation across the network, a technician may use the concept of VLANs (Virtual Local Area Networks). VLANs are a way of dividing a single physical network into multiple logical networks, each with its own unique identifier or "tag."

By assigning each department a specific VLAN identifier, the technician can segment the network traffic and ensure that the different departments' traffic is kept separate from one another. This can help to improve network security, performance, and scalability, as well as allowing for better monitoring and control of the network traffic.

To implement VLANs, the technician will need to configure VLAN tagging on the network devices, such as switches and routers, and assign each department's devices to the appropriate VLAN. The technician may also need to configure VLAN trunking to allow the different VLANs to communicate with each other.

By using VLANs, the technician can effectively monitor and segment the network traffic, providing better control and visibility into the network.

NEW QUESTION 239

- (Exam Topic 3)

Which of the following commands can be used to display the IP address, subnet address, gateway address, and DNS address on a Windows computer?

- A. netstat -a
- B. ifconfig
- C. ip addr
- D. ipconfig /all

Answer: D

Explanation:

The ipconfig command is a utility that allows you to view and modify the network configuration of a Windows computer. By running the command "ipconfig /all", you can view detailed information about the network configuration of your computer, including the IP address, subnet mask, default gateway, and DNS server addresses.

Option A (netstat -a) is a command that displays active network connections and their status, but it does not display IP address or other network configuration information. Option B (ifconfig) is a command used on Linux and Unix systems to view and modify network configuration, but it is not available on Windows. Option C (ip addr) is a command used on Linux and Unix systems to view and modify network configuration, but it is not available on Windows.

NEW QUESTION 241

- (Exam Topic 3)

A company with multiple routers would like to implement an HA network gateway with the least amount of downtime possible. This solution should not require changes on the gateway setting of the network clients. Which of the following should a technician configure?

- A. Automate a continuous backup and restore process of the system's state of the active gateway.
- B. Use a static assignment of the gateway IP address on the network clients.
- C. Configure DHCP relay and allow clients to receive a new IP setting.
- D. Configure a shared VIP and deploy VRRP on the routers.

Answer: D

Explanation:

The open standard protocol Virtual Router Redundancy Protocol (VRRP) is similar to HSRP, the differences mainly being in terminology and packet formats. In VRRP, the active router is known as the master, and all other routers in the group are known as backup routers. There is no specific standby router; instead, all backup routers monitor the status of the master, and in the event of a failure, a new master router is selected from the available backup routers based on priority.

NEW QUESTION 242

- (Exam Topic 3)

An engineer is gathering data to determine the effectiveness of UPSs in use at remote retail locations. Which of the following statistics can the engineer use to determine the availability of the remote network equipment?

- A. Uptime
- B. NetFlow baseline
- C. SNMP traps
- D. Interface statistics

Answer: A

Explanation:

Uptime is a statistic that can be used to determine the availability of the remote network equipment. Uptime is the amount of time that a device or system has been running without experiencing any failures or disruptions. It is commonly expressed as a percentage of total time, such as 99.99% uptime. By measuring the uptime of the network equipment at the remote retail locations, the engineer can determine how reliable and available the equipment is.

NEW QUESTION 245

- (Exam Topic 3)

Which of the following would be the MOST cost-effective recovery solution for a company's lower-priority applications?

- A. Warm site
- B. Cloud site
- C. Hot site
- D. Cold site

Answer: C

NEW QUESTION 247

- (Exam Topic 3)

A network administrator would like to purchase a device that provides access ports to endpoints and has the ability to route between networks. Which of the following would be BEST for the administrator to purchase?

- A. An IPS
- B. A Layer 3 switch
- C. A router
- D. A wireless LAN controller

Answer: B

NEW QUESTION 252

- (Exam Topic 3)

All packets arriving at an interface need to be fully analyzed. Which of the following features should be used to enable monitoring of the packets?

- A. LACP
- B. Flow control
- C. Port mirroring
- D. NetFlow exporter

Answer: C

Explanation:

Port mirroring is a feature that can be used to enable monitoring of all packets arriving at an interface. This feature is used to direct a copy of all traffic passing through the switch to a monitoring device, such as a network analyzer. This allows the switch to be monitored with the network analyzer in order to identify any malicious or suspicious activity. Additionally, port mirroring can be used to troubleshoot network issues, such as latency or poor performance.

NEW QUESTION 254

- (Exam Topic 3)

A help desk technician is concerned that a client's network cable issues may be causing intermittent connectivity. Which of the following would help the technician determine if this is the issue?

- A. Run the show interface command on the switch
- B. Run the traceroute command on the server
- C. Run iperf on the technician's desktop
- D. Ping the client's computer from the router
- E. Run a port scanner on the client's IP address

Answer: A

Explanation:

To determine if a client's network cable issues may be causing intermittent connectivity, the help desk technician can run the show interface command on the switch. This command allows the technician to view the status and statistics of the various interfaces on the switch, including the physical link status and the number of transmitted and received packets. If the interface is experiencing a large number of errors or dropped packets, this could indicate a problem with the network cable or with the connection between the client's device and the switch.

"Cisco routers and switches have a show interfaces IOS command that provides interface statistics/status information, including link state (up/down), speed/duplex, send/receive traffic, cyclic redundancy checks (CRCs), and protocol packet and byte counts."

NEW QUESTION 255

- (Exam Topic 3)

A public, wireless ISP mounts its access points on top of traffic signal poles. Fiber-optic cables are installed from a fiber switch through the ground and up the pole to a fiber-copper media converter, and then connected to the AP. In one location, the switchport is showing sporadic link loss to the attached AP. A similar link loss is not seen at the AP interface. The fiber-optic cable is moved to another unused switchport with a similar result. Which of the following steps should the assigned technician complete NEXT?

- A. Disable and enable the switchport.
- B. Clean the fiber-optic cable ends.
- C. Replace the media converter.
- D. Replace the copper patch cord.

Answer: B

Explanation:

Fiber-optic cables are cables that use light signals to transmit data over long distances at high speeds.

Fiber-optic cables are sensitive to dirt, dust, moisture, or other contaminants that can interfere with the light signals and cause link loss or signal degradation. To troubleshoot link loss issues with fiber-optic cables, one of the steps that should be completed next is to clean the fiber-optic cable ends with a lint-free cloth or a specialized cleaning tool. Cleaning the fiber-optic cable ends can remove any dirt or debris that may be blocking or reflecting the light signals and restore the link quality.

NEW QUESTION 258

- (Exam Topic 3)

A network is secured and is only accessible via TLS and IPSec VPNs. Which of the following would need to be present to allow a user to access network resources on a laptop without logging in to the VPN application?

- A. Site-to-site
- B. Secure Shell
- C. In-band management
- D. Remote desktop connection

Answer: A

Explanation:

A site-to-site VPN is a type of VPN that connects two or more networks over the Internet using a secure tunnel. A site-to-site VPN allows users to access network resources on a laptop without logging in to the VPN application, as long as the laptop is connected to one of the networks in the VPN. A site-to-site VPN is transparent to the users and does not require any additional software or configuration on the client devices. References: Network+ Study Guide Objective 3.4: Explain the purposes and use cases for VPNs.

NEW QUESTION 261

- (Exam Topic 3)

On a network with redundant switches, a network administrator replaced one of the switches but was unable to get a connection with another switch. Which of the following should the administrator check after successfully testing the cable that was wired for TIA/EIA-568A on both ends?

- A. If MDIX is enabled on the new switch
- B. If PoE is enabled
- C. If a plenum cable is being used
- D. If STP is disabled on the switches

Answer: A

Explanation:

Auto-MDIX (or medium dependent interface crossover) is a feature that automatically detects the type of cable connection and configures the interface accordingly (i.e. straight-through or crossover). This ensures that the connection between the two switches is successful. This is referenced in the CompTIA Network+ Study Manual, page 519.

NEW QUESTION 263

- (Exam Topic 3)

A technician needs to configure a routing protocol for an internet-facing edge router. Which of the following routing protocols will the technician MOST likely use?

- A. BGP
- B. RIPv2
- C. OSPF
- D. EIGRP

Answer: A

NEW QUESTION 268

- (Exam Topic 3)

A technician knows the MAC address of a device and is attempting to find the device's IP address. Which of the following should the technician look at to find the IP address? (Select TWO).

- A. ARP table
- B. DHCP leases
- C. IP route table
- D. DNS cache
- E. MAC address table
- F. STP topology

Answer: BE

NEW QUESTION 271

- (Exam Topic 3)

A company is opening a new building on the other side of its campus. The distance from the closest building to the new building is 1,804ft (550m). The company needs to connect the networking equipment in the new building to the Other buildings on the campus without using a repeater. Which Of the following transceivers should the company use?

- A. 10GBASE-SW
- B. 10GBASE-LR
- C. 10GBASE-LX4 over multimode fiber
- D. 10GBASE-SR

Answer: B

Explanation:

10GBASE-LR is a standard for 10 Gbps Ethernet over single-mode fiber optic cable. It can support a maximum distance of 6.2 miles (10 km), which is much longer than the distance between the buildings. 10GBASE-SW, 10GBASE-LX4, and 10GBASE-SR are all standards for 10 Gbps Ethernet over multimode fiber optic cable, which have shorter maximum distances ranging from 984ft (300m) to 1,312ft (400m).

References: CompTIA Network+ Certification Exam Objectives Version 7.0 (N10-007), Objective 1.5: Compare and contrast network cabling types, standards and speeds.

NEW QUESTION 273

- (Exam Topic 3)

A network administrator needs to provide evidence to confirm that recent network outages were caused by increased traffic generated by a recently released application. Which of the following actions will BEST support the administrator's response?

- A. Generate a network baseline report for comparison.
- B. Export the firewall traffic logs.
- C. Collect the router's NetFlow data.
- D. Plot interface statistics for dropped packets.

Answer: C

NEW QUESTION 274

- (Exam Topic 3)

A technician discovered that some information on the local database server was changed during a file transfer to a remote server. Which of the following should concern the technician the MOST?

- A. Confidentiality
- B. Integrity
- C. DDoS
- D. On-path attack

Answer: B

Explanation:

The technician should be most concerned about data integrity and security. If information on the local database server was changed during a file transfer to a remote server, it could indicate that unauthorized access or modifications were made to the data. It could also indicate a failure in the file transfer process, which could result in data loss or corruption. The technician should investigate the cause of the changes and take steps to prevent it from happening again in the future. Additionally, they should verify the integrity of the data and restore it from a backup if necessary to ensure that the correct and complete data is available. The technician should also take appropriate actions such as notifying the system administrator and management of the incident, and following the incident management process to minimize the damage caused by the incident.

NEW QUESTION 276

- (Exam Topic 3)

A new company recently moved into an empty office space. Within days, users in the next office began noticing increased latency and packet drops with their Wi-Fi-connected devices. Which of the following is the MOST likely reason for this issue?

- A. Channel overlap
- B. Distance from the AP
- C. Bandwidth latency
- D. RF attenuation
- E. Network congestion

Answer: A

NEW QUESTION 280

- (Exam Topic 3)

An IT technician needs to increase bandwidth to a server. The server has multiple gigabit ports. Which of the following can be used to accomplish this without replacing hardware?

- A. STP
- B. 802.1Q
- C. Duplex
- D. LACP

Answer: D

Explanation:

LACP stands for Link Aggregation Control Protocol and is a protocol that allows multiple physical ports to be combined into a single logical port. This can increase bandwidth, redundancy, and load balancing for a server. LACP is part of the IEEE 802.3ad standard for link aggregation. STP stands for Spanning Tree Protocol and is a protocol that prevents loops in a network by blocking redundant links. 802.1Q is a standard for VLAN (Virtual Local Area Network) tagging, which allows multiple logical networks to share the same physical infrastructure. Duplex is a mode of communication that determines how data is transmitted and received on a link. Full duplex allows simultaneous transmission and reception, while half duplex allows only one direction at a time.

References: CompTIA Network+ Certification Exam Objectives Version 7.0 (N10-007), Objective 1.5: Compare and contrast network cabling types, standards and speeds.

NEW QUESTION 282

- (Exam Topic 3)

Which of the following would be the BEST choice to connect branch sites to a main office securely?

- A. VPN headend
- B. Proxy server
- C. Bridge
- D. Load balancer

Answer: A

Explanation:

Host-to-Site, or Client-to-Site, VPN allows for remote servers, clients, and other hosts to establish tunnels through a VPN gateway (or VPN headend) via a private

network. The tunnel between the headend and the client host encapsulates and encrypts data.

NEW QUESTION 283

- (Exam Topic 3)

A company wants to add a local redundant data center to its network in case of failure at its primary location. Which of the following would give the LEAST amount of redundancy for the company's network?

- A. Cold site
- B. Hot site
- C. Cloud site
- D. Warm site

Answer: A

NEW QUESTION 288

- (Exam Topic 3)

A systems administrator wants to use the least amount of equipment to segment two departments that have cables terminating in the same room. Which of the following would allow this to occur?

- A. A load balancer
- B. A proxy server
- C. A Layer 3 switch
- D. A hub
- E. A Layer 7 firewall
- F. The RSSI was not strong enough on the link

Answer: C

NEW QUESTION 292

- (Exam Topic 3)

A large metropolitan city is looking to standardize the ability for police department laptops to connect to the city government's VPN. The city would like a wireless solution that provides the largest coverage across the city with a minimal number of transmission towers. Latency and overall bandwidth needs are not high priorities. Which of the following would BEST meet the city's needs?

- A. 5G
- B. LTE
- C. Wi-Fi 4
- D. Wi-Fi 5
- E. Wi-Fi 6

Answer: B

NEW QUESTION 294

- (Exam Topic 3)

Which of the following is an advanced distance vector routing protocol that automates routing tables and also uses some features of link-state routing protocols?

- A. OSPF
- B. RIP
- C. EIGRP
- D. BGP

Answer: C

Explanation:

EIGRP is an advanced distance vector routing protocol that is able to automatically update routing tables and also uses features of link-state routing protocols, such as the ability to send updates about the current topology of the network. EIGRP also has the ability to use a variety of algorithms to determine the best route for a packet to take, allowing for more efficient routing across the network.

NEW QUESTION 297

- (Exam Topic 3)

A network technician recently installed 35 additional workstations. After installation, some users are unable to access network resources. Many of the original workstations that are experiencing the network access issue were offline when the new workstations were turned on. Which of the following is the MOST likely cause of this issue?

- A. Incorrect VLAN setting
- B. Insufficient DHCP scope
- C. Improper NIC setting
- D. Duplicate IP address

Answer: B

NEW QUESTION 300

- (Exam Topic 3)

Which of the following layers of the OSI model receives data from the application layer and converts it into syntax that is readable by other devices on the network?

- A. Layer 1
- B. Layer 3

- C. Layer 6
- D. Layer 7

Answer: C

NEW QUESTION 303

- (Exam Topic 3)

A network technician is working at a new office location and needs to connect one laptop to another to transfer files. The laptops are newer models and do not have Ethernet ports. Access points are not available either. Which Of the following types Of wireless network SSIDs does the network technician need to configure to be able to connect the laptops together?

- A. Independent Basic Service Set
- B. Extended Service Set
- C. Distribution System Service
- D. Basic Service Set

Answer: A

Explanation:

An Independent Basic Service Set (IBSS) is a type of wireless network that does not require an access point or a wired network. An IBSS allows wireless devices to communicate directly with each other using ad hoc mode. An IBSS is also known as an ad hoc network or a peer-to-peer network. A network technician can configure an IBSS to connect two laptops together and transfer files.

References: Network+ Study Guide Objective 1.4: Explain the properties and characteristics of TCP/IP

NEW QUESTION 307

- (Exam Topic 3)

An administrator would like to allow Windows clients from outside me office to access workstations without using third-party software. Which or the following access methods would meet this requirement?

- A. Remote desktop gateway
- B. Spit tunnel
- C. Site-to-site VPN
- D. VNC

Answer: A

Explanation:

To allow Windows clients from outside the office to access workstations without using third-party software, the administrator can use the Remote Desktop Protocol (RDP). RDP is a built-in feature of the Windows operating system that allows users to remotely connect to and control other Windows computers over a network connection.

To use RDP, the administrator will need to enable the Remote Desktop feature on the workstations that need to be accessed, and ensure that the appropriate firewall rules are in place to allow RDP traffic to pass through. The administrator will also need to provide the remote users with the necessary credentials to access the workstations.

Once RDP is set up and configured, the remote users can use the Remote Desktop client on their own computers to connect to the workstations and access them as if they were physically present in the office. This allows the administrator to provide remote access to the workstations without the need for any additional software or third-party tools.

NEW QUESTION 312

- (Exam Topic 3)

An international company is transferring its IT assets including a number of WAPs from the United States to an office in Europe for deployment. Which of the following considerations should the company research before implementing the wireless hardware?

- A. WPA2 cipher
- B. Regulatory Impacts
- C. CDMA configuration
- D. 802.11 standards

Answer: B

Explanation:

When transferring IT assets, including wireless access points (WAPs), from one country to another, it's important to research the regulatory impacts of the move. Different countries have different regulations and compliance requirements for wireless devices, such as frequency bands, power levels, and encryption standards. Failing to comply with these regulations can result in fines or other penalties.

NEW QUESTION 315

- (Exam Topic 3)

A network engineer needs to create a subnet that has the capacity for five VLANs. with the following number of clients lo be allowed on each:

VLAN 10	50 users
VLAN 20	35 users
VLAN 30	20 users
VLAN 40	75 users
VLAN 50	130 users

Which of the following is the SMALLEST subnet capable of this setup that also has the capacity to double the number of clients in the future?

- A. 10.0.0.0/21
- B. 10.0.0.0/22

- C. 10.0.0.0/23
- D. 10.0.0.0/24

Answer: B

NEW QUESTION 318

- (Exam Topic 3)

An employee working in a warehouse facility is experiencing interruptions in mobile applications while walking around the facility. According to a recent site survey, the WLAN comprises autonomous APs that are directly connected to the internet, providing adequate signal coverage. Which of the following is the BEST solution to improve network stability?

- A. Implement client roaming using an extended service deployment employing a wireless controller.
- B. Remove omnidirectional antennas and adopt a directional bridge.
- C. Ensure all APs of the warehouse support MIMO and Wi-Fi 4.
- D. Verify that the level of EIRP power settings is set to the maximum permitted by regulations.

Answer: A

Explanation:

Client roaming refers to the ability of a wireless device to seamlessly connect to a different access point (AP) as the user moves around the facility. This can help to improve network stability and reduce interruptions in mobile applications. An extended service deployment is a type of wireless network configuration that uses multiple APs to cover a large area, such as a warehouse facility. By using a wireless controller to manage the APs, the network can be better optimized for client roaming, which can improve network stability.

"Roaming With multiple WAPs in an ESS, clients will connect to whichever WAP has the strongest signal. As clients move through the space covered by the broadcast area, they will change WAP connections seamlessly, a process called roaming."

NEW QUESTION 322

- (Exam Topic 3)

Which of the following can be used to decrease latency during periods of high utilization of a firewall?

- A. Hot site
- B. NIC teaming
- C. HA pair
- D. VRRP

Answer: B

Explanation:

NIC Teaming, also known as load balancing and failover (LBFO), allows multiple network adapters on a computer to be placed into a team for the following purposes: (<https://www.bing.com/search?q=what+is+nic+teaming+used+for%3F&form=QBLH&sp=-1&pq=what+is+nic>)

NEW QUESTION 326

- (Exam Topic 3)

A computer engineer needs to ensure that only a specific workstation can connect to port 1 on a switch. Which of the following features should the engineer configure on the switch interface?

- A. Port tagging
- B. Port security
- C. Port mirroring
- D. Port aggregation

Answer: B

Explanation:

Port security is a feature that can be configured on a switch interface to limit and identify the MAC addresses of workstations that are allowed to connect to that specific port. This can help ensure that only a specific workstation (or workstations) can connect to the interface. According to the CompTIA Network+ Study Manual, "Port security can be used to specify which MAC addresses are allowed to connect to a particular switch port. If a port security violation is detected, the switch can take a number of different actions, such as shutting down the port, sending an SNMP trap, or sending an email alert."

NEW QUESTION 330

- (Exam Topic 3)

An ISP is unable to provide services to a user in a remote area through cable and DSL. Which of the following is the NEXT best solution to provide services without adding external infrastructure?

- A. Fiber
- B. Leased line
- C. Satellite
- D. Metro optical

Answer: C

Explanation:

If an ISP is unable to provide services to a user in a remote area through cable and DSL, the next best solution to provide services without adding external infrastructure would likely be satellite. Satellite is a wireless communication technology that uses a network of satellites orbiting the Earth to transmit and receive data. It is well-suited for providing connectivity to remote or rural areas where other types of infrastructure may not be available or may be cost-prohibitive to install.

NEW QUESTION 334

- (Exam Topic 3)

Which of the following is most likely to have the HIGHEST latency while being the most accessible?

- A. Satellite
- B. DSL
- C. Cable
- D. 4G

Answer: A

NEW QUESTION 338

- (Exam Topic 3)

Which of the following BEST describes a split-tunnel client-to-server VPN connection?

- A. The client sends all network traffic down the VPN tunnel
- B. The client has two different IP addresses that can be connected to a remote site from two different ISPs to ensure availability
- C. The client sends some network traffic down the VPN tunnel and other traffic to the local gateway.
- D. The client connects to multiple remote sites at the same time

Answer: C

Explanation:

In a split-tunnel VPN, the client can access both the local network and the remote network simultaneously, with some network traffic sent through the VPN tunnel and other traffic sent to the local gateway. This approach allows for more efficient use of bandwidth and reduces the load on the VPN server. It also allows the client to continue accessing local resources while connected to the remote network.

NEW QUESTION 342

- (Exam Topic 3)

An administrator notices that after contact with several switches in an MDF they failed due to electrostatic discharge. Which of the following sensors should the administrator deploy to BEST monitor static electricity conditions in the MDF?

- A. Temperature
- B. Humidity
- C. Smoke
- D. Electrical

Answer: B

Explanation:

"Humidity control prevents the buildup of static electricity and reduces the chances of electronic components becoming vulnerable to damage from electrostatic shock; not only can very low humidity lead to increased static electricity, but it can also contribute to health problems, such as skin irritation."

NEW QUESTION 343

- (Exam Topic 3)

Which of the following topologies is designed to fully support applications hosted in on-premises data centers, public or private clouds, and SaaS services?

- A. SDWAN
- B. MAN
- C. PAN
- D. MPLS

Answer: A

NEW QUESTION 344

- (Exam Topic 3)

Users are reporting intermittent Wi-Fi connectivity in specific parts of a building. Which of the following should the network administrator check FIRST when troubleshooting this issue? (Select TWO).

- A. Site survey
- B. EIRP
- C. AP placement
- D. Captive portal
- E. SSID assignment
- F. AP association time

Answer: AC

Explanation:

This is a coverage issue. WAP placement and power need to be checked. Site survey should be done NEXT because it takes a while.

NEW QUESTION 349

- (Exam Topic 3)

Due to space constraints in an IDF, a network administrator can only do a single switch to accommodate three data networks. The administrator needs a configuration that will allow each device to access its expected network without additional connections. The configuration must also allow each device to access the rest of the network. Which of the following should the administrator do to meet these requirements? (Select TWO).

- A. Untag the three VLANs across the uplink
- B. Tag an individual VLAN across the uplink

- C. Untag an individual VLAN per device port
- D. Tag an individual VLAN per device port
- E. Tag the three VLANs across the uplink.
- F. Tag the three VLANs per device port.

Answer: AC

Explanation:

To achieve this, you should do two things:

- Tag the three VLANs across the uplink port that connects to another switch or router. This will allow data packets from different VLANs to cross over into other networks.
- Untag an individual VLAN per device port that connects to an end device. This will assign each device to its expected network without additional connections.

NEW QUESTION 353

- (Exam Topic 3)

A switch is connected to another switch. Incompatible hardware causes a surge in traffic on both switches. Which of the following configurations will cause traffic to pause, allowing the switches to drain buffers?

- A. Speed
- B. Flow control
- C. 802.1Q
- D. Duplex

Answer: B

Explanation:

Flow control is a mechanism that allows a network device to regulate the amount of traffic it can receive or send. Flow control can help prevent congestion and buffer overflow by sending pause frames or signals to the sender when the receiver's buffer is full or nearly full. Flow control can cause traffic to pause, allowing the switches to drain buffers and resume normal operation. Speed is a parameter that determines the data transfer rate of a network link. 802.1Q is a standard for VLAN (Virtual Local Area Network) tagging, which allows multiple logical networks to share the same physical infrastructure. Duplex is a mode of communication that determines how data is transmitted and received on a link. Full duplex allows simultaneous transmission and reception, while half duplex allows only one direction at a time.

References: CompTIA Network+ Certification Exam Objectives Version 7.0 (N10-007), Objective 1.5: Compare and contrast network cabling types, standards and speeds.

NEW QUESTION 358

- (Exam Topic 3)

A network administrator is troubleshooting a client's device that cannot connect to the network. A physical inspection of the switch shows the RJ45 is connected. The NIC shows no activity lights. The network administrator moves the device to another location and connects to the network without issues. Which Of the following tools would be the BEST option for the network administrator to use to further troubleshoot?

- A. Tone generator
- B. Multimeter
- C. Optical time-domain reflectometer
- D. Cable tester

Answer: D

Explanation:

A cable tester is a tool that can verify the integrity and functionality of a network cable. It can measure the electrical characteristics of the cable, such as resistance, capacitance, and impedance, and detect any faults or defects, such as shorts, opens, or crosstalk. A cable tester can help the network administrator troubleshoot the problem by determining if the cable is faulty or not. A tone generator is a tool that can send an audible signal through a cable to help locate and identify it. A multimeter is a tool that can measure voltage, current, and resistance of electrical circuits. An optical time-domain reflectometer (OTDR) is a tool that can test the quality and length of fiber optic cables.

References: CompTIA Network+ Certification Exam Objectives Version 7.0 (N10-007), Objective 2.3: Given a scenario, use the appropriate tool to support wired or wireless networks.

NEW QUESTION 361

- (Exam Topic 3)

After rebooting an AP a user is no longer able to connect to the enterprise LAN. A technician plugs a laptop into the same network jack and receives the IP 169.254.0.0. Which of the following is MOST likely causing the issue?

- A. DHCP scope exhaustion
- B. Signal attenuation
- C. Channel overlap
- D. Improper DNS configuration

Answer: A

Explanation:

DHCP scope exhaustion occurs when the number of available IP addresses to be leased from a DHCP server have been used up. This could be caused by a large number of clients on the network, or a misconfigured DHCP scope. When this happens, clients will be assigned an IP address from the APIPA range (169.254.0.0 to 169.254.255.255). To resolve this issue, the DHCP scope needs to be expanded or adjusted to accommodate the number of clients on the network.

NEW QUESTION 366

- (Exam Topic 3)

A desktop support department has observed slow wireless speeds for a new line of laptops using the organization's standard image. No other devices have experienced the same issue. Which of the following should the network administrator recommend troubleshooting FIRST to resolve this issue?

- A. Increasing wireless signal power
- B. Installing a new WAP
- C. Changing the protocol associated to the SSID
- D. Updating the device wireless drivers

Answer: D

Explanation:

Wireless drivers can affect the performance and compatibility of your wireless connection. If only a new line of laptops using the organization's standard image has experienced slow wireless speeds, it could be that their wireless drivers are outdated or incompatible with the network. Updating the device wireless drivers could resolve this issue.

Wireless drivers play an important role in the performance of a wireless connection, as they control how the device interacts with the wireless network. If the laptops in question are using an outdated version of the wireless driver, it could be causing the slow speeds. The network administrator should recommend updating the device wireless drivers first to see if this resolves the issue.

NEW QUESTION 367

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

N10-009 Practice Exam Features:

- * N10-009 Questions and Answers Updated Frequently
- * N10-009 Practice Questions Verified by Expert Senior Certified Staff
- * N10-009 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * N10-009 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The N10-009 Practice Test Here](#)