

# CompTIA

## Exam Questions N10-008

CompTIA Network+Exam



**NEW QUESTION 1**

After the A record of a public website was updated, some visitors were unable to access the website. Which of the following should be adjusted to address the issue?

- A. TTL
- B. MX
- C. TXT
- D. SOA

**Answer:** A

**NEW QUESTION 2**

A local firm has hired a consulting company to clean up its IT infrastructure. The consulting company notices remote printing is accomplished by port forwarding via publicly accessible IPs through the firm's firewall. Which of the following would be the MOST appropriate way to enable secure remote printing?

- A. SSH
- B. VPN
- C. Telnet
- D. SSL

**Answer:** A

**NEW QUESTION 3**

A network technician was troubleshooting an issue for a user who was being directed to cloned websites that were stealing credentials. The URLs were correct for the websites but an incorrect IP address was revealed when the technician used ping on the user's PC. After checking the settings, the technician found the DNS server address was incorrect. Which of the following describes the issue?

- A. Rogue DHCP server
- B. Misconfigured HSRP
- C. DNS poisoning
- D. Exhausted IP scope

**Answer:** D

**NEW QUESTION 4**

A network technician is observing the behavior of an unmanaged switch when a new device is added to the network and transmits data. Which of the following BEST describes how the switch processes this information?

- A. The data is flooded out of every port
- B. including the one on which it came in.
- C. The data is flooded out of every port but only in the VLAN where it is located.
- D. The data is flooded out of every port, except the one on which it came in
- E. The data is flooded out of every port, excluding the VLAN where it is located

**Answer:** C

**NEW QUESTION 5**

Which of the following devices would be used to manage a corporate WLAN?

- A. A wireless NAS
- B. A wireless bridge
- C. A wireless router
- D. A wireless controller

**Answer:** D

**NEW QUESTION 6**

A network administrator redesigned the positioning of the APs to create adjacent areas of wireless coverage. After project validation, some users still report poor connectivity when their devices maintain an association to a distanced AP. Which of the following should the network administrator check FIRST?

- A. Validate the roaming settings on the APs and WLAN clients
- B. Verify that the AP antenna type is correct for the new layout
- C. Check to see if MU-MIMO was properly activated on the APs
- D. Deactivate the 2.4GHz band on the APS

**Answer:** A

**NEW QUESTION 7**

A network technician is installing new software on a Windows-based server in a different geographical location. Which of the following would be BEST for the technician to use to perform this task?

- A. RDP
- B. SSH
- C. FTP
- D. DNS

**Answer:** A

#### NEW QUESTION 8

A customer wants to segregate the traffic between guests on a hypervisor. Which of the following does a technician need to configure to meet the requirement?

- A. Virtual switches
- B. OSPF routing
- C. Load balancers
- D. NIC teaming
- E. Fibre Channel

**Answer:** A

#### NEW QUESTION 9

A network device is configured to send critical events to a syslog server; however, the following alerts are not being received:  
Severity 5 LINK-UPDOWN: Interface 1/1, changed state to down Severity 5LINK-UPDOWN: Interface 1/3, changed state to down  
Which of the following describes the reason why the events are not being received?

- A. The network device is not configured to log that level to the syslog server
- B. The network device was down and could not send the event
- C. The syslog server is not compatible with the network device
- D. The syslog server did not have the correct MIB loaded to receive the message

**Answer:** A

#### NEW QUESTION 10

A technician is deploying a new switch model and would like to add it to the existing network monitoring software. The technician wants to know what metrics can be gathered from a given switch. Which of the following should the technician utilize for the switch?

- A. MIB
- B. Trap
- C. Syslog
- D. Audit log

**Answer:** A

#### NEW QUESTION 10

A client recently added 100 users who are using VMs. All users have since reported slow or unresponsive desktops. Reports show minimal network congestion, zero packet loss, and acceptable packet delay. Which of the following metrics will MOST accurately show the underlying performance issues? (Choose two.)

- A. CPU usage
- B. Memory
- C. Temperature
- D. Bandwidth
- E. Latency
- F. Jitter

**Answer:** AB

#### NEW QUESTION 15

Which of the following systems would MOST likely be found in a screened subnet?

- A. RADIUS
- B. FTP
- C. SQL
- D. LDAP

**Answer:** B

#### NEW QUESTION 16

Which of the following is MOST likely to generate significant East-West traffic in a datacenter?

- A. A backup of a large video presentation to cloud storage for archival purposes
- B. A duplication of a hosted virtual server to another physical server for redundancy
- C. A download of navigation data to a portable device for offline access
- D. A query from an IoT device to a cloud-hosted server for a firmware update

**Answer:** B

#### NEW QUESTION 20

Which of the following would be BEST to use to detect a MAC spoofing attack?

- A. Internet Control Message Protocol
- B. Reverse Address Resolution Protocol
- C. Dynamic Host Configuration Protocol

D. Internet Message Access Protocol

**Answer: B**

#### NEW QUESTION 21

There are two managed legacy switches running that cannot be replaced or upgraded. These switches do not support cryptographic functions, but they are password protected. Which of the following should a network administrator configure to BEST prevent unauthorized access?

- A. Enable a management access list
- B. Disable access to unnecessary services.
- C. Configure a stronger password for access
- D. Disable access to remote management
- E. Use an out-of-band access method.

**Answer: A**

#### NEW QUESTION 25

A technician receives feedback that some users are experiencing high amounts of jitter while using the wireless network. While troubleshooting the network, the technician uses the ping command with the IP address of the default gateway and verifies large variations in latency. The technician thinks the issue may be interference from other networks and non-802.11 devices. Which of the following tools should the technician use to troubleshoot the issue?

- A. NetFlow analyzer
- B. Bandwidth analyzer
- C. Protocol analyzer
- D. Spectrum analyzer

**Answer: D**

#### NEW QUESTION 26

A city has hired a new employee who needs to be able to work when traveling at home and at the municipal sourcing of a neighboring city that snares services. The employee is issued a laptop, and a technician needs to train the employee on the appropriate solutions for secure access to the network from all the possible locations On which of the following solutions would the technician MOST likely train the employee?

- A. Site-to-site VPNs between the two city locations and client-to-site software on the employee's laptop for all other remote access
- B. Client-to-site VPNs between the travel locations and site-to-site software on the employee's laptop for all other remote access
- C. Client-to-site VPNs between the two city locations and site-to-site software on the employee's laptop for all other remote access
- D. Site-to-site VPNs between the home and city locations and site-to-site software on the employee's laptop for all other remote access

**Answer: A**

#### NEW QUESTION 30

A network administrator is installing a wireless network at a client's office. Which of the following IEEE 802.11 standards would be BEST to use for multiple simultaneous client access?

- A. CDMA
- B. CSMA/CD
- C. CSMA/CA
- D. GSM

**Answer: A**

#### NEW QUESTION 35

Which of the following routing protocols is used to exchange route information between public autonomous systems?

- A. OSPF
- B. BGP
- C. EIGRP
- D. RIP

**Answer: B**

#### NEW QUESTION 40

A network is experiencing a number of CRC errors during normal network communication. At which of the following layers of the OSI model will the administrator MOST likely start to troubleshoot?

- A. Layer 1
- B. Layer 2
- C. Layer 3
- D. Layer 4
- E. Layer 5
- F. Layer 6
- G. Layer 7

**Answer: B**

#### NEW QUESTION 45

Which of the following is used to prioritize Internet usage per application and per user on the network?

- A. Bandwidth management
- B. Load balance routing
- C. Border Gateway Protocol
- D. Administrative distance

**Answer:** A

**NEW QUESTION 46**

A Chief Information Officer (CIO) wants to improve the availability of a company's SQL database Which of the following technologies should be utilized to achieve maximum availability?

- A. Clustering
- B. Port aggregation
- C. NIC teaming
- D. Snapshots

**Answer:** C

**NEW QUESTION 51**

A branch of a company recently switched to a new ISP. The network engineer was given a new IP range to assign. The ISP assigned 196.26.4.0/26, and the branch gateway router now has the following configurations on the interface that peers to the ISP:

The network engineer observes that all users have lost Internet connectivity. Which of the following describes the issue?

- A. The incorrect subnet mask was configured
- B. The incorrect gateway was configured
- C. The incorrect IPaddress was configured
- D. The incorrect interface was configured

**Answer:** A

**NEW QUESTION 53**

Several WIFI users are reporting the inability to connect to the network. WLAN users on the guest network are able to access all network resources without any performance issues. The following table summarizes the findings after a site survey of the area in question:

Which of the following should a wireless technician do NEXT to troubleshoot this issue?

- A. Reconfigure the channels to reduce overlap
- B. Replace the omni antennas with directional antennas
- C. Update the SSIDs on all the APs
- D. Decrease power in AP 3 and AP 4

**Answer:** A

**NEW QUESTION 57**

Which of the following technologies allows traffic to be sent through two different ISPs to increase performance?

- A. Fault tolerance
- B. Quality of service
- C. Load balancing
- D. Port aggregation

**Answer:** A

**NEW QUESTION 59**

A company that uses VoIP telephones is experiencing intermittent issues with one-way audio and dropped conversations The manufacturer says the system will work if ping times are less than 50ms. The company has recorded the following ping times:

Which of the following is MOST likely causing the issue?

- A. Attenuation
- B. Latency
- C. VLAN mismatch
- D. Jitter

**Answer:** A

#### NEW QUESTION 62

A website administrator is concerned the company's static website could be defaced by hackers or used as a pivot point to attack internal systems. Which of the following should a network security administrator recommend to assist with detecting these activities?

- A. Implement file integrity monitoring.
- B. Change the default credentials.
- C. Use SSL encryption.
- D. Update the web-server software.

**Answer: C**

#### NEW QUESTION 66

A network engineer is investigating reports of poor network performance. Upon reviewing a device configuration, the engineer finds that duplex settings are mismatched on both ends. Which of the following would be the MOST likely result of this finding?

- A. Increased CRC errors
- B. Increased giants and runs
- C. Increased switching loops
- D. Increased device temperature

**Answer: A**

#### NEW QUESTION 67

Branch users are experiencing issues with videoconferencing. Which of the following will the company MOST likely configure to improve performance for these applications?

- A. Link Aggregation Control Protocol
- B. Dynamic routing
- C. Quality of service
- D. Network load balancer
- E. Static IP addresses

**Answer: C**

#### NEW QUESTION 71

A user recently made changes to a PC that caused it to be unable to access websites by both FQDN and IP. Local resources, such as the file server, remain accessible. Which of the following settings did the user MOST likely misconfigure?

- A. Static IP
- B. Default gateway
- C. DNS entries
- D. Local host file

**Answer: B**

#### NEW QUESTION 73

A user tries to ping 192.168.1.100 from the command prompt on the 192.168.2.101 network but gets the following response: U.U.U.U. Which of the following needs to be configured for these networks to reach each other?

- A. Network address translation
- B. Default gateway
- C. Loopback
- D. Routing protocol

**Answer: B**

#### NEW QUESTION 77

The management team needs to ensure unnecessary modifications to the corporate network are not permitted and version control is maintained. Which of the following documents would BEST support this?

- A. An incident response plan
- B. A business continuity plan
- C. A change management policy
- D. An acceptable use policy

**Answer: C**

#### NEW QUESTION 81

Which of the following is the LARGEST MTU for a standard Ethernet frame?

- A. 1452
- B. 1492
- C. 1500
- D. 2304

**Answer: C**

#### NEW QUESTION 82

An IT organization needs to optimize speeds for global content distribution and wants to reduce latency in high-density user locations. Which of the following technologies BEST meets the organization's requirements?

- A. Load balancing
- B. Geofencing
- C. Public cloud
- D. Content delivery network
- E. Infrastructure as a service

**Answer: D**

#### NEW QUESTION 86

Access to a datacenter should be individually recorded by a card reader even when multiple employees enter the facility at the same time. Which of the following allows the enforcement of this policy?

- A. Motion detection
- B. Access control vestibules
- C. Smart lockers
- D. Cameras

**Answer: B**

#### NEW QUESTION 89

A network administrator walks into a datacenter and notices an unknown person is following closely. The administrator stops and directs the person to the security desk. Which of the following attacks did the network administrator prevent?

- A. Evil twin
- B. Tailgating
- C. Piggybacking
- D. Shoulder surfing

**Answer: B**

#### NEW QUESTION 91

Client devices cannot enter a network, and the network administrator determines the DHCP scope is exhausted. The administrator wants to avoid creating a new DHCP pool. Which of the following can the administrator perform to resolve the issue?

- A. Install load balancers
- B. Install more switches
- C. Decrease the number of VLANs
- D. Reduce the lease time

**Answer: D**

#### NEW QUESTION 92

A network administrator is downloading a large patch that will be uploaded to several enterprise switches simultaneously during the day's upgrade cycle. Which of the following should the administrator do to help ensure the upgrade process will be less likely to cause problems with the switches?

- A. Confirm the patch's MD5 hash prior to the upgrade
- B. Schedule the switches to reboot after an appropriate amount of time.
- C. Download each switch's current configuration before the upgrade
- D. Utilize FTP rather than TFTP to upload the patch

**Answer: C**

#### NEW QUESTION 97

A network administrator is designing a new datacenter in a different region that will need to communicate to the old datacenter with a secure connection. Which of the following access methods would provide the BEST security for this new datacenter?

- A. Virtual network computing
- B. Secure Socket Shell
- C. In-band connection
- D. Site-to-site VPN

**Answer: D**

#### NEW QUESTION 99

A network field technician is installing and configuring a secure wireless network. The technician performs a site survey. Which of the following documents would MOST likely be created as a result of the site survey?

- A. Physical diagram
- B. Heat map
- C. Asset list
- D. Device map

**Answer:** B

**NEW QUESTION 104**

A technician needs to configure a Linux computer for network monitoring. The technician has the following information:  
Linux computer details:

Switch mirror port details:

After connecting the Linux computer to the mirror port on the switch, which of the following commands should the technician run on the Linux computer?

- A. ifconfig ecth0 promisc
- B. ifconfig eth1 up
- C. ifconfig eth0 10.1.2.3
- D. ifconfig eth1 hw ether A1:B2:C3:D4:E5:F6

**Answer:** A

**NEW QUESTION 109**

Which of the following security devices would be BEST to use to provide mechanical access control to the MDF/IDF?

- A. A smart card
- B. A key fob
- C. An employee badge
- D. A door lock

**Answer:** B

**NEW QUESTION 113**

At which of the following OSI model layers would a technician find an IP header?

- A. Layer 1
- B. Layer 2
- C. Layer 3
- D. Layer 4

**Answer:** C

**NEW QUESTION 118**

.....

## Thank You for Trying Our Product

### We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

### N10-008 Practice Exam Features:

- \* N10-008 Questions and Answers Updated Frequently
- \* N10-008 Practice Questions Verified by Expert Senior Certified Staff
- \* N10-008 Most Realistic Questions that Guarantee you a Pass on Your First Try
- \* N10-008 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

**100% Actual & Verified — Instant Download, Please Click**  
**[Order The N10-008 Practice Test Here](#)**