

Amazon

Exam Questions AWS-Certified-Solutions-Architect-Professional

Amazon AWS Certified Solutions Architect Professional



NEW QUESTION 1

In the context of AWS IAM, identify a true statement about user passwords (login profiles).

- A. They must contain Unicode characters.
- B. They can contain any Basic Latin (ASCII) characters.
- C. They must begin and end with a forward slash (/).
- D. They cannot contain Basic Latin (ASCII) characters.

Answer: B

Explanation:

The user passwords (login profiles) of IAM users can contain any Basic Latin (ASCII) characters. Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/LimitationsOnEntities.html>

NEW QUESTION 2

What is the default maximum number of VPCs allowed per region?

- A. 5
- B. 10
- C. 100
- D. 15

Answer: A

Explanation:

The maximum number of VPCs allowed per region is 5.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Appendix_Limits.html

NEW QUESTION 3

An organization has 4 people in the IT operations team who are responsible to manage the AWS infrastructure. The organization wants to setup that each user will have access to launch and manage an instance in a zone which the other user cannot modify. Which of the below mentioned options is the best solution to set this up?

- A. Create four AWS accounts and give each user access to a separate account.
- B. Create an IAM user and allow them permission to launch an instance of a different sizes only.
- C. Create four IAM users and four VPCs and allow each IAM user to have access to separate VPCs.
- D. Create a VPC with four subnets and allow access to each subnet for the individual IAM user

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. The user can create subnets as per the requirement within a VPC. The VPC also work with IAM and the organization can create IAM users who have access to various VPC services. The organization can setup access for the IAM user who can modify the security groups of the VPC. The sample policy is given below:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "ec2:RunInstances",
      "Resource": [
        "arn:aws:ec2:region::image/ami-*",
        "arn:aws:ec2:region:account:subnet/subnet-1a2b3c4d",
        "arn:aws:ec2:region:account:network-interface/*",
        "arn:aws:ec2:region:account:volume/*",
        "arn:aws:ec2:region:account:key-pair/*",
        "arn:aws:ec2:region:account:security-group/sg-123abc123"
      ]
    }
  ]
}
```

With this policy the user can create four subnets in separate zones and provide IAM user access to each subnet

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_IAM.html

NEW QUESTION 4

An organization is planning to host an application on the AWS VPC. The organization wants dedicated instances. However, an AWS consultant advised the organization not to use dedicated instances with VPC as the design has a few limitations. Which of the below mentioned statements is not a limitation of dedicated instances with VPC?

- A. All instances launched with this VPC will always be dedicated instances and the user cannot use a default tenancy model for them.
- B. It does not support the AWS RDS with a dedicated tenancy VPC.
- C. The user cannot use Reserved Instances with a dedicated tenancy model.
- D. The EBS volume will not be on the same tenant hardware as the EC2 instance though the user has configured dedicated tenancy.

Answer: C

Explanation:

The Amazon Virtual Private Cloud (Amazon VPC) allows the user to define a virtual networking environment in a private, isolated section of the Amazon Web Services (AWS) cloud. The user has complete control over the virtual networking environment. Dedicated instances are Amazon EC2 instances that run in a Virtual Private Cloud (VPC) on hardware that is dedicated to a single customer. The client's dedicated instances are physically isolated at the host hardware level from instances that are not dedicated instances as well as from instances that belong to other AWS accounts.

All instances launched with the dedicated tenancy model of VPC will always be dedicated instances. Dedicated tenancy has a limitation that it may not support a few services, such as RDS. Even the EBS will not be on dedicated hardware. However the user can save some cost as well as reserve some capacity by using a Reserved Instance model with dedicated tenancy.

Reference: <http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/dedicated-instance.html>

NEW QUESTION 5

How many g2.2xlarge on-demand instances can a user run in one region without taking any limit increase approval from AWS?

- A. 20
- B. 2
- C. 5
- D. 10

Answer: C

Explanation:

Generally AWS EC2 allows running 20 on-demand instances and 100 spot instances at a time. This limit can be increased by requesting at <https://aws.amazon.com/contact-us/ec2-request>. Excluding certain types of instances, the limit is lower than mentioned above. For g2.2xlarge, the user can run only 5

on-demand instance at a time.

Reference: http://docs.aws.amazon.com/general/latest/gr/aws_service_limits.html#limits_ec2

NEW QUESTION 6

When does an AWS Data Pipeline terminate the AWS Data Pipeline-managed compute resources?

- A. AWS Data Pipeline terminates AWS Data Pipeline-managed compute resources every 2 hours.
- B. When the final actMty that uses the resources is running
- C. AWS Data Pipeline terminates AWS Data Pipeline-managed compute resources every 12 hours.
- D. When the final actMty that uses the resources has completed successfully or failed

Answer: D

Explanation:

Compute resources will be provisioned by AWS Data Pipeline when the first actMty for a scheduled time that uses those resources is ready to run, and those instances will be terminated when the final actMty that uses the resources has completed successfully or failed.

Reference: <https://aws.amazon.com/datapipeline/faqs/>

NEW QUESTION 7

The Principal element of an IAM policy refers to the specific entity that should be allowed or denied permission, whereas the translates to everyone except the specified entity.

- A. NotPrincipal
- B. Vendor
- C. Principal
- D. Action

Answer: A

Explanation:

The element NotPrincipal that is included within your IAM policy statements allows you to specify an exception to a list of principals to whom the access to a specific resource is either allowed or denied. Use the NotPrincipal element to specify an exception to a list of principals. For example, you can deny access to all principals except the one named in the NotPrincipal element.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/reference_policies_elements.html#Principal

NEW QUESTION 8

Doug has created a VPC with CIDR 10.201.0.0/16 in his AWS account. In this VPC he has created a public subnet with CIDR block 10.201.31.0/24. While launching a new EC2 from the console, he is not able to assign the private IP address 10.201.31.6 to this instance. Which is the most likely reason for this issue?

- A. Private address IP 10.201.31.6 is currently assigned to another interface.
- B. Private IP address 10.201.31.6 is reserved by Amazon for IP networking purposes.
- C. Private IP address 10.201.31.6 is blocked via ACLs in Amazon infrastructure as a part of platform security.
- D. Private IP address 10.201.31.6 is not part of the associated subnet's IP address rang

Answer: A

Explanation:

In Amazon VPC, you can assign any Private IP address to your instance as long as it is: Part of the associated subnet's IP address range

Not reserved by Amazon for IP networking purposes Not currently assigned to another interface Reference: <http://aws.amazon.com/vpc/faqs/>

NEW QUESTION 9

If no explicit deny is found while applying IAM's Policy Evaluation Logic, the enforcement code looks for any instructions that would apply to the request.

- A. "cancel"
- B. "suspend"
- C. "allow"
- D. "valid"

Answer: C

Explanation:

If an explicit deny is not found among the applicable policies for a specific request, IAM's Policy Evaluation Logic checks for any "allow" instructions to check if the request can be successfully completed.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_EvaluationLogic.html

NEW QUESTION 10

An organization is hosting a scalable web application using AWS. The organization has configured ELB and Auto Scaling to make the application scalable. Which of the below mentioned statements is not required to be followed for ELB when the application is planning to host a web application on VPC?

- A. The ELB and all the instances should be in the same subnet.
- B. Configure the security group rules and network ACLs to allow traffic to be routed between the subnets in the VPC.
- C. The internet facing ELB should have a route table associated with the internet gateway.
- D. The internet facing ELB should be only in a public subne

Answer: A

Explanation:

Amazon Virtual Private Cloud (Amazon VPC) allows the user to define a virtual networking environment in a private, isolated section of the Amazon Web Services (AWS) cloud. The user has complete control over the virtual networking environment. Within this virtual private cloud, the user can launch AWS resources, such as an ELB, and EC2 instances. There are two ELBs available with VPC: internet facing and internal (private) ELB. For the internet facing ELB it is required that the ELB should be in a public subnet. After the user creates the public subnet, he should ensure to associate the route table of the public subnet with the internet gateway to enable the load balancer in the subnet to connect with the internet. The ELB and instances can be in a separate subnet. However, to allow communication between the instance and the

ELB the user must configure the security group rules and network ACLs to allow traffic to be routed between the subnets in his VPC.

Reference: <http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/CreateVPCForELB.html>

NEW QUESTION 10

How can multiple compute resources be used on the same pipeline in AWS Data Pipeline?

- A. You can use multiple compute resources on the same pipeline by defining multiple cluster objects in your definition file and associating the cluster to use for each actMty via its runsOn field.
- B. You can use multiple compute resources on the same pipeline by defining multiple cluster definition files.
- C. You can use multiple compute resources on the same pipeline by defining multiple clusters for your actMty.
- D. You cannot use multiple compute resources on the same pipelin

Answer: A

Explanation:

Multiple compute resources can be used on the same pipeline in AWS Data Pipeline by defining multiple cluster objects in your definition file and associating the cluster to use for each actMty via its runsOn field, which allows pipelines to combine AWS and on-premise resources, or to use a mix of instance types for their actMties.

Reference: <https://aws.amazon.com/datapipeline/faqs/>

NEW QUESTION 14

The two policies that you attach to an IAM role are the access policy and the trust policy. The trust policy identifies who can assume the role and grants the permission in the AWS Lambda account principal by adding the action.

- A. aws:AssumeAdmin
- B. lambda:InvokeAsync
- C. sts:InvokeAsync
- D. sts:AssumeRole

Answer: D

Explanation:

The two policies that you attach to an IAM role are the access policy and the trust policy.

Remember that adding an account to the trust policy of a role is only half of establishing the trust relationship. By default, no users in the trusted accounts can assume the role until the administrator for that account grants the users the permission to assume the role by adding the Amazon Resource Name (ARN) of the role to an Allow element for the sts:AssumeRole action.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/id_roles_manage_modify.html

NEW QUESTION 17

One of your AWS Data Pipeline actMties has failed consequently and has entered a hard failure state after retrying thrice. You want to try it again. Is it possible to increase the number of automatic retries to more than thrice?

- A. Yes, you can increase the number of automatic retries to 6.
- B. Yes, you can increase the number of automatic retries to indefinite number.
- C. No, you cannot increase the number of automatic retries.
- D. Yes, you can increase the number of automatic retries to 10.

Answer: D

Explanation:

In AWS Data Pipeline, an actMty fails if all of its actMty attempts return with a failed state. By default, an actMty retries three times before entering a hard failure state. You can increase the number of automatic retries to 10. However, the system does not allow indefinite retries.

Reference: <https://aws.amazon.com/datapipeline/faqs/>

NEW QUESTION 18

IAM Secure And Scalable is an organization which provides scalable and secure SAAS to its clients. They are planning to host a web server and App server on AWS VPC as separate tiers. The organization wants to implement the scalability by configuring Auto Scaling and load balancer with their app servers (middle tier) too. Which of the below mentioned options suits their requirements?

- A. Since ELB is internet facing, it is recommended to setup HAProxy as the Load balancer within the VPC.
- B. Create an Internet facing ELB with VPC and configure all the App servers with it.

- C. The user should make ELB with EC2-CLASSIC and enable SSH with it for security.
D. Create an Internal Load balancer with VPC and register all the App servers with it

Answer: D

Explanation:

The Amazon Virtual Private Cloud (Amazon VPC) allows the user to define a virtual networking environment in a private, isolated section of the Amazon Web Services (AWS) cloud. The user has complete control over the virtual networking environment. Within this virtual private cloud, the user can launch AWS resources, such as an ELB, and EC2 instances.

There are two ELBs available with VPC: internet facing and internal (private) ELB. For internal servers, such as App servers the organization can create an internal load balancer in their VPC and then place back-end application instances behind the internal load balancer. The internal load balancer will route requests to the back-end application instances, which are also using private IP addresses and only accept requests from the internal load balancer.

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/vpc-loadbalancer-types.html>

NEW QUESTION 23

True or False: Amazon ElastiCache supports the Redis key-value store.

- A. True, ElastiCache supports the Redis key-value store, but with limited functionalities.
B. False, ElastiCache does not support the Redis key-value store.
C. True, ElastiCache supports the Redis key-value store.
D. False, ElastiCache supports the Redis key-value store only if you are in a VPC environment

Answer: C

Explanation:

This is true. ElastiCache supports two open-source in-memory caching engines: 1. Memcached - a widely adopted memory object caching system. ElastiCache is protocol compliant with Memcached, so popular tools that you use today with existing Memcached environments will work seamlessly with the service. 2. Redis - a popular open-source in-memory key-value store that supports data structures such as sorted sets and lists. ElastiCache supports Master / Slave replication and Multi-AZ which can be used to achieve cross AZ redundancy.

Reference: <https://aws.amazon.com/elasticache/>

NEW QUESTION 26

An organization is setting up an application on AWS to have both High Availability (HA) and Disaster Recovery (DR). The organization wants to have both Recovery point objective (RPO) and Recovery time objective (RTO) of 10 minutes. Which of the below mentioned service configurations does not help the organization achieve the said RPO and RTO?

- A. Take a snapshot of the data every 10 minutes and copy it to the other region.
B. Use an elastic IP to assign to a running instance and use Route 53 to map the user's domain with that IP.
C. Create ELB with multi-region routing to allow automated failover when required.
D. Use an AMI copy to keep the AMI available in other region

Answer: C

Explanation:

AWS provides an on demand, scalable infrastructure. AWS EC2 allows the user to launch On-Demand instances and the organization should create an AMI of the running instance. Copy the AMI to another region to enable Disaster Recovery (DR) in case of region failure. The organization should also use EBS for persistent storage and take a snapshot every 10 minutes to meet Recovery time objective (RTO). They should also setup an elastic IP and use it with Route 53 to route requests to the same IP.

When one of the instances fails the organization can launch new instances and assign the same EIP to a new instance to achieve High Availability (HA). The ELB works only for a particular region and does not route requests across regions.

Reference: http://d36cz9buwru1tt.cloudfront.net/AWS_Disaster_Recovery.pdf

NEW QUESTION 30

What feature of the load balancing service attempts to force subsequent connections to a service to be redirected to the same node as long as it is online?

- A. Node balance
B. Session retention
C. Session multiplexing
D. Session persistence

Answer: D

Explanation:

Session persistence is a feature of the load balancing service. It attempts to force subsequent connections to a service to be redirected to the same node as long as it is online.

Reference:

<http://docs.rackspace.com/loadbalancers/api/v1.0/clb-devguide/content/Concepts-d1e233.html>

NEW QUESTION 31

The CFO of a company wants to allow one of his employees to view only the AWS usage report page. Which of the below mentioned IAM policy statements allows the user to have access to the AWS usage report page?

- A. "Effect": "Allow", "Action": ["Describe"], "Resource": "Billing"
B. "Effect": "Allow", "Action": ["aws-portal:ViewBilling"], "Resource": "*"
C. "Effect": "Allow", "Action": ["aws-portal:ViewUsage"], "Resource": "*"
D. "Effect": "Allow", "Action": ["AccountUsage"], "Resource": "*"

Answer: C

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If the CFO wants to allow only AWS usage report page access, the policy for that IAM user will be as given below:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow", "Action": [
        "aws-portal:ViewUsage"
      ],
      "Resource": "*"
    }
  ]
}
```

Reference: <http://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/billing-permissions-ref.html>

NEW QUESTION 35

A user is planning to use EBS for his DB requirement. The user already has an EC2 instance running in the VPC private subnet. How can the user attach the EBS volume to a running instance?

- A. The user can create EBS in the same zone as the subnet of instance and attach that EBS to instance.
- B. It is not possible to attach an EBS to an instance running in VPC until the instance is stopped.
- C. The user can specify the same subnet while creating EBS and then attach it to a running instance.
- D. The user must create EBS within the same VPC and then attach it to a running instance.

Answer: A

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. The user can create subnets as per the requirement within a VPC. The VPC is always specific to a region. The user can create a VPC which can span multiple Availability Zones by adding one or more subnets in each Availability Zone. The instance launched will always be in the same availability zone of the respective subnet. When creating an EBS the user cannot specify the subnet or VPC. However, the user must create the EBS in the same zone as the instance so that it can attach the EBS volume to the running instance.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Subnets.html#VPCSubnet

NEW QUESTION 36

A user is trying to create a vault in AWS Glacier. The user wants to enable notifications. In which of the below mentioned options can the user enable the notifications from the AWS console?

- A. Glacier does not support the AWS console
- B. Archival Upload Complete
- C. Vault Upload Job Complete
- D. Vault Inventory Retrieval Job Complete

Answer: D

Explanation:

From AWS console the user can configure to have notifications sent to Amazon Simple Notifications Service (SNS). The user can select specific jobs that, on completion, will trigger the notifications such as Vault Inventory Retrieval Job Complete and Archive Retrieval Job Complete.

Reference: <http://docs.aws.amazon.com/amazonglacier/latest/dev/configuring-notifications-console.html>

NEW QUESTION 38

ExamKiller has three separate departments and each department has their own AWS accounts. The HR department has created a file sharing site where all the on roll employees' data is uploaded. The Admin department uploads data about the employee presence in the office to their DB hosted in the VPC. The Finance department needs to access data from the HR department to know the on roll employees to calculate the salary based on the number of days that an employee is present in the office.

How can ExamKiller setup this scenario?

- A. It is not possible to configure VPC peering since each department has a separate AWS account.
- B. Setup VPC peering for the VPCs of Admin and Finance.
- C. Setup VPC peering for the VPCs of Finance and HR as well as between the VPCs of Finance and Admin.
- D. Setup VPC peering for the VPCs of Admin and HR

Answer: C

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. A VPC peering connection allows the user to route traffic between the peer VPCs using private IP addresses as if they are a part of the same network. This is helpful when one VPC from the same or different AWS account wants to connect with resources of the other VPC.

Reference:

<http://docs.aws.amazon.com/AmazonVPC/latest/PeeringGuide/peering-configurations-full-access.html#three-vpcs-full-access>

NEW QUESTION 40

An organization is undergoing a security audit. The auditor wants to view the AWS VPC configurations as the organization has hosted all the applications in the AWS VPC. The auditor is from a remote place and wants to have access to AWS to view all the VPC records.

How can the organization meet the expectations of the auditor without compromising on the security of their AWS infrastructure?

- A. The organization should not accept the request as sharing the credentials means compromising on security.
- B. Create an IAM role which will have read only access to all EC2 services including VPC and assign that role to the auditor.
- C. Create an IAM user who will have read only access to the AWS VPC and share those credentials with the auditor.
- D. The organization should create an IAM user with VPC full access but set a condition that will not allow to modify anything if the request is from any IP other than

the organization's data center.

Answer: C

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. The user can create subnets as per the requirement within a VPC. The VPC also works with IAM and the organization can create IAM users who have access to various VPC services.

If an auditor wants to have access to the AWS VPC to verify the rules, the organization should be careful before sharing any data which can allow making updates to the AWS infrastructure. In this scenario it is recommended that the organization creates an IAM user who will have read only access to the VPC. Share the above mentioned credentials with the auditor as it cannot harm the organization. The sample policy is given below:

```
{
  "Effect": "Allow",
  "Action": [ "ec2:DescribeVpcs", "ec2:DescribeSubnets",
    "ec2:DescribeInternetGateways", "ec2:DescribeCustomerGateways", "ec2:DescribeVpnGateways", "ec2:DescribeVpnConnections", "ec2:DescribeRouteTables",
    "ec2:DescribeAddresses", "ec2:DescribeSecurityGroups", "ec2:DescribeNetworkAcls", "ec2:DescribeDhcpOptions", "ec2:DescribeTags", "ec2:DescribeInstances"
  ],
  "Resource": "*"
}
```

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_IAM.html

NEW QUESTION 45

What is the maximum length for an instance profile name in AWS IAM?

- A. 512 characters
- B. 128 characters
- C. 1024 characters
- D. 64 characters

Answer: B

Explanation:

The maximum length for an instance profile name is 128 characters.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/LimitationsOnEntities.html>

NEW QUESTION 48

A user has configured EBS volume with PIOPS. The user is not experiencing the optimal throughput. Which of the following could not be factor affecting I/O performance of that EBS volume?

- A. EBS bandwidth of dedicated instance exceeding the PIOPS
- B. EC2 bandwidth
- C. EBS volume size
- D. Instance type is not EBS optimized

Answer: C

Explanation:

If the user is not experiencing the expected IOPS or throughput that is provisioned, ensure that the EC2 bandwidth is not the limiting factor, the instance is EBS-optimized (or include 10 Gigabit network connectMty) and the instance type EBS dedicated bandwidth exceeds the IOPS more than he has provisioned.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-io-characteristics.html>

NEW QUESTION 53

Which statement is NOT true about a stack which has been created in a Virtual Private Cloud (VPC) in AWS OpsWorks?

- A. Subnets whose instances cannot communicate with the Internet are referred to as public subnets.
- B. Subnets whose instances can communicate only with other instances in the VPC and cannot communicate directly with the Internet are referred to as private subnets.
- C. All instances in the stack should have access to any package repositories that your operating system depends on, such as the Amazon Linux or Ubuntu Linux repositories.
- D. Your app and custom cookbook repositories should be accessible for all instances in the stack

Answer: A

Explanation:

In AWS OpsWorks, you can control user access to a stack's instances by creating it in a virtual private cloud (VPC). For example, you might not want users to have direct access to your stack's app servers or databases and instead require that all public traffic be channeled through an Elastic Load Balancer.

A VPC consists of one or more subnets, each of which contains one or more instances. Each subnet has an associated routing table that directs outbound traffic based on its destination IP address.

Instances within a VPC can generally communicate with each other, regardless of their subnet. Subnets whose instances can communicate with the Internet are referred to as public subnets. Subnets whose instances can communicate only with other instances in the VPC and cannot communicate directly with the Internet are referred to as private subnets.

AWS OpsWorks requires the VPC to be configured so that every instance in the stack, including instances in private subnets, has access to the following endpoints:

The AWS OpsWorks service, <https://opsworks-instance-service.us-east-1.amazonaws.com> . Amazon S3

The package repositories for Amazon Linux or Ubuntu 12.04 LTS, depending on which operating system you specify.

Your app and custom cookbook repositories. Reference:

<http://docs.aws.amazon.com/opsworks/latest/userguide/workingstacks-vpc.html#workingstacks-vpc-basics>

NEW QUESTION 58

What RAID method is used on the Cloud Block Storage back-end to implement a very high level of reliability and performance?

- A. RAID 1 (Mirror)
- B. RAID 5 (Blocks striped, distributed parity)
- C. RAID 10 (Blocks mirrored and striped)
- D. RAID 2 (Bit level striping)

Answer: C

Explanation:

Cloud Block Storage back-end storage volumes employs the RAID 10 method to provide a very high level of reliability and performance.

Reference: http://www.rackspace.com/knowledge_center/product-faq/cloud-block-storage

NEW QUESTION 63

In Amazon SNS, to send push notifications to mobile devices using Amazon SNS and ADM, you need to obtain the following, except:

- A. Device token
- B. Client ID
- C. Registration ID
- D. Client secret

Answer: A

Explanation:

To send push notifications to mobile devices using Amazon SNS and ADM, you need to obtain the following: Registration ID and Client secret.

Reference: <http://docs.aws.amazon.com/sns/latest/dg/SNSMobilePushPrereq.html>

NEW QUESTION 66

An organization is setting up a highly scalable application using Elastic Beanstalk. They are using Elastic Load Balancing (ELB) as well as a Virtual Private Cloud (VPC) with public and private subnets. They have the following requirements:

- . All the EC2 instances should have a private IP
- . All the EC2 instances should receive data via the ELB's. Which of these will not be needed in this setup?

- A. Launch the EC2 instances with only the public subnet.
- B. Create routing rules which will route all inbound traffic from ELB to the EC2 instances.
- C. Configure ELB and NAT as a part of the public subnet only.
- D. Create routing rules which will route all outbound traffic from the EC2 instances through NA

Answer: A

Explanation:

The Amazon Virtual Private Cloud (Amazon VPC) allows the user to define a virtual networking environment in a private, isolated section of the Amazon Web Services (AWS) cloud. The user has complete control over the virtual networking environment. If the organization wants the Amazon EC2 instances to have a private IP address, he should create a public and private subnet for VPC in each Availability Zone (this is an AWS Elastic Beanstalk requirement). The organization should add their public resources, such as ELB and NAT to the public subnet, and AWS Elastic Beanstalk will assign them unique elastic IP addresses (a static, public IP address). The organization should launch Amazon EC2 instances in a private subnet so that AWS Elastic Beanstalk assigns them non-routable private IP addresses. Now the organization should configure route tables with the following rules:

- . route all inbound traffic from ELB to EC2 instances
- . route all outbound traffic from EC2 instances through NAT

Reference: <http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/AWSHowTo-vpc.html>

NEW QUESTION 70

An organization is making software for the CIA in US

- A. CIA agreed to host the application on AWS but in a secure environment
- B. The organization is thinking of hosting the application on the AWS GovCloud region
- C. Which of the below mentioned difference is not correct when the organization is hosting on the AWS GovCloud in comparison with the AWS standard region?
- D. The billing for the AWS GovCloud will be in a different account than the Standard AWS account.
- E. GovCloud region authentication is isolated from Amazon.com.
- F. Physical and logical administrative access only to U.S. persons.
- G. persons.
- H. It is physically isolated and has logical network isolation from all the other region

Answer: A

Explanation:

AWS GovCloud (US) is an isolated AWS region designed to allow U.S. government agencies and customers to move sensitive workloads into the cloud by addressing their specific regulatory and compliance requirements. The AWS GovCloud (US) Region adheres to the U.S. International Traffic in Arms Regulations (ITAR) requirements. It has added advantages, such as: Restricting physical and logical administrative access to U.S. persons only. There will be a separate AWS GovCloud (US) credentials, such as access key and secret access key than the standard AWS account.

The user signs in with the IAM user name and password.

The AWS GovCloud (US) Region authentication is completely isolated from Amazon.com.

If the organization is planning to host on EC2 in AWS GovCloud then it will be billed to standard AWS account of organization since AWS GovCloud billing is linked with the standard AWS account and is not billed separately.

Reference: <http://docs.aws.amazon.com/govcloud-us/latest/UserGuide/whatis.html>

NEW QUESTION 74

How does in-memory caching improve the performance of applications in ElastiCache?

- A. It improves application performance by deleting the requests that do not contain frequently accessed data.
- B. It improves application performance by implementing good database indexing strategies.
- C. It improves application performance by using a part of instance RAM for caching important data.
- D. It improves application performance by storing critical pieces of data in memory for low-latency access

Answer: D

Explanation:

In Amazon ElastiCache, in-memory caching improves application performance by storing critical pieces of data in memory for low-latency access. Cached information may include the results of I/O-intensive database queries or the results of computationally intensive calculations.

Reference: <http://aws.amazon.com/elasticache/faqs/#g4>

NEW QUESTION 76

An organization is setting up a multi-site solution where the application runs on premise as well as on AWS to achieve the minimum recovery time objective(RTO). Which of the below mentioned configurations will not meet the requirements of the multi-site solution scenario?

- A. Configure data replication based on RTO.
- B. Keep an application running on premise as well as in AWS with full capacity.
- C. Setup a single DB instance which will be accessed by both sites.
- D. Setup a weighted DNS service like Route 53 to route traffic across site

Answer: C

Explanation:

AWS has many solutions for DR(Disaster recovery) and HA(High Availability). When the organization wants to have HA and DR with multi-site solution, it should setup two sites: one on premise and the other on AWS with full capacity. The organization should setup a weighted DNS service which can route traffic to both sites based on the weightage. When one of the sites fails it can route the entire load to another site. The organization would have minimal RTO in this scenario. If the organization setups a single DB instance, it will not work well in failover.

Instead they should have two separate DBs in each site and setup data replication based on RTO(recovery time objective)of the organization.

Reference: http://d36cz9buwru1tt.cloudfront.net/AWS_Disaster_Recovery.pdf

NEW QUESTION 78

In the context of policies and permissions in AWS IAM, the Condition element is .

- A. crucial while writing the IAM policies
- B. an optional element
- C. always set to null
- D. a mandatory element

Answer: B

Explanation:

The Condition element (or Condition block) lets you specify conditions for when a policy is in effect. The Condition element is optional.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_ElementDescriptions.html

NEW QUESTION 80

Which of the following is true while using an IAM role to grant permissions to applications running on Amazon EC2 instances?

- A. All applications on the instance share the same role, but different permissions.
- B. All applications on the instance share multiple roles and permissions.
- C. Multiple roles are assigned to an EC2 instance at a time.
- D. Only one role can be assigned to an EC2 instance at a time

Answer: D

Explanation:

Only one role can be assigned to an EC2 instance at a time, and all applications on the instance share the same role and permissions.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/role-usecase-ec2app.html>

NEW QUESTION 82

Attempts, one of the three types of items associated with the schedule pipeline in the AWS Data Pipeline, provides robust data management.

Which of the following statements is NOT true about Attempts?

- A. Attempts provide robust data management.
- B. AWS Data Pipeline retries a failed operation until the count of retries reaches the maximum number of allowed retry attempts.
- C. An AWS Data Pipeline Attempt object compiles the pipeline components to create a set of actionable instances.
- D. AWS Data Pipeline Attempt objects track the various attempts, results, and failure reasons if applicable.

Answer: C

Explanation:

Attempts, one of the three types of items associated with a schedule pipeline in AWS Data Pipeline, provides robust data management. AWS Data Pipeline retries a failed operation. It continues to do so until the task reaches the maximum number of allowed retry attempts. Attempt objects track the various attempts, results, and failure reasons if applicable. Essentially, it is the instance with a counter. AWS Data Pipeline performs retries using the same resources from the previous attempts, such as Amazon EMR clusters and EC2 instances.

Reference:

<http://docs.aws.amazon.com/datapipeline/latest/DeveloperGuide/dp-how-tasks-scheduled.html>

NEW QUESTION 85

Which of the following cannot be done using AWS Data Pipeline?

- A. Create complex data processing workloads that are fault tolerant, repeatable, and highly available.
- B. Regularly access your data where it's stored, transform and process it at scale, and efficiently transfer the results to another AWS service.
- C. Generate reports over data that has been stored.
- D. Move data between different AWS compute and storage services as well as on-premise data sources at specified intervals.

Answer: C

Explanation:

AWS Data Pipeline is a web service that helps you reliably process and move data between different AWS compute and storage services as well as on-premise data sources at specified intervals. With AWS Data Pipeline, you can regularly access your data where it's stored, transform and process it at scale, and efficiently transfer the results to another AWS.

AWS Data Pipeline helps you easily create complex data processing workloads that are fault tolerant, repeatable, and highly available. AWS Data Pipeline also allows you to move and process data that was previously locked up in on-premise data silos. Reference: <http://aws.amazon.com/datapipeline/>

NEW QUESTION 88

Identify an application that polls AWS Data Pipeline for tasks and then performs those tasks.

- A. A task executor
- B. A task deployer
- C. A task runner
- D. A task optimizer

Answer: C

Explanation:

A task runner is an application that polls AWS Data Pipeline for tasks and then performs those tasks. You can either use Task Runner as provided by AWS Data Pipeline, or create a custom Task Runner application.

Task Runner is a default implementation of a task runner that is provided by AWS Data Pipeline. When Task Runner is installed and configured, it polls AWS Data Pipeline for tasks associated with pipelines that you have activated. When a task is assigned to Task Runner, it performs that task and reports its status back to AWS Data Pipeline. If your workflow requires non-default behavior, you'll need to implement that functionality in a custom task runner.

Reference:

<http://docs.aws.amazon.com/datapipeline/latest/DeveloperGuide/dp-how-remote-taskrunner-client.html>

NEW QUESTION 89

You create a VPN connection, and your VPN device supports Border Gateway Protocol (BGP). Which of the following should be specified to configure the VPN connection?

- A. Classless routing
- B. Classfull routing
- C. Dynamic routing
- D. Static routing

Answer: C

Explanation:

If you create a VPN connection, you must specify the type of routing that you plan to use, which will depend upon on the make and model of your VPN devices. If your VPN device supports Border Gateway Protocol (BGP), you need to specify dynamic routing when you configure your VPN connection. If your device does not support BGP, you should specify static routing.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_VPN.html

NEW QUESTION 93

An organization is having a VPC for the HR department, and another VPC for the Admin department. The HR department requires access to all the instances running in the Admin VPC while the Admin department requires access to all the resources in the HR department. How can the organization setup this scenario?

- A. Setup VPC peering between the VPCs of Admin and HR.
- B. Setup ACL with both VPCs which will allow traffic from the CIDR of the other VPC.
- C. Setup the security group with each VPC which allows traffic from the CIDR of another VPC.
- D. It is not possible to connect resources of one VPC from another VPC.

Answer: A

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. A VPC peering connection allows the user to route traffic between the peer VPCs using private IP addresses as if they are a part of the same network.

This is helpful when one VPC from the same or different AWS account wants to connect with resources of the other VPC.

Reference: <http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/vpc-peering.html>

NEW QUESTION 95

Identify a true statement about using an IAM role to grant permissions to applications running on Amazon EC2 instances.

- A. When AWS credentials are rotated, developers have to update only the root Amazon EC2 instance that uses their credentials.
- B. When AWS credentials are rotated, developers have to update only the Amazon EC2 instance on which the password policy was applied and which uses their credentials.

- C. When AWS credentials are rotated, you don't have to manage credentials and you don't have to worry about long-term security risks.
- D. When AWS credentials are rotated, you must manage credentials and you should consider precautions for long-term security risks.

Answer: C

Explanation:

Using IAM roles to grant permissions to applications that run on EC2 instances requires a bit of extra configuration. Because role credentials are temporary and rotated automatically, you don't have to manage credentials, and you don't have to worry about long-term security risks.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/role-usecase-ec2app.html>

NEW QUESTION 99

In the context of IAM roles for Amazon EC2, which of the following NOT true about delegating permission to make API requests?

- A. You cannot create an IAM role.
- B. You can have the application retrieve a set of temporary credentials and use them.
- C. You can specify the role when you launch your instances.
- D. You can define which accounts or AWS services can assume the rol

Answer: A

Explanation:

Amazon designed IAM roles so that your applications can securely make API requests from your instances, without requiring you to manage the security credentials that the applications use. Instead of creating and distributing your AWS credentials, you can delegate permission to make API requests using IAM roles as follows: Create an IAM role. Define which accounts or AWS services can assume the role. Define which API actions and resources the application can use after assuming the role. Specify the role when you launch your instances. Have the application retrieve a set of temporary credentials and use them.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/iam-roles-for-amazon-ec2.html>

NEW QUESTION 101

How does AWS Data Pipeline execute activities on on-premise resources or AWS resources that you manage?

- A. By supplying a Task Runner package that can be installed on your on-premise hosts
- B. None of these
- C. By supplying a Task Runner file that the resources can access for execution
- D. By supplying a Task Runner script that can be installed on your on-premise hosts

Answer: A

Explanation:

To enable running activities using on-premise resources, AWS Data Pipeline does the following: It supply a Task Runner package that can be installed on your on-premise hosts.

This package continuously polls the AWS Data Pipeline service for work to perform.

When it's time to run a particular activity on your on-premise resources, it will issue the appropriate command to the Task Runner.

Reference: <https://aws.amazon.com/datapipeline/faqs/>

NEW QUESTION 105

In AWS IAM, which of the following predefined policy condition keys checks how long ago (in seconds) the MFA-validated security credentials making the request were issued using multi-factor authentication (MFA)?

- A. aws:MultiFactorAuthAge
- B. aws:MultiFactorAuthLast
- C. aws:MFAAge
- D. aws:MultiFactorAuthPrevious

Answer: A

Explanation:

aws:MultiFactorAuthAge is one of the predefined keys provided by AWS that can be included within a Condition element of an IAM policy. The key allows to check how long ago (in seconds) the

MFA-validated security credentials making the request were issued using Multi-Factor Authentication (MFA).

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_ElementDescriptions.html

NEW QUESTION 106

A user is configuring MySQL RDS with PIOPS. What should be the minimum PIOPS that the user should provision?

- A. 1000
- B. 200
- C. 2000
- D. 500

Answer: A

Explanation:

If a user is trying to enable PIOPS with MySQL RDS, the minimum size of storage should be 100 GB and the minimum PIOPS should be 1000.

Reference: http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_PIOPS.html

NEW QUESTION 107

Once the user has set ElastiCache for an application and it is up and running, which services, does Amazon not provide for the user:

- A. The ability for client programs to automatically identify all of the nodes in a cache cluster, and to initiate and maintain connections to all of these nodes
- B. Automating common administrative tasks such as failure detection and recovery, and software patching
- C. Providing default Time To Live (TTL) in the AWS ElastiCache Redis Implementation for different type of data.
- D. Providing detailed monitoring metrics associated with your Cache Nodes, enabling you to diagnose and react to issues very quickly

Answer: C

Explanation:

Amazon provides failure detection and recovery, and software patching and monitoring tools which is called CloudWatch. In addition it provides also Auto Discovery to automatically identify and initialize all nodes of cache cluster for Amazon ElastiCache.

Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/WhatIs.html>

NEW QUESTION 112

In the context of AWS Cloud Hardware Security Module(HSM), does your application need to reside in the same VPC as the CloudHSM instance?

- A. No, but the server or instance on which your application and the HSM client is running must have network (IP) reachability to the HSM.
- B. Yes, always
- C. No, but they must reside in the same Availability Zone.
- D. No, but it should reside in same Availability Zone as the DB instance

Answer: A

Explanation:

Your application does not need to reside in the same VPC as the CloudHSM instance.

However, the server or instance on which your application and the HSM client is running must have network (IP) reachability to the HSM. You can establish network connectivity in a variety of ways, including operating your application in the same VPC, with VPC peering, with a VPN connection, or with Direct Connect.

Reference: <https://aws.amazon.com/cloudhsm/faqs/>

NEW QUESTION 116

A government client needs you to set up secure cryptographic key storage for some of their extremely confidential data. You decide that the AWS CloudHSM is the best service for this. However, there seem to be a few pre-requisites before this can happen, one of those being a security group that has certain ports open. Which of the following is correct in regards to those security groups?

- A. A security group that has no ports open to your network.
- B. A security group that has only port 3389 (for RDP) open to your network.
- C. A security group that has only port 22 (for SSH) open to your network.
- D. A security group that has port 22 (for SSH) or port 3389 (for RDP) open to your network

Answer: D

Explanation:

AWS CloudHSM provides secure cryptographic key storage to customers by making hardware security modules (HSMs) available in the AWS cloud.

AWS CloudHSM requires the following environment before an HSM appliance can be provisioned. A virtual private cloud (VPC) in the region where you want the AWS CloudHSM service.

One private subnet (a subnet with no Internet gateway) in the VPC. The HSM appliance is provisioned into this subnet.

One public subnet (a subnet with an Internet gateway attached). The control instances are attached to this subnet.

An AWS Identity and Access Management (IAM) role that delegates access to your AWS resources to AWS CloudHSM.

An EC2 instance, in the same VPC as the HSM appliance, that has the SafeNet client software installed. This instance is referred to as the control instance and is used to connect to and manage the HSM appliance.

A security group that has port 22 (for SSH) or port 3389 (for RDP) open to your network. This security group is attached to your control instances so you can access them remotely.

NEW QUESTION 117

What is the network performance offered by the c4.8xlarge instance in Amazon EC2?

- A. Very High but variable
- B. 20 Gigabit
- C. 5 Gigabit
- D. 10 Gigabit

Answer: D

Explanation:

Networking performance offered by the c4.8xlarge instance is 10 Gigabit. Reference: <http://aws.amazon.com/ec2/instance-types/>

NEW QUESTION 118

You're trying to delete an SSL certificate from the IAM certificate store, and you're getting the message "Certificate: <certificate-id> is being used by CloudFront." Which of the following statements is probably the reason why you are getting this error?

- A. Before you can delete an SSL certificate you need to set up https on your server.
- B. Before you can delete an SSL certificate, you need to set up the appropriate access level in IAM
- C. Before you can delete an SSL certificate, you need to either rotate SSL certificates or revert from using a custom SSL certificate to using the default CloudFront certificate.
- D. You can't delete SSL certificates. You need to request it from AWS

Answer: C

Explanation:

CloudFront is a web service that speeds up distribution of your static and dynamic web content, for example, .html, .css, .php, and image files, to end users. Every CloudFront web distribution must be associated either with the default CloudFront certificate or with a custom SSL certificate. Before you can delete an SSL certificate, you need to either rotate SSL certificates (replace the current custom SSL certificate with another custom SSL certificate) or revert from using a custom SSL certificate to using the default CloudFront certificate.

Reference: <http://docs.aws.amazon.com/AmazonCloudFront/latest/DeveloperGuide/Troubleshooting.html>

NEW QUESTION 119

A user has set the IAM policy where it denies all requests if a request is not from IP 10.10.10.1/32. The other policy says allow all requests between 5 PM to 7 PM. What will happen when a user is requesting access from IP 55.109.10.12/32 at 6 PM?

- A. It will deny access
- B. It is not possible to set a policy based on the time or IP
- C. IAM will throw an error for policy conflict
- D. It will allow access

Answer: A

Explanation:

When a request is made, the AWS IAM policy decides whether a given request should be allowed or denied. The evaluation logic follows these rules:

By default, all requests are denied. (In general, requests made using the account credentials for resources in the account are always allowed.)

An explicit allow policy overrides this default.

An explicit deny policy overrides any allows.

In this case since there are explicit deny and explicit allow statements. Thus, the request will be denied since deny overrides allow.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_EvaluationLogic.html

NEW QUESTION 123

You want to use Amazon Redshift and you are planning to deploy dw1.8xlarge nodes. What is the minimum amount of nodes that you need to deploy with this kind of configuration?

- A. 1
- B. 4
- C. 3
- D. 2

Answer: D

Explanation:

For a single-node configuration in Amazon Redshift, the only option available is the smallest of the two options. The 8XL extra-large nodes are only available in a multi-node configuration

Reference: <http://docs.aws.amazon.com/redshift/latest/mgmt/working-with-clusters.html>

NEW QUESTION 127

Can Provisioned IOPS be used on RDS instances launched in a VPC?

- A. Yes, they can be used only with Oracle based instances.
- B. Yes, they can be used for all RDS instances.
- C. No
- D. Yes, they can be used only with MySQL based instance

Answer: B

Explanation:

The basic building block of Amazon RDS is the DB instance. DB instance storage comes in three types: Magnetic, General Purpose (SSD), and Provisioned IOPS (SSD). When you buy a server, you get CPU, memory, storage, and IOPS, all bundled together. With Amazon RDS, these are split apart so that you can scale them independently. So, for example, if you need more CPU, less IOPS, or more storage, you can easily allocate them.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/RDSFAQ.PIOPS.html>

NEW QUESTION 129

To get started using AWS Direct Connect, in which of the following steps do you configure Border Gateway Protocol (BGP)?

- A. Complete the Cross Connect
- B. Configure Redundant Connections with AWS Direct Connect
- C. Create a Virtual Interface
- D. Download Router Configuration

Answer: C

Explanation:

In AWS Direct Connect, your network must support Border Gateway Protocol (BGP) and BGP MD5 authentication, and you need to provide a private Autonomous System Number (ASN) for that to connect to Amazon Virtual Private Cloud (VPC). To connect to public AWS products such as Amazon EC2 and Amazon S3, you will also need to provide a public ASN that you own (preferred) or a private ASN. You have to configure BGP in the Create a Virtual Interface step.

Reference: <http://docs.aws.amazon.com/directconnect/latest/UserGuide/getstarted.html#createvirtualinterface>

NEW QUESTION 132

Which of the following components of AWS Data Pipeline polls for tasks and then performs those tasks?

- A. Pipeline Definition
- B. Task Runner
- C. Amazon Elastic MapReduce (EMR)
- D. AWS Direct Connect

Answer: B

Explanation:

Task Runner polls for tasks and then performs those tasks.

Reference: <http://docs.aws.amazon.com/datapipeline/latest/DeveloperGuide/what-is-datapipeline.html>

NEW QUESTION 133

A user is hosting a public website on AWS. The user wants to have the database and the app server on the AWS VPC. The user wants to setup a database that can connect to the Internet for any patch upgrade but cannot receive any request from the internet. How can the user set this up?

- A. Setup DB in a private subnet with the security group allowing only outbound traffic.
- B. Setup DB in a public subnet with the security group allowing only inbound data.
- C. Setup DB in a local data center and use a private gateway to connect the application with DB.
- D. Setup DB in a private subnet which is connected to the internet via NAT for outbound.

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. AWS provides two features that the user can use to increase security in VPC: security groups and network ACLs. When the user wants to setup both the DB and App on VPC, the user should make one public and one private subnet. The DB should be hosted in a private subnet and instances in that subnet cannot reach the internet. The user can allow an instance in his VPC to initiate outbound connections to the internet but prevent unsolicited inbound connections from the internet by using a Network Address Translation (NAT) instance.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Subnets.html

NEW QUESTION 135

In Amazon ElastiCache, the default cache port is:

- A. for Memcached 11210 and for Redis 6380.
- B. for Memcached 11211 and for Redis 6380.
- C. for Memcached 11210 and for Redis 6379.
- D. for Memcached 11211 and for Redis 6379.

Answer: D

Explanation:

In Amazon ElastiCache, you can specify a new port number for your cache cluster, which by default is 11211 for Memcached and 6379 for Redis.

Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/GettingStarted.AuthorizeAccess.htm>

NEW QUESTION 140

A user has created a VPC with public and private subnets using the VPC wizard. The VPC has CIDR 20.0.0.0/16. The private subnet uses CIDR 20.0.0.0/24 . The NAT instance ID is i-a12345. Which of the below mentioned entries are required in the main route table attached with the private subnet to allow instances to connect with the internet?

- A. Destination: 20.0.0.0/0 and Target: 80
- B. Destination: 20.0.0.0/0 and Target: i-a12345
- C. Destination: 20.0.0.0/24 and Target: i-a12345
- D. Destination: 0.0.0.0/0 and Target: i-a12345

Answer: D

Explanation:

A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet, the instances in the public subnet can receive inbound traffic directly from the Internet, whereas the instances in the private subnet cannot. If these subnets are created with Wizard, AWS will create two route tables and attach to the subnets. The main route table will have the entry "Destination: 0.0.0.0/0 and Target: i-a12345", which allows all the instances in the private subnet to connect to the internet using NAT.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Scenario2.html

NEW QUESTION 144

An organization is hosting a scalable web application using AWS. The organization has configured internet facing ELB and Auto Scaling to make the application scalable. Which of the below mentioned statements is required to be followed when the application is planning to host a web application on VPC?

- A. The ELB can be in a public or a private subnet but should have the ENI which is attached to an elastic IP.
- B. The ELB must not be in any subnet; instead it should face the internet directly.
- C. The ELB must be in a public subnet of the VPC to face the internet traffic.
- D. The ELB can be in a public or a private subnet but must have routing tables attached to divert the internet traffic to it.

Answer: C

Explanation:

The Amazon Virtual Private Cloud (Amazon VPC) allows the user to define a virtual networking environment in a private, isolated section of the Amazon Web Services (AWS) cloud. The user has complete control over the virtual networking environment. Within this virtual private cloud, the user can launch AWS

resources, such as an ELB, and EC2 instances. There are two ELBs available with VPC: internet facing and internal (private) ELB. For internet facing ELB it is required that ELB should be in a public subnet.
After the user creates the public subnet, he should ensure to associate the route table of the public subnet with the internet gateway to enable the load balancer in the subnet to connect with the internet. Reference: <http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/CreateVPCForELB.html>

NEW QUESTION 147

Is there any way to own a direct connection to Amazon Web Services?

- A. No, AWS only allows access from the public Internet.
- B. No, you can create an encrypted tunnel to VPC, but you cannot own the connection.
- C. Yes, you can via Amazon Dedicated Connection.
- D. Yes, you can via AWS Direct Connect

Answer: D

Explanation:

AWS Direct Connect links your internal network to an AWS Direct Connect location over a standard 1 gigabit or 10 gigabit Ethernet fiber-optic cable. One end of the cable is connected to your router, the other to an AWS Direct Connect router. With this connection in place, you can create virtual interfaces directly to the AWS cloud (for example, to Amazon Elastic Compute Cloud (Amazon EC2) and Amazon Simple Storage Service (Amazon S3)) and to Amazon Virtual Private Cloud (Amazon VPC), bypassing Internet service providers in your network path.
Reference: <http://docs.aws.amazon.com/directconnect/latest/UserGuide/Welcome.html>

NEW QUESTION 149

In Amazon ElastiCache, which of the following statements is correct?

- A. When you launch an ElastiCache cluster into an Amazon VPC private subnet, every cache node is assigned a public IP address within that subnet.
- B. You cannot use ElastiCache in a VPC that is configured for dedicated instance tenancy.
- C. If your AWS account supports only the EC2-VPC platform, ElastiCache will never launch your cluster in a VPC.
- D. ElastiCache is not fully integrated with Amazon Virtual Private Cloud (VPC).

Answer: B

Explanation:

The VPC must allow non-dedicated EC2 instances. You cannot use ElastiCache in a VPC that is configured for dedicated instance tenancy.
Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/AmazonVPC.EC.html>

NEW QUESTION 153

You are looking to migrate your Development (Dev) and Test environments to AWS. You have decided to use separate AWS accounts to host each environment. You plan to link each accounts bill to a Master AWS account using Consolidated Billing. To make sure you Keep within budget you would like to implement a way for administrators in the Master account to have access to stop, delete and/or terminate resources in both the Dev and Test accounts. Identify which option will allow you to achieve this goal.

- A. Create IAM users in the Master account with full Admin permission
- B. Create cross-account roles in the Dev and Test accounts that grant the Master account access to the resources in the account by inheriting permissions from the Master account.
- C. Create IAM users and a cross-account role in the Master account that grants full Admin permissions to the Dev and Test accounts.
- D. Create IAM users in the Master account Create cross-account roles in the Dev and Test accounts that have full Admin permissions and grant the Master account access.
- E. Link the accounts using Consolidated Billin
- F. This will give IAM users in the Master account access to resources in the Dev and Test accounts

Answer: C

NEW QUESTION 155

You have deployed a web application targeting a global audience across multiple AWS Regions under the domain name.example.com. You decide to use Route53 Latency-Based Routing to serve web requests to users from the region closest to the user. To provide business continuity in the event of server downtime you configure weighted record sets associated with two web servers in separate Availability Zones per region. Dunning a DR test you notice that when you disable all web sewers in one of the regions Route53 does not automatically direct all users to the other region. What could be happening? (Choose 2 answers)

- A. Latency resource record sets cannot be used in combination with weighted resource record sets.
- B. You did not setup an HTTP health check to one or more of the weighted resource record sets associated with me disabled web sewers.
- C. The value of the weight associated with the latency alias resource record set in the region with the disabled sewers is higher than the weight for the other region.
- D. One of the two working web sewers in the other region did not pass its HTTP health check.
- E. You did not set "Evaluate Target Health" to "Yes" on the latency alias resource record set associated with example com in the region where you disabled the servers.

Answer: BE

NEW QUESTION 158

A read only news reporting site with a combined web and application tier and a database tier that receives large and unpredictable traffic demands must be able to respond to these traffic fluctuations automatically. What AWS services should be used meet these requirements?

- A. Stateless instances for the web and application tier synchronized using ElastiCache Memcached in an autoscaimg group monitored with CloudWatch and RDS with read replicas.
- B. Stateful instances for the web and application tier in an autoscaling group monitored with CloudWatch and RDS with read replicas.
- C. Stateful instances for the web and application tier in an autoscaling group monitored with CloudWate
- D. And multi-AZ RDS.

E. Stateless instances for the web and application tier synchronized using ElastiCache Memcached in an autoscaling group monitored with CloudWatch and multi-AZ RDS.

Answer: A

NEW QUESTION 159

You are designing a photo-sharing mobile app. The application will store all pictures in a single Amazon S3 bucket. Users will upload pictures from their mobile device directly to Amazon S3 and will be able to view and download their own pictures directly from Amazon S3.

You want to configure security to handle potentially millions of users in the most secure manner possible. What should your server-side application do when a new user registers on the photo-sharing mobile application?

- A. Create an IAM use
- B. Update the bucket policy with appropriate permissions for the IAM use
- C. Generate an access key and secret key for the IAM user, store them in the mobile app and use these credentials to access Amazon S3.
- D. Create an IAM use
- E. Assign appropriate permissions to the IAM use
- F. Generate an access key and secret key for the IAM user, store them in the mobile app and use these credentials to access Amazon S3.
- G. Create a set of long-term credentials using AWS Security Token Service with appropriate permission
- H. Store these credentials in the mobile app and use them to access Amazon S3.
- I. Record the user's information in Amazon RDS and create a role in IAM with appropriate permission
- J. When the user uses their mobile app, create temporary credentials using the AWS Security Token Service "AssumeRole" function
- K. Store these credentials in the mobile app's memory and use them to access Amazon S3. Generate new credentials the next time the user runs the mobile app.
- L. Record the user's information in Amazon DynamoDB
- M. When the user uses their mobile app, create temporary credentials using AWS Security Token Service with appropriate permission
- N. Store these credentials in the mobile app's memory and use them to access Amazon S3. Generate new credentials the next time the user runs the mobile app.

Answer: D

NEW QUESTION 162

You have a periodic image analysis application that gets some files in input analyzes them and for each file writes some data in output to a text file the number of files in input per day is high and concentrated in a few hours of the day.

Currently you have a server on EC2 with a large EBS volume that hosts the input data and the results it takes almost 20 hours per day to complete the process. What services could be used to reduce the elaboration time and improve the availability of the solution?

- A. S3 to store I/O file
- B. SQS to distribute elaboration commands to a group of hosts working in parallel
- C. Auto scaling to dynamically size the group of hosts depending on the length of the SQS queue
- D. EBS with Provisioned IOPS (PIOPS) to store I/O file
- E. SNS to distribute elaboration commands to a group of hosts working in parallel Auto Scaling to dynamically size the group of hosts depending on the number of SNS notifications
- F. S3 to store I/O files, SNS to distribute elaboration commands to a group of hosts working in parallel
- G. Auto scaling to dynamically size the group of hosts depending on the number of SNS notifications
- H. EBS with Provisioned IOPS (PIOPS) to store I/O files SQS to distribute elaboration commands to a group of hosts working in parallel Auto Scaling to dynamically size the group of hosts depending on the length of the SQS queue.

Answer: D

NEW QUESTION 165

A large real-estate brokerage is exploring the option of adding a cost-effective location based alert to their existing mobile application. The application backend infrastructure currently runs on AWS. Users who opt in to this service will receive alerts on their mobile device regarding real-estate offers in proximity to their location. For the alerts to be relevant delivery time needs to be in the low minute count the existing mobile app has 5 million users across the US. Which one of the following architectural suggestions would you make to the customer?

- A. The mobile application will submit its location to a web service endpoint utilizing Elastic Load Balancing and EC2 instances. DynamoDB will be used to store and retrieve relevant offers. EC2 instances will communicate with mobile carriers/device providers to push alerts back to mobile application.
- B. Use AWS DirectConnect or VPN to establish connectivity with mobile carriers. EC2 instances will receive the mobile applications' location through carrier connection. RDS will be used to store and relevant offers. EC2 instances will communicate with mobile carriers to push alerts back to the mobile application.
- C. The mobile application will send device location using SQS.
- D. EC2 instances will retrieve the relevant offers from DynamoDB. AWS Mobile Push will be used to send offers to the mobile application.
- E. The mobile application will send device location using AWS Mobile Push. EC2 instances will retrieve the relevant offers from DynamoDB. EC2 instances will communicate with mobile carriers/device providers to push alerts back to the mobile application.

Answer: A

NEW QUESTION 166

You require the ability to analyze a large amount of data, which is stored on Amazon S3 using Amazon Elastic MapReduce. You are using the cc2.8xlarge instance type, whose CPUs are mostly idle during processing. Which of the below would be the most cost efficient way to reduce the runtime of the job?

- A. Create more smaller files on Amazon S3.
- B. Add additional cc2.8xlarge instances by introducing a task group.
- C. Use smaller instances that have higher aggregate I/O performance.
- D. Create fewer, larger files on Amazon S3.

Answer: C

NEW QUESTION 169

Your company runs a customer facing event registration site. This site is built with a 3-tier architecture with web and application tier servers and a MySQL database. The application requires 6 web tier servers and 6 application tier servers for normal operation, but can run on a minimum of 65% server capacity and a single

MySQL database. When deploying this application in a region with three availability zones (AZs) which architecture provides high availability?

- A. A web tier deployed across 2 AZs with 3 EC2 (Elastic Compute Cloud) instances in each AZ inside an Auto Scaling Group behind an ELB (elastic load balancer), and an application tier deployed across 2 AZs with 3 EC2 instances in each AZ inside an Auto Scaling Group behind an ELB and one RDS (Relational Database Service) instance deployed with read replicas in the other AZ.
- B. A web tier deployed across 3 AZs with 2 EC2 (Elastic Compute Cloud) instances in each AZ inside an Auto Scaling Group behind an ELB (elastic load balancer) and an application tier deployed across 3 AZs with 2 EC2 instances in each AZ inside an Auto Scaling Group behind an ELB and one RDS (Relational Database Service) Instance deployed with read replicas in the two other AZs.
- C. A web tier deployed across 2 AZs with 3 EC2 (Elastic Compute Cloud) instances in each AZ inside an Auto Scaling Group behind an ELB (elastic load balancer) and an application tier deployed across 2 AZs with 3 EC2 instances in each AZ inside an Auto Scaling Group behind an ELB and a Multi-AZ RDS (Relational Database Service) deployment.
- D. A web tier deployed across 3 AZs with 2 EC2 (Elastic Compute Cloud) instances in each AZ Inside an Auto Scaling Group behind an ELB (elastic load balancer). And an application tier deployed across 3 AZs with 2 EC2 instances in each AZ inside an Auto Scaling Group behind an ELB and a Multi-AZ RDS (Relational Database services) deployment.

Answer: D

NEW QUESTION 173

Your company has HQ in Tokyo and branch offices all over the world and is using a logistics software with a multi-regional deployment on AWS in Japan, Europe and US

- A. The logistic software has a 3-tier architecture and currently uses MySQL 5.6 for data persistence
- B. Each region has deployed its own database In the HQ region you run an hourly batch process reading data from every region to compute cross-regional reports that are sent by email to all offices this batch process must be completed as fast as possible to quickly optimize logistics how do you build the database architecture in order to meet the requirements'?
- C. For each regional deployment, use RDS MySQL with a master in the region and a read replica in the HQ region
- D. For each regional deployment, use MySQL on EC2 with a master in the region and send hourly EBS snapshots to the HQ region
- E. For each regional deployment, use RDS MySQL with a master in the region and send hourly RDS snapshots to the HQ region
- F. For each regional deployment, use MySQL on EC2 with a master in the region and use S3 to copy data files hourly to the HQ region
- G. Use Direct Connect to connect all regional MySQL deployments to the HQ region and reduce network latency for the batch process

Answer: A

NEW QUESTION 176

Your company currently has a 2-tier web application running in an on-premises data center. You have experienced several infrastructure failures in the past two months resulting in significant financial losses. Your CIO is strongly agreeing to move the application to AWS. While working on achieving buy-in from the other company executives, he asks you to develop a disaster recovery plan to help improve Business continuity in the short term. He specifies a target Recovery Time Objective (RTO) of 4 hours and a Recovery Point Objective (RPO) of 1 hour or less. He also asks you to implement the solution within 2 weeks. Your database is 200GB in size and you have a 20Mbps Internet connection. How would you do this while minimizing costs?

- A. Create an EBS backed private AMI which includes a fresh install of your application
- B. Develop a Cloud Formation template which includes your AMI and the required EC2, AutoScaling, and ELB resources to support deploying the application across Multiple- Availability-Zone
- C. Asynchronously replicate transactions from your on-premises database to a database instance in AWS across a secure VPN connection.
- D. Deploy your application on EC2 instances within an Auto Scaling group across multiple availability zone
- E. Asynchronously replicate transactions from your on-premises database to a database instance in AWS across a secure VPN connection.
- F. Create an EBS backed private AMI which includes a fresh install of your application
- G. Setup a script in your data center to backup the local database every 1 hour and to encrypt and copy the resulting file to an S3 bucket using multi-part upload.
- H. Install your application on a compute-optimized EC2 instance capable of supporting the application's average load
- I. Synchronously replicate transactions from your on-premises database to a database instance in AWS across a secure Direct Connect connection.

Answer: A

NEW QUESTION 180

An enterprise wants to use a third-party SaaS application. The SaaS application needs to have access to issue several API commands to discover Amazon EC2 resources running within the enterprise's account The enterprise has internal security policies that require any outside access to their environment must conform to the principles of least privilege and there must be controls in place to ensure that the credentials used by the SaaS vendor cannot be used by any other third party. Which of the following would meet all of these conditions?

- A. From the AWS Management Console, navigate to the Security Credentials page and retrieve the access and secret key for your account.
- B. Create an IAM user within the enterprise account assign a user policy to the IAM user that allows only the actions required by the SaaS application create a new access and secret key for the user and provide these credentials to the SaaS provider.
- C. Create an IAM role for cross-account access allows the SaaS provider's account to assume the role and assign it a policy that allows only the actions required by the SaaS application.
- D. Create an IAM role for EC2 instances, assign it a policy that allows only the actions required for the SaaS application to work, provide the role ARN to the SaaS provider to use when launching their application instances.

Answer: C

NEW QUESTION 181

An AWS customer runs a public blogging website. The site users upload two million blog entries a month. The average blog entry size is 200 KB. The access rate to blog entries drops to negligible 6 months after publication and users rarely access a blog entry 1 year after publication. Additionally, blog entries have a high update rate during the first 3 months following publication, this drops to no updates after 6 months. The customer wants to use CloudFront to improve his user's load times. Which of the following recommendations would you make to the customer?

- A. Duplicate entries into two different buckets and create two separate CloudFront distributions where S3 access is restricted only to Cloud Front identity
- B. Create a CloudFront distribution with "US Europe" price class for US/Europe users and a different CloudFront distribution with "All Edge Locations" for the remaining users.
- C. Create a CloudFront distribution with S3 access restricted only to the CloudFront identity and partition the blog entry's location in S3 according to the month it

was uploaded to be used with CloudFront behaviors.

D. Create a CloudFront distribution with Restrict Viewer Access Forward Query string set to true and minimum TTL of 0.

Answer: C

NEW QUESTION 183

You are implementing a URL whitelisting system for a company that wants to restrict outbound HTTP'S connections to specific domains from their EC2-hosted applications you deploy a single EC2 instance running proxy software and configure It to accept traffic from all subnets and EC2 instances in the VPC. You configure the proxy to only pass through traffic to domains that you define in its whitelist configuration You have a nightly maintenance window or 10 minutes where ail instances fetch new software updates. Each update ls about 200MB In size and there are 500 instances In the VPC that routinely fetch updates After a few days you notice that some machines are failing to successfully download some, but not all of their updates within the maintenance window. The download URLs used for these updates are correctly listed in the proxy's whitelist configuration and you are able to access them manually using a web browser on the instances. What might be happening? (Choose 2 answers)

- A. You are running the proxy on an undersized EC2 instance type so network throughput is not sufficient for all instances to download their updates in time.
- B. You are running the proxy on a sufficiently-sized EC2 instance in a private subnet andits network throughput is being throttled by a NAT running on an undersized EC2 instance.
- C. The route table for the subnets containing the affected EC2 instances is not configured to direct network traffic for the software update locations to the proxy.
- D. You have not allocated enough storage to the EC2 instance running the proxy so the network buffer is filling up, causing some requests to fail.
- E. You are running the proxy in a public subnet but have not allocated enough EIPs to support the needed network throughput through the Internet Gateway (IGW).

Answer: AB

NEW QUESTION 187

Company B is launching a new game app for mobile devices. Users will log into the game using their existing social media account to streamline data capture. Company B would like to directly save player data and scoring information from the mobile app to a DynamoDS table named Score Data When a user saves their game the progress data will be stored to the Game state S3 bucket. What is the best approach for storing data to DynamoDB and S3?

- A. Use an EC2 Instance that is launched with an EC2 role providing access to the Score Data DynamoDB table and the GameState S3 bucket that communicates with the mobile app via web services.
- B. Use temporary security credentials that assume a role providing access to the Score Data DynamoDB table and the Game State S3 bucket using web identity federation.
- C. Use Login with Amazon allowing users to sign in with an Amazon account providing the mobile app with access to the Score Data DynamoDB table and the Game State S3 bucket.
- D. Use an IAM user with access credentials assigned a role providing access to the Score Data DynamoDB table and the Game State S3 bucket for distribution with the mobile app.

Answer: B

NEW QUESTION 191

Your website is serving on-demand training videos to your workforce. Videos are uploaded monthly in high resolution MP4 format. Your workforce is distributed globally often on the move and using company-provided tablets that require the HTTP Live Streaming (HLS) protocol to watch a video. Your company has no video transcoding expertise and it required you may need to pay for a consultant.

How do you implement the most cost-efficient architecture without compromising high availability and quality of video delivery'?

- A. A video transcoding pipeline running on EC2 using SQS to distribute tasks and Auto Scaling to adjust the number of nodes depending on the length of the queue
- B. EBS volumes to host videos and EBS snapshots to incrementally backup original files after a few day
- C. CloudFront to serve HLS transcoded videos from EC2.
- D. Elastic Transcoder to transcode original high-resolution MP4 videos to HL
- E. EBS volumes to host videos and EBS snapshots to incrementally backup original files after a few day
- F. CloudFront to serve HLS transcoded videos from EC2.
- G. Elastic Transcoder to transcode original high-resolution MP4 videos to HL
- H. S3 to host videos with Lifecycle Management to archive original files to Glacier after a few day
- I. CloudFront to serve HLS transcoded videos from S3.
- J. A video transcoding pipeline running on EC2 using SQS to distribute tasks and Auto Scaling to adjust the number of nodes depending on the length of the queue
- K. S3 to host videos with Lifecycle Management to archive all files to Glacier after a few day
- L. CloudFront to serve HLS transcoded videos from Glacier.

Answer: C

NEW QUESTION 192

A customer has established an AWS Direct Connect connection to AWS. The link is up and routes are being advertised from the customer's end, however the customer is unable to connect from EC2 instances inside its VPC to servers residing in its datacenter.

Which of the following options provide a viable solution to remedy this situation? (Choose 2 answers)

- A. Add a route to the route table with an IPsec VPN connection as the target.
- B. Enable route propagation to the virtual pinnate gateway (VGW).
- C. Enable route propagation to the customer gateway (CGW).
- D. Modify the route table of all Instances using the 'route' command.
- E. Modify the Instances VPC subnet route table by adding a route back to the customer's on-premises environment.

Answer: AC

NEW QUESTION 193

A corporate web application is deployed within an Amazon Virtual Private Cloud (VPC) and is connected to the corporate data center via an IPSec VPN. The application must authenticate against the

on-premises LDAP server. After authentication, each logged-in user can only access an Amazon Simple Storage Space (S3) keyspace specific to that user. Which two approaches can satisfy these objectives? (Choose 2 answers)

- A. Develop an identity broker that authenticates against IAM security Token service to assume a IAM role in order to get temporary AWS security credentials The application calls the identity broker to get AWS temporary security credentials with access to the appropriate S3 bucket.
- B. The application authenticates against LDAP and retrieves the name of an IAM role associated with the use
- C. The application then calls the IAM Security Token Service to assume that IAM rol
- D. The application can use the temporary credentials to access the appropriate S3 bucket.
- E. Develop an identity broker that authenticates against LDAP and then calls IAM Security Token Service to get IAM federated user credential
- F. The application calls the identity broker to get IAM federated user credentials with access to the appropriate S3 bucket.
- G. The application authenticates against LDAP the application then calls the AWS identity and AccessManagement (IAM) Security service to log in to IAM using the LDAP credentials the application can use the IAM temporary credentials to access the appropriate S3 bucket.
- H. The application authenticates against IAM Security Token Service using the LDAP credentials the application uses those temporary AWS security credentials to access the appropriate S3 bucket.

Answer: BC

NEW QUESTION 194

Your company previously configured a heavily used, dynamically routed VPN connection between your on-premises data center and AWS. You recently provisioned a DirectConnect connection and would like to start using the new connection. After configuring DirectConnect settings in the AWS Console, which of the following options win provide the most seamless transition for your users?

- A. Delete your existing VPN connection to avoid routing loops configure your DirectConnect router with the appropriate settings and verity network traffic is leveraging DirectConnect.
- B. Configure your DirectConnect router with a higher BGP priority man your VPN router, verify network traffic is leveraging Directconnect and then delete your existing VPN connection.
- C. Update your VPC route tables to point to the DirectConnect connection configure your DirectConnect router with the appropriate settings verify network traffic is leveraging DirectConnect and then delete the VPN connection.
- D. Configure your DirectConnect router, update your VPC route tables to point to the DirectConnect connection, configure your VPN connection with a higher BGP priorit
- E. And verify network traffic is leveraging the DirectConnect connection.

Answer: D

NEW QUESTION 198

Your company hosts a social media website for storing and sharing documents. The web application allows user to upload large files while resuming and pausing the upload as needed. Currently, files are uploaded to your PHP front end backed by Elastic load Balancing and an autoscaling fileet of Amazon Elastic Compute Cloud (EC2) instances that scale upon average of bytes received (NetworkIn). After a file has been uploaded, it is copied to Amazon Simple Storage Service (S3). Amazon EC2 instances use an AWS Identity and Access Management (IAM) role that allows Amazon S3 uploads. Over the last six months, your user base and scale have increased significantly, forcing you to increase the Auto Scaling group's Max parameter a few times. Your CFO is concerned about rising costs and has asked you to adjust the architecture where needed to better optimize costs.

Which architecture change could you introduce to reduce costs and still keep your web application secure and scalable?

- A. Replace the Auto Scaling launch configuration to include c3.8xlarge instances; those instances can potentially yield a network throuthput of 10gbps.
- B. Re-architect your ingest pattern, have the app authenticate against your identity provider, and use your identity provider as a broker fetching temporary AWS credentials from AWS Secure Token Service (GetFederationToken). Securely pass the credentials and S3 endpoint/prefix to your ap
- C. Implement client-side logic to directly upload the file to Amazon S3 using the given credentials and S3 prefix.
- D. Re-architect your ingest pattern, and move your web application instances into a VPC public subne
- E. Attach a public IP address for each EC2 instance (using the Auto Scaling launch configuration settings). Use Amazon Route 53 Round Robin records set and HTTP health check to DNS load balance the apprequests; this approach will significantly reduce the cost by bypassing Elastic Load Balancing.
- F. Re-architect your ingest pattern, have the app authenticate against your identity provider, and use your identity provider as a broker fetching temporary AWS credentials from AWS Secure Token Service (GetFederationToken). Securely pass the credentials and S3 endpoint/prefix to your ap
- G. Implement client-side logic that used the S3 multipart upload API to directly upload the file to Amazon S3 using the given credentials and S3 prefix.

Answer: C

NEW QUESTION 200

You require the ability to analyze a customer's clickstream data on a website so they can do behavioral analysis. Your customer needs to know what sequence of pages and ads their customer clicked on. This data will be used in real time to modify the page layouts as customers click through the site to increase stickiness and advertising click-through. Which option meets the requirements for captioning and analyzing this data?

- A. Log clicks in weblogs by URL store to Amazon S3, and then analyze with Elastic MapReduce
- B. Push web clicks by session to Amazon Kinesis and analyze behavior using Kinesis workers
- C. Write click events directly to Amazon Redshift and then analyze with SQL
- D. Publish web clicks by session to an Amazon SQS queue then periodically drain these events to Amazon RDS and analyze with SQL.

Answer: B

NEW QUESTION 203

You have deployed a three-tier web application in a VPC with a CIDR block of 10.0.0.0/28 You initially deploy two web servers, two application sewers, two database sewers and one NAT instance tor a total of seven EC2 instances The web. Application and database sewers are deployed across two availability zones (AZs). You also deploy an ELB in front of the two web servers, and use Route53 for DNS Web (raffile gradually increases in the first few days following the deployment, so you attempt to double the number of instances in each tier of the application to handle the new load unfortunately some of these new instances fail to launch.

Which of the following could be the root caused? (Choose 2 answers)

- A. AWS reserves the first and the last private IP address in each subnet's CIDR block so you do not have enough addresses left to launch all of the new EC2 instances
- B. The Internet Gateway (IGW) of your VPC has scaled-up, adding more instances to handle the traffic spike, reducing the number of available private IP

addresses for new instance launches

- C. The ELB has scaled-up, adding more instances to handle the traffic spike, reducing the number of available private IP addresses for new instance launches
- D. AWS reserves one IP address in each subnet's CIDR block for Route53 so you do not have enough addresses left to launch all of the new EC2 instances
- E. AWS reserves the first four and the last IP address in each subnet's CIDR block so you do not have enough addresses left to launch all of the new EC2 instances

Answer: CE

NEW QUESTION 207

Your company produces customer commissioned one-of-a-kind skiing helmets combining high fashion with custom technical enhancements. Customers can show off their individuality on the ski slopes and have access to head-up-displays, GPS rear-view cams and any other technical innovation they wish to embed in the helmet.

The current manufacturing process is data rich and complex including assessments to ensure that the custom electronics and materials used to assemble the helmets are to the highest standards. Assessments are a mixture of human and automated assessments; you need to add a new set of assessment to model the failure modes of the custom electronics using GPUs with CUDA, across a cluster of servers with low latency networking.

What architecture would allow you to automate the existing process using a hybrid approach and ensure that the architecture can support the evolution of processes over time?

- A. Use AWS Data Pipeline to manage movement of data & meta-data and assessments. Use an auto-scaling group of G2 instances in a placement group.
- B. Use Amazon Simple Workflow (SWF) to manage assessments, movement of data & meta-data. Use an auto-scaling group of G2 instances in a placement group.
- C. Use Amazon Simple Workflow (SWF) to manage assessments, movement of data & meta-data. Use an auto-scaling group of C3 instances with SR-IOV (Single Root I/O Virtualization).
- D. Use AWS data Pipeline to manage movement of data & meta-data and assessments. Use an auto-scaling group of C3 with SR-IOV (Single Root I/O virtualization).

Answer: B

NEW QUESTION 211

You are designing a personal document-archiving solution for your global enterprise with thousands of employees. Each employee has potentially gigabytes of data to be backed up in this archiving solution. The solution will be exposed to the employees as an application, where they can just drag and drop their files to the archiving system. Employees can retrieve their archives through a web interface. The corporate network has high bandwidth. AWS Direct Connect connects to AWS.

You have a regulatory requirement that all data needs to be encrypted before being uploaded to the cloud.

How do you implement this in a highly available and cost-efficient way?

- A. Manage encryption keys on-premises in an encrypted relational database
- B. Set up an on-premises server with sufficient storage to temporarily store files, and then upload them to Amazon S3, providing a client-side master key.
- C. Manage encryption keys in a Hardware Security Module (HSM) appliance on-premises. Server with sufficient storage to temporarily store, encrypt, and upload files directly into Amazon Glacier.
- D. Manage encryption keys in Amazon Key Management Service (KMS), upload to Amazon Simple Storage Service (S3) with client-side encryption using a KMS customer master key ID, and configure Amazon S3 lifecycle policies to store each object using the Amazon Glacier storage tier.
- E. Manage encryption keys in an AWS CloudHSM appliance
- F. Encrypt files prior to uploading on the employee desktop, and then upload directly into Amazon Glacier.

Answer: C

NEW QUESTION 213

You are designing a connectivity solution between on-premises infrastructure and Amazon VPC. Your servers on-premises will be communicating with your VPC instances. You will be establishing IPsec tunnels over the Internet. You will be using VPN gateways, and terminating the IPsec tunnels on AWS supported customer gateways.

Which of the following objectives would you achieve by implementing an IPsec tunnel as outlined above? Choose 4 answers

- A. End-to-end protection of data in transit
- B. End-to-end Identity authentication
- C. Data encryption across the Internet
- D. Protection of data in transit over the Internet
- E. Peer identity authentication between VPN gateway and customer gateway
- F. Data integrity protection across the Internet

Answer: CDEF

NEW QUESTION 218

You are responsible for a web application that consists of an Elastic Load Balancing (ELB) load balancer in front of an Auto Scaling group of Amazon Elastic Compute Cloud (EC2) instances. For a recent deployment of a new version of the application, a new Amazon Machine Image (AMI) was created, and the Auto Scaling group was updated with a new launch configuration that refers to this new AMI. During the deployment, you received complaints from users that the website was responding with errors. All instances passed the ELB health checks.

What should you do in order to avoid errors for future deployments? (Choose 2 answers)

- A. Add an Elastic Load Balancing health check to the Auto Scaling group
- B. Set a short period for the health checks to operate as soon as possible in order to prevent premature registration of the instance to the load balancer.
- C. Enable EC2 instance CloudWatch alerts to change the launch configuration's AMI to the previous one
- D. Gradually terminate instances that are using the new AMI.
- E. Set the Elastic Load Balancing health check configuration to target a part of the application that fully tests application health and returns an error if the tests fail.
- F. Create a new launch configuration that refers to the new AMI, and associate it with the group
- G. Double the size of the group, wait for the new instances to become healthy, and reduce back to the original size. If new instances do not become healthy, associate the previous launch configuration.
- H. Increase the Elastic Load Balancing Unhealthy Threshold to a higher value to prevent an unhealthy instance from going into service behind the load balancer.

Answer: CD

NEW QUESTION 222

Which is a valid Amazon Resource name (ARN) for IAM?

- A. aws:iam::123456789012:instance-profile\Nebserver
- B. arn:aws:iam::123456789012:instance-profile/Webserver
- C. 123456789012:aws:iam::instance-profile\Nebserver
- D. arn:aws:iam::123456789012::instance-profile\Nebserver

Answer: B

NEW QUESTION 224

Dave is the main administrator in Example Corp., and he decides to use paths to help delineate the users in the company and set up a separate administrator group for each path-based division. Following is a subset of the full list of paths he plans to use:

. /marketing
. /sales
. Legal

Dave creates an administrator group for the marketing part of the company and calls it MktAdmin. He assigns it the /marketing path. The group's ARN is arn:aws:iam::123456789012:group/marketing/MktAdmin.

Dave assigns the following policy to the MktAdmin group that gives the group permission to use all IAM actions with all groups and users in the /marketing path. The policy also gives the MktAdmin group permission to perform any AWS S3 actions on the objects in the portion of the corporate bucket.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Deny",
      "Action": "iam:*",
      "Resource": [
        "arn:aws:iam::123456789012:group/marketing/*",
        "arn:aws:iam::123456789012:user/marketing/*"
      ]
    },
    {
      "Effect": "Allow",
      "Action": "s3:*",
      "Resource": "arn:aws:s3:::example_bucket/marketing/*"
    },
    {
      "Effect": "Allow",
      "Action": "s3:ListBucket",
      "Resource": "arn:aws:s3:::example_bucket",
      "Condition": {
        "StringLike": {
          "s3:prefix": "marketing/*"
        }
      }
    }
  ]
}
```

- A. True
- B. False

Answer: B

NEW QUESTION 225

A company is running a batch analysis every hour on their main transactional DB, running on an RDS MySQL instance, to populate their central Data Warehouse running on Redshift. During the execution of the batch, their transactional applications are very slow. When the batch completes they need to update the top management dashboard with the new data. The dashboard is produced by another system running on-premises that is currently started when a manually-sent email notifies that an update is required. The on-premises system cannot be modified because it is managed by another team. How would you optimize this scenario to solve performance issues and automate the process as much as possible?

- A. Replace RDS with Redshift for the batch analysis and SNS to notify the on-premises system to update the dashboard
- B. Replace RDS with Redshift for the batch analysis and SQS to send a message to the on-premises system to update the dashboard
- C. Create an RDS Read Replica for the batch analysis and SNS to notify the on-premises system to update the dashboard
- D. Create an RDS Read Replica for the batch analysis and SQS to send a message to the on-premises system to update the dashboard.

Answer: A

NEW QUESTION 228

You are designing a data leak prevention solution for your VPC environment. You want your VPC Instances to be able to access software depots and distributions on the Internet for product updates. The depots and distributions are accessible via third party CDNs by their URLs. You want to explicitly deny any other outbound connections from your VPC instances to hosts on the internet.

Which of the following options would you consider?

- A. Configure a web proxy server in your VPC and enforce URL-based rules for outbound access. Remove default routes.
- B. Implement security groups and configure outbound rules to only permit traffic to software depots.
- C. Move all your instances into private VPC subnets, remove default routes from all routing tables and add specific routes to the software depots and distributions only.
- D. Implement network access control lists to all specific destinations, with an implicit deny as a rule.

Answer: A

NEW QUESTION 232

You have an application running on an EC2 instance which will allow users to download files from a private S3 bucket using a pre-signed URL. Before generating the URL, the application should verify the existence of the file in S3. How should the application use AWS credentials to access the S3 bucket securely?

- A. Use the AWS account access keys; the application retrieves the credentials from the source code of the application.
- B. Create an IAM role for EC2 that allows list access to objects in the S3 bucket; launch the Instance with the role, and retrieve the role's credentials from the EC2 instance metadata service.

instance metadata.

C. Create an IAM user for the application with permissions that allow list access to the S3 bucket; the application retrieves the IAM user credentials from a temporary directory with permissions that allow read access only to the Application user.

D. Create an IAM user for the application with permissions that allow list access to the S3 bucket; launch the instance as the IAN user, and retrieve the IAM user's credentials from the EC2 instance user data.

Answer: B

NEW QUESTION 235

A 3-tier e-commerce web application is current deployed on-premises and will be migrated to AWS for greater scalability and elasticity The web server currently shares read-only data using a network distributed file system The app server tier uses a clustering mechanism for discovery and shared session state that depends on IP multicast The database tier uses shared-storage clustering to provide database fail over capability, and uses several read slaves for scaling Data on all servers and the distributed file system directory is backed up weekly to off-site tapes Which AWS storage and database architecture meets the requirements of the application?

- A. Web servers: store read-only data in S3, and copy from S3 to root volume at boot tim
- B. App servers: share state using a combination of DynamoDB and IP unicas
- C. Database: use RDS with multi-AZ deployment and one or more read replica
- D. Backup: web sewers, app sewers, and database backed up weekly to Glacier using snapshots.
- E. Web sewers: store read-only data in an EC2 NFS sewer; mount to each web server at boot tim
- F. App servers: share state using a combination of DynamoDB and IP multicas
- G. Database: use RDS with multi-AZ deployment and one or more Read Replica
- H. Backup: web and app servers backed up weekly via AMIs, database backed up via DB snapshots.
- I. Web sewers: store read-only data in S3, and copy from S3 to root volume at boot tim
- J. App sewers: share state using a combination of DynamoDB and IP unicas
- K. Database: use RDS with multi-AZ deployment and one or more Read Replica
- L. Backup: web and app sewers backed up weekly via AMIs, database backed up via DB snapshots.
- M. Web sewers: store read-only data in S3, and copy from S3 to root volume at boot tim
- N. App sewers: share state using a combination of DynamoDB and IP unicas
- O. Database: use RDS with multi-AZ deploymen
- P. Backup: web and app servers backed up weekly via AMIs, database backed up via DB snapshots.

Answer: C

NEW QUESTION 240

Your company plans to host a large donation website on Amazon Web Sewices (AWS). You anticipate a large and undetermined amount of traffic that will create many database writes. To be certain that you do not drop any writes to a database hosted on AWS. Which sewice should you use?

- A. Amazon RDS with provisioned IOPS up to the anticipated peak write throughput.
- B. Amazon Simple Queue Service (SQS) for capturing the writes and draining the queue to write to the database.
- C. Amazon ElastiCache to store the writes until the writes are committed to the database.
- D. Amazon DynamoDB with provisioned write throughput up to the anticipated peak write throughpu

Answer: B

NEW QUESTION 243

An administrator is using Amazon CloudFormation to deploy a three tier web application that consists of a web tier and application tier that will utilize Amazon DynamoDB for storage when creating the CloudFormation template which of the following would allow the application instance access to the DynamoDB tables without exposing API credentials?

- A. Create an Identity and Access Management Role that has the required permissions to read and write from the required DynamoDB table and associate the Role to the application instances by referencing an instance profile.
- B. Use the Parameter section in the Cloud Formation template to nave the user input Access and Secret Keys from an already created IAM user that has me permissions required to read and write from the required DynamoDB table.
- C. Create an Identity and Access Management Role that has the required permissions to read and write from the required DynamoDB table and reference the Role in the instance profile property of the application instance.
- D. Create an identity and Access Management user in the CloudFormation template that has permissions to read and write from the required DynamoDB table, use the GetAtt function to retrieve the Access and secret keys and pass them to the application instance through user-data.

Answer: C

NEW QUESTION 247

Your company has recently extended its datacenter into a VPC on AWS to add burst computing capacity as needed Members of your Network Operations Center need to be able to go to the AWS Management Console and administer Amazon EC2 instances as necessary You don't want to create new IAM users for each NOC member and make those users sign in again to the AWS Management Console Which option below will meet the needs for your NOC members?

- A. Use OAuth 2.0 to retrieve temporary AWS security credentials to enable your NOC members to sign in to the AWS Management Console.
- B. Use web Identity Federation to retrieve AWS temporary security credentials to enable your NOC members to sign in to the AWS Management Console.
- C. Use your on-premises SAML 2.0-compliant identity provider (IDP) to grant the NOC members federated access to the AWS Management Console via the AWS single sign-on (SSO) endpoint.
- D. Use your on-premises SAML2.0-compliam identity provider (IDP) to retrieve temporary security credentials to enable NOC members to sign in to the AWS Management Console.

Answer: D

NEW QUESTION 250

Select the correct set of options. These are the initial settings for the default security group:

- A. Allow no inbound traffic, Allow all outbound traffic and Allow instances associated with this security group to talk to each other
- B. Allow all inbound traffic, Allow no outbound traffic and Allow instances associated with this security group to talk to each other
- C. Allow no inbound traffic, Allow all outbound traffic and Does NOT allow instances associated with this security group to talk to each other
- D. Allow all inbound traffic, Allow all outbound traffic and Does NOT allow instances associated with this security group to talk to each other

Answer: A

NEW QUESTION 252

Which of the following are characteristics of Amazon VPC subnets? Choose 2 answers

- A. Each subnet spans at least 2 Availability Zones to provide a high-availability environment.
- B. Each subnet maps to a single Availability Zone.
- C. CIDR block mask of /25 is the smallest range supported.
- D. By default, all subnets can route between each other, whether they are private or public.
- E. Instances in a private subnet can communicate with the Internet only if they have an Elastic I

Answer: AE

NEW QUESTION 255

In AWS, which security aspects are the customer's responsibility? Choose 4 answers

- A. Security Group and ACL (Access Control List) settings
- B. Decommissioning storage devices
- C. Patch management on the EC2 instance's operating system
- D. Life-cycle management of IAM credentials
- E. Controlling physical access to compute resources
- F. Encryption of EBS (Elastic Block Storage) volumes

Answer: ACDF

NEW QUESTION 256

When you put objects in Amazon S3, what is the indication that an object was successfully stored?

- A. A HTTP 200 result code and MD5 checksum, taken together, indicate that the operation was successful.
- B. Amazon S3 is engineered for 99.999999999% durabilit
- C. Therefore there is no need to confirm that data was inserted.
- D. A success code is inserted into the S3 object metadata.
- E. Each S3 account has a special bucket named _s3_log
- F. Success codes are written to this bucket witha timestamp and checksum.

Answer: A

NEW QUESTION 259

A company is storing data on Amazon Simple Storage Service (S3). The company's security policy mandates that data is encrypted at rest. Which of the following methods can achieve this?

Choose 3 answers

- A. Use Amazon S3 server-side encryption with AWS Key Management Service managed keys.
- B. Use Amazon S3 server-side encryption with customer-provided keys.
- C. Use Amazon S3 server-side encryption with EC2 key pair.
- D. Use Amazon S3 bucket policies to restrict access to the data at rest.
- E. Encrypt the data on the client-side before ingesting to Amazon S3 using their own master key.
- F. Use SSL to encrypt the data while in transit to Amazon S3.

Answer: ABE

NEW QUESTION 262

You are designing Internet connectMty for your VPC. The Web sewers must be available on the Internet. The application must have a highly available architecture. Which alternatives should you consider? (Choose 2 answers)

- A. Configure a NAT instance in your VPC Create a default route via the NAT instance and associate itwith all subnets Configure a DNS A record that points to the NAT instance public IP address.
- B. Configure a C|oudFront distribution and configure the origin to point to the private IP addresses of your Web sewers Configure a Route53 CNAME record to your CloudFront distribution.
- C. Place all your web servers behind ELB Configure a Route53 CNMIE to point to the ELB DNS name.
- D. Assign EIPs to all web sewer
- E. Configure a Route53 record set with all E|Ps, with health checks and DNS failover.
- F. Configure ELB with an EIP Place all your Web servers behind ELB Configure a Route53 A record that points to the EIP.

Answer: CD

NEW QUESTION 266

Your team has a tomcat-based Java application you need to deploy into development, test and production environments. After some research, you opt to use Elastic Beanstalk due to its tight integration with your developer tools and RDS due to its ease of management. Your QA team lead points out that you need to roll a sanitized set of production data into your environment on a nightly basis.

Similarly, other software teams in your org want access to that same restored data via their EC2 instances in your VPC .The optimal setup for persistence and security that meets the above requirements would be the following.

- A. Create your RDS instance as part of your Elastic Beanstalk definition and alter its security group to allow access to it from hosts in your application subnets.
- B. Create your RDS instance separately and add its IP address to your application's DB connection strings in your code. Alter its security group to allow access to it from hosts within your VPC's IP address block.
- C. Create your RDS instance separately and pass its DNS name to your app's DB connection string as an environment variable.
- D. Create a security group for client machines and add it as a valid source for DB traffic to the security group of the RDS instance itself.
- E. Create your RDS instance separately and pass its DNS name to your app's DB connection string as an environment variable. Alter its security group to allow access to it from hosts in your application subnets.

Answer: A

NEW QUESTION 271

Your company has an on-premises multi-tier PHP web application, which recently experienced downtime due to a large burst in web traffic due to a company announcement. Over the coming days, you are expecting similar announcements to drive similar unpredictable bursts, and are looking to find ways to quickly improve your infrastructure's ability to handle unexpected increases in traffic.

The application currently consists of 2 tiers: a web tier which consists of a load balancer and several Linux Apache web servers as well as a database tier which hosts a Linux server hosting a MySQL database. Which scenario below will provide full site functionality, while helping to improve the ability of your application in the short timeframe required?

- A. Failover environment: Create an S3 bucket and configure it for website hosting.
- B. Migrate your DNS to Route53 using zone file import, and leverage Route53 DNS failover to failover to the S3 hosted website.
- C. Hybrid environment: Create an AMI, which can be used to launch web servers in EC2. Create an Auto Scaling group, which uses the AMI to scale the web tier based on incoming traffic.
- D. Leverage Elastic Load Balancing to balance traffic between on-premises web servers and those hosted in AWS.
- E. Offload traffic from on-premises environment: Setup a CloudFront distribution, and configure CloudFront to cache objects from a custom origin.
- F. Choose to customize your object cache behavior, and select a TTL that objects should exist in cache.
- G. Migrate to AWS: Use VM Import/Export to quickly convert an on-premises web server to an AMI.
- H. Create an Auto Scaling group, which uses the imported AMI to scale the web tier based on incoming traffic.
- I. Create an RDS read replica and setup replication between the RDS instance and on-premises MySQL server to migrate the database.

Answer: C

NEW QUESTION 276

An ERP application is deployed across multiple AZs in a single region. In the event of failure, the Recovery Time Objective (RTO) must be less than 3 hours, and the Recovery Point Objective (RPO) must be 15 minutes. The customer realizes that data corruption occurred roughly 1.5 hours ago.

What DR strategy could be used to achieve this RTO and RPO in the event of this kind of failure?

- A. Take hourly DB backups to S3, with transaction logs stored in S3 every 5 minutes.
- B. Use synchronous database master-slave replication between two availability zones.
- C. Take hourly DB backups to EC2 Instance Store volumes with transaction logs stored in S3 every 5 minutes.
- D. Take 15 minute DB backups stored in Glacier with transaction logs stored in S3 every 5 minutes.

Answer: A

NEW QUESTION 280

The following are AWS Storage services? Choose 2 Answers

- A. AWS Relational Database Service (AWS RDS)
- B. AWS ElastiCache
- C. AWS Glacier
- D. AWS Import/Export

Answer: BD

NEW QUESTION 283

How is AWS readily distinguished from other vendors in the traditional IT computing landscape?

- A. Experience
- B. Scalable and elastic
- C. Secure
- D. Cost-effective
- E. Reliable
- F. Secure
- G. Flexible
- H. Cost-effective
- I. Scalable and elastic
- J. Global
- K. Secure
- L. Flexible
- M. Cost-effective
- N. Scalable and elastic
- O. Experienced
- P. Flexible
- Q. Cost-effective
- R. Dynamic
- S. Secure
- T. Experience

Answer: C

NEW QUESTION 286

A newspaper organization has a on-premises application which allows the public to search its back catalogue and retrieve individual newspaper pages via a website written in Java. They have scanned the old newspapers into JPEGs (approx 17TB) and used Optical Character Recognition (OCR) to populate a commercial search product. The hosting platform and software are now end of life and the organization wants to migrate its archive to AWS and produce a cost efficient architecture and still be designed for availability and durability. Which is the most appropriate?

- A. Use S3 with reduced redundancy to store and serve the scanned files, install the commercial search application on EC2 instances and configure with auto-scaling and an Elastic Load Balancer.
- B. Model the environment using CloudFormation, use an EC2 instance running Apache webserver and an open source search application, stripe multiple standard EBS volumes together to store the JPEGs and search index.
- C. Use S3 with standard redundancy to store and serve the scanned files, use CloudSearch for query processing, and use Elastic Beanstalk to host the website across multiple availability zones.
- D. Use a single-AZ RDS MySQL instance to store the search index and the JPEG images, use an EC2 instance to serve the website and translate user queries into SQL.
- E. Use a CloudFront download distribution to serve the JPEGs to the end users and install the current commercial search product, along with a Java container for the website on EC2 instances and use Route53 with DNS round-robin.

Answer: C

NEW QUESTION 287

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

AWS-Certified-Solutions-Architect-Professional Practice Exam Features:

- * AWS-Certified-Solutions-Architect-Professional Questions and Answers Updated Frequently
- * AWS-Certified-Solutions-Architect-Professional Practice Questions Verified by Expert Senior Certified Staff
- * AWS-Certified-Solutions-Architect-Professional Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * AWS-Certified-Solutions-Architect-Professional Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The AWS-Certified-Solutions-Architect-Professional Practice Test Here](#)