



# Fortinet

## Exam Questions NSE7\_EFW-7.0

Fortinet NSE 7 - Enterprise Firewall 7.0

## About ExamBible

*[Your Partner of IT Exam](#)*

## Found in 1998

ExamBible is a company specialized on providing high quality IT exam practice study materials, especially Cisco CCNA, CCDA, CCNP, CCIE, Checkpoint CCSE, CompTIA A+, Network+ certification practice exams and so on. We guarantee that the candidates will not only pass any IT exam at the first attempt but also get profound understanding about the certificates they have got. There are so many alike companies in this industry, however, ExamBible has its unique advantages that other companies could not achieve.

## Our Advances

### \* 99.9% Uptime

All examinations will be up to date.

### \* 24/7 Quality Support

We will provide service round the clock.

### \* 100% Pass Rate

Our guarantee that you will pass the exam.

### \* Unique Gurantee

If you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

### NEW QUESTION 1

A FortiGate device has the following LDAP configuration:

```
config user ldap
  edit "WindowsLDAP"
    set server "10.0.1.10"
    set cnid "cn"
    set dn "cn=user, dc=trainingAD, dc=training, dc=lab"
    set type regular
    set username "cn=administrator, cn=users, dc=trainingAD,
dc=training, dc=lab"
    set password xxxxx
  next
end
```

The LDAP user student cannot authenticate. The exhibit shows the output of the authentication real time debug while testing the student account:

```
#diagnose debug application fnbamd -1
#diagnose debug enable
#diagnose test authserver ldap WindowsLDAP student password
fnbamd_fsm.c[1819] handle_req-Rcvd auth req 4 for student in WindowsLDAP
opt=27 prot=0
fnbamd_fsm.c[336]_compose_group_list_from_req_Group 'WindowsLDAP'
fnbamd_pop3.c[573] fnbamd_pop3_start-student
fnbamd_cfg.c[932] fnbamd_cfg-get_ldap_ist_by_server-Loading LDAP server
'WindowsLDAP'
fnbamd_ldap.c[992] resolve_ldap_FQDN-Resolved address 10.0.1.10, result 10.0.1.10
fnbamd_fsm.c[428] create_auth_session-Total 1 server(s) to try
fnbamd_ldap.c[1700] fnbamd_ldap_get_result-Error in ldap result: 49
(Invalid credentials)
fnbamd_ldap.c[2028] fnbamd_ldap_get_result-Auth denied
fnbamd_auth.c[2188] fnbamd_auth_poll_ldap-Result for ldap svr 10.0.1.10 is denied
fnbamd_comm.c[169] fnbamd_comm_send_result-Sending result 1 for req 4
fnbamd_fsm.c[568] destroy_auth_session-delete session 4
authenticate 'student' against 'WindowsLDAP' failed!
```

Based on the above output, what FortiGate LDAP settings must the administrator check? (Choose two.)

- A. cnid.
- B. username.
- C. password.
- D. dn.

**Answer:** BC

**Explanation:**

<https://kb.fortinet.com/kb/viewContent.do?externalId=13141>

### NEW QUESTION 2

What does the dirty flag mean in a FortiGate session?

- A. Traffic has been blocked by the antivirus inspection.
- B. The next packet must be re-evaluated against the firewall policies.
- C. The session must be removed from the former primary unit after an HA failover.
- D. Traffic has been identified as from an application that is not allowed.

**Answer:** B

**Explanation:**

<https://kb.fortinet.com/kb/viewContent.do?externalId=FD40119&sliceId=1>

### NEW QUESTION 3

What is the purpose of an internal segmentation firewall (ISFW)?

- A. It inspects incoming traffic to protect services in the corporate DMZ.
- B. It is the first line of defense at the network perimeter.
- C. It splits the network into multiple security segments to minimize the impact of breaches.
- D. It is an all-in-one security appliance that is placed at remote sites to extend the enterprise network.

**Answer:** C

**Explanation:**

ISFW splits your network into multiple security segments. They serve as a breach containers from attacks that come from inside.

#### NEW QUESTION 4

View the central management configuration shown in the exhibit, and then answer the question below.

```
config system central-management
  set type fortimanager
  set fmg "10.0.1.242"
  config server-list
    edit 1
      set server-type rating
      set server-address 10.0.1.240
    next
    edit 2
      set server-type update
      set server-address 10.0.1.243
    next
    edit 3
      set server-type rating
      set server-address 10.0.1.244
    next
  end
  set include-default-servers enable
end
```

Which server will FortiGate choose for antivirus and IPS updates if 10.0.1.243 is experiencing an outage?

- A. 10.0.1.240
- B. One of the public FortiGuard distribution servers
- C. 10.0.1.244
- D. 10.0.1.242

**Answer:** B

#### NEW QUESTION 5

Which statements about bulk configuration changes using FortiManager CLI scripts are correct? (Choose two.)

- A. When executed on the Policy Package, ADOM database, changes are applied directly to the managed FortiGate.
- B. When executed on the Device Database, you must use the installation wizard to apply the changes to the managed FortiGate.
- C. When executed on the All FortiGate in ADOM, changes are automatically installed without creating a new revision history.
- D. When executed on the Remote FortiGate directly, administrators do not have the option to review the changes prior to installation.

**Answer:** BD

#### Explanation:

CLI scripts can be run in three different ways: Device Database: By default, a script is executed on the device database. It is recommended you run the changes on the device database (default setting), as this allows you to check what configuration changes you will send to the managed device. Once scripts are run on the device database, you can install these changes to a managed device using the installation wizard.

Policy Package, ADOM database: If a script contains changes related to ADOM level objects and policies, you can change the default selection to run on Policy Package, ADOM database and can then be installed using the installation wizard.

Remote FortiGate directly (through CLI): A script can be executed directly on the device and you don't need to install these changes using the installation wizard. As the changes are directly installed on the managed device, no option is provided to verify and check the configuration changes through FortiManager prior to executing it.

#### NEW QUESTION 6

Refer to the exhibit, which contains partial output from an IKE real-time debug.

```
ike 0: comes 10.0.0.2:500->10.0.0.1:500, ifindex=7. . .
ike 0: IKEv2 exchange=Aggressive id=a2fbd6bb6394401a/06b89c022d4df682 len=426
ike 0: Remotesite:3: initiator: aggressive mode get 1st response. . .
ike 0: Remotesite:3: VID DPD AFCAD71368A1F1C96B8696FC77570100
ike 0: Remotesite:3: DPD negotiated
ike 0: Remotesite:3: VID FORTIGATE 8299031757A36082C6A621DE00000000
ike 0: Remotesite:3: peer is FortiGate/PortiOS (v0 b0)
ike 0: Remotesite:3: VID FRAGMENTATION 4048B7D56EBCE88525E7DE7F00D6C2D3
ike 0: Remotesite:3: VID FRAGMENTATION 4048B7D56EBCE88525E7DE7F00D6C2D3C0000000
ike 0: Remotesite:3: received peer identifier PQDN 'remote'
ike 0: Remotesite:3: negotiation result
ike 0: Remotesite:3: proposal id = 1:
ike 0: Remotesite:3:   protocol id = ISAKMP:
ike 0: Remotesite:3:   trans_id = KEY_IKE.
ike 0: Remotesite:3:   encapsulation = IKE/none.
ike 0: Remotesite:3:   type=OAKLEY_ENCRYPT_ALG, val=AES_CBC, key-len=128
ike 0: Remotesite:3:   type=OAKLEY_HASH_ALG, val=SHA.
ike 0: Remotesite:3:   type=AUTH_METHOD, val=PRESHARED_KEY.
ike 0: Remotesite:3:   type=OAKLEY_GROUP, val=MODP1024.
ike 0: Remotesite:3: ISAKMP SA lifetime=86400
ike 0: Remotesite:3: NAT-T unavailable
ike 0: Remotesite:3: ISAKMP SA a2fbd6bb6394401a/06b89c022d4df682 key
16:39915120ED73ED73E520787C801DE3678916
ike 0: Remotesite:3: PSK authentication succeeded
ike 0: Remotesite:3: authentication OK
ike 0: Remotesite:3: add INITIAL-CONTACT
ike 0: Remotesite:3: enc
A2FBD6BB6394401A06B89C022D4DF6820810040100000000000000500B000018882A07BE09026CA8B2
ike 0: Remotesite:3: out
A2FBD6BB6394401A06B89C022D4DF6820810040100000000000005C64D5CBA90B873F150CB8B5CC2A
ike 0: Remotesite:3: sent IKE msg (agg_i2send): 10.0.0.1:500->10.0.0.2:500, len=140,
id=a2fbd6bb6394401a/
ike 0: Remotesite:3: established IKE SA a2fbd6bb6394401a/06b89c022d4df682
```

Which two statements about this debug output are correct? (Choose two.)

- A. The remote gateway IP address is 10.0.0.1.
- B. The initiator provided remote as its IPsec peer ID.
- C. It shows a phase 1 negotiation.
- D. The negotiation is using AES128 encryption with CBC hash.

**Answer:** BC

#### NEW QUESTION 7

Which of the following conditions must be met for a static route to be active in the routing table? (Choose three.)

- A. The next-hop IP address is up.
- B. There is no other route, to the same destination, with a higher distance.
- C. The link health monitor (if configured) is up.
- D. The next-hop IP address belongs to one of the outgoing interface subnets.
- E. The outgoing interface is up.

**Answer:** CDE

#### Explanation:

A configured static route only goes to routing table from routing database when all the following are met :

- > The outgoing interface is up
- > There is no other matching route with a lower distance
- > The link health monitor (if configured) is successful
- > The next-hop IP address belongs to one of the outgoing interface subnets

#### NEW QUESTION 8

How does FortiManager handle FortiGuard requests from FortiGate devices, when it is configured as a local FDS?

- A. FortiManager can download and maintain local copies of FortiGuard databases.
- B. FortiManager supports only FortiGuard push to managed devices.
- C. FortiManager will respond to update requests only if they originate from a managed device.
- D. FortiManager does not support rating requests.

**Answer:** A

#### NEW QUESTION 9

Examine the output of the 'diagnose sys session list expectation' command shown in the exhibit; than answer the question below.



```
#diagnose sys session list expectation

session info: proto= proto_state=0 0 duration=3 expire=26 timeout=3600
flags=00000000
sockflag=00000000 sockport=0 av_idx=0 use=3
origin-shaper=
reply-shaper=
per-ip_shaper=
ha_id=0 policy_dir=1 tunnel=/
state=new complex
statistic (bytes/packets/allow_err): org=0/0/0 reply=0/0/0 tuples=2
orgin-> sink: org pre-> post, reply pre->post dev=2->4/4->2
gwy=10.0.1.10/10.200.1.254
hook=pre dir=org act=dnat 10.171.121.38:0-> 10.200.1.1: 60426
(10.0.1.10: 50365)
hook= pre dir=org act=noop 0.0.0.0:0-> 0.0.0.0:0 (0.0.0.0:0)
pos/(before, after) 0/(0,0), 0/(0,0)
misc=0 policy_id=1 auth_info=0 chk_client_info=0 vd=0
seriall=000000e9 tos=ff/ff ips_view=0 app_list=0 app=0
dd type=0 dd_mode=0
```

Which statement is true regarding the session in the exhibit?

- A. It was created by the FortiGate kernel to allow push updates from FotiGuard.
- B. It is for management traffic terminating at the FortiGate.
- C. It is for traffic originated from the FortiGate.
- D. It was created by a session helper or ALG.

**Answer: D**

#### NEW QUESTION 10

View the exhibit, which contains the output of a BGP debug command, and then answer the question below.

```
# get router info bgp summary
BGP router identifier 0.0.0.117, local AS number 65117
BGP table version is 104
3 BGP AS-PATH entries
0 BGP community entries

Neighbor    V    AS  MsgRcvd  MsgSent  TblVer  InQ  OutQ  Up/Down  State/PfxRcd
10.125.0.60 4  65060   1698      1756    103   0    0 03:02:49        1
10.127.0.75 4  65075   2206      2250    102   0    0 02:45:55        1
10.200.3.1  4  65501    101        115     0    0    0 never         Active

Total number of neighbors 3
```

Which of the following statements about the exhibit are true? (Choose two.)

- A. For the peer 10.125.0.60, the BGP state of is Established.
- B. The local BGP peer has received a total of three BGP prefixes.
- C. Since the BGP counters were last reset, the BGP peer 10.200.3.1 has never been down.
- D. The local BGP peer has not established a TCP session to the BGP peer 10.200.3.1.

**Answer: AD**

#### NEW QUESTION 10

An LDAP user cannot authenticate against a FortiGate device. Examine the real time debug output shown in the exhibit when the user attempted the authentication; then answer the question below.

```
# debug application fnbamd -1
# diagnose debug enable
# diagnose test authserver ldap WindowsLDAP student password
fnbamd_fsm.c[1819] handle_req-Rcvd auth req 5 for student in WindowsLDAP opt=27 prot=0
fnbamd_fsm.c[336] __compose_group_list_from_req-Group 'WindowsLDAP'
fnbamd_pop3.c[573] fnbamd_pop3_start-student
fnbamd_cfg.c[932] __fnbamd_cfg_get_ldap_list_by_server-Loading LDAP server
'WindowsLDAP'
fnbamd_ldap.c[992] resolve_ldap_FQDN-Resolved address 10.0.1.10, result 10.0.1.10
fnbamd_fsm.c[428] create_auth_session-Total 1 server(s) to try
fnbamd_ldap.c[437] start_search_dn-base: 'cn=user,dc=trainingAD,dc=training,dc=lab'
filter:cn=student
fnbamd_ldap.c[1730] fnbamd_ldap_get_result-Going to SEARCH state
fnbamd_fsm.c[2407] auth_ldap_result-Continue pending for req 5
fnbamd_ldap.c[480] get_all_dn-Found no DN
fnbamd_ldap.c[503] start_next_dn_bind-No more DN left
fnbamd_ldap.c[2028] fnbamd_ldap_get_result-Auth denied
fnbamd_auth.c[2188] fnbamd_auth_poll_ldap-Result for ldap svr 10.0.1.10 is denied
fnbamd_comm.c[169] fnbamd_comm_send_result-Sending result 1 for req 5
fnbamd_fsm.c[568] destroy_auth_session-delete session 5
authenticate 'student' against 'WindowsLDAP' failed!
```

Based on the output in the exhibit, what can cause this authentication problem?

- A. User student is not found in the LDAP server.
- B. User student is using a wrong password.
- C. The FortiGate has been configured with the wrong password for the LDAP administrator.
- D. The FortiGate has been configured with the wrong authentication schema.

**Answer:** A

#### NEW QUESTION 14

Which two tasks are automated using the Install Wizard on FortiManager? (Choose two.)

- A. Installing configuration changes to managed devices
- B. Importing interface mappings from managed devices
- C. Adding devices to FortiManager
- D. Previewing pending configuration changes for managed devices

**Answer:** AD

#### NEW QUESTION 15

Examine the IPsec configuration shown in the exhibit; then answer the question below.

Name	Remote	
Comments	Comments	
Network		
IP Version	<input checked="" type="radio"/> IPv4 <input type="radio"/> IPv6	
Remote Gateway	Static IP Address	<input checked="" type="checkbox"/>
IP Address	10.0.10.1	
Interface	port1	<input checked="" type="checkbox"/>
Mode Config	<input type="checkbox"/>	
NAT Traversal	<input checked="" type="checkbox"/>	
Keepalive Frequency	10	
Dead Peer Detection	<input checked="" type="checkbox"/>	

An administrator wants to monitor the VPN by enabling the IKE real time debug using these commands: diagnose vpn ike log-filter src-addr4 10.0.10.1  
diagnose debug application ike -1  
diagnose debug enable

The VPN is currently up, there is no traffic crossing the tunnel and DPD packets are being interchanged between both IPsec gateways. However, the IKE real time debug does NOT show any output. Why isn't there any output?

- A. The IKE real time shows the phases 1 and 2 negotiations onl
- B. It does not show any more output once the tunnel is up.
- C. The log-filter setting is set incorrectl
- D. The VPN's traffic does not match this filter.
- E. The IKE real time debug shows the phase 1 negotiation onl
- F. For information after that, the administrator must use the IPsec real time debug instead: diagnose debug application ipsec -1.
- G. The IKE real time debug shows error messages onl
- H. If it does not provide any output, it indicates that the tunnel is operating normally.

**Answer:** B

#### NEW QUESTION 19

An administrator has enabled HA session synchronization in a HA cluster with two members. Which flag is added to a primary unit's session to indicate that it has been synchronized to the secondary unit?

- A. redir.
- B. dirty.
- C. synced
- D. nds.

**Answer:** C

#### Explanation:

The synced sessions have the 'synced' flag. The command 'diag sys session list' can be used to see the sessions on the member, with the associated flags.

#### NEW QUESTION 21

Which statement about memory conserve mode is true?

- A. A FortiGate exits conserve mode when the configured memory use threshold reaches yellow.
- B. A FortiGate starts dropping all the new and old sessions when the configured memory use threshold reaches extreme.
- C. A FortiGate starts dropping new sessions when the configured memory use threshold reaches red
- D. A FortiGate enters conserve mode when the configured memory use threshold reaches red

**Answer:** D

#### NEW QUESTION 26

An administrator is running the following sniffer in a FortiGate: diagnose sniffer packet any "host 10.0.2.10" 2  
What information is included in the output of the sniffer? (Choose two.)

- A. Ethernet headers.
- B. IP payload.
- C. IP headers.
- D. Port names.

**Answer:** BC

#### Explanation:

<https://kb.fortinet.com/kb/documentLink.do?externalID=11186>

#### NEW QUESTION 29

Which two tasks are automated using the Install Wizard on FortiManager? (Choose two.)

- A. Preview pending configuration changes for managed devices.
- B. Add devices to FortiManager.
- C. Import policy packages from managed devices.
- D. Install configuration changes to managed devices.
- E. Import interface mappings from managed devices.

**Answer:** AD

#### Explanation:

[https://help.fortinet.com/fmgr/50hlp/56/5-6-2/FortiManager\\_Admin\\_Guide/1000\\_Device%20Manager/1200\\_ins](https://help.fortinet.com/fmgr/50hlp/56/5-6-2/FortiManager_Admin_Guide/1000_Device%20Manager/1200_ins)

There are 4 main wizards: Add Device: is used to add devices to central management and import their configurations.


Install: is used to install configuration changes from Device Manager or Policies & Objects to the managed devices. It allows you to preview the changes and, if the administrator doesn't agree with the changes, cancel and modify them.

Import policy: is used to import interface mapping, policy database, and objects associated with the managed devices into a policy package under the Policy & Object tab. It runs with the Add Device wizard by default and may be run at any time from the managed device list.

Re-install policy: is used to perform a quick install of the policy package. It doesn't give the ability to preview the changes that will be installed to the managed device.

#### NEW QUESTION 34

Refer to exhibit, which contains the output of a BGP debug command.



```
FGT # get router info bgp summary
BGP router identifier 10.200.1.1, local AS number 655
BGP table version is 2
1 BGP AS-PATH entries
0 BGP community entries

Neighbor      V   AS      MsgRcvd MsgSent   TblVer
10.200.3.1    4 65501     92     1756      0

Total number of neighbors 1
```

Which statement explains why the state of the 10.200.3.1 peer is Connect?

- A. The local router is receiving BGP keepalives from the remote peer, but the local peer has not received the OpenConfirm yet.
- B. The TCP session to 10.200.3.1 has not completed the three-way handshake.
- C. The local router is receiving the BGP keepalives from the peer, but it has not received a BGP prefix yet.
- D. The local router has received the BGP prefixes from the remote peer.

**Answer:** B

#### Explanation:

BGP neighbor states and how they change:• Idle: Initial state• Connect: Waiting for a successful three-way TCP connection• Active: Unable to establish the TCP session• OpenSent: Waiting for an OPEN message from the peer• OpenConfirm: Waiting for the keepalive message from the peer• Established: Peers have successfully exchanged OPEN and keepalive messages

#### NEW QUESTION 38

Examine the output from the BGP real time debug shown in the exhibit, then the answer the question below:



```
# diagnose ip router bgp all enable
# diagnose ip router bgp level info
# diagnose debug enable
"BGP: 10.200.3.1-Outgoing [DECODE] KAlive: Received!"
"BGP: 10.200.3.1-Outgoing [FSM] State: OpenConfirm Event: 26"
"BGP: 10.200.3.1-Outgoing [DECODE] Msg-Hdr: type 2, length 56"
"BGP: 10.200.3.1-Outgoing [DECODE] Update: Starting UPDATE decoding... Byt
(37), msg_size (37)"
"BGP: 10.200.3.1-Outgoing [DECODE] Update: NLRI Len(13)"
"BGP: 10.200.3.1-Outgoing [FSM] State: Established Event: 27"
"BGP: 10.200.3.1-Outgoing [RIB] Update: Received Prefix 0.0.0.0/0"
"BGP: 10.200.3.1-Outgoing [RIB] Update: Received Prefix 10.200.4.0/24"
"BGP: 10.200.3.1-Outgoing [RIB] Update: Received Prefix 10.200.3.0/24"
"BGP: 10.200.3.1-Outgoing [RIB] Update: Received Prefix 10.0.2.0/24"
"BGP: 10.200.3.1-Outgoing [FSM] State: Established Event: 34"
"BGP: 10.200.3.1-Outgoing [ENCODE] Msg-Hdr: Type 2"
"BGP: 10.200.3.1-Outgoing [ENCODE] Attr IP-Unicast: Tot-attr-len 20"
"BGP: 10.200.3.1-Outgoing [ENCODE] Update: Msg #5 Size 55"
"BGP: 10.200.3.1-Outgoing [FSM] State: Established Event: 34"
```

Which statements are true regarding the output in the exhibit? (Choose two.)

- A. BGP peers have successfully interchanged Open and Keepalive messages.
- B. Local BGP peer received a prefix for a default route.
- C. The state of the remote BGP peer is OpenConfirm.
- D. The state of the remote BGP peer will go to Connect after it confirms the received prefixes.

**Answer: AB**

#### NEW QUESTION 43

Refer to the exhibits.

```
config vpn ipsec phase1-interface
edit "user-1"
set type dynamic
set interface "port1"
set mode main
set xauthtype auto
set authusrgrp "Users-1"
set peertype any
set dhgrp 14 15 19
set proposal aes128-sha256 aes256-sha384
set psksecret <encrypted_password>
next
```

Which contain the partial configurations of two VPNs on FortiGate.

An administrator has configured two VPNs for two different user groups. Users who are in the Users-2 group are not able to connect to the VPN. After running a diagnostics command, the administrator discovered that FortiGate is not matching the user-2 VPN for members of the Users-2 group.

Which two changes must administrator make to fix the issue? (Choose two.)

- A. Use different pre-shared keys on both VPNs
- B. Enable Mode Config on both VPNs.
- C. Set up specific peer IDs on both VPNs.
- D. Change to aggressive mode on both VPNs.

**Answer: CD**

#### NEW QUESTION 46

A FortiGate is rebooting unexpectedly without any apparent reason. What troubleshooting tools could an administrator use to get more information about the problem? (Choose two.)

- A. Firewall monitor.
- B. Policy monitor.
- C. Logs.
- D. Crashlogs.

**Answer: CD**

#### NEW QUESTION 48

Examine the following traffic log; then answer the question below.

date=20xx-02-01 time=19:52:01 devname=master device\_id="xxxxxxx" log\_id=0100020007 type=event subtype=system pri critical vd=root service=kemel status=failure msg="NAT port is exhausted."

What does the log mean?

- A. There is not enough available memory in the system to create a new entry in the NAT port table.
- B. The limit for the maximum number of simultaneous sessions sharing the same NAT port has been reached.
- C. FortiGate does not have any available NAT port for a new connection.

D. The limit for the maximum number of entries in the NAT port table has been reached.

**Answer:** B

#### NEW QUESTION 50

View the exhibit, which contains the output of a diagnose command, and then answer the question below.

```
# diagnose debug rating
Locale      : english
License     : Contract
Expiration  : Thu Sep 28 17:00:00 20xx
-- Server List (Thu Apr 19 10:41:32 20xx) --
```

IP	Weight	RTT	Flags	TZ	Packets	Curr Lost	Total Lost
64.26.151.37	10	45		-5	262432	0	846
64.26.151.35	10	46		-5	329072	0	6806
66.117.56.37	10	75		-5	71638	0	275
65.210.95.240	20	71		-8	36875	0	92
209.222.147.36	20	103	DI	-8	34784	0	1070
208.91.112.194	20	107	D	-8	35170	0	1533
96.45.33.65	60	144		0	33728	0	120
80.85.69.41	71	226		1	33797	0	192
62.209.40.74	150	97		9	33754	0	145
121.111.236.179	45	44	F	-5	26410	26226	26227

Which statements are true regarding the output in the exhibit? (Choose two.)

- A. FortiGate will probe 121.111.236.179 every fifteen minutes for a response.
- B. Servers with the D flag are considered to be down.
- C. Servers with a negative TZ value are experiencing a service outage.
- D. FortiGate used 209.222.147.3 as the initial server to validate its contract.

**Answer:** AD

#### Explanation:

A – because flag is Failed so fortigate will check if server is available every 15 minD-state is I , contact to validate contract info

#### NEW QUESTION 53

Examine the following partial output from a sniffer command; then answer the question below.

```
# diagnose sniff packet any 'icmp' 4
interfaces= [any]
filters = [icmp]
2.101199 wan2 in 192.168.1.110-> 4.2.2.2: icmp: echo request
2.101400 wan1 out 172.17.87.16-> 4.2.2.2: icmp: echo request
.....
2.123500 wan2 out 4.2.2.2-> 192.168.1.110: icmp: echo reply
244 packets received by filter
5 packets dropped by kernel
```

What is the meaning of the packets dropped counter at the end of the sniffer?

- A. Number of packets that didn't match the sniffer filter.
- B. Number of total packets dropped by the FortiGate.
- C. Number of packets that matched the sniffer filter and were dropped by the FortiGate.
- D. Number of packets that matched the sniffer filter but could not be captured by the sniffer.

**Answer:** D

#### Explanation:

<https://kb.fortinet.com/kb/documentLink.do?externalID=11655>

#### NEW QUESTION 55

View the exhibit, which contains the output of a debug command, and then answer the question below.

```
# diagnose hardware sysinfo conserve
memory conserve mode:      on
total RAM:                 3040 MB
memory used:               2706 MB 89% of total RAM
Memory freeable:           334 MB 11% of total RAM
memory used + freeable threshold extreme: 2887 MB 95% of total RAM
memory used threshold red:  2675 MB 88% of total RAM
memory used threshold green: 2492 MB 82% of total RAM
```

Which one of the following statements about this FortiGate is correct?

- A. It is currently in system conserve mode because of high CPU usage.
- B. It is currently in extreme conserve mode because of high memory usage.
- C. It is currently in proxy conserve mode because of high memory usage.
- D. It is currently in memory conserve mode because of high memory usage.

**Answer:** D

#### NEW QUESTION 58

An administrator has configured a FortiGate device with two VDOMs: root and internal. The administrator has also created an inter-VDOM link that connects both VDOMs. The objective is to have each VDOM advertise some routes to the other VDOM via OSPF through the inter-VDOM link. What OSPF configuration settings must match in both VDOMs to have the OSPF adjacency successfully forming? (Choose three.)

- A. Router ID.
- B. OSPF interface area.
- C. OSPF interface cost.
- D. OSPF interface MTU.
- E. Interface subnet mask.

**Answer:** BDE

#### NEW QUESTION 59


A FortiGate's port1 is connected to a private network. Its port2 is connected to the Internet. Explicit web proxy is enabled in port1 and only explicit web proxy users can access the Internet. Web cache is NOT enabled. An internal web proxy user is downloading a file from the Internet via HTTP. Which statements are true regarding the two entries in the FortiGate session table related with this traffic? (Choose two.)

- A. Both sessions have the local flag on.
- B. The destination IP addresses of both sessions are IP addresses assigned to FortiGate's interfaces.
- C. One session has the proxy flag on, the other one does not.
- D. One of the sessions has the IP address of port2 as the source IP address.

**Answer:** AD

#### NEW QUESTION 64

View the exhibit, which contains a partial web filter profile configuration, and then answer the question below.



The screenshot shows the configuration for a web filter profile named 'default'. The 'FortiGuard category based filter' is enabled, showing a list of categories: 'Bandwidth Consuming' and 'File Sharing and Storage'. The 'Status URL Filter' is also enabled, with 'Block invalid URLs' and 'URL Filter' both checked. Below this is a table of URL filters:

URL	Type	Action	Status
*dropbox.com	Wildcard	Block	Enable

The 'Web content filter' is also enabled. Below it is a table of web content filters:

Pattern Type	Pattern	Language	Action	Status
Wildcard	*dropbox*	Western	Exempt	Enable

Which action will FortiGate take if a user attempts to access www.dropbox.com, which is categorized as File Sharing and Storage?

- A. FortiGate will exempt the connection based on the Web Content Filter configuration.
- B. FortiGate will block the connection based on the URL Filter configuration.
- C. FortiGate will allow the connection based on the FortiGuard category based filter configuration.
- D. FortiGate will block the connection as an invalid URL.

**Answer:** B

#### Explanation:

fortigate does it in order Static URL -> FortiGuard -> Content -> Advanced (java, cookie removal..)so block it in first step

#### NEW QUESTION 68

Which statement is true regarding File description (FD) conserve mode?

- A. IPS inspection is affected when FortiGate enters FD conserve mode.
- B. A FortiGate enters FD conserve mode when the amount of available description is less than 5%.
- C. FD conserve mode affects all daemons running on the device.
- D. Restarting the WAD process is required to leave FD conserve mode.

**Answer:** B



#### NEW QUESTION 69

Which statement about NGFW policy-based application filtering is true?

- A. After the application has been identified, the kernel uses only the Layer 4 header to match the traffic.
- B. The IPS security profile is the only security option you can apply to the security policy with the action set to ACCEPT.
- C. After IPS identifies the application, it adds an entry to a dynamic ISDB table.
- D. FortiGate will drop all packets until the application can be identified.

**Answer:** D

#### NEW QUESTION 72

Examine the output of the 'get router info ospf neighbor' command shown in the exhibit; then answer the question below.

```
# get router info ospf neighbor
```

```
OSPF process 0:
```

Neighbor ID	Pri	State	Dead Time	Address	Interface
0.0.0.69	1	Full/DR	00:00:32	10.126.0.69	wan1
0.0.0.117	1	Full/DROther	00:00:34	10.126.0.117	wan1
0.0.0.2	1	Full/-	00:00:36	172.16.1.2	ToRemote

Which statements are true regarding the output in the exhibit? (Choose two.) Refer to the exhibit, which shows the output of a debug command.  
Which statement about the output is true?

- A. The OSPF routers with the IDs 0.0.0.69 and 0.0.0.117 are both designated routers for the wan1 network.
- B. The OSPF router with the ID 0.0.0.2 is the designated router for the ToRemote network.
- C. The local FortiGate is the designated router for the wan1 network.
- D. The interface ToRemote is a point-to-point OSPF network.

**Answer:** D

#### Explanation:

<https://www.cisco.com/c/en/us/support/docs/ip/open-shortest-path-first-ospf/13685-13.html>

#### NEW QUESTION 77

The CLI command `set intelligent-mode <enable | disable>` controls the IPS engine's adaptive scanning behavior. Which of the following statements describes IPS adaptive scanning?

- A. Determines the optimal number of IPS engines required based on system load.
- B. Downloads signatures on demand from FDS based on scanning requirements.
- C. Determines when it is secure enough to stop scanning session traffic.
- D. Choose a matching algorithm based on available memory and the type of inspection being performed.

**Answer:** C

#### Explanation:

Configuring IPS intelligenceStarting with FortiOS 5.2, intelligent-mode is a new adaptive detection method. This command is enabled the default and it means that the IPS engine will perform adaptive scanning so that, for some traffic, the FortiGate can quickly finish scanning and offload the traffic to NPU or kernel. It is a balanced method which could cover all known exploits. When disabled, the IPS engine scans every single byte.

```
config ips globalset intelligent-mode {enable|disable}end
```

#### NEW QUESTION 80

Which of the following statements are true regarding the SIP session helper and the SIP application layer gateway (ALG)? (Choose three.)

- A. SIP session helper runs in the kernel; SIP ALG runs as a user space process.
- B. SIP ALG supports SIP HA failover; SIP helper does not.
- C. SIP ALG supports SIP over IPv6; SIP helper does not.
- D. SIP ALG can create expected sessions for media traffic; SIP helper does not.
- E. SIP helper supports SIP over TCP and UDP; SIP ALG supports only SIP over UDP.

**Answer:** BCD

#### NEW QUESTION 81

Examine the partial output from two web filter debug commands; then answer the question below:



```
# diagnose test application urlfilter 3
Domain | IP      DB Ver  T URL
34000000| 34000000  16.40224 P Bhttp://www.fgt99.com/
# get webfilter categories
g07 General Interest - Business:
  34 Finance and Banking
  37 Search Engines and Portals
  43 General Organizations
  49 Business
  50 Information and Computer Security
  51 Government and Legal Organizations
  52 Information Technology
```

Based on the above outputs, which is the FortiGuard web filter category for the web site www.fgt99.com?


- A. Finance and banking
- B. General organization.
- C. Business.
- D. Information technology.

**Answer: C**

#### NEW QUESTION 84

Refer to the exhibit, which contains a TCL script configuration on FortiManager.

An administrator has configured the TCL script on FortiManager, but the TCL script failed to apply any changes to the managed device after being run.



Why did the TCL script fail to make any changes to the managed device?

- A. The TCL command run\_cmd has not been created.
- B. The TCL script must start with tinclude <>.
- C. Incomplete commands are ignored in TCL scripts.
- D. Changes to an interface configuration can be made only by a CLI script.

**Answer: A**

#### NEW QUESTION 86

Which two conditions must be met for a statistic route to be active in the routing table? (Choose two.)

- A. The link health monitor (if configured) is up.
- B. There is no other route, to the same destination, with a higher distance.
- C. The outgoing interface is up.
- D. The next-hop IP address is up.

**Answer: AC**

#### NEW QUESTION 91

Which configuration can be used to reduce the number of BGP sessions in an IBGP network?

- A. Neighbor range
- B. Route reflector
- C. Next-hop-self
- D. Neighbor group

**Answer: B**

#### Explanation:

Route reflectors help to reduce the number of IBGP sessions inside an AS. A route reflector forwards the routes learned from one peer to the other peers. If you configure route reflectors, you don't need to create a full mesh IBGP network. All clients in a cluster only talk to route reflector to get sync routing updates. Route reflectors pass the routing updates to other route reflectors and border routers within the AS.

#### NEW QUESTION 96

View the exhibit, which contains the output of a diagnose command, and the answer the question below.

```
# diagnose debug rating
Locale      : English
License     : Contract
Expiration  : Thu Sep 28 17:00:00 20XX
== Server List (Thu APR 19 10:41:32 20XX) ==
IP           Weight  RTT   Flags  TZ    Packets  Curr Lost  Total Lost
64.26.151.37   10     45    -5     -5    262432   0          846
64.26.151.35   10     46    -5     -5    329072   0         6806
66.117.56.37   10     75    -5     -5    71638    0         275
66.210.95.240  20     71    -8     -8    36875    0         92
209.222.147.36 20    103    DI    -8    34784    0        1070
208.91.112.194 20    107    D     -8    35170    0        1533
96.45.33.65    60    144     0     0    33728    0         120
80.85.69.41    71    226     1     1    33797    0         192
62.209.40.74   150    97     9     9    33754    0         145
121.111.236.179 45    44     F    -5    26410   26226    26227
```

Which statements are true regarding the Weight value?

- A. Its initial value is calculated based on the round trip delay (RTT).
- B. Its initial value is statically set to 10.
- C. Its value is incremented with each packet lost.
- D. It determines which FortiGuard server is used for license validation.

**Answer: C**

#### NEW QUESTION 98

Refer to the exhibit, which contains partial output from an IKE real-time debug.

```
ike 0:H2S_0_1:1249: notify msg received: SHORTCUT-QUERY
ike 0:H2S_0_1:  recv shortcut-query 12594932268010586978 4384dd592d62cd52/0000000000000000 100.64.3.1
10.1.1.254->10.1.2.254 psk 64 ppk 0 ttl 32 nat 0 ver 1 mode 0
ike 0:H2S_0: iif 13 10.1.1.254->10.1.2.254 route lookup oif 13
ike 0:H2S_0_0: forward shortcut-query 12594932268010586978 4384dd592d62cd52/0000000000000000
100.64.3.1 10.1.1.254->10.1.2.254 psk 64 ppk 0 ttl 31 ver 1 mode 0, ext-ma
ike 0:H2S_0_0:1248: sent IKE msg (SHORTCUT-QUERY): 100.64.1.1:500->100.64.5.1:500, len=236,
id=e2beec89f13c7074/06a73dfb3a5d3b54:340a645c
ike 0: comes 100.64.5.1:500->100.64.1.1:500, ifindex=3. . .
ike 0: IKEv1 exchange=Informational id=e2beec89f13c7074/06a73dfb3a5d3b5d:26254ae9 len=236
ike 0:H2S_0_0:1248: notify msg received: SHORTCUT-REPLY
ike 0:H2S_0_0:  recv shortcut-reply 12594932268010586978 4384dd592d62cd52/89bf040f5f7408c0 100.64.5.1
to 10.1.1.254 psk 64 ppk 0 ver 1 mode 0 ext-mapping 100.64.3.1:500
ike 0:H2S_0: iif 13.10.1.2.254->10.1.1.254 route lookup oif 13
ike 0:H2S_0_1: forward shortcut-reply 12594932268010586978 4384dd592d62cd52/89bf040f5f7408c0
100.64.5.1 to 10.1.1.254 psk 64 ppk 0 ttl 31 ver 1 mode 0 ext-mapping 100.
```

Based on the debug output, which phase 1 setting is enabled in the configuration of this VPN?

- A. auto-discovery-shortcut
- B. auto-discovery-forwarder
- C. auto-discovery-sender
- D. auto-discovery-receiver

**Answer: D**

#### NEW QUESTION 99

View the exhibit, which contains the partial output of an IKE real-time debug, and then answer the question below.

```
ike 0: comes 10.0.0.2:500-> 10.0.0.1:500, ifindex=7...
ike 0: IKEv1 exchange-Aggressive id-baf47d0988e9237f/2f405ef3952f6fda len 430
ike 0: in
BAF47D0988E9237F2F405EF3952F6FDA011004000000000000001AE0400003C000000010000000300101000
ike 0: RemoteSite:4: initiator: aggressive mode get 1st response
ike 0: RemoteSite:4: VID RPC 3947 4A131C81070358455C5728F20E95452F
ike 0: RemoteSite:4: VID DPD APCAD71368A1F1c96B8696FC77570100
ike 0: RemoteSite:4: VID PORTIGATE 8299031757A36082C6A621DE000502D7
ike 0: RemoteSite:4: peer is FortiGate/FortiOS (v6 b932)
ike 0: RemoteSite:4: VID FRAGMENTATION 4048B7D56EBCE88525E7DE7F00D6C2D3
ike 0: RemoteSite:4: VID FRAGMENTATION 4048B7D56EBCE88525E7DE7F00D6C2D3C0000000
ike 0: RemoteSite:4: received peer identifier FQDN 'remote'
ike 0: RemoteSite:4: negotiation result
ike 0: RemoteSite:4: proposal id = 1:
ike 0: RemoteSite:4:   protocol id - ISAKMP:
ike 0: RemoteSite:4:   trans_id - KEY_IKE.
ike 0: RemoteSite:4:   encapsulation - IKE/none
ike 0: RemoteSite:4:   type-OAKLEY_ENCRYPT_ALG, val-AES_CBC, key-len=128
ike 0: RemoteSite:4:   type-OAKLEY_HASH_ALG, val-SHA
ike 0: RemoteSite:4:   type-AUTH_METHOD, val-PRESHARED_KEY.
ike 0: RemoteSite:4:   type-OAKLEY_GROUP, val-MODP1024.
ike 0: RemoteSite:4: ISAKMP SA lifetime=86400
ike 0: RemoteSite:4: ISAKMP SA baf47d0988e9237f/2f405ef3952f6fda key
16:B25B6C9384D8BDB24E3DA3DC90CF5E73
ike 0: RemoteSite:4: PSK authentication succeeded
ike 0: RemoteSite:4: authentication OK
ike 0: RemoteSite:4: add INITIAL-CONTACT
ike 0: RemoteSite:4: enc
BAF47D0988E9237F2F405EF3952F6FDA081004010000000000000080140000181F2E48BFD8E9D603F
ike 0: RemoteSite:4: out
BAF47D0988E9237F2F405EF3952F6FDA08100401000000000000008c2E3FC9BA061816A396F009A12
ike 0: RemoteSite:4: sent IKE msg (agg_12send) : 10.0.0.1:500 ->10.0.0.2:500, len=140, id-
baf47d0988e9237f/2
ike 0: RemoteSite:4: established IKE SA baf47d0988e9237f/2f405ef3952f6fda
```

Which statements about this debug output are correct? (Choose two.)

- A. The remote gateway IP address is 10.0.0.1.
- B. It shows a phase 1 negotiation.
- C. The negotiation is using AES128 encryption with CBC hash.
- D. The initiator has provided remote as its IPsec peer ID.

**Answer: BD**

#### NEW QUESTION 102

Examine the output of the 'get router info ospf interface' command shown in the exhibit; then answer the question below.

```
# get router info ospf interface port4
port4 is up, line protocol is up
  Internet Address 172.20.121.236/24, Area 0.0.0.0, MTU 1500
  Process ID 0, Router ID 0.0.0.4, Network Type BROADCAST, Cost: 1
  Transmit Delay is 1 sec, State DROther, Priority 1
  Designated Router (ID) 172.20.140.2, Interface Address 172.20.121.2
  Backup Designated Router (ID) 0.0.0.1, Interface Address
  172.20.121.239
  Timer intervals configured, Hello 10.000, Dead 40, Wait 40, Retransmit
  5
    Hello due in 00:00:05
  Neighbor Count is 4, Adjacent neighbor count is 2
  Crypt Sequence Number is 411
  Hello received 106, sent 27, DD received 7 sent 9
  LS-Req received 2 sent 2, LS-Upd received 7 sent 5
  LS-Ack received 4 sent 3, Discarded 1
```

Which statements are true regarding the above output? (Choose two.)

- A. The port4 interface is connected to the OSPF backbone area.
- B. The local FortiGate has been elected as the OSPF backup designated router.
- C. There are at least 5 OSPF routers connected to the port4 network.
- D. Two OSPF routers are down in the port4 network.

**Answer: AC**

#### Explanation:

on BROADCAST network there are 4 neighbors, among which 1\*DR +1\*BDR. So our FG has 4 neighbors, but create adjacency only with 2 (with DR and BDR). 2 neighbors DROther (not down).

#### NEW QUESTION 105

Which statement about the designated router (DR) and backup designated router (BDR) in an OSPF multi-access network is true?

- A. FortiGate first checks the OSPF ID to elect a DR.
- B. Non-DR and non-BDR routers will form full adjacencies to DR and BDR only.
- C. BDR is responsible for forwarding link state information from one router to another.
- D. Only the DR receives link state information from non-DR routers.

**Answer: B**



#### NEW QUESTION 110

View the exhibit, which contains a session entry, and then answer the question below.

```
session info: proto=1 proto_state=00 duration=1 expire=59 timeout=0 flags=00000000
sockflag=00000000 sockport=0 av_idx=0 use=3
origin-shaper=
reply-shaper=
per_ip_shaper=
ha_id=0 policy_dir=0 tunnel=/ vlan_cos=0/255
state=log may_dirty none
statistic(bytes/packets/allow_err): org=168/2/1 reply=168/2/1 tuples=2
tx speed(Bps/kbps): 97/0 rx speed(Bps/kbps): 97/0
orgin->sink: org pre->post, reply pre->post dev=9->3/3->9 gwy=10.200.1.254/10.1.0.1
hook=post dir=org act=snat 10.1.10.10:40602->10.200.5.1:8(10.200.1.254/10.1.0.1
hook=pre dir=reply act=dnat 10.200.5.1:60430->10.200.1.1:0(10.1.10.10:40602)
misc=0 policy_id=1 auth_info=0 chk_client_info=0 vd=0
serial=0002a5c9 tos=ff/ff app_list=0 app=0 url_cat=0
dd_type=0 dd_mode=0
```

Which statement is correct regarding this session?

- A. It is an ICMP session from 10.1.10.10 to 10.200.1.1.
- B. It is an ICMP session from 10.1.10.10 to 10.200.5.1.
- C. It is a TCP session in ESTABLISHED state from 10.1.10.10 to 10.200.5.1.
- D. It is a TCP session in CLOSE\_WAIT state from 10.1.10.10 to 10.200.1.1.

**Answer:** B

#### NEW QUESTION 115

Which two statements about OCVPN are true? (Choose two.)

- A. Only root vdom supports OCVPN.
- B. OCVPN supports static and dynamic IPs in WAN interface.
- C. OCVPN offers only Hub-Spoke VPNs.
- D. FortiGate devices under different FortiCare accounts can be used to form OCVPN.

**Answer:** AB

#### NEW QUESTION 116

What configuration changes can reduce the memory utilization in a FortiGate? (Choose two.)

- A. Reduce the session time to live.
- B. Increase the TCP session timers.
- C. Increase the FortiGuard cache time to live.
- D. Reduce the maximum file size to inspect.

**Answer:** AD

#### NEW QUESTION 117

Which two statements about an auxiliary session are true? (Choose two.)

- A. With the auxiliary session setting enabled, ECMP traffic is accelerated to the NP6 processor.
- B. With the auxiliary session setting enabled, two sessions will be created in case of routing change.
- C. With the auxiliary session setting disabled, for each traffic path, FortiGate will use the same auxiliary session.
- D. With the auxiliary session disabled, only auxiliary sessions will be offloaded.

**Answer:** CD

#### NEW QUESTION 121

Refer to the exhibit, which shows a partial routing table.

```
FGT # get router info routing-table all
...
Routing table for VRF=7
C    10.73.9.0/24 is directly connected, port2

Routing table for VRF=12
C    10.1.0.0/24 is directly connected, port3
S    10.10.4.0/24 [10/0] via 10.1.0.100, port3
C    10.64.1.0/24 is directly connected, port1

Routing table for VRF=21
S    10.1.0.0/24 [10/0] via 10.72.3.254, port4
C    10.72.3.0/24 is directly connected, port4
```



Assuming all the appropriate firewall policies are configured, which two pings will FortiGate route? (Choose two.)

- A. Source IP address: 10.1.0.10. Destination IP address: 10.64.1.52
- B. Source IP address: 10.72.3.52. Destination IP address: 10.1.0.254
- C. Source IP address: 10.10.4.24, Destination IP address: 10.72.3.20
- D. Source IP address: 10.73.9.10, Destination IP address: 10.72.3.15

Answer: AB

#### NEW QUESTION 124

View the exhibit, which contains the output of a diagnose command, and then answer the question below.

```
diagnose sys session list expectation

session info: proto=6 proto_state=00 duration=3 expire=26 timeout=3600 flags=00000000
sockflag=00000000 sockport=0 av_idx=0 use=3
origin-shaper=
reply-shaper=
ha_id=0 policy_dir=1 tunnel=/
state=new complex
statistic(bytes/packets/allow_err): org=0/0/0 reply=0/0/0 tuples=2
orgin->sink: org pre->post, reply pre->post dev=2->4/4->2 gwy=10.0.1.10/10.200.1.254
hook=pre dir-org act=dnat 10.171.121.38:0->10.200.1.1:60426(10.0.1.10:50365)
hook-pre dir-org act=noop 0.0.0.0:0->0.0.0.0:0(0.0.0.0:0)
pos/(before, after) 0/(0,0), 0/(0,0)
misc=0 policy_id=1 auth_info=0 chk_client_info=0 vd=0
serial=000000e9 tos=ff/ff ips_view=0 app_list=0 app=0
dd_type=0 dd_mode=0
```

What statements are correct regarding the output? (Choose two.)

- A. This is an expected session created by a session helper.
- B. Traffic in the original direction (coming from the IP address 10.171.122.38) will be routed to the next-hop IP address 10.0.1.10.
- C. Traffic in the original direction (coming from the IP address 10.171.122.38) will be routed to the next-hop IP address 10.200.1.1.
- D. This is an expected session created by an application control profile.

Answer: AC

#### NEW QUESTION 128

An administrator added the following Ipsec VPN to a FortiGate configuration:

```
config vpn ipsec phase1-interface edit "RemoteSite"
set type dynamic
set interface "port1" set mode main
set psksecret ENC LCVkCiK2E2PhVUzZe next
end
config vpn ipsec phase2-interface edit "RemoteSite"
set phase1 name "RemoteSite" set proposal 3des-sha256
next end
```

However, the phase 1 negotiation is failing. The administrator executed the IKF real time debug while attempting the Ipsec connection. The output is shown in the exhibit.

```
ike 0: comes 10.200.3.1:500->10.200.1.1:500, ifindex=2....
ike 0: IKEv1 exchange=Identity Protection id=xxx/xxx len=716
ike 0:xxx/xxx:16: responder: main mode get 1st message...
ike 0:xxx/xxx:16: VID RFC 3947 4A131C81070358455C5728F20E95452F
...
ike 0:xxx/xxx:16: negotiation result
ike 0:xxx/xxx:16: proposal id = 1:
ike 0:xxx/xxx:16:   protocol id = ISAKMP:
ike 0:xxx/xxx:16:   trans_id = KEY IKE.
ike 0:xxx/xxx:16:   encapsulation = IKE/none
ike 0:xxx/xxx:16:   type=OAKLEY_ENCRYPT_ALG, val=AES_CBC.
ike 0:xxx/xxx:16:   type=OAKLEY_HASH_ALG, val=SHA2_256.
ike 0:xxx/xxx:16:   type=AUTH_METHOD, val=PRESHARED_KEY.
ike 0:xxx/xxx:16:   type=OAKLEY_GROUP, val=MODP2048.
ike 0:xxx/xxx:16: ISAKMP SA lifetime=86400
ike 0:xxx/xxx:16: SA proposal chosen, matched gateway DialUpUsers
...
ike 0:DialUpUsers:16: sent IKE msg (ident_r1send): 10.200.1.1:500->10.200.3.1:500, len
id=xxx/xxx
ike 0: comes 10.200.3.1:500->10.200.1.1:500, ifindex=2....
ike 0: IKEv1 exchange=Identity Protection id=xxx/xxx len=380
ike 0:DialUpUsers:16: responder: main mode get 2nd message...
ike 0:DialUpUsers:16: NAT not detected
ike 0:DialUpUsers:16: sent IKE msg (ident_r2send): 10.200.1.1:500->10.200.3.1:500, len
id=xxx/xxx
ike 0:DialUpUsers:16: ISAKMP SA xxx/xxx key 16:3D33E2EF00BE927701B5C25B05A62415
ike 0: comes 10.200.3.1:500->10.200.1.1:500, ifindex=2....
ike 0: IKEv1 exchange=Identity Protection id=xxx/xxx len=108
ike 0:DialUpUsers:16: responder: main mode get 3rd message...
ike 0:DialUpUsers:16: probable pre-shared secret mismatch
ike 0:DialUpUsers:16: unable to parse msg
```

What is causing the IPsec problem in the phase 1 ?

- A. The incoming IPsec connection is matching the wrong VPN configuration
- B. The phrase-1 mode must be changed to aggressive
- C. The pre-shared key is wrong
- D. NAT-T settings do not match

**Answer: C**

#### NEW QUESTION 133

Examine the output of the 'get router info bgp summary' command shown in the exhibit; then answer the question below.

```
# get router info bgp summary
BGP router identifier 0.0.0.117, local AS number 65117
BGP table version is 104
3 BGP AS-PATH entries
0 BGP community entries

Neighbor    V    AS  MsgRcvd  MsgSent  TblVer  InQ  OutQ  Up/Down  State/PfxRcd
10.125.0.60  4   65060   1698      1756    103   0    0  03:02:49        1
10.127.0.75  4   65075   2206      2250    102   0    0  02:45:55        1
10.200.3.1   4   65501    101        115     0    0    0    never        Active

Total number of neighbors 3
```

Which statements are true regarding the output in the exhibit? (Choose two.)

- A. BGP state of the peer 10.125.0.60 is Established.
- B. BGP peer 10.200.3.1 has never been down since the BGP counters were cleared.
- C. Local BGP peer has not received an OpenConfirm from 10.200.3.1.
- D. The local BGP peer has received a total of 3 BGP prefixes.

**Answer: AC**

#### NEW QUESTION 138

View the exhibit, which contains the output of a debug command, and then answer the question below.

```
#dia hardware sysinfo shm
SHM counter:          150
SHM allocated:         0
SHM total:          625057792
conserve mode: on - mem
system last entered: Mon Apr 24 16:36:37 2017
sys fd last entered: n/a
SHM FS total:   641236992
SHM FS free:    641208320
SHM FS avail:   641208320
SHM FS alloc:    28672
```

What statement is correct about this FortiGate?

- A. It is currently in system conserve mode because of high CPU usage.
- B. It is currently in FD conserve mode.
- C. It is currently in kernel conserve mode because of high memory usage.
- D. It is currently in system conserve mode because of high memory usage.

**Answer: D**

#### NEW QUESTION 140

View the exhibit, which contains the partial output of a diagnose command, and then answer the question below.



```
Spoke-2 # dia vpn tunnel list
list all ipsec tunnel in vd 0
name=VPN ver=1 serial=1 10.200.5.1:0->10.200.4.1:0
bound_if=3 lgwy=static/1 tun=intf/0 mode=auto/1 encap=none/0
proxyid_num=1 child_num=0 refcnt=15 ilast=10 olast=792 auto-discovery=0
stat: rxp=0 txp=0 rxb=0 txb=0
dpd: mode=on-demand on=1 idle=20000 ms retry=3 count=0 seqno=0
natt: mode=none draft=0 interval=0 remote_port=0
proxyid=VPN proto=0 sa=1 ref=2 serial=1
  src: 0:10.1.2.0/255.255.0:0
  dst: 0:10.1.1.0/255.255.255.0:0
  SA: ref=3 options=2e type=00 soft=0 mtu=1438 expire=42403/0B replaywin=2048 seqno=1 esn=0
replaywin_lastseq=00000000
life: type=01 bytes=0/0 timeout=43177/43200
dec: spi=cccl1f66d esp=aes key=16 280e5cd6f9bacc65ac771556c464ffbd
  ah=shal key=20 c68091d68753578785de6a7a6b276b506c527efe
enc: spi=df14200b esp=aes key=16 b02a7e9f5542b69aff6aa391738ee393
  ah=shal key=20 889f7529887c215c25950be2ba83e6fe1a5367be
dec:pkts/bytes=0/0, enc:pkts/bytes=0/0
```

Based on the output, which of the following statements is correct?

- A. Anti-reply is enabled.
- B. DPD is disabled.
- C. Quick mode selectors are disabled.
- D. Remote gateway IP is 10.200.5.1.

**Answer:** A

#### NEW QUESTION 144

Which real time debug should an administrator enable to troubleshoot RADIUS authentication problems?

- A. Diagnose debug application radius -1.
- B. Diagnose debug application fnbamd -1.
- C. Diagnose authd console -log enable.
- D. Diagnose radius console -log enable.

**Answer:** B

#### Explanation:

<https://kb.fortinet.com/kb/documentLink.do?externalID=FD32838>

#### NEW QUESTION 145

View the following FortiGate configuration.

```
config system global
  set snat-route-change disable
end
config router static
  edit 1
    set gateway 10.200.1.254
    set priority 5
    set device "port1"
  next
  edit 2
    set gateway 10.200.2.254
    set priority 10
    set device "port2"
  next
end
```

All traffic to the Internet currently egresses from port1. The exhibit shows partial session information for Internet traffic from a user on the internal network:

```
# diagnose sys session list
session info: proto=6 proto_state=01 duration=17 expire=7 timeout=3600
flags=00000000 sockflag=00000000 sockport=0 av_idx=0 use=3
ha_id=0 policy_dir=0 tunnel=/
state=may_dirty none app_ntf
statistic(bytes/packets/allow_err): org=57555/7/1 reply=23367/19/1 tuples=2
orgin->sink: org pre->post, reply pre->post dev=4->2/2->4
gwy=10.200.1.254/10.0.1.10
hook=post dir=org act=snat 10.0.1.10:64907-
>54.239.158.170:80(10.200.1.1:64907)
hook=pre dir=reply act=dnat 54.239.158.170:80-
>10.200.1.1:64907(10.0.1.10:64907)
pos/(before, after) 0/(0,0), 0/(0,0)
misc=0 policy_id=1 auth_info=0 chk_client_info=0 vd=0
serial=00000294 tos=ff/ff ips_view=0 app_list=0 app=0
dd_type=0 dd_mode=0
```

If the priority on route ID 1 were changed from 5 to 20, what would happen to traffic matching that user's session?

- A. The session would remain in the session table, and its traffic would still egress from port1.
- B. The session would remain in the session table, but its traffic would now egress from both port1 and port2.
- C. The session would remain in the session table, and its traffic would start to egress from port2.
- D. The session would be deleted, so the client would need to start a new session.

**Answer:** A

**Explanation:**

<http://kb.fortinet.com/kb/documentLink.do?externalID=FD40943>

#### NEW QUESTION 149

Refer to the exhibit, which contains the output of diagnose sys session list.

```
# diagnose sys session list
session info: proto=6 proto_state=01 duration=73 expire=3597 timeout=3600
flags=00000000 sockflag=00000000 sockport=0 av_idx=0 use=3
origin-shaper=
reply-shaper=
per_ip_shaper=
class_id=0 ha_id=0 policy_dir=0 tunnel=/ vlan_cos=0/255
state=may_dirty synced none app_ntf
statistic(bytes/packets/allow_err): org=822/11/1 reply=9037/15/1 tuples=2
origin->sink: org pre->post, reply pre->post dev=4->2/2->4
gw=100.64.1.254/10.0.1.10
hook=post dir=org act=snat 10.0.1.10:65464->54.192.15.182:80(100.64.1.1:65464)
hook-pre dir=reply act=dnat 54.192.15.182:80->100.64.1.1:65464(10.0.1.10:65464)
pos/(before,after) 0/(0,0), 0/(0,0)
misc=0 policy_id=1 auth_info=0 chk_client_info=0 vd=0
serial=00000098 tos=ff/ff ips_view=0 app_list=0 app=0
dd_type=0 dd_mode=0
```

If the HA ID for the primary unit is zero (0), which statement about the output is true?

- A. This session cannot be synced with the slave unit.
- B. The inspection of this session has been offloaded to the slave unit.
- C. The master unit is processing this traffic.
- D. This session is for HA heartbeat traffic.

**Answer:** C

#### NEW QUESTION 154

A corporate network allows Internet Access to FSSO users only. The FSSO user student does not have Internet access after successfully logged into the Windows AD network. The output of the 'diagnose debug authd fssolist' command does not show student as an active FSSO user. Other FSSO users can access the Internet without problems. What should the administrator check? (Choose two.)

- A. The user student must not be listed in the CA's ignore user list.
- B. The user student must belong to one or more of the monitored user groups.
- C. The student workstation's IP subnet must be listed in the CA's trusted list.
- D. At least one of the student's user groups must be allowed by a FortiGate firewall policy.

**Answer:** AD

**Explanation:**

<https://kb.fortinet.com/kb/documentLink.do?externalID=FD38828>

#### NEW QUESTION 159

Which two statements about the Security Fabric are true? (Choose two.)

- A. Only the root FortiGate collects network information and forwards it to FortiAnalyzer.
- B. FortiGate uses FortiTelemetry protocol to communicate with FortiAnalyzer.
- C. All FortiGate devices in the Security Fabric must have bidirectional FortiTelemetry connectivity.
- D. Branch FortiGate devices must be configured first.

**Answer:** BC

#### NEW QUESTION 162

Which two configuration settings change the behavior for content-inspected traffic while FortiGate is in conserve mode? (Choose two.)

- A. IPS failopen
- B. mem failopen
- C. AV failopen
- D. UTM failopen

**Answer:** AC

#### NEW QUESTION 165

.....



## Relate Links

**100% Pass Your NSE7\_EFW-7.0 Exam with ExamBible Prep Materials**

[https://www.exambible.com/NSE7\\_EFW-7.0-exam/](https://www.exambible.com/NSE7_EFW-7.0-exam/)

## Contact us

We are proud of our high-quality customer service, which serves you around the clock 24/7.

Viste - <https://www.exambible.com/>