

## AWS-Certified-DevOps-Engineer-Professional Dumps

### Amazon AWS Certified DevOps Engineer Professional

<https://www.certleader.com/AWS-Certified-DevOps-Engineer-Professional-dumps.html>



### NEW QUESTION 1

A DevOps engineer is building an application that uses an AWS Lambda function to query an Amazon Aurora MySQL DB cluster. The Lambda function performs only read queries. Amazon EventBridge events invoke the Lambda function.

As more events invoke the Lambda function each second, the database's latency increases and the database's throughput decreases. The DevOps engineer needs to improve the performance of the application.

Which combination of steps will meet these requirements? (Select THREE.)

- A. Use Amazon RDS Proxy to create a proxy
- B. Connect the proxy to the Aurora cluster reader endpoint
- C. Set a maximum connections percentage on the proxy.
- D. Implement database connection pooling inside the Lambda code
- E. Set a maximum number of connections on the database connection pool.
- F. Implement the database connection opening outside the Lambda event handler code.
- G. Implement the database connection opening and closing inside the Lambda event handler code.
- H. Connect to the proxy endpoint from the Lambda function.
- I. Connect to the Aurora cluster endpoint from the Lambda function.

**Answer:** ACE

#### Explanation:

To improve the performance of the application, the DevOps engineer should use Amazon RDS Proxy, implement the database connection opening outside the Lambda event handler code, and connect to the proxy endpoint from the Lambda function. References:

? Amazon RDS Proxy is a fully managed, highly available database proxy for Amazon Relational Database Service (RDS) that makes applications more scalable, more resilient to database failures, and more secure<sup>1</sup>. By using Amazon RDS Proxy, the DevOps engineer can reduce the overhead of opening and closing connections to the database, which can improve latency and throughput<sup>2</sup>.

? The DevOps engineer should connect the proxy to the Aurora cluster reader endpoint, which allows read-only connections to one of the Aurora Replicas in the DB cluster<sup>3</sup>. This can help balance the load across multiple read replicas and improve performance for read-intensive workloads<sup>4</sup>.

? The DevOps engineer should implement the database connection opening outside the Lambda event handler code, which means using a global variable to store the database connection object<sup>5</sup>. This can enable connection reuse across multiple invocations of the Lambda function, which can reduce latency and improve performance.

? The DevOps engineer should connect to the proxy endpoint from the Lambda function, which is a unique URL that represents the proxy. This can allow the Lambda function to access the database through the proxy, which can provide benefits such as connection pooling, load balancing, failover handling, and enhanced security.

? The other options are incorrect because:

### NEW QUESTION 2

A company uses AWS Key Management Service (AWS KMS) keys and manual key rotation to meet regulatory compliance requirements. The security team wants to be notified when any keys have not been rotated after 90 days.

Which solution will accomplish this?

- A. Configure AWS KMS to publish to an Amazon Simple Notification Service (Amazon SNS) topic when keys are more than 90 days old.
- B. Configure an Amazon EventBridge event to launch an AWS Lambda function to call the AWS Trusted Advisor API and publish to an Amazon Simple Notification Service (Amazon SNS) topic.
- C. Develop an AWS Config custom rule that publishes to an Amazon Simple Notification Service (Amazon SNS) topic when keys are more than 90 days old.
- D. Configure AWS Security Hub to publish to an Amazon Simple Notification Service (Amazon SNS) topic when keys are more than 90 days old.

**Answer:** C

#### Explanation:

<https://aws.amazon.com/blogs/security/how-to-use-aws-config-to-determine-compliance-of-aws-kms-key-policies-to-your-specifications/>

### NEW QUESTION 3

A company is using an organization in AWS Organizations to manage multiple AWS accounts. The company's development team wants to use AWS Lambda functions to meet resiliency requirements and is rewriting all applications to work with Lambda functions that are deployed in a VPC. The development team is using Amazon Elastic File System (Amazon EFS) as shared storage in Account A in the organization.

The company wants to continue to use Amazon EFS with Lambda. Company policy requires all serverless projects to be deployed in Account B.

A DevOps engineer needs to reconfigure an existing EFS file system to allow Lambda functions to access the data through an existing EFS access point.

Which combination of steps should the DevOps engineer take to meet these requirements? (Select THREE.)

- A. Update the EFS file system policy to provide Account B with access to mount and write to the EFS file system in Account A.
- B. Create SCPs to set permission guardrails with fine-grained control for Amazon EFS.
- C. Create a new EFS file system in Account B. Use AWS Database Migration Service (AWS DMS) to keep data from Account A and Account B synchronized.
- D. Update the Lambda execution roles with permission to access the VPC and the EFS file system.
- E. Create a VPC peering connection to connect Account A to Account B.
- F. Configure the Lambda functions in Account B to assume an existing IAM role in Account A.

**Answer:** AEF

#### Explanation:

A Lambda function in one account can mount a file system in a different account. For this scenario, you configure VPC peering between the function VPC and the file system VPC. <https://docs.aws.amazon.com/lambda/latest/dg/services-efs.html> <https://aws.amazon.com/ru/blogs/storage/mount-amazon-efs-file-systems-cross-account-from-amazon-eks/>

\* 1. Need to update the file system policy on EFS to allow mounting the file system into Account B.

## File System Policy

```
$ cat file-system-policy.json
```

```
{
  "Statement": [
    {
```

```
"Effect": "Allow", "Action": [
"elasticfilesystem:ClientMount", "elasticfilesystem:ClientWrite"
],
"Principal": {
"AWS": "arn:aws:iam::<aws-account-id-A>:root" # Replace with AWS account ID of EKS cluster
}
}
]
```

\* 2. Need VPC peering between Account A and Account B as the pre-requisite

\* 3. Need to assume cross-account IAM role to describe the mounts so that a specific mount can be chosen.

#### NEW QUESTION 4

A company is developing a new application. The application uses AWS Lambda functions for its compute tier. The company must use a canary deployment for any changes to the Lambda functions. Automated rollback must occur if any failures are reported.

The company's DevOps team needs to create the infrastructure as code (IaC) and the CI/CD pipeline for this solution.

Which combination of steps will meet these requirements? (Choose three.)

- A. Create an AWS CloudFormation template for the applicatio
- B. Define each Lambda function in the template by using the AWS::Lambda::Function resource typ
- C. In the template, include a version for the Lambda function by using the AWS::Lambda::Version resource typ
- D. Declare the CodeSha256 propert
- E. Configure an AWS::Lambda::Alias resource that references the latest version of the Lambda function.
- F. Create an AWS Serverless Application Model (AWS SAM) template for the applicatio
- G. Define each Lambda function in the template by using the AWS::Serverless::Function resource typ
- H. For each function, include configurations for the AutoPublishAlias property and the DeploymentPreference propert
- I. Configure the deployment configuration type to LambdaCanary10Percent10Minutes.
- J. Create an AWS CodeCommit repositor
- K. Create an AWS CodePipeline pipelin
- L. Use the CodeCommit repository in a new source stage that starts the pipelin
- M. Create an AWS CodeBuild project to deploy the AWS Serverless Application Model (AWS SAM) templat
- N. Upload the template and source code to the CodeCommit repositor
- O. In the CodeCommit repository, create a buildspec.yml file that includes the commands to build and deploy the SAM application.
- P. Create an AWS CodeCommit repositor
- Q. Create an AWS CodePipeline pipelin
- R. Use the CodeCommit repository in a new source stage that starts the pipelin
- S. Create an AWS CodeDeploy deployment group that is configured for canary deployments with a DeploymentPreference type of Canary10Percent10Minute
- T. Upload the AWS CloudFormation template and source code to the CodeCommit repositor
- . In the CodeCommit repository, create an appspec.yml file that includes the commands to deploy the CloudFormation template.
- . Create an Amazon CloudWatch composite alarm for all the Lambda function
- . Configure an evaluation period and dimensions for Lambd
- . Configure the alarm to enter the ALARMstate if any errors are detected or if there is insufficient data.
- . Create an Amazon CloudWatch alarm for each Lambda functio
- . Configure the alarms to enter the ALARM state if any errors are detecte
- . Configure an evaluation period, dimensions for each Lambda function and version, and the namespace as AWS/Lambda on the Errors metric.

**Answer:** BCF

#### Explanation:

The requirement is to create the infrastructure as code (IaC) and the CI/CD pipeline for the Lambda application that uses canary deployment and automated rollback. To do this, the DevOps team needs to use the following steps:

? Create an AWS Serverless Application Model (AWS SAM) template for the application. AWS SAM is a framework that simplifies the development and deployment of serverless applications on AWS. AWS SAM allows customers to define Lambda functions and other resources in a template by using a simplified syntax. For each Lambda function, the DevOps team can include configurations for the AutoPublishAlias property and the DeploymentPreference property. The AutoPublishAlias property specifies the name of the alias that points to the latest version of the function. The DeploymentPreference property specifies how CodeDeploy deploys new versions of the function. By configuring the deployment configuration type to LambdaCanary10Percent10Minutes, the DevOps team can enable canary deployment with 10% of traffic shifted to the new version every 10 minutes.

? Create an AWS CodeCommit repository. Create an AWS CodePipeline pipeline.

Use the CodeCommit repository in a new source stage that starts the pipeline. Create an AWS CodeBuild project to deploy the AWS SAM template. CodeCommit is a fully managed source control service that hosts Git repositories. CodePipeline is a fully managed continuous delivery service that automates the release process of software applications. CodeBuild is a fully managed continuous integration service that compiles source code and runs tests. By using these services, the DevOps team can create a CI/CD pipeline for the Lambda application. The pipeline should use the CodeCommit repository as the source stage, where the DevOps team can upload the SAM template and source code. The pipeline should also use a CodeBuild project as the build stage, where the SAM template can be built and deployed.

? Create an Amazon CloudWatch alarm for each Lambda function. Configure the alarms to enter the ALARM state if any errors are detected. Configure an evaluation period, dimensions for each Lambda function and version, and the namespace as AWS/Lambda on the Errors metric. CloudWatch is a service that monitors and collects metrics from AWS resources and applications. CloudWatch alarms are actions that are triggered when a metric crosses a specified threshold. By creating CloudWatch alarms for each Lambda function, the DevOps team can monitor the health and performance of each function version during deployment. By configuring the alarms to enter the ALARM state if any errors are detected, the DevOps team can enable automated rollback if any failures are reported.

#### NEW QUESTION 5

A company has containerized all of its in-house quality control applications. The company is running Jenkins on Amazon EC2 instances, which require patching and upgrading. The compliance officer has requested a DevOps engineer begin encrypting build artifacts since they contain company intellectual property.

What should the DevOps engineer do to accomplish this in the MOST maintainable manner?

- A. Automate patching and upgrading using AWS Systems Manager on EC2 instances and encrypt Amazon EBS volumes by default.
- B. Deploy Jenkins to an Amazon ECS cluster and copy build artifacts to an Amazon S3 bucket with default encryption enabled.
- C. Leverage AWS CodePipeline with a build action and encrypt the artifacts using AWS Secrets Manager.
- D. Use AWS CodeBuild with artifact encryption to replace the Jenkins instance running on EC2 instances.

**Answer:** D

**Explanation:**

The following are the steps involved in accomplishing this in the most maintainable manner:

? Use AWS CodeBuild with artifact encryption to replace the Jenkins instance running on EC2 instances.

? Configure CodeBuild to encrypt the build artifacts using AWS Secrets Manager.

? Deploy the containerized quality control applications to CodeBuild.

This approach is the most maintainable because it eliminates the need to manage Jenkins on EC2 instances. CodeBuild is a managed service, so the DevOps engineer does not need to worry about patching or upgrading the service. <https://docs.aws.amazon.com/codebuild/latest/userguide/security-encryption.html> Build artifact encryption - CodeBuild requires access to an AWS KMS CMK in order to encrypt its build output artifacts. By default, CodeBuild uses an AWS Key Management Service CMK for Amazon S3 in your AWS account. If you do not want to use this CMK, you must create and configure a customer-managed CMK. For more information Creating keys.

**NEW QUESTION 6**

A company is developing an application that will generate log events. The log events consist of five distinct metrics every one tenth of a second and produce a large amount of data The company needs to configure the application to write the logs to Amazon Time stream The company will configure a daily query against the Timestream table.

Which combination of steps will meet these requirements with the FASTEST query performance? (Select THREE.)

- A. Use batch writes to write multiple log events in a Single write operation
- B. Write each log event as a single write operation
- C. Treat each log as a single-measure record
- D. Treat each log as a multi-measure record
- E. Configure the memory store retention period to be longer than the magnetic store retention period
- F. Configure the memory store retention period to be shorter than the magnetic store retention period

**Answer:** ADF

**Explanation:**

A comprehensive and detailed explanation is:

? Option A is correct because using batch writes to write multiple log events in a single write operation is a recommended practice for optimizing the performance and cost of data ingestion in Timestream. Batch writes can reduce the number of network round trips and API calls, and can also take advantage of parallel processing by Timestream. Batch writes can also improve the compression ratio of data in the memory store and the magnetic store, which can reduce the storage costs and improve the query performance<sup>1</sup>.

? Option B is incorrect because writing each log event as a single write operation is not a recommended practice for optimizing the performance and cost of data ingestion in Timestream. Writing each log event as a single write operation would increase the number of network round trips and API calls, and would also reduce the compression ratio of data in the memory store and the magnetic store. This would increase the storage costs and degrade the query performance<sup>1</sup>.

? Option C is incorrect because treating each log as a single-measure record is not a recommended practice for optimizing the query performance in Timestream. Treating each log as a single-measure record would result in creating multiple records for each timestamp, which would increase the storage size and the query latency. Moreover, treating each log as a single-measure record would require using joins to query multiple measures for the same timestamp, which would add complexity and overhead to the query processing<sup>2</sup>.

? Option D is correct because treating each log as a multi-measure record is a recommended practice for optimizing the query performance in Timestream. Treating each log as a multi-measure record would result in creating a single record for each timestamp, which would reduce the storage size and the query latency. Moreover, treating each log as a multi-measure record would allow querying multiple measures for the same timestamp without using joins, which would simplify and speed up the query processing<sup>2</sup>.

? Option E is incorrect because configuring the memory store retention period to be longer than the magnetic store retention period is not a valid option in Timestream. The memory store retention period must always be shorter than or equal to the magnetic store retention period. This ensures that data is moved from the memory store to the magnetic store before it expires out of the memory store<sup>3</sup>.

? Option F is correct because configuring the memory store retention period to be shorter than the magnetic store retention period is a valid option in Timestream. The memory store retention period determines how long data is kept in the memory store, which is optimized for fast point-in-time queries. The magnetic store retention period determines how long data is kept in the magnetic store, which is optimized for fast analytical queries. By configuring these retention periods appropriately, you can balance your storage costs and query performance according to your application needs<sup>3</sup>.

References:

? 1: Batch writes

? 2: Multi-measure records vs. single-measure records

? 3: Storage

**NEW QUESTION 7**

A company requires that its internally facing web application be highly available. The architecture is made up of one Amazon EC2 web server instance and one NAT instance that provides outbound internet access for updates and accessing public data.

Which combination of architecture adjustments should the company implement to achieve high availability? (Choose two.)

- A. Add the NAT instance to an EC2 Auto Scaling group that spans multiple Availability Zone
- B. Update the route tables.
- C. Create additional EC2 instances spanning multiple Availability Zone
- D. Add an Application Load Balancer to split the load between them.
- E. Configure an Application Load Balancer in front of the EC2 instanc
- F. Configure Amazon CloudWatch alarms to recover the EC2 instance upon host failure.
- G. Replace the NAT instance with a NAT gateway in each Availability Zon
- H. Update the route tables.
- I. Replace the NAT instance with a NAT gateway that spans multiple Availability Zone
- J. Update the route tables.

**Answer:** BD

**Explanation:**

<https://docs.aws.amazon.com/vpc/latest/userguide/vpc-nat-gateway.html>

**NEW QUESTION 8**

A company wants to ensure that their EC2 instances are secure. They want to be notified if any new vulnerabilities are discovered on their instances and they also want an audit trail of all login activities on the instances.

Which solution will meet these requirements'?

- A. Use AWS Systems Manager to detect vulnerabilities on the EC2 instances Install the Amazon Kinesis Agent to capture system logs and deliver them to Amazon S3.
- B. Use AWS Systems Manager to detect vulnerabilities on the EC2 instances Install the Systems Manager Agent to capture system logs and view login activity in the CloudTrail console.
- C. Configure Amazon CloudWatch to detect vulnerabilities on the EC2 instances Install the AWS Config daemon to capture system logs and view them in the AWS Config console.
- D. Configure Amazon Inspector to detect vulnerabilities on the EC2 instances Install the Amazon CloudWatch Agent to capture system logs and record them via Amazon CloudWatch Logs.

**Answer:** D

**Explanation:**

This solution will meet the requirements because it will use Amazon Inspector to scan the EC2 instances for any new vulnerabilities and generate findings that can be viewed in the Inspector console or sent as notifications via Amazon Simple Notification Service (SNS). It will also use the Amazon CloudWatch Agent to collect and send system logs from the EC2 instances to Amazon CloudWatch Logs, where they can be stored, searched, and analyzed. The system logs can provide an audit trail of all login activities on the instances, as well as other useful information such as performance metrics, errors, and events.

<https://docs.aws.amazon.com/inspector/latest/user/what-is-inspector.html>

**NEW QUESTION 9**

A company uses an organization in AWS Organizations to manage its AWS accounts. The company recently acquired another company that has standalone AWS accounts. The acquiring company's DevOps team needs to consolidate the administration of the AWS accounts for both companies and retain full administrative control of the accounts. The DevOps team also needs to collect and group findings across all the accounts to implement and maintain a security posture.

Which combination of steps should the DevOps team take to meet these requirements? (Select TWO.)

- A. Invite the acquired company's AWS accounts to join the organizatio
- B. Create an SCP that has full administrative privilege
- C. Attach the SCP to the management account.
- D. Invite the acquired company's AWS accounts to join the organizatio
- E. Create the OrganizationAccountAccessRole 1AM role in the invited account
- F. Grant permission to the management account to assume the role.
- G. Use AWS Security Hub to collect and group findings across all account
- H. Use Security Hub to automatically detect new accounts as the accounts are added to the organization.
- I. Use AWS Firewall Manager to collect and group findings across all account
- J. Enable all features for the organizatio
- K. Designate an account in the organization as the delegated administrator account for Firewall Manager.
- L. Use Amazon Inspector to collect and group findings across all account
- M. Designate an account in the organization as the delegated administrator account for Amazon Inspector.

**Answer:** BC

**Explanation:**

The correct answer is B and C. Option B is correct because inviting the acquired company's AWS accounts to join the organization and creating the OrganizationAccountAccessRole IAM role in the invited accounts allows the management account to assume the role and gain full administrative access to the member accounts. Option C is correct because using AWS Security Hub to collect and group findings across all accounts enables the DevOps team to monitor and improve the security posture of the organization. Security Hub can automatically detect new accounts as the accounts are added to the organization and enable Security Hub for them. Option A is incorrect because creating an SCP that has full administrative privileges and attaching it to the management account does not grant the management account access to the member accounts. SCPs are used to restrict the permissions of the member accounts, not to grant permissions to the management account. Option D is incorrect because using AWS Firewall Manager to collect and group findings across all accounts is not a valid use case for Firewall Manager. Firewall Manager is used to centrally configure and manage firewall rules across the organization, not to collect and group security findings. Option E is incorrect because using Amazon Inspector to collect and group findings across all accounts is not a valid use case for Amazon Inspector. Amazon Inspector is used to assess the security and compliance of applications running on Amazon EC2 instances, not to collect and group security findings across accounts. References:

? Inviting an AWS account to join your organization

? Enabling and disabling AWS Security Hub

? Service control policies

? AWS Firewall Manager

? Amazon Inspector

**NEW QUESTION 10**

A company is storing 100 GB of log data in csv format in an Amazon S3 bucket SQL developers want to query this data and generate graphs to visualize it. The SQL developers also need an efficient automated way to store metadata from the csv file.

Which combination of steps will meet these requirements with the LEAST amount of effort? (Select THREE.)

- A. Fitter the data through AWS X-Ray to visualize the data.
- B. Filter the data through Amazon QuickSight to visualize the data.
- C. Query the data with Amazon Athena.
- D. Query the data with Amazon Redshift.
- E. Use the AWS Glue Data Catalog as the persistent metadata store.
- F. Use Amazon DynamoDB as the persistent metadata store.

**Answer:** BCE

**Explanation:**

<https://docs.aws.amazon.com/glue/latest/dg/components-overview.html>

**NEW QUESTION 10**

A company's DevOps engineer is working in a multi-account environment. The company uses AWS Transit Gateway to route all outbound traffic through a network operations account. In the network operations account all account traffic passes through a firewall appliance for inspection before the traffic goes to an internet gateway.

The firewall appliance sends logs to Amazon CloudWatch Logs and includes event severities of CRITICAL, HIGH, MEDIUM, LOW, and INFO. The security team wants to receive an alert if any CRITICAL events occur. What should the DevOps engineer do to meet these requirements?

- A. Create an Amazon CloudWatch Synthetics canary to monitor the firewall stat
- B. If the firewall reaches a CRITICAL state or logs a CRITICAL event use a CloudWatch alarm to publish a notification to an Amazon Simple Notification Service (Amazon SNS) topic Subscribe the security team's email address to the topic.
- C. Create an Amazon CloudWatch metric filter by using a search for CRITICAL events Publish a custom metric for the findin
- D. Use a CloudWatch alarm based on the custom metric to publish a notification to an Amazon Simple Notification Service (Amazon SNS) topic
- E. Subscribe the security team's email address to the topic.
- F. Enable Amazon GuardDuty in the network operations account
- G. Configure GuardDuty to monitor flow logs Create an Amazon EventBridge event rule that is invoked by GuardDuty events that are CRITICAL Define an Amazon Simple Notification Service (Amazon SNS) topic as a target Subscribe the security team's email address to the topic.
- H. Use AWS Firewall Manager to apply consistent policies across all account
- I. Create an Amazon EventBridge event rule that is invoked by Firewall Manager events that are CRITICAL Define an Amazon Simple Notification Service (Amazon SNS) topic as a target Subscribe the security team's email address to the topic.
- J. EventBridge event rule that is invoked by Firewall Manager events that are CRITICAL Define an Amazon Simple Notification Service (Amazon SNS) topic as a target Subscribe the security team's email address to the topic.

**Answer:** B

**Explanation:**

"The firewall appliance sends logs to Amazon CloudWatch Logs and includes event severities of CRITICAL, HIGH, MEDIUM, LOW, and INFO"

**NEW QUESTION 15**

A company is testing a web application that runs on Amazon EC2 instances behind an Application Load Balancer. The instances run in an Auto Scaling group across multiple Availability Zones. The company uses a blue green deployment process with immutable instances when deploying new software. During testing users are being automatically logged out of the application at random times. Testers also report that when a new version of the application is deployed all users are logged out. The development team needs a solution to ensure users remain logged in across scaling events and application deployments. What is the MOST operationally efficient way to ensure users remain logged in?

- A. Enable smart sessions on the load balancer and modify the application to check for an existing session.
- B. Enable session sharing on the load balancer and modify the application to read from the session store.
- C. Store user session information in an Amazon S3 bucket and modify the application to read session information from the bucket.
- D. Modify the application to store user session information in an Amazon ElastiCache cluster.

**Answer:** D

**Explanation:**

<https://aws.amazon.com/caching/session-management/>

**NEW QUESTION 18**

A DevOps engineer used an AWS CloudFormation custom resource to set up AD Connector. The AWS Lambda function ran and created AD Connector, but CloudFormation is not transitioning from CREATE\_IN\_PROGRESS to CREATE\_COMPLETE. Which action should the engineer take to resolve this issue?

- A. Ensure the Lambda function code has exited successfully.
- B. Ensure the Lambda function code returns a response to the pre-signed URL.
- C. Ensure the Lambda function IAM role has cloudformation UpdateStack permissions for the stack ARN.
- D. Ensure the Lambda function IAM role has ds ConnectDirectory permissions for the AWS account.

**Answer:** B

**Explanation:**

Reference: <https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/crpg-ref-responses.html>

**NEW QUESTION 22**

A company uses a series of individual Amazon CloudFormation templates to deploy its multi-Region Applications. These templates must be deployed in a specific order. The company is making more changes to the templates than previously expected and wants to deploy new templates more efficiently. Additionally, the data engineering team must be notified of all changes to the templates. What should the company do to accomplish these goals?

- A. Create an AWS Lambda function to deploy the CloudFormation templates in the required order Use stack policies to alert the data engineering team.
- B. Host the CloudFormation templates in Amazon S3 Use Amazon S3 events to directly trigger CloudFormation updates and Amazon SNS notifications.
- C. Implement CloudFormation StackSets and use drift detection to trigger update alerts to the data engineering team.
- D. Leverage CloudFormation nested stacks and stack sets (or deployments) Use Amazon SNS to notify the data engineering team.

**Answer:** D

**Explanation:**

This solution will meet the requirements because it will use CloudFormation nested stacks and stack sets to deploy the templates more efficiently and consistently across multiple regions. Nested stacks allow the company to separate out common components and reuse templates, while stack sets allow the company to create stacks in multiple accounts and regions with a single template. The company can also use Amazon SNS to send notifications to the data engineering team whenever a change is made to the templates or the stacks. Amazon SNS is a service that allows you to publish messages to subscribers, such as email addresses, phone numbers, or other AWS services. By using Amazon SNS, the company can ensure that the data engineering team is aware of all changes to the templates and can take appropriate actions if needed. What is Amazon SNS? - Amazon Simple Notification Service

**NEW QUESTION 25**

A company has a legacy application A DevOps engineer needs to automate the process of building the deployable artifact for the legacy application. The solution must store the deployable artifact in an existing Amazon S3 bucket for future deployments to reference Which solution will meet these requirements in the MOST operationally efficient way?

- A. Create a custom Docker image that contains all the dependencies for the legacy application Store the custom Docker image in a new Amazon Elastic Container Registry (Amazon ECR) repository Configure a new AWS CodeBuild project to use the custom Docker image to build the deployable artifact and to save the artifact to the S3 bucket.
- B. Launch a new Amazon EC2 instance Install all the dependencies (or the legacy application on the EC2 instance Use the EC2 instance to build the deployable artifact and to save the artifact to the S3 bucket.
- C. Create a custom EC2 Image Builder image Install all the dependencies for the legacy application on the image Launch a new Amazon EC2 instance from the image Use the new EC2 instance to build the deployable artifact and to save the artifact to the S3 bucket.
- D. Create an Amazon Elastic Kubernetes Service (Amazon EKS) cluster with an AWS Fargate profile that runs in multiple Availability Zones Create a custom Docker image that contains all the dependencies for the legacy application Store the custom Docker image in a new Amazon Elastic Container Registry (Amazon ECR) repository Use the custom Docker image inside the EKS cluster to build the deployable artifact and to save the artifact to the S3 bucket.

**Answer:** A

**Explanation:**

This approach is the most operationally efficient because it leverages the benefits of containerization, such as isolation and reproducibility, as well as AWS managed services. AWS CodeBuild is a fully managed build service that can compile your source code, run tests, and produce deployable software packages. By using a custom Docker image that includes all dependencies, you can ensure that the environment in which your code is built is consistent. Using Amazon ECR to store Docker images lets you easily deploy the images to any environment. Also, you can directly upload the build artifacts to Amazon S3 from AWS CodeBuild, which is beneficial for version control and archival purposes.

**NEW QUESTION 26**

A company has deployed an application in a production VPC in a single AWS account. The application is popular and is experiencing heavy usage. The company's security team wants to add additional security, such as AWS WAF, to the application deployment. However, the application's product manager is concerned about cost and does not want to approve the change unless the security team can prove that additional security is necessary. The security team believes that some of the application's demand might come from users that have IP addresses that are on a deny list. The security team provides the deny list to a DevOps engineer. If any of the IP addresses on the deny list access the application, the security team wants to receive automated notification in near real time so that the security team can document that the application needs additional security. The DevOps engineer creates a VPC flow log for the production VPC. Which set of additional steps should the DevOps engineer take to meet these requirements MOST cost-effectively?

- A. Create a log group in Amazon CloudWatch Log
- B. Configure the VPC flow log to capture accepted traffic and to send the data to the log group
- C. Create an Amazon CloudWatch metric filter for IP addresses on the deny list
- D. Create a CloudWatch alarm with the metric filter as input
- E. Set the period to 5 minutes and the datapoints to alarm to 1. Use an Amazon Simple Notification Service (Amazon SNS) topic to send alarm notices to the security team.
- F. Create an Amazon S3 bucket for log file
- G. Configure the VPC flow log to capture all traffic and to send the data to the S3 bucket
- H. Configure Amazon Athena to return all log files in the S3 bucket for IP addresses on the deny list
- I. Configure Amazon QuickSight to accept data from Athena and to publish the data as a dashboard that the security team can access
- J. Create a threshold alert of 1 for successful access
- K. Configure the alert to automatically notify the security team as frequently as possible when the alert threshold is met.
- L. Create an Amazon S3 bucket for log file
- M. Configure the VPC flow log to capture accepted traffic and to send the data to the S3 bucket
- N. Configure an Amazon OpenSearch Service cluster and domain for the log file
- O. Create an AWS Lambda function to retrieve the logs from the S3 bucket, format the logs, and load the logs into the OpenSearch Service cluster
- P. Schedule the Lambda function to run every 5 minutes
- Q. Configure an alert and condition in OpenSearch Service to send alerts to the security team through an Amazon Simple Notification Service (Amazon SNS) topic when access from the IP addresses on the deny list is detected.
- R. Create a log group in Amazon CloudWatch Log
- S. Create an Amazon S3 bucket to hold query results
- T. Configure the VPC flow log to capture all traffic and to send the data to the log group
- . Deploy an Amazon Athena CloudWatch connector in AWS Lambda
- . Connect the connector to the log group
- . Configure Athena to periodically query for all accepted traffic from the IP addresses on the deny list and to store the results in the S3 bucket
- . Configure an S3 event notification to automatically notify the security team through an Amazon Simple Notification Service (Amazon SNS) topic when new objects are added to the S3 bucket.

**Answer:** A

**NEW QUESTION 31**

A company uses AWS and has a VPC that contains critical compute infrastructure with predictable traffic patterns. The company has configured VPC flow logs that are published to a log group in Amazon CloudWatch Logs. The company's DevOps team needs to configure a monitoring solution for the VPC flow logs to identify anomalies in network traffic to the VPC over time. If the monitoring solution detects an anomaly, the company needs the ability to initiate a response to the anomaly. How should the DevOps team configure the monitoring solution to meet these requirements?

- A. Create an Amazon Kinesis data stream
- B. Subscribe the log group to the data stream
- C. Configure Amazon Kinesis Data Analytics to detect log anomalies in the data stream
- D. Create an AWS Lambda function to use as the output of the data stream
- E. Configure the Lambda function to write to the default Amazon EventBridge event bus in the event of an anomaly finding.
- F. Create an Amazon Kinesis Data Firehose delivery stream that delivers events to an Amazon S3 bucket
- G. Subscribe the log group to the delivery stream
- H. Configure Amazon Lookout for Metrics to monitor the data in the S3 bucket for anomalies
- I. Create an AWS Lambda function to run in response to Lookout for Metrics anomaly finding

- J. Configure the Lambda function to publish to the default Amazon EventBridge event bus.
- K. Create an AWS Lambda function to detect anomalies
- L. Configure the Lambda function to publish an event to the default Amazon EventBridge event bus if the Lambda function detects an anomaly
- M. Subscribe the Lambda function to the log group.
- N. Create an Amazon Kinesis data stream
- O. Subscribe the log group to the data stream
- P. Create an AWS Lambda function to detect log anomalies
- Q. Configure the Lambda function to write to the default Amazon EventBridge event bus if the Lambda function detects an anomaly
- R. Set the Lambda function as the processor for the data stream.

**Answer: D**

**Explanation:**

To meet the requirements, the DevOps team needs to configure a monitoring solution for the VPC flow logs that can detect anomalies in network traffic over time and initiate a response to the anomaly. The DevOps team can use Amazon Kinesis Data Streams to ingest and process streaming data from CloudWatch Logs. The DevOps team can subscribe the log group to a Kinesis data stream, which will deliver log events from CloudWatch Logs to Kinesis Data Streams in near real-time. The DevOps team can then create an AWS Lambda function to detect log anomalies using machine learning or statistical methods. The Lambda function can be set as a processor for the data stream, which means that it will process each record from the stream before sending it to downstream applications or destinations. The Lambda function can also write to the default Amazon EventBridge event bus if it detects an anomaly, which will allow other AWS services or custom applications to respond to the anomaly event.

**NEW QUESTION 32**

A DevOps engineer is planning to deploy a Ruby-based application to production. The application needs to interact with an Amazon RDS for MySQL database and should have automatic scaling and high availability. The stored data in the database is critical and should persist regardless of the state of the application stack. The DevOps engineer needs to set up an automated deployment strategy for the application with automatic rollbacks. The solution also must alert the application team when a deployment fails.

Which combination of steps will meet these requirements? (Select THREE.)

- A. Deploy the application on AWS Elastic Beanstalk
- B. Deploy an Amazon RDS for MySQL DB instance as part of the Elastic Beanstalk configuration.
- C. Deploy the application on AWS Elastic Beanstalk
- D. Deploy a separate Amazon RDS for MySQL DB instance outside of Elastic Beanstalk.
- E. Configure a notification email address that alerts the application team in the AWS Elastic Beanstalk configuration.
- F. Configure an Amazon EventBridge rule to monitor AWS Health events
- G. Use an Amazon Simple Notification Service (Amazon SNS) topic as a target to alert the application team.
- H. Use the immutable deployment method to deploy new application versions.
- I. Use the rolling deployment method to deploy new application versions.

**Answer: BDE**

**Explanation:**

For deploying a Ruby-based application with requirements for interaction with an Amazon RDS for MySQL database, automatic scaling, high availability, and data persistence, the following steps will meet the requirements:

? B. Deploy the application on AWS Elastic Beanstalk. Deploy a separate Amazon RDS for MySQL DB instance outside of Elastic Beanstalk. This approach ensures that the database persists independently of the Elastic Beanstalk environment, which can be torn down and recreated without affecting the database<sup>123</sup>.

? E. Use the immutable deployment method to deploy new application versions. Immutable deployments provide a zero-downtime deployment method that ensures that if any part of the deployment process fails, the environment is rolled back to the original state automatically<sup>4</sup>.

? D. Configure an Amazon EventBridge rule to monitor AWS Health events. Use an Amazon Simple Notification Service (Amazon SNS) topic as a target to alert the application team. This setup allows for automated monitoring and alerting of the application team in case of deployment failures or other health events<sup>56</sup>.

References:

? AWS Elastic Beanstalk documentation on deploying Ruby applications<sup>1</sup>.

? AWS documentation on application auto-scaling<sup>7</sup>.

? AWS documentation on automated deployment strategies with automatic rollbacks and alerts<sup>456</sup>.

**NEW QUESTION 34**

A company has configured an Amazon S3 event source on an AWS Lambda function. The company needs the Lambda function to run when a new object is created or an existing object is modified in a particular S3 bucket. The Lambda function will use the S3 bucket name and the S3 object key of the incoming event to read the contents of the created or modified S3 object. The Lambda function will parse the contents and save the parsed contents to an Amazon DynamoDB table. The Lambda function's execution role has permissions to read from the S3 bucket and to write to the DynamoDB table. During testing, a DevOps engineer

discovers that the Lambda function does not run when objects are added to the S3 bucket or when existing objects are modified.

Which solution will resolve this problem?

- A. Increase the memory of the Lambda function to give the function the ability to process large files from the S3 bucket.
- B. Create a resource policy on the Lambda function to grant Amazon S3 the permission to invoke the Lambda function for the S3 bucket
- C. Configure an Amazon Simple Queue Service (Amazon SQS) queue as an OnFailure destination for the Lambda function
- D. Provision space in the /tmp folder of the Lambda function to give the function the ability to process large files from the S3 bucket

**Answer: B**

**Explanation:**

? Option A is incorrect because increasing the memory of the Lambda function does not address the root cause of the problem, which is that the Lambda function is not triggered by the S3 event source. Increasing the memory of the Lambda function might improve its performance or reduce its execution time, but it does not affect its invocation. Moreover, increasing the memory of the Lambda function might incur higher costs, as Lambda charges based on the amount of memory allocated to the function.

? Option B is correct because creating a resource policy on the Lambda function to grant Amazon S3 the permission to invoke the Lambda function for the S3 bucket is a necessary step to configure an S3 event source. A resource policy is a JSON document that defines who can access a Lambda resource and under what conditions. By granting Amazon S3 permission to invoke the Lambda function, the company ensures that the Lambda function runs when a new object is

created or an existing object is modified in the S3 bucket1.

? Option C is incorrect because configuring an Amazon Simple Queue Service (Amazon SQS) queue as an On-Failure destination for the Lambda function does not help with triggering the Lambda function. An On-Failure destination is a feature that allows Lambda to send events to another service, such as SQS or Amazon Simple Notification Service (Amazon SNS), when a function invocation fails. However, this feature only applies to asynchronous invocations, and S3 event sources use synchronous invocations. Therefore, configuring an SQS queue as an On-Failure destination would have no effect on the problem.

? Option D is incorrect because provisioning space in the /tmp folder of the Lambda function does not address the root cause of the problem, which is that the Lambda function is not triggered by the S3 event source. Provisioning space in the /tmp folder of the Lambda function might help with processing large files from the S3 bucket, as it provides temporary storage for up to 512 MB of data. However, it does not affect the invocation of the Lambda function.

References:

- ? Using AWS Lambda with Amazon S3
- ? Lambda resource access permissions
- ? AWS Lambda destinations
- ? [AWS Lambda file system]

### NEW QUESTION 38

A company has multiple development teams in different business units that work in a shared single AWS account All Amazon EC2 resources that are created in the account must include tags that specify who created the resources. The tagging must occur within the first hour of resource creation.

A DevOps engineer needs to add tags to the created resources that include the user ID that created the resource and the cost center ID The DevOps engineer configures an AWS Lambda function With the cost center mappings to tag the resources. The DevOps engineer also sets up AWS CloudTrail in the AWS account. An Amazon S3 bucket stores the CloudTrail event logs

Which solution will meet the tagging requirements?

- A. Create an S3 event notification on the S3 bucket to invoke the Lambda function for s3.ObjectTagging:Put event
- B. Enable bucket versioning on the S3 bucket.
- C. Enable server access logging on the S3 bucket
- D. Create an S3 event notification on the S3 bucket for s3.ObjectTagging events
- E. Create a recurring hourly Amazon EventBridge scheduled rule that invokes the Lambda function
- F. Modify the Lambda function to read the logs from the S3 bucket
- G. Create an Amazon EventBridge rule that uses Amazon EC2 as the event source
- H. Configure the rule to match events delivered by CloudTrail
- I. Configure the rule to target the Lambda function

**Answer: D**

#### Explanation:

? Option A is incorrect because S3 event notifications do not support s3.ObjectTagging:Put events. S3 event notifications only support events related to object creation, deletion, replication, and restore. Moreover, enabling bucket versioning on the S3 bucket is not relevant to the tagging requirements, as it only keeps multiple versions of objects in the bucket.

? Option B is incorrect because enabling server access logging on the S3 bucket does not help with tagging the resources. Server access logging only records requests for access to the bucket or its objects. It does not capture the user ID or the cost center ID of the resources. Furthermore, creating an S3 event notification on the S3 bucket for s3.ObjectTagging:Put events is not possible, as explained in option A.

? Option C is incorrect because creating a recurring hourly Amazon EventBridge scheduled rule that invokes the Lambda function is not efficient or timely. The Lambda function would have to read the logs from the S3 bucket every hour and tag the resources accordingly, which could incur unnecessary costs and delays. A better solution would be to trigger the Lambda function as soon as a resource is created, rather than waiting for an hourly schedule.

? Option D is correct because creating an Amazon EventBridge rule that uses Amazon EC2 as the event source and matches events delivered by CloudTrail is a valid way to tag the resources. CloudTrail records all API calls made to AWS services, including EC2, and delivers them as events to EventBridge. The EventBridge rule can filter the events based on the user ID and the resource type, and then target the Lambda function to tag the resources with the cost center ID. This solution meets the tagging requirements in a timely and efficient manner.

References:

- ? S3 event notifications
- ? Server access logging
- ? Amazon EventBridge rules
- ? AWS CloudTrail

### NEW QUESTION 43

A company has an on-premises application that is written in Go. A DevOps engineer must move the application to AWS. The company's development team wants to enable blue/green deployments and perform A/B testing.

Which solution will meet these requirements?

- A. Deploy the application on an Amazon EC2 instance, and create an AMI of the instance
- B. Use the AMI to create an automatic scaling launch configuration that is used in an Auto Scaling group
- C. Use Elastic Load Balancing to distribute traffic
- D. When changes are made to the application, a new AMI will be created, which will initiate an EC2 instance refresh.
- E. Use Amazon Lightsail to deploy the application
- F. Store the application in a zipped format in an Amazon S3 bucket
- G. Use this zipped version to deploy new versions of the application to Lightsail
- H. Use Lightsail deployment options to manage the deployment.
- I. Use AWS CodeArtifact to store the application code
- J. Use AWS CodeDeploy to deploy the application to a fleet of Amazon EC2 instances
- K. Use Elastic Load Balancing to distribute the traffic to the EC2 instance
- L. When making changes to the application, upload a new version to CodeArtifact and create a new CodeDeploy deployment.
- M. Use AWS Elastic Beanstalk to host the application
- N. Store a zipped version of the application in Amazon S3. Use that location to deploy new versions of the application
- O. Use Elastic Beanstalk to manage the deployment options.

**Answer: D**

#### Explanation:

<https://aws.amazon.com/quickstart/architecture/blue-green-deployment/>

**NEW QUESTION 45**

A DevOps engineer is setting up a container-based architecture. The engineer has decided to use AWS CloudFormation to automatically provision an Amazon ECS cluster and an Amazon EC2 Auto Scaling group to launch the EC2 container instances. After successfully creating the CloudFormation stack, the engineer noticed that, even though the ECS cluster and the EC2 instances were created successfully and the stack finished the creation, the EC2 instances were associating with a different cluster.

How should the DevOps engineer update the CloudFormation template to resolve this issue?

- A. Reference the EC2 instances in the AWS: ECS: Cluster resource and reference the ECS cluster in the AWS: ECS: Service resource.
- B. Reference the ECS cluster in the AWS: AutoScaling: LaunchConfiguration resource of the UserData property.
- C. Reference the ECS cluster in the AWS:EC2: Instance resource of the UserData property.
- D. Reference the ECS cluster in the AWS: CloudFormation: CustomResource resource to trigger an AWS Lambda function that registers the EC2 instances with the appropriate ECS cluster.

**Answer: B**

**Explanation:**

The UserData property of the AWS: AutoScaling: LaunchConfiguration resource can be used to specify a script that runs when the EC2 instances are launched. This script can include the ECS cluster name as an environment variable for the ECS agent running on the EC2 instances. This way, the EC2 instances will register with the correct ECS cluster. Option A is incorrect because the AWS: ECS: Cluster resource does not have a property to reference the EC2 instances. Option C is incorrect because the EC2 instances are launched by the Auto Scaling group, not by the AWS: EC2: Instance resource. Option D is incorrect because using a custom resource and a Lambda function is unnecessary and overly complex for this scenario. References: AWS::AutoScaling::LaunchConfiguration, Amazon ECS Container Agent Configuration

**NEW QUESTION 47**

A company is using AWS CodePipeline to automate its release pipeline. AWS CodeDeploy is being used in the pipeline to deploy an application to Amazon Elastic Container Service (Amazon ECS) using the blue/green deployment model. The company wants to implement scripts to test the green version of the application before shifting traffic. These scripts will complete in 5 minutes or less. If errors are discovered during these tests, the application must be rolled back. Which strategy will meet these requirements?

- A. Add a stage to the CodePipeline pipeline between the source and deploy stage
- B. Use AWS CodeBuild to create a runtime environment and build commands in the buildspec file to invoke test script
- C. If errors are found, use the aws deploy stop-deployment command to stop the deployment.
- D. Add a stage to the CodePipeline pipeline between the source and deploy stage
- E. Use this stage to invoke an AWS Lambda function that will run the test script
- F. If errors are found, use the aws deploy stop-deployment command to stop the deployment.
- G. Add a hooks section to the CodeDeploy AppSpec file
- H. Use the AfterAllowTestTraffic lifecycle event to invoke an AWS Lambda function to run the test script
- I. If errors are found, exit the Lambda function with an error to initiate rollback.
- J. Add a hooks section to the CodeDeploy AppSpec file
- K. Use the AfterAllowTraffic lifecycle event to invoke the test script
- L. If errors are found, use the aws deploy stop-deployment CLI command to stop the deployment.

**Answer: C**

**Explanation:**

<https://docs.aws.amazon.com/codedeploy/latest/userguide/reference-appspec-file-structure-hooks.html>

**NEW QUESTION 50**

A company is implementing an Amazon Elastic Container Service (Amazon ECS) cluster to run its workload. The company architecture will run multiple ECS services on the cluster. The architecture includes an Application Load Balancer on the front end and uses multiple target groups to route traffic. A DevOps engineer must collect application and access logs. The DevOps engineer then needs to send the logs to an Amazon S3 bucket for near-real-time analysis.

Which combination of steps must the DevOps engineer take to meet these requirements? (Choose three.)

- A. Download the Amazon CloudWatch Logs container instance from AW
- B. Configure this instance as a task
- C. Update the application service definitions to include the logging task.
- D. Install the Amazon CloudWatch Logs agent on the ECS instance
- E. Change the logging driver in the ECS task definition to awslogs.
- F. Use Amazon EventBridge to schedule an AWS Lambda function that will run every 60 seconds and will run the Amazon CloudWatch Logs create-export-task command
- G. Then point the output to the logging S3 bucket.
- H. Activate access logging on the ALB
- I. Then point the ALB directly to the logging S3 bucket.
- J. Activate access logging on the target groups that the ECS services use
- K. Then send the logs directly to the logging S3 bucket.
- L. Create an Amazon Kinesis Data Firehose delivery stream that has a destination of the logging S3 bucket
- M. Then create an Amazon CloudWatch Logs subscription filter for Kinesis Data Firehose.

**Answer: BDF**

**Explanation:**

<https://docs.aws.amazon.com/AmazonECS/latest/developerguide/ecs-logging-monitoring.html>

**NEW QUESTION 54**

A company has developed an AWS Lambda function that handles orders received through an API. The company is using AWS CodeDeploy to deploy the Lambda function as the final stage of a CI/CD pipeline.

A DevOps engineer has noticed there are intermittent failures of the ordering API for a few seconds after deployment. After some investigation the DevOps engineer believes the failures are due to database changes not having fully propagated before the Lambda function is invoked

How should the DevOps engineer overcome this?

- A. Add a BeforeAllowTraffic hook to the AppSpec file that tests and waits for any necessary database changes before traffic can flow to the new version of the Lambda function.
- B. Add an AfterAllowTraffic hook to the AppSpec file that forces traffic to wait for any pending database changes before allowing the new version of the Lambda function to respond.
- C. Add a BeforeAllowTraffic hook to the AppSpec file that tests and waits for any necessary database changes before deploying the new version of the Lambda function.
- D. Add a validateService hook to the AppSpec file that inspects incoming traffic and rejects the payload if dependent services such as the database are not yet ready.

**Answer:** A

**Explanation:**

<https://docs.aws.amazon.com/codedeploy/latest/userguide/reference-appspec-file-structure-hooks.html#appspec-hooks-lambda>

**NEW QUESTION 55**

A company's application uses a fleet of Amazon EC2 On-Demand Instances to analyze and process data. The EC2 instances are in an Auto Scaling group. The Auto Scaling group is a target group for an Application Load Balancer (ALB). The application analyzes critical data that cannot tolerate interruption. The application also analyzes noncritical data that can withstand interruption.

The critical data analysis requires quick scalability in response to real-time application demand. The noncritical data analysis involves memory consumption. A DevOps engineer must implement a solution that reduces scale-out latency for the critical data. The solution also must process the noncritical data. Which combination of steps will meet these requirements? (Select TWO.)

- A. For the critical data, modify the existing Auto Scaling group
- B. Create a warm pool instance in the stopped state
- C. Define the warm pool size
- D. Create a new version of the launch template that has detailed monitoring enabled
- E. Use Spot Instances.
- F. For the critical data, modify the existing Auto Scaling group
- G. Create a warm pool instance in the stopped state
- H. Define the warm pool size
- I. Create a new version of the launch template that has detailed monitoring enabled
- J. Use On-Demand Instances.
- K. For the critical data
- L. Modify the existing Auto Scaling group
- M. Create a lifecycle hook to ensure that bootstrap scripts are completed successfully
- N. Ensure that the application on the instances is ready to accept traffic before the instances are registered
- O. Create a new version of the launch template that has detailed monitoring enabled.
- P. For the noncritical data, create a second Auto Scaling group that uses a launch template
- Q. Configure the launch template to install the unified Amazon CloudWatch agent and to configure the CloudWatch agent with a custom memory utilization metric
- R. Use Spot Instance
- S. Add the new Auto Scaling group as the target group for the ALB
- T. Modify the application to use two target groups for critical data and noncritical data.
- . For the noncritical data, create a second Auto Scaling group
- . Choose the predefined memory utilization metric type for the target tracking scaling policy
- . Use Spot Instance
- . Add the new Auto Scaling group as the target group for the ALB
- . Modify the application to use two target groups for critical data and noncritical data.

**Answer:** BD

**Explanation:**

? For the critical data, using a warm pool<sup>1</sup> can reduce the scale-out latency by having pre-initialized EC2 instances ready to serve the application traffic. Using On-Demand Instances can ensure that the instances are always available and not interrupted by Spot interruptions<sup>2</sup>.

? For the noncritical data, using a second Auto Scaling group with Spot Instances can reduce the cost and leverage the unused capacity of EC2<sup>3</sup>. Using a launch template with the CloudWatch agent<sup>4</sup> can enable the collection of memory utilization metrics, which can be used to scale the group based on the memory demand. Adding the second group as a target group for the ALB and modifying the application to use two target groups can enable routing the traffic based on the data type.

References: 1: Warm pools for Amazon EC2 Auto Scaling 2: Amazon EC2 On-Demand Capacity Reservations 3: Amazon EC2 Spot Instances 4: Metrics collected by the CloudWatch agent

**NEW QUESTION 59**

A company uses AWS Storage Gateway in file gateway mode in front of an Amazon S3 bucket that is used by multiple resources. In the morning when business begins, users do not see the objects processed by a third party the previous evening. When a DevOps engineer looks directly at the S3 bucket, the data is there, but it is missing in Storage Gateway.

Which solution ensures that all the updated third-party files are available in the morning?

- A. Configure a nightly Amazon EventBridge event to invoke an AWS Lambda function to run the RefreshCache command for Storage Gateway.
- B. Instruct the third party to put data into the S3 bucket using AWS Transfer for SFTP.
- C. Modify Storage Gateway to run in volume gateway mode.
- D. Use S3 Same-Region Replication to replicate any changes made directly in the S3 bucket to Storage Gateway.

**Answer:** A

**Explanation:**

[https://docs.aws.amazon.com/storagegateway/latest/APIReference/API\\_RefreshCache.html](https://docs.aws.amazon.com/storagegateway/latest/APIReference/API_RefreshCache.html) "It only updates the cached inventory to reflect changes in the inventory of the objects in the S3 bucket. This operation is only supported in the S3 File Gateway types."

**NEW QUESTION 61**

A company wants to use AWS CloudFormation for infrastructure deployment. The company has strict tagging and resource requirements and wants to limit the deployment to two Regions. Developers will need to deploy multiple versions of the same application.

Which solution ensures resources are deployed in accordance with company policy?

- A. Create AWS Trusted Advisor checks to find and remediate unapproved CloudFormation StackSets.
- B. Create a Cloud Formation drift detection operation to find and remediate unapproved CloudFormation StackSets.
- C. Create CloudFormation StackSets with approved CloudFormation templates.
- D. Create AWS Service Catalog products with approved CloudFormation templates.

**Answer:** D

**Explanation:**

service catalog uses stacksets and can enforce tag and restrict resources AWS Customer case with tag enforcement  
<https://aws.amazon.com/ko/blogs/apn/enforce-centralized-tag-compliance-using-aws-service-catalog-amazon-dynamodb-aws-lambda-and-amazon-cloudwatch-events/> And Youtube video showing how to restrict resources per user with portfolio <https://www.youtube.com/watch?v=LzvhTcqqyog>

**NEW QUESTION 66**

A company uses AWS Organizations to manage multiple accounts. Information security policies require that all unencrypted Amazon EBS volumes be marked as non-compliant. A DevOps engineer needs to automatically deploy the solution and ensure that this compliance check is always present. Which solution will accomplish this?

- A. Create an AWS CloudFormation template that defines an AWS Inspector rule to check whether EBS encryption is enable
- B. Save the template to an Amazon S3 bucket that has been shared with all accounts within the compan
- C. Update the account creation script pointing to the CloudFormation template in Amazon S3.
- D. Create an AWS Config organizational rule to check whether EBS encryption is enabled and deploy the rule using the AWS CL
- E. Create and apply an SCP to prohibit stopping and deleting AWS Config across the organization.
- F. Create an SCP in Organization
- G. Set the policy to prevent the launch of Amazon EC2 instances without encryption on the EBS volumes using a conditional expressio
- H. Apply the SCP to all AWS account
- I. Use Amazon Athena to analyze the AWS CloudTrail output, looking for events that deny an ec2: RunInstances action.
- J. Deploy an IAM role to all accounts from a single trusted account
- K. Build a pipeline withAWS CodePipeline with a stage in AWS Lambda to assume the IAM role, and list all EBS volumes in the account
- L. Publish a report to Amazon S3.

**Answer:** B

**Explanation:**

<https://docs.aws.amazon.com/config/latest/developerguide/ec2-ebs-encryption-by-default.html>

**NEW QUESTION 69**

A company updated the AWS Cloud Formation template for a critical business application. The stack update process failed due to an error in the updated template and AWS CloudFormation automatically began the stack rollback process Later a DevOps engineer discovered that the application was still unavailable and that the stack was in the UPDATE\_ROLLBACK\_FAILED state.

Which combination of actions should the DevOps engineer perform so that the stack rollback can complete successfully? (Select TWO.)

- A. Attach the AWS CloudFormation FullAccess IAM policy to the AWS CloudFormation role.
- B. Automatically recover the stack resources by using AWS CloudFormation drift detection.
- C. Issue a ContinueUpdateRollback command from the AWS CloudFormation console or the AWS CLI.
- D. Manually adjust the resources to match the expectations of the stack.
- E. Update the existing AWS CloudFormation stack by using the original template.

**Answer:** CD

**Explanation:**

<https://docs.aws.amazon.com/cli/latest/reference/cloudformation/continue-update-rollback.html> For a specified stack that is in the UPDATE\_ROLLBACK\_FAILED state, continues rolling it back to the UPDATE\_ROLLBACK\_COMPLETE state. Depending on the cause of the failure, you can manually fix the error and continue the rollback. By continuing the rollback, you can return your stack to a working state (the UPDATE\_ROLLBACK\_COMPLETE state), and then try to update the stack again.

**NEW QUESTION 70**

A company must encrypt all AMIs that the company shares across accounts. A DevOps engineer has access to a source account where an unencrypted custom AMI has been built. The DevOps engineer also has access to a target account where an Amazon EC2 Auto Scaling group will launch EC2 instances from the AMI. The DevOps engineer must share the AMI with the target account.

The company has created an AWS Key Management Service (AWS KMS) key in the source account.

Which additional steps should the DevOps engineer perform to meet the requirements? (Choose three.)

- A. In the source account, copy the unencrypted AMI to an encrypted AM
- B. Specify the KMS key in the copy action.
- C. In the source account, copy the unencrypted AMI to an encrypted AM
- D. Specify the default Amazon Elastic Block Store (Amazon EBS) encryption key in the copy action.
- E. In the source account, create a KMS grant that delegates permissions to the Auto Scaling group service-linked role in the target account.
- F. In the source account, modify the key policy to give the target account permissions to create a gran
- G. In the target account, create a KMS grant that delegates permissions to the Auto Scaling group service-linked role.
- H. In the source account, share the unencrypted AMI with the target account.
- I. In the source account, share the encrypted AMI with the target account.

**Answer:** ADF

**Explanation:**

The Auto Scaling group service-linked role must have a specific grant in the source account in order to decrypt the encrypted AMI. This is because the service-linked role does not have permissions to assume the default IAM role in the source account. The following steps are required to meet the requirements:

? In the source account, copy the unencrypted AMI to an encrypted AMI. Specify the KMS key in the copy action.

? In the source account, create a KMS grant that delegates permissions to the Auto Scaling group service-linked role in the target account.  
? In the source account, share the encrypted AMI with the target account.  
? In the target account, attach the KMS grant to the Auto Scaling group service-linked role.  
The first three steps are the same as the steps that I described earlier. The fourth step is required to grant the Auto Scaling group service-linked role permissions to decrypt the AMI in the target account.

#### NEW QUESTION 72

An online retail company based in the United States plans to expand its operations to Europe and Asia in the next six months. Its product currently runs on Amazon EC2 instances behind an Application Load Balancer. The instances run in an Amazon EC2 Auto Scaling group across multiple Availability Zones. All data is stored in an Amazon Aurora database instance.

When the product is deployed in multiple regions, the company wants a single product catalog across all regions, but for compliance purposes, its customer information and purchases must be kept in each region.

How should the company meet these requirements with the LEAST amount of application changes?

- A. Use Amazon Redshift for the product catalog and Amazon DynamoDB tables for the customer information and purchases.
- B. Use Amazon DynamoDB global tables for the product catalog and regional tables for the customer information and purchases.
- C. Use Aurora with read replicas for the product catalog and additional local Aurora instances in each region for the customer information and purchases.
- D. Use Aurora for the product catalog and Amazon DynamoDB global tables for the customer information and purchases.

**Answer: C**

#### NEW QUESTION 75

A development team wants to use AWS CloudFormation stacks to deploy an application. However, the developer IAM role does not have the required permissions to provision the resources that are specified in the AWS CloudFormation template. A DevOps engineer needs to implement a solution that allows the developers to deploy the stacks. The solution must follow the principle of least privilege.

Which solution will meet these requirements?

- A. Create an IAM policy that allows the developers to provision the required resource
- B. Attach the policy to the developer IAM role.
- C. Create an IAM policy that allows full access to AWS CloudFormation
- D. Attach the policy to the developer IAM role.
- E. Create an AWS CloudFormation service role that has the required permission
- F. Grant the developer IAM role a cloudformation:\* action
- G. Use the new service role during stack deployments.
- H. Create an AWS CloudFormation service role that has the required permission
- I. Grant the developer IAM role the iam:PassRole permission
- J. Use the new service role during stack deployments.

**Answer: D**

#### Explanation:

<https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/using-iam-service-role.html>

#### NEW QUESTION 77

An application running on a set of Amazon EC2 instances in an Auto Scaling group requires a configuration file to operate. The instances are created and maintained with AWS CloudFormation. A DevOps engineer wants the instances to have the latest configuration file when launched and wants changes to the configuration file to be reflected on all the instances with a minimal delay when the CloudFormation template is updated. Company policy requires that application configuration files be maintained along with AWS infrastructure configuration files in source control.

Which solution will accomplish this?

- A. In the CloudFormation template add an AWS Config rule
- B. Place the configuration file content in the rule's InputParameters property and set the Scope property to the EC2 Auto Scaling group
- C. Add an AWS Systems Manager Resource Data Sync resource to the template to poll for updates to the configuration.
- D. In the CloudFormation template add an EC2 launch template resource
- E. Place the configuration file content in the launch template
- F. Configure the cfn-init script to run when the instance is launched and configure the cfn-hup script to poll for updates to the configuration.
- G. In the CloudFormation template add an EC2 launch template resource
- H. Place the configuration file content in the launch template
- I. Add an AWS Systems Manager Resource Data Sync resource to the template to poll for updates to the configuration.
- J. In the CloudFormation template add CloudFormation intrinsic metadata
- K. Place the configuration file content in the metadata
- L. Configure the cfn-init script to run when the instance is launched and configure the cfn-hup script to poll for updates to the configuration.

**Answer: D**

#### Explanation:

Use the AWS::CloudFormation::Init type to include metadata on an Amazon EC2 instance for the cfn-init helper script. If your template calls the cfn-init script, the script looks for resource metadata rooted in the AWS::CloudFormation::Init metadata key. Reference:

<https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/aws-resource-init.html>

#### NEW QUESTION 81

A company wants to use a grid system for a proprietary enterprise in-memory data store on top of AWS. This system can run in multiple server nodes in any Linux-based distribution. The system must be able to reconfigure the entire cluster every time a node is added or removed. When adding or removing nodes an /etc./cluster/nodes config file must be updated listing the IP addresses of the current node members of that cluster.

The company wants to automate the task of adding new nodes to a cluster. What can a DevOps engineer do to meet these requirements?

- A. Use AWS OpsWorks Stacks to layer the server nodes of that cluster
- B. Create a Chef recipe that populates the content of the /etc./cluster/nodes config file and restarts the service by using the current members of the layer

- C. Assign that recipe to the Configure lifecycle event.
- D. Put the file nodes config in version contro
- E. Create an AWS CodeDeploy deployment configuration and deployment group based on an Amazon EC2 tag value for the cluster node
- F. When adding a new node to the cluster update the file with all tagged instances and make a commit in version contro
- G. Deploy the new file and restart the services.
- H. Create an Amazon S3 bucket and upload a version of the /etc./cluster/nodes config file Create a crontab script that will poll for that S3 file and download it frequentl
- I. Use a process manager such as Monit or system, to restart the cluster services when it detects that the new file was modifie
- J. When adding a node to the cluster edit the file's most recent members Upload the new file to the S3 bucket.
- K. Create a user data script that lists all members of the current security group of the cluster and automatically updates the /etc/cluster/. nodes confi
- L. Tile whenever a new instance is added to the cluster.

**Answer:** A

**Explanation:**

You can run custom recipes manually, but the best approach is usually to have AWS OpsWorks Stacks run them automatically. Every layer has a set of built-in recipes assigned each of five lifecycle events—Setup, Configure, Deploy, Undeploy, and Shutdown. Each time an event occurs for an instance, AWS OpsWorks Stacks runs the associated recipes for each of the instance's layers, which handle the corresponding tasks. For example, when an instance finishes booting, AWS OpsWorks Stacks triggers a Setup event. This event runs the associated layer's Setup recipes, which typically handle tasks such as installing and configuring packages

**NEW QUESTION 82**

An ecommerce company has chosen AWS to host its new platform. The company's DevOps team has started building an AWS Control Tower landing zone. The DevOps team has set the identity store within AWS IAM Identity Center (AWS Single Sign-On) to external identity provider (IdP) and has configured SAML 2.0. The DevOps team wants a robust permission model that applies the principle of least privilege. The model must allow the team to build and manage only the team's own resources.

Which combination of steps will meet these requirements? (Choose three.)

- A. Create IAM policies that include the required permission
- B. Include the aws:PrincipalTag condition key.
- C. Create permission set
- D. Attach an inline policy that includes the required permissions and uses the aws:PrincipalTag condition key to scope the permissions.
- E. Create a group in the Id
- F. Place users in the grou
- G. Assign the group to accounts and the permission sets in IAM Identity Center.
- H. Create a group in the Id
- I. Place users in the grou
- J. Assign the group to OUs and IAM policies.
- K. Enable attributes for access control in IAM Identity Cente
- L. Apply tags to user
- M. Map the tags as key-value pairs.
- N. Enable attributes for access control in IAM Identity Cente
- O. Map attributes from the IdP as key-value pairs.

**Answer:** BCF

**Explanation:**

Using the principalTag in the Permission Set inline policy a logged in user belonging to a specific AD group in the IDP can be permitted access to perform operations on certain resources if their group matches the group used in the PrincipleTag. Basically you are narrowing the scope of privileges assigned via Permission policies conditionally based on whether the logged in user belongs to a specific AD Group in IDP. The mapping of the AD group to the request attributes can be done using SSO attributes where we can pass other attributes like the SAML token as well.

<https://docs.aws.amazon.com/singlesignon/latest/userguide/abac.html>

**NEW QUESTION 86**

A DevOps engineer has implemented a CI/CO pipeline to deploy an AWS Cloud Format ion template that provisions a web application. The web application consists of an Application Load Balancer (ALB) a target group, a launch template that uses an Amazon Linux 2 AMI an Auto Scaling group of Amazon EC2 instances, a security group and an Amazon RDS for MySQL database The launch template includes user data that specifies a script to install and start the application.

The initial deployment of the application was successful. The DevOps engineer made changes to update the version of the application with the user data. The CI/CD pipeline has deployed a new version of the template However, the health checks on the ALB are now failing The health checks have marked all targets as unhealthy.

During investigation the DevOps engineer notices that the Cloud Formation stack has a status of UPDATE\_COMPLETE. However, when the DevOps engineer connects to one of the EC2 instances and checks /varar/log messages, the DevOps engineer notices that the Apache web server failed to start successfully because of a configuration error

How can the DevOps engineer ensure that the CloudFormation deployment will fail if the user data fails to successfully finish running?

- A. Use the cfn-signal helper script to signal success or failure to CloudFormation Use the WaitOnResourceSignals update policy within the CloudFormation template Set an appropriate timeout for the update policy.
- B. Create an Amazon CloudWatch alarm for the UnhealthyHostCount metri
- C. Include an appropriate alarm threshold for the target group Create an Amazon Simple Notification Service (Amazon SNS) topic as the target to signal success or failure to CloudFormation
- D. Create a lifecycle hook on the Auto Scaling group by using the AWS AutoScaling LifecycleHook resource Create an Amazon Simple Notification Service (Amazon SNS) topic as the target to signal success or failure to CloudFormation Set an appropriate timeout on the lifecycle hook.
- E. Use the Amazon CloudWatch agent to stream the cloud-init logs Create a subscription filter that includes an AWS Lambda function with an appropriate invocation timeout Configure the Lambda function to use the SignalResource API operation to signal success or failure to CloudFormation.

**Answer:** A

**Explanation:**

<https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/aws-attribute-updatepolicy.html>

**NEW QUESTION 89**

A company manages multiple AWS accounts in AWS Organizations. The company's security policy states that AWS account root user credentials for member accounts must not be used. The company monitors access to the root user credentials.

A recent alert shows that the root user in a member account launched an Amazon EC2 instance. A DevOps engineer must create an SCP at the organization's root level that will prevent the root user in member accounts from making any AWS service API calls.

Which SCP will meet these requirements?

A)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "*",
      "Resource": "*",
      "Condition": {
        "StringNotLike": { "aws:PrincipalArn": "arn:aws:iam::*:root" }
      }
    }
  ]
}
```

B)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Deny",
      "Action": "*",
      "Resource": "*",
      "Principal": { "AWS": "arn:aws:iam::*:root" }
    }
  ]
}
```

C)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Deny",
      "Action": "*",
      "Resource": "*",
      "Condition": {
        "StringLike": { "aws:PrincipalArn": "arn:aws:iam::*:root" }
      }
    }
  ]
}
```

D)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "*",
      "Resource": "*",
      "Principal": "root"
    }
  ]
}
```

A. Option A

- B. Option B
- C. Option C
- D. Option D

**Answer:** D

#### NEW QUESTION 94

A company uses an organization in AWS Organizations that has all features enabled. The company uses AWS Backup in a primary account and uses an AWS Key Management Service (AWS KMS) key to encrypt the backups.

The company needs to automate a cross-account backup of the resources that AWS Backup backs up in the primary account. The company configures cross-account backup in the Organizations management account. The company creates a new AWS account in the organization and configures an AWS Backup backup vault in the new account. The company creates a KMS key in the new account to encrypt the backups. Finally, the company configures a new backup plan in the primary account. The destination for the new backup plan is the backup vault in the new account.

When the AWS Backup job in the primary account is invoked, the job creates backups in the primary account. However, the backups are not copied to the new account's backup vault.

Which combination of steps must the company take so that backups can be copied to the new account's backup vault? (Select TWO.)

- A. Edit the backup vault access policy in the new account to allow access to the primary account.
- B. Edit the backup vault access policy in the primary account to allow access to the new account.
- C. Edit the backup vault access policy in the primary account to allow access to the KMS key in the new account.
- D. Edit the key policy of the KMS key in the primary account to share the key with the new account.
- E. Edit the key policy of the KMS key in the new account to share the key with the primary account.

**Answer:** AE

#### Explanation:

To enable cross-account backup, the company needs to grant permissions to both the backup vault and the KMS key in the destination account. The backup vault access policy in the destination account must allow the primary account to copy backups into the vault. The key policy of the KMS key in the destination account must allow the primary account to use the key to encrypt and decrypt the backups. These steps are described in the AWS documentation<sup>12</sup>. Therefore, the correct answer is A and E.

References:

? 1: Creating backup copies across AWS accounts - AWS Backup

? 2: Using AWS Backup with AWS Organizations - AWS Backup

#### NEW QUESTION 98

A company is performing vulnerability scanning for all Amazon EC2 instances across many accounts. The accounts are in an organization in AWS Organizations. Each account's VPCs are attached to a shared transit gateway. The VPCs send traffic to the internet through a central egress VPC. The company has enabled Amazon Inspector in a delegated administrator account and has enabled scanning for all member accounts.

A DevOps engineer discovers that some EC2 instances are listed in the "not scanning" tab in Amazon Inspector.

Which combination of actions should the DevOps engineer take to resolve this issue? (Choose three.)

- A. Verify that AWS Systems Manager Agent is installed and is running on the EC2 instances that Amazon Inspector is not scanning.
- B. Associate the target EC2 instances with security groups that allow outbound communication on port 443 to the AWS Systems Manager service endpoint.
- C. Grant inspector: StartAssessmentRun permissions to the IAM role that the DevOps engineer is using.
- D. Configure EC2 Instance Connect for the EC2 instances that Amazon Inspector is not scanning.
- E. Associate the target EC2 instances with instance profiles that grant permissions to communicate with AWS Systems Manager.
- F. Create a managed-instance activation
- G. Use the Activation Code and the Activation ID to register the EC2 instances.

**Answer:** ABE

#### Explanation:

<https://docs.aws.amazon.com/inspector/latest/user/scanning-ec2.html>

#### NEW QUESTION 103

A company needs to ensure that flow logs remain configured for all existing and new VPCs in its AWS account. The company uses an AWS CloudFormation stack to manage its VPCs. The company needs a solution that will work for any VPCs that any IAM user creates.

Which solution will meet these requirements?

- A. Add the resource to the CloudFormation stack that creates the VPCs.
- B. Create an organization in AWS Organization
- C. Add the company's AWS account to the organization
- D. Create an SCP to prevent users from modifying VPC flow logs.
- E. Turn on AWS Config
- F. Create an AWS Config rule to check whether VPC flow logs are turned on
- G. Configure automatic remediation to turn on VPC flow logs.
- H. Create an IAM policy to deny the use of API calls for VPC flow log
- I. Attach the IAM policy to all IAM users.

**Answer:** C

#### Explanation:

To meet the requirements of ensuring that flow logs remain configured for all existing and new VPCs in the AWS account, the company should use AWS Config and automatic remediation. AWS Config is a service that enables customers to assess, audit, and evaluate the configurations of their AWS resources. AWS Config continuously monitors and records the configuration changes of the AWS resources and evaluates them against desired configurations. Customers can use AWS Config rules to define the desired configuration state of their AWS resources and trigger actions when a resource configuration violates a rule.

One of the AWS Config rules that customers can use is vpc-flow-logs-enabled, which checks whether VPC flow logs are enabled for all VPCs in an AWS account. Customers can also configure automatic remediation for this rule, which means that AWS Config will automatically enable VPC flow logs for any VPCs that do not have them enabled. Customers can specify the destination (CloudWatch Logs or S3) and the traffic type (all, accept, or reject) for the flow logs as remediation parameters. By using AWS Config and automatic remediation, the company can ensure that flow logs remain configured for all existing and new VPCs in its AWS

account, regardless of who creates them or how they are created.

The other options are not correct because they do not meet the requirements or follow best practices. Adding the resource to the CloudFormation stack that creates the VPCs is not a sufficient solution because it will only work for VPCs that are created by using the CloudFormation stack. It will not work for VPCs that are created by using other methods, such as the console or the API. Creating an organization in AWS Organizations and creating an SCP to prevent users from modifying VPC flow logs is not a good solution because it will not ensure that flow logs are enabled for all VPCs in the first place. It will only prevent users from disabling or changing flow logs after they are enabled. Creating an IAM policy to deny the use of API calls for VPC flow logs and attaching it to all IAM users is not a valid solution because it will prevent users from enabling or disabling flow logs at all.

It will also not work for VPCs that are created by using other methods, such as the console or CloudFormation.

References:

? 1: AWS::EC2::FlowLog - AWS CloudFormation

? 2: Amazon VPC Flow Logs extends CloudFormation Support to custom format subscriptions, 1-minute aggregation intervals and tagging

? 3: Logging IP traffic using VPC Flow Logs - Amazon Virtual Private Cloud

? : About AWS Config - AWS Config

? : vpc-flow-logs-enabled - AWS Config

? : Remediate Noncompliant Resources with AWS Config Rules - AWS Config

#### NEW QUESTION 107

A company has its AWS accounts in an organization in AWS Organizations. AWS Config is manually configured in each AWS account. The company needs to implement a solution to centrally configure AWS Config for all accounts in the organization. The solution also must record resource changes to a central account. Which combination of actions should a DevOps engineer perform to meet these requirements? (Choose two.)

- A. Configure a delegated administrator account for AWS Config
- B. Enable trusted access for AWS Config in the organization.
- C. Configure a delegated administrator account for AWS Config
- D. Create a service-linked role for AWS Config in the organization's management account.
- E. Create an AWS CloudFormation template to create an AWS Config aggregator
- F. Configure a CloudFormation stack set to deploy the template to all accounts in the organization.
- G. Create an AWS Config organization aggregator in the organization's management account
- H. Configure data collection from all AWS accounts in the organization and from all AWS Regions.
- I. Create an AWS Config organization aggregator in the delegated administrator account
- J. Configure data collection from all AWS accounts in the organization and from all AWS Regions.

**Answer:** AE

#### Explanation:

<https://aws.amazon.com/blogs/mt/org-aggregator-delegated-admin/> <https://docs.aws.amazon.com/organizations/latest/userguide/services-that-can-integrate-config.html>

#### NEW QUESTION 109

A company that runs many workloads on AWS has an Amazon EBS spend that has increased over time. The DevOps team notices there are many unattached EBS volumes. Although there are workloads where volumes are detached, volumes over 14 days old are stale and no longer needed. A DevOps engineer has been tasked with creating automation that deletes unattached EBS volumes that have been unattached for 14 days. Which solution will accomplish this?

- A. Configure the AWS Config ec2-volume-inuse-check managed rule with a configuration changes trigger type and an Amazon EC2 volume resource target
- B. Create a new Amazon CloudWatch Events rule scheduled to execute an AWS Lambda function in 14 days to delete the specified EBS volume.
- C. Use Amazon EC2 and Amazon Data Lifecycle Manager to configure a volume lifecycle policy
- D. Set the interval period for unattached EBS volumes to 14 days and set the retention rule to delete
- E. Set the policy target volumes as \*
- F. Create an Amazon CloudWatch Events rule to execute an AWS Lambda function daily
- G. The Lambda function should find unattached EBS volumes and tag them with the current date, and delete unattached volumes that have tags with dates that are more than 14 days old.
- H. Use AWS Trusted Advisor to detect EBS volumes that have been detached for more than 14 days
- I. Execute an AWS Lambda function that creates a snapshot and then deletes the EBS volume.

**Answer:** C

#### Explanation:

The requirement is to create automation that deletes unattached EBS volumes that have been unattached for 14 days. To do this, the DevOps engineer needs to use the following steps:

? Create an Amazon CloudWatch Events rule to execute an AWS Lambda function

daily. CloudWatch Events is a service that enables event-driven architectures by delivering events from various sources to targets. Lambda is a service that lets you

run code without provisioning or managing servers. By creating a CloudWatch Events rule that executes a Lambda function daily, the DevOps engineer can schedule a recurring task to check and delete unattached EBS volumes.

? The Lambda function should find unattached EBS volumes and tag them with the

current date, and delete unattached volumes that have tags with dates that are more than 14 days old. The Lambda function can use the EC2 API to list and filter unattached EBS volumes based on their state and tags. The function can then tag each unattached volume with the current date using the create-tags command. The function can also compare the tag value with the current date and delete any unattached volume that has been tagged more than 14 days ago using the delete-volume command.

#### NEW QUESTION 112

A DevOps engineer is working on a data archival project that requires the migration of on-premises data to an Amazon S3 bucket. The DevOps engineer develops a script that incrementally archives on-premises data that is older than 1 month to Amazon S3. Data that is transferred to Amazon S3 is deleted from the on-premises location. The script uses the S3 PutObject operation.

During a code review the DevOps engineer notices that the script does not verify whether the data was successfully copied to Amazon S3. The DevOps engineer must update the script to ensure that data is not corrupted during transmission. The script must use MD5 checksums to verify data integrity before the on-premises data is deleted.

Which solutions for the script will meet these requirements? (Select TWO.)

- A. Check the returned response for the Versioned Compare the returned Versioned against the MD5 checksum.
- B. Include the MD5 checksum within the Content-MD5 parameter
- C. Check the operationcall's return status to find out if an error was returned.
- D. Include the checksum digest within the tagging parameter as a URL query parameter.
- E. Check the returned response for the ETag
- F. Compare the returned ETag against the MD5 checksum.
- G. Include the checksum digest within the Metadata parameter as a name-value pair After upload use the S3 HeadObject operation to retrieve metadata from the object.

**Answer:** BD

**Explanation:**

<https://docs.aws.amazon.com/AmazonS3/latest/userguide/checking-object-integrity.html>

**NEW QUESTION 113**

A company is implementing AWS CodePipeline to automate its testing process The company wants to be notified when the execution state fails and used the following custom event pattern in Amazon EventBridge:

```
{
  "source": [
    "aws.codepipeline"
  ],
  "detail-type": [
    "CodePipeline Action Execution State Change"
  ],
  "detail": {
    "state": [
      "FAILED"
    ]
  },
  "type": {
    "category": ["Approval"]
  }
}
```

Which type of events will match this event pattern?

- A. Failed deploy and build actions across all the pipelines
- B. All rejected or failed approval actions across all the pipelines
- C. All the events across all pipelines
- D. Approval actions across all the pipelines

**Answer:** B

**Explanation:**

Action-level states in events  
 Action state Description  
 STARTED The action is currently running. SUCCEEDED The action was completed successfully.  
 FAILED For Approval actions, the FAILED state means the action was either rejected by the reviewer or failed due to an incorrect action configuration.  
 CANCELED The action was canceled because the pipeline structure was updated.

**NEW QUESTION 118**

To run an application, a DevOps engineer launches an Amazon EC2 instance with public IP addresses in a public subnet. A user data script obtains the application artifacts and installs them on the instances upon launch. A change to the security classification of the application now requires the instances to run with no access to the internet. While the instances launch successfully and show as healthy, the application does not seem to be installed. Which of the following should successfully install the application while complying with the new rule?

- A. Launch the instances in a public subnet with Elastic IP addresses attached
- B. Once the application is installed and running, run a script to disassociate the Elastic IP addresses afterwards.
- C. Set up a NAT gateway
- D. Deploy the EC2 instances to a private subnet
- E. Update the private subnet's route table to use the NAT gateway as the default route.
- F. Publish the application artifacts to an Amazon S3 bucket and create a VPC endpoint for S3. Assign an IAM instance profile to the EC2 instances so they can read the application artifacts from the S3 bucket.
- G. Create a security group for the application instances and allow only outbound traffic to the artifact repository
- H. Remove the security group rule once the install is complete.

**Answer:** C

**Explanation:**

EC2 instances running in private subnets of a VPC can now have controlled access to S3 buckets, objects, and API functions that are in the same region as the VPC. You can use an S3 bucket policy to indicate which VPCs and which VPC Endpoints have access to your S3 buckets 1-  
<https://aws.amazon.com/pt/blogs/aws/new-vpc-endpoint-for-amazon-s3/>

**NEW QUESTION 122**

A company runs its container workloads in AWS App Runner. A DevOps engineer manages the company's container repository in Amazon Elastic Container Registry (Amazon ECR). The DevOps engineer must implement a solution that continuously monitors the container repository. The solution must create a new container image when the solution detects an operating system vulnerability or language package vulnerability. Which solution will meet these requirements?

- A. Use EC2 Image Builder to create a container image pipeline
- B. Use Amazon ECR as the target repository
- C. Turn on enhanced scanning on the ECR repository
- D. Create an Amazon EventBridge rule to capture an Inspector2 finding even
- E. Use the event to invoke the image pipeline
- F. Re-upload the container to the repository.
- G. Use EC2 Image Builder to create a container image pipeline
- H. Use Amazon ECR as the target repository
- I. Enable Amazon GuardDuty Malware Protection on the container workload
- J. Create an Amazon EventBridge rule to capture a GuardDuty finding even
- K. Use the event to invoke the image pipeline.
- L. Create an AWS CodeBuild project to create a container image
- M. Use Amazon ECR as the target repository
- N. Turn on basic scanning on the repository
- O. Create an Amazon EventBridge rule to capture an ECR image action even
- P. Use the event to invoke the CodeBuild project
- Q. Re-upload the container to the repository.
- R. Create an AWS CodeBuild project to create a container image
- S. Use Amazon ECR as the target repository
- T. Configure AWS Systems Manager Compliance to scan all managed nodes
- . Create an Amazon EventBridge rule to capture a configuration compliance state change even
- . Use the event to invoke the CodeBuild project.

**Answer:** A

**Explanation:**

The solution that meets the requirements is to use EC2 Image Builder to create a container image pipeline, use Amazon ECR as the target repository, turn on enhanced scanning on the ECR repository, create an Amazon EventBridge rule to capture an Inspector2 finding event, and use the event to invoke the image pipeline. Re-upload the container to the repository.

This solution will continuously monitor the container repository for vulnerabilities using enhanced scanning, which is a feature of Amazon ECR that provides detailed information and guidance on how to fix security issues found in your container images. Enhanced scanning uses Inspector2, a security assessment service that integrates with Amazon ECR and generates findings for any vulnerabilities detected in your images. You can use Amazon EventBridge to create a rule that triggers an action when an Inspector2 finding event occurs. The action can be to invoke an EC2 Image Builder pipeline, which is a service that automates the creation of container images. The pipeline can use the latest patches and updates to build a new container image and upload it to the same ECR repository, replacing the vulnerable image.

The other options are not correct because they do not meet all the requirements or use services that are not relevant for the scenario.

Option B is not correct because it uses Amazon GuardDuty Malware Protection, which is a feature of GuardDuty that detects malicious activity and unauthorized behavior on your AWS accounts and resources. GuardDuty does not scan container images for vulnerabilities, nor does it integrate with Amazon ECR or EC2 Image Builder.

Option C is not correct because it uses basic scanning on the ECR repository, which only provides a summary of the vulnerabilities found in your container images. Basic scanning does not use Inspector2 or generate findings that can be captured by Amazon EventBridge. Moreover, basic scanning does not provide guidance on how to fix the vulnerabilities.

Option D is not correct because it uses AWS Systems Manager Compliance, which is a feature of Systems Manager that helps you monitor and manage the compliance status of your AWS resources based on AWS Config rules and AWS Security Hub standards. Systems Manager Compliance does not scan container images for vulnerabilities, nor does it integrate with Amazon ECR or EC2 Image Builder.

**NEW QUESTION 127**

A DevOps engineer is working on a project that is hosted on Amazon Linux and has failed a security review. The DevOps manager has been asked to review the company buildspec.yaml file for an AWS CodeBuild project and provide recommendations. The buildspec.yaml file is configured as follows:

```
env:
  variables:
    AWS_ACCESS_KEY_ID: AKIAJF7BRFWJBA4GHXNA
    AWS_SECRET_ACCESS_KEY: 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
    AWS_DEFAULT_REGION: us-east-1
    DB_PASSWORD: cuj5RptFa3va
  phases:
    build:
      commands:
        - aws s3 cp s3://db-deploy-bucket/my.cnf.template /tmp/my.cnf
        - sed -i 's/DB_PW/${DB_PASSWORD}/' /tmp/my.cnf
        - aws s3 cp s3://db-deploy-bucket/instance.key /tmp/instance.key
        - chmod 600 /tmp/instance.key
        - scp -i /tmp/instance.key /tmp/my.cnf root@10.25.15.23:/etc/my.cnf
        - ssh -i /tmp/instance.key root@10.25.15.23 /etc/init.d/mysqld restart
```

What changes should be recommended to comply with AWS security best practices? (Select THREE.)

- A. Add a post-build command to remove the temporary files from the container before termination to ensure they cannot be seen by other CodeBuild users.
- B. Update the CodeBuild project role with the necessary permissions and then remove the AWS credentials from the environment variable.
- C. Store the db\_password as a SecureString value in AWS Systems Manager Parameter Store and then remove the db\_password from the environment variables.
- D. Move the environment variables to the 'db-deploy-bucket' Amazon S3 bucket, add a prebuild stage to download then export the variables.
- E. Use AWS Systems Manager run command versus sec and ssh commands directly to the instance.

**Answer:** BCE

**Explanation:**

B. Update the CodeBuild project role with the necessary permissions and then remove the AWS credentials from the environment variable. C. Store the DB\_PASSWORD as a SecureString value in AWS Systems Manager Parameter Store and then remove the DB\_PASSWORD from the environment variables. E. Use AWS Systems Manager run command versus scp and ssh commands directly to the instance.

**NEW QUESTION 131**

A company is running an application on Amazon EC2 instances in an Auto Scaling group. Recently an issue occurred that prevented EC2 instances from launching successfully and it took several hours for the support team to discover the issue. The support team wants to be notified by email whenever an EC2 instance does not start successfully.

Which action will accomplish this?

- A. Add a health check to the Auto Scaling group to invoke an AWS Lambda function whenever an instance status is impaired.
- B. Configure the Auto Scaling group to send a notification to an Amazon SNS topic whenever a failed instance launch occurs.
- C. Create an Amazon CloudWatch alarm that invokes an AWS Lambda function when a failed AttachInstances Auto Scaling API call is made.
- D. Create a status check alarm on Amazon EC2 to send a notification to an Amazon SNS topic whenever a status check fail occurs.

**Answer: B**

**Explanation:**

<https://docs.aws.amazon.com/autoscaling/ec2/userguide/ASGettingNotifications.html#auto-scaling-sns-notifications>

**NEW QUESTION 133**

An ecommerce company is receiving reports that its order history page is experiencing delays in reflecting the processing status of orders. The order processing system consists of an AWS Lambda function that uses reserved concurrency. The Lambda function processes order messages from an Amazon Simple Queue Service (Amazon SQS) queue and inserts processed orders into an Amazon DynamoDB table. The DynamoDB table has auto scaling enabled for read and write capacity.

Which actions should a DevOps engineer take to resolve this delay? (Choose two.)

- A. Check the ApproximateAgeOfOldestMessage metric for the SQS queue
- B. Increase the Lambda function concurrency limit.
- C. Check the ApproximateAgeOfOldestMessage metric for the SQS queue. Configure a redrive policy on the SQS queue.
- D. Check the NumberOfMessagesSent metric for the SQS queue
- E. Increase the SQS queue visibility timeout.
- F. Check the WriteThrottleEvents metric for the DynamoDB table
- G. Increase the maximum write capacity units (WCUs) for the table's scaling policy.
- H. Check the Throttles metric for the Lambda function
- I. Increase the Lambda function timeout.

**Answer: AD**

**Explanation:**

A: If the ApproximateAgeOfOldestMessages indicate that orders are remaining in the SQS queue for longer than expected, the reserved concurrency limit may be set too small to keep up with the number of orders entering the queue and is being throttled. D: The DynamoDB table is using Auto Scaling. With Auto Scaling, you create a scaling policy that specifies whether you want to scale read capacity or write capacity (or both), and the minimum and maximum provisioned capacity unit settings for the table. The ThrottledWriteRequests metric will indicate if there is a throttling issue on the DynamoDB table, which can be resolved by increasing the maximum write capacity units for the table's Auto Scaling policy. <https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/AutoScaling.html>

**NEW QUESTION 135**

A company requires its developers to tag all Amazon Elastic Block Store (Amazon EBS) volumes in an account to indicate a desired backup frequency. This requirement includes EBS volumes that do not require backups. The company uses custom tags named Backup\_Frequency that have values of none, daily, or weekly that correspond to the desired backup frequency. An audit finds that developers are occasionally not tagging the EBS volumes.

A DevOps engineer needs to ensure that all EBS volumes always have the Backup\_Frequency tag so that the company can perform backups at least weekly unless a different value is specified.

Which solution will meet these requirements?

- A. Set up AWS Config in the account
- B. Create a custom rule that returns a compliance failure for all Amazon EC2 resources that do not have a Backup Frequency tag applied. Configure a remediation action that uses a custom AWS Systems Manager Automation runbook to apply the Backup\_Frequency tag with a value of weekly.
- C. Set up AWS Config in the account
- D. Use a managed rule that returns a compliance failure for EC2::Volume resources that do not have a Backup Frequency tag applied
- E. Configure a remediation action that uses a custom AWS Systems Manager Automation runbook to apply the Backup\_Frequency tag with a value of weekly.
- F. Turn on AWS CloudTrail in the account
- G. Create an Amazon EventBridge rule that reacts to EBS CreateVolume event
- H. Configure a custom AWS Systems Manager Automation runbook to apply the Backup\_Frequency tag with a value of weekly
- I. Specify the runbook as the target of the rule.
- J. Turn on AWS CloudTrail in the account
- K. Create an Amazon EventBridge rule that reacts to EBS CreateVolume events or EBS ModifyVolume event
- L. Configure a custom AWS Systems Manager Automation runbook to apply the Backup\_Frequency tag with a value of weekly
- M. Specify the runbook as the target of the rule.

**Answer: B**

**Explanation:**

The following are the steps that the DevOps engineer should take to ensure that all EBS volumes always have the Backup\_Frequency tag so that the company can perform backups at least weekly unless a different value is specified:

? Set up AWS Config in the account.

? Use a managed rule that returns a compliance failure for EC2::Volume resources that do not have a Backup Frequency tag applied.

? Configure a remediation action that uses a custom AWS Systems Manager Automation runbook to apply the Backup\_Frequency tag with a value of weekly.

The managed rule AWS::Config::EBSVolumesWithoutBackupTag will return a compliance failure for any EBS volume that does not have the Backup\_Frequency tag applied. The remediation action will then use the Systems Manager Automation runbook to apply the Backup\_Frequency tag with a value of weekly to the EBS

volume.

**NEW QUESTION 136**

A company's DevOps engineer is creating an AWS Lambda function to process notifications from an Amazon Simple Notification Service (Amazon SNS) topic. The Lambda function will process the notification messages and will write the contents of the notification messages to an Amazon RDS Multi-AZ DB instance. During testing a database administrator accidentally shut down the DB instance. While the database was down the company lost several of the SNS notification messages that were delivered during that time.

The DevOps engineer needs to prevent the loss of notification messages in the future Which solutions will meet this requirement? (Select TWO.)

- A. Replace the RDS Multi-AZ DB instance with an Amazon DynamoDB table.
- B. Configure an Amazon Simple Queue Service (Amazon SQS) queue as a destination of the Lambda function.
- C. Configure an Amazon Simple Queue Service (Amazon SQS) dead-letter queue for the SNS topic.
- D. Subscribe an Amazon Simple Queue Service (Amazon SQS) queue to the SNS topic Configure the Lambda function to process messages from the SQS queue.
- E. Replace the SNS topic with an Amazon EventBridge event bus Configure an EventBridge rule on the new event bus to invoke the Lambda function for each event.

**Answer:** CD

**Explanation:**

These solutions will meet the requirement because they will prevent the loss of notification messages in the future. An Amazon SQS queue is a service that provides a reliable, scalable, and secure message queue for asynchronous communication between distributed components. You can use an SQS queue to buffer messages from an SNS topic and ensure that they are delivered and processed by a Lambda function, even if the function or the database is temporarily unavailable.

Option C will configure an SQS dead-letter queue for the SNS topic. A dead-letter queue is a queue that receives messages that could not be delivered to any subscriber after a specified number of retries. You can use a dead-letter queue to store and analyze failed messages, or to reprocess them later. This way, you can avoid losing messages that could not be delivered to the Lambda function due to network errors, throttling, or other issues. Option D will subscribe an SQS queue to the SNS topic and configure the Lambda function to process messages from the SQS queue. This will decouple the SNS topic from the Lambda function and provide more flexibility and control over the message delivery and processing. You can use an SQS queue to store messages from the SNS topic until they are ready to be processed by the Lambda function, and also to retry processing in case of failures. This way, you can avoid losing messages that could not be processed by the Lambda function due to database errors, timeouts, or other issues.

**NEW QUESTION 138**

A company's development team uses AVMS Cloud Formation to deploy its application resources The team must use for an changes to the environment The team cannot use AWS Management Console or the AWS CLI to make manual changes directly.

The team uses a developer IAM role to access the environment The role is configured with the AdministratorAccess managed policy. The company has created a new CloudFormationDeployment IAM role that has the following policy.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "elasticloadbalancing:*",
        "lambda:*",
        "dynamodb:*"
      ],
      "Resource": "*"
    }
  ]
}
```

The company wants ensure that only CloudFormation can use the new role. The development team cannot make any manual changes to the deployed resources. Which combination of steps meet these requirements? (Select THREE.)

- A. Remove the AdministratorAccess polic
- B. Assign the ReadOnlyAccess managed IAM policy to the developer rol
- C. Instruct the developers to use the CloudFormationDeployment role as a CloudFormation service role when the developers deploy new stacks.
- D. Update the trust of CloudFormationDeployment role to allow the developer IAM role to assume the CloudFormationDepoyment role.
- E. Configure the IAM to be to get and pass the CloudFormationDeployment role if cloudformation actions for resources,
- F. Update the trust Of the CloudFormationDepoyment role to anow the cloudformation.amazonaws.com AWS principal to perform the iam:AssumeR01e action
- G. Remove me Administratoraccess polic
- H. Assign the ReadOnly/Access managed IAM policy to the developer role Instruct the developers to assume the CloudFormatondeployment role when the developers new stacks
- I. Add an IAM policy to CloudFormationDeplyment to allow cloudformation \* on an Add a policy that allows the iam.PassR01e action for ARN of if iam PassedT0Service equal cloudformation.amazonaws.com

**Answer:** ADF

**Explanation:**

A comprehensive and detailed explanation is:

? Option A is correct because removing the AdministratorAccess policy and assigning the ReadOnlyAccess managed IAM policy to the developer role is a valid

way to prevent the developers from making any manual changes to the deployed resources. The AdministratorAccess policy grants full access to all AWS resources and actions, which is not necessary for the developers. The ReadOnlyAccess policy grants read-only access to most AWS resources and actions, which is sufficient for the developers to view the status of their stacks. Instructing the developers to use the CloudFormationDeployment role as a CloudFormation service role when they deploy new stacks is also a valid way to ensure that only CloudFormation can use the new role. A CloudFormation service role is an IAM role that allows CloudFormation to make calls to resources in a stack on behalf of the user1. The user can specify a service role when they create or update a stack, and CloudFormation will use that role's credentials for all operations that are performed on that stack1.

? Option B is incorrect because updating the trust of CloudFormationDeployment role to allow the developer IAM role to assume the CloudFormationDeployment role is not a valid solution. This would allow the developers to manually assume the CloudFormationDeployment role and perform actions on the deployed resources, which is not what the company wants. The trust of CloudFormationDeployment role should only allow the cloudformation.amazonaws.com AWS principal to assume the role, as in option D.

? Option C is incorrect because configuring the IAM user to be able to get and pass the CloudFormationDeployment role if cloudformation actions for resources is not a valid solution. This would allow the developers to manually pass the CloudFormationDeployment role to other services or resources, which is not what the company wants. The IAM user should only be able to pass the CloudFormationDeployment role as a service role when they create or update a stack with CloudFormation, as in option A.

? Option D is correct because updating the trust of CloudFormationDeployment role to allow the cloudformation.amazonaws.com AWS principal to perform the iam:AssumeRole action is a valid solution. This allows CloudFormation to assume the CloudFormationDeployment role and access resources in other services on behalf of the user2. The trust policy of an IAM role defines which entities can assume the role2. By specifying cloudformation.amazonaws.com as the principal, you grant permission only to CloudFormation to assume this role.

? Option E is incorrect because instructing the developers to assume the CloudFormationDeployment role when they deploy new stacks is not a valid solution. This would allow the developers to manually assume the CloudFormationDeployment role and perform actions on the deployed resources, which is not what the company wants. The developers should only use the CloudFormationDeployment role as a service role when they deploy new stacks with CloudFormation, as in option A.

? Option F is correct because adding an IAM policy to CloudFormationDeployment that allows cloudformation:\* on all resources and adding a policy that allows the iam:PassRole action for ARN of CloudFormationDeployment if iam:PassedToService equals cloudformation.amazonaws.com are valid solutions. The first policy grants permission for CloudFormationDeployment to perform any action with any resource using cloudformation.amazonaws.com as a service principal3. The second policy grants permission for passing this role only if it is passed by cloudformation.amazonaws.com as a service principal4. This ensures that only CloudFormation can use this role.

References:

? 1: AWS CloudFormation service roles

? 2: How to use trust policies with IAM roles

? 3: AWS::IAM::Policy

? 4: IAM: Pass an IAM role to a specific AWS service

#### NEW QUESTION 143

A company has multiple development groups working in a single shared AWS account. The Senior Manager of the groups wants to be alerted via a third-party API call when the creation of resources approaches the service limits for the account.

Which solution will accomplish this with the LEAST amount of development effort?

- A. Create an Amazon CloudWatch Event rule that runs periodically and targets an AWS Lambda function
- B. Within the Lambda function, evaluate the current state of the AWS environment and compare deployed resource values to resource limits on the account
- C. Notify the Senior Manager if the account is approaching a service limit.
- D. Deploy an AWS Lambda function that refreshes AWS Trusted Advisor checks, and configure an Amazon CloudWatch Events rule to run the Lambda function periodically
- E. Create another CloudWatch Events rule with an event pattern matching Trusted Advisor events and a target Lambda function
- F. In the target Lambda function, notify the Senior Manager.
- G. Deploy an AWS Lambda function that refreshes AWS Personal Health Dashboard checks, and configure an Amazon CloudWatch Events rule to run the Lambda function periodically
- H. Create another CloudWatch Events rule with an event pattern matching Personal Health Dashboard events and a target Lambda function
- I. In the target Lambda function, notify the Senior Manager.
- J. Add an AWS Config custom rule that runs periodically, checks the AWS service limit status, and streams notifications to an Amazon SNS topic
- K. Deploy an AWS Lambda function that notifies the Senior Manager, and subscribe the Lambda function to the SNS topic.

**Answer: B**

#### Explanation:

To meet the requirements, the company needs to create a solution that alerts the Senior Manager when the creation of resources approaches the service limits for the account with the least amount of development effort. The company can use AWS Trusted Advisor, which is a service that provides best practice recommendations for cost optimization, performance, security, and service limits. The company can deploy an AWS Lambda function that refreshes Trusted Advisor checks, and configure an Amazon CloudWatch Events rule to run the Lambda function periodically. This will ensure that Trusted Advisor checks are up to date and reflect the current state of the account. The company can then create another CloudWatch Events rule with an event pattern matching Trusted Advisor events and a target Lambda function. The event pattern can filter for events related to service limit checks and their status. The target Lambda function can notify the Senior Manager via a third-party API call if the event indicates that the account is approaching or exceeding a service limit.

#### NEW QUESTION 144

A DevOps team is merging code revisions for an application that uses an Amazon RDS Multi-AZ DB cluster for its production database. The DevOps team uses continuous integration to periodically verify that the application works. The DevOps team needs to test the changes before the changes are deployed to the production database.

Which solution will meet these requirements?

- A. Use a buildspec file in AWS CodeBuild to restore the DB cluster from a snapshot of the production database run integration tests, and drop the restored database after verification.
- B. Deploy the application to production
- C. Configure an audit log of data control language (DCL) operations to capture database activities to perform if verification fails.
- D. Create a snapshot of the DB cluster before deploying the application Use the Update requires Replacement property on the DB instance in AWS CloudFormation to deploy the application and apply the changes.
- E. Ensure that the DB cluster is a Multi-AZ deployment
- F. Deploy the application with the update
- G. Fail over to the standby instance if verification fails.

**Answer: A**

**Explanation:**

This solution will meet the requirements because it will create a temporary copy of the production database using a snapshot, run the integration tests on the copy, and delete the copy after the tests are done. This way, the production database will not be affected by the code revisions, and the DevOps team can test the changes before deploying them to production. A buildspec file is a YAML file that contains the commands and settings that CodeBuild uses to run a build1. The buildspec file can specify the steps to restore the DB cluster from a snapshot, run the integration tests, and drop the restored database2

**NEW QUESTION 149**

A company recently migrated its legacy application from on-premises to AWS. The application is hosted on Amazon EC2 instances behind an Application Load Balancer which is behind Amazon API Gateway. The company wants to ensure users experience minimal disruptions during any deployment of a new version of the application. The company also wants to ensure it can quickly roll back updates if there is an issue.

Which solution will meet these requirements with MINIMAL changes to the application?

- A. Introduce changes as a separate environment parallel to the existing one Configure API Gateway to use a canary release deployment to send a small subset of user traffic to the new environment.
- B. Introduce changes as a separate environment parallel to the existing one Update the application's DNS alias records to point to the new environment.
- C. Introduce changes as a separate target group behind the existing Application Load Balancer Configure API Gateway to route user traffic to the new target group in steps.
- D. Introduce changes as a separate target group behind the existing Application Load Balancer Configure API Gateway to route all traffic to the Application Load Balancer which then sends the traffic to the new target group.

**Answer:** A

**Explanation:**

API Gateway supports canary deployment on a deployment stage before you direct all traffic to that stage. A parallel environment means we will create a new ALB and a target group that will target a new set of EC2 instances on which the newer version of the app will be deployed. So the canary setting associated to the new version of the API will connect with the new ALB instance which in turn will direct the traffic to the new EC2 instances on which the newer version of the application is deployed.

**NEW QUESTION 152**

A company has multiple AWS accounts. The company uses AWS IAM Identity Center (AWS Single Sign-On) that is integrated with AWS Toolkit for Microsoft Azure DevOps. The attributes for access control feature is enabled in IAM Identity Center.

The attribute mapping list contains two entries. The department key is mapped to

`$(path:enterprise.department)`. The costCenter key is mapped to

`$(path:enterprise.costCenter)`.

All existing Amazon EC2 instances have a department tag that corresponds to three company departments (d1, d2, d3). A DevOps engineer must create policies based on the matching attributes. The policies must minimize administrative effort and must grant each Azure AD user access to only the EC2 instances that are tagged with the user's respective department name.

Which condition key should the DevOps engineer include in the custom permissions policies to meet these requirements?

A.

```
"Condition": {
  "ForAllValues:StringEquals": {
    "aws:TagKeys": ["department"]
  }
}
```

B.

```
"Condition": {
  "StringEquals": {
    "aws:PrincipalTag/department": "$(aws:ResourceTag/department)"
  }
}
```

C.

```
"Condition": {
  "StringEquals": {
    "ec2:ResourceTag/department": "$(aws:PrincipalTag/department)"
  }
}
```

D.

```
"Condition": {
  "ForAllValues:StringEquals": {
    "ec2:ResourceTag/department": ["d1", "d2", "d3"]
  }
}
```

A.

**Answer:** C

**Explanation:**

<https://docs.aws.amazon.com/singlesignon/latest/userguide/configure-abac.html>

**NEW QUESTION 153**

.....

## Thank You for Trying Our Product

\* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

\* One year free update

You can enjoy free update one year. 24x7 online support.

\* Trusted by Millions

We currently serve more than 30,000,000 customers.

\* Shop Securely

All transactions are protected by VeriSign!

**100% Pass Your AWS-Certified-DevOps-Engineer-Professional Exam with Our Prep Materials Via below:**

<https://www.certleader.com/AWS-Certified-DevOps-Engineer-Professional-dumps.html>