

Amazon-Web-Services

Exam Questions SOA-C02

AWS Certified SysOps Administrator - Associate (SOA-C02)



NEW QUESTION 1

- (Exam Topic 1)

An organization with a large IT department has decided to migrate to AWS. With different job functions in the IT department, it is not desirable to give all users access to all AWS resources. Currently, the organization handles access via LDAP group membership. What is the BEST method to allow access using current LDAP credentials?

- A. Create an AWS Directory Service Simple AD. Replicate the on-premises LDAP directory to Simple AD.
- B. Create a Lambda function to read LDAP groups and automate the creation of IAM users.
- C. Use AWS CloudFormation to create IAM roles. Deploy Direct Connect to allow access to the on-premises LDAP server.
- D. Federate the LDAP directory with IAM using SAML. Create different IAM roles to correspond to different LDAP groups to limit permissions.

Answer: D

NEW QUESTION 2

- (Exam Topic 1)

A company has an application that is running on Amazon EC2 instances in a VPC. The application needs access to download software updates from the internet. The VPC has public subnets and private subnets. The company's security policy requires all EC2 instances to be deployed in private subnets. What should a SysOps administrator do to meet those requirements?

- A. Add an internet gateway to the VPC. In the route table for the private subnets, add a route to the internet gateway.
- B. Add a NAT gateway to a private subnet.
- C. In the route table for the private subnets, add a route to the NAT gateway.
- D. Add a NAT gateway to a public subnet. In the route table for the private subnets, add a route to the NAT gateway.
- E. Add two internet gateways to the VPC.
- F. In the route table for the private subnets and public subnets, add a route to each internet gateway.

Answer: C

NEW QUESTION 3

- (Exam Topic 1)

A SysOps administrator applies the following policy to an AWS CloudFormation stack:

```
{
  "Statement": [
    {
      "Effect": "Deny",
      "Action": "Update:*",
      "Principal": "*",
      "Resource": ["LogicalResourceId/Production*"]
    },
    {
      "Effect": "Allow",
      "Action": "Update:*",
      "Principal": "*",
      "Resource": "*"
    }
  ]
}
```

What is the result of this policy?

- A. Users that assume an IAM role with a logical ID that begins with "Production" are prevented from running the update-stack command.
- B. Users can update all resources in the stack except for resources that have a logical ID that begins with "Production".
- C. Users can update all resources in the stack except for resources that have an attribute that begins with "Production".
- D. Users in an IAM group with a logical ID that begins with "Production" are prevented from running the update-stack command.

Answer: B

NEW QUESTION 4

- (Exam Topic 1)

An application team uses an Amazon Aurora MySQL DB cluster with one Aurora Replica. The application team notices that the application read performance degrades when user connections exceed 200. The number of user connections is typically consistent around 180, with occasional sudden increases above 200 connections. The application team wants the application to automatically scale as user demand increases or decreases. Which solution will meet these requirements?

- A. Migrate to a new Aurora multi-master DB cluster.
- B. Modify the application database connection string.
- C. Modify the DB cluster by changing to serverless mode whenever user connections exceed 200.
- D. Create an auto scaling policy with a target metric of 195 DatabaseConnections.
- E. Modify the DB cluster by increasing the Aurora Replica instance size.

Answer: C

NEW QUESTION 5

- (Exam Topic 1)

A company has created a NAT gateway in a public subnet in a VPC. The VPC also contains a private subnet that includes Amazon EC2 instances. The EC2 instances use the NAT gateway to access the internet to download patches and updates. The company has configured a VPC flow log for the elastic network interface of the NAT gateway. The company is publishing the output to Amazon CloudWatch Logs.

A SysOps administrator must identify the top five internet destinations that the EC2 instances in the private subnet communicate with for downloads.

What should the SysOps administrator do to meet this requirement in the MOST operationally efficient way?

- A. Use AWS CloudTrail Insights events to identify the top five internet destinations.
- B. Use Amazon CloudFront standard logs (access logs) to identify the top five internet destinations.
- C. Use CloudWatch Logs Insights to identify the top five internet destinations.
- D. Change the flow log to publish logs to Amazon S3. Use Amazon Athena to query the log files in Amazon S3.

Answer: C

NEW QUESTION 6

- (Exam Topic 1)

A company needs to archive all audit logs for 10 years. The company must protect the logs from any future edits.

Which solution will meet these requirements?

- A. Store the data in an Amazon Elastic Block Store (Amazon EBS) volume
- B. Configure AWS Key Management Service (AWS KMS) encryption.
- C. Store the data in an Amazon S3 Glacier vault
- D. Configure a vault lock policy for write-once, read-many (WORM) access.
- E. Store the data in Amazon S3 Standard-Infrequent Access (S3 Standard-IA). Configure server-side encryption.
- F. Store the data in Amazon S3 Standard-Infrequent Access (S3 Standard-IA). Configure multi-factor authentication (MFA).

Answer: B

Explanation:

To meet the requirements of the workload, a company should store the data in an Amazon S3 Glacier vault and configure a vault lock policy for write-once, read-many (WORM) access. This will ensure that the data is stored securely and cannot be edited in the future. The other solutions (storing the data in an Amazon Elastic Block Store (Amazon EBS) volume and configuring AWS Key Management Service (AWS KMS) encryption, storing the data in Amazon S3 Standard-Infrequent Access (S3 Standard-IA) and configuring server-side encryption, or storing the data in Amazon S3 Standard-Infrequent Access (S3 Standard-IA) and configuring multi-factor authentication (MFA)) will not meet the requirements, as they do not provide a way to protect the audit logs from future edits.

https://docs.aws.amazon.com/zh_tw/AmazonS3/latest/userguide/object-lock.html

NEW QUESTION 7

- (Exam Topic 1)

A SysOps administrator noticed that the cache hit ratio for an Amazon CloudFront distribution is less than 10%.

Which collection of configuration changes will increase the cache hit ratio for the distribution? (Select TWO.)

- A. Ensure that only required cookies, query strings, and headers are forwarded in the Cache Behavior Settings.
- B. Change the Viewer Protocol Policy to use HTTPS only.
- C. Configure the distribution to use presigned cookies and URLs to restrict access to the distribution.
- D. Enable automatic compression of objects in the Cache Behavior Settings.
- E. Increase the CloudFront time to live (TTL) settings in the Cache Behavior Settings.

Answer: AE

Explanation:

<https://docs.aws.amazon.com/AmazonCloudFront/latest/DeveloperGuide/cache-hit-ratio.html#cache-hit-ratio-ht>

NEW QUESTION 8

- (Exam Topic 1)

A company is running a website on Amazon EC2 instances behind an Application Load Balancer (ALB). The company configured an Amazon CloudFront distribution and set the ALB as the origin. The company created an Amazon Route 53 CNAME record to send all traffic through the CloudFront distribution. As an unintended side effect, mobile users are now being served the desktop version of the website.

Which action should a SysOps administrator take to resolve this issue?

- A. Configure the CloudFront distribution behavior to forward the User-Agent header.
- B. Configure the CloudFront distribution origin setting
- C. Add a User-Agent header to the list of origin custom headers.
- D. Enable IPv6 on the AL
- E. Update the CloudFront distribution origin settings to use the dualstack endpoint.
- F. Enable IPv6 on the CloudFront distributio
- G. Update the Route 53 record to use the dualstack endpoint.

Answer: A

Explanation:

<https://docs.aws.amazon.com/AmazonCloudFront/latest/DeveloperGuide/header-caching.html#header-caching->

NEW QUESTION 9

- (Exam Topic 1)

A SysOps administrator receives an alert from Amazon GuardDuty about suspicious network activity on an Amazon EC2 instance. The GuardDuty finding lists a

new external IP address as a traffic destination. The SysOps administrator does not recognize the external IP address. The SysOps administrator must block traffic to the external IP address that GuardDuty identified. Which solution will meet this requirement?

- A. Create a new security group to block traffic to the external IP address
- B. Assign the new security group to the EC2 instance
- C. Use VPC flow logs with Amazon Athena to block traffic to the external IP address
- D. Create a network ACL. Add an outbound deny rule for traffic to the external IP address
- E. Create a new security group to block traffic to the external IP address. Assign the new security group to the entire VPC

Answer: A

NEW QUESTION 10

- (Exam Topic 1)

A company recently migrated its server infrastructure to Amazon EC2 instances. The company wants to use Amazon CloudWatch metrics to track instance memory utilization and available disk space.

What should a SysOps administrator do to meet these requirements?

- A. Configure CloudWatch from the AWS Management Console for all the instances that require monitoring by CloudWatch
- B. AWS automatically installs and configures the agents for the specified instances.
- C. Install and configure the CloudWatch agent on all the instances
- D. Attach an IAM role to allow the instances to write logs to CloudWatch.
- E. Install and configure the CloudWatch agent on all the instances
- F. Attach an IAM user to allow the instances to write logs to CloudWatch.
- G. Install and configure the CloudWatch agent on all the instances
- H. Attach the necessary security groups to allow the instances to write logs to CloudWatch

Answer: C

NEW QUESTION 10

- (Exam Topic 1)

A company with multiple AWS accounts needs to obtain recommendations for AWS Lambda functions and identify optimal resource configurations for each Lambda function. How should a SysOps administrator provide these recommendations?

- A. Create an AWS Serverless Application Repository and export the Lambda function recommendations.
- B. Enable AWS Compute Optimizer and export the Lambda function recommendations
- C. Enable all features of AWS Organization and export the recommendations from AWS CloudTrail Insights.
- D. Run AWS Trusted Advisor and export the Lambda function recommendations

Answer: B

NEW QUESTION 15

- (Exam Topic 1)

A SysOps administrator is setting up an automated process to recover an Amazon EC2 instance in the event of an underlying hardware failure. The recovered instance must have the same private IP address and the same Elastic IP address that the original instance had. The SysOps team must receive an email notification when the recovery process is initiated.

Which solution will meet these requirements?

- A. Create an Amazon CloudWatch alarm for the EC2 instance, and specify the `StatusCheckFailed_Instance` metric
- B. Add an EC2 action to the alarm to recover the instance
- C. Add an alarm notification to publish a message to an Amazon Simple Notification Service (Amazon SNS) topic
- D. Subscribe the SysOps team email address to the SNS topic.
- E. Create an Amazon CloudWatch alarm for the EC2 instance, and specify the `StatusCheckFailed_System` metric
- F. Add an EC2 action to the alarm to recover the instance
- G. Add an alarm notification to publish a message to an Amazon Simple Notification Service (Amazon SNS) topic
- H. Subscribe the SysOps team email address to the SNS topic.
- I. Create an Auto Scaling group across three different subnets in the same Availability Zone with a minimum, maximum, and desired size of 1. Configure the Auto Scaling group to use a launch template that specifies the private IP address and the Elastic IP address
- J. Add an activity notification for the Auto Scaling group to send an email message to the SysOps team through Amazon Simple Email Service (Amazon SES).
- K. Create an Auto Scaling group across three Availability Zones with a minimum, maximum, and desired size of 1. Configure the Auto Scaling group to use a launch template that specifies the private IP address and the Elastic IP address
- L. Add an activity notification for the Auto Scaling group to publish a message to an Amazon Simple Notification Service (Amazon SNS) topic
- M. Subscribe the SysOps team email address to the SNS topic.

Answer: B

Explanation:

You can create an Amazon CloudWatch alarm that monitors an Amazon EC2 instance and automatically recovers the instance if it becomes impaired due to an underlying hardware failure or a problem that requires AWS involvement to repair. Terminated instances cannot be recovered. A recovered instance is identical to the original instance, including the instance ID, private IP addresses, Elastic IP addresses, and all instance metadata. If the impaired instance has a public IPv4 address, the instance retains the public IPv4 address after recovery. If the impaired instance is in a placement group, the recovered instance runs in the placement group. When the `StatusCheckFailed_System` alarm is triggered, and the recover action is initiated, you will be notified by the Amazon SNS topic that you selected when you created the alarm and associated the recover action. <https://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ec2-instance-recover.html>

NEW QUESTION 19

- (Exam Topic 1)

A company is attempting to manage its costs in the AWS Cloud. A SysOps administrator needs specific company-defined tags that are assigned to resources to appear on the billing report.

What should the SysOps administrator do to meet this requirement?

- A. Activate the tags as AWS generated cost allocation tags.
- B. Activate the tags as user-defined cost allocation tags.
- C. Create a new cost category
- D. Select the account billing dimension.
- E. Create a new AWS Cost and Usage Report
- F. Include the resource IDs.

Answer: B

Explanation:

<https://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/custom-tags.html> "User-defined tags are tags that you define, create, and apply to resources. After you have created and applied the user-defined tags, you can activate by using the Billing and Cost Management console for cost allocation tracking. "

To meet this requirement, the SysOps administrator should activate the company-defined tags as user-defined cost allocation tags. This will ensure that the tags appear on the billing report and that the resources can be tracked with the specific tags. The other options (activating the tags as AWS generated cost allocation tags, creating a new cost category and selecting the account billing dimension, and creating a new AWS Cost and Usage Report and including the resource IDs) will not meet the requirements and are not the correct solutions for this issue.

NEW QUESTION 21

- (Exam Topic 1)

While setting up an AWS managed VPN connection, a SysOps administrator creates a customer gateway resource in AWS. The customer gateway device resides in a data center with a NAT gateway in front of it.

What address should be used to create the customer gateway resource?

- A. The private IP address of the customer gateway device
- B. The MAC address of the NAT device in front of the customer gateway device
- C. The public IP address of the customer gateway device
- D. The public IP address of the NAT device in front of the customer gateway device

Answer: D

NEW QUESTION 23

- (Exam Topic 1)

A SysOps administrator launches an Amazon EC2 Linux instance in a public subnet. When the instance is running, the SysOps administrator obtains the public IP address and attempts to remotely connect to the instance multiple times. However, the SysOps administrator always receives a timeout error.

Which action will allow the SysOps administrator to remotely connect to the instance?

- A. Add a route table entry in the public subnet for the SysOps administrator's IP address.
- B. Add an outbound network ACL rule to allow TCP port 22 for the SysOps administrator's IP address.
- C. Modify the instance security group to allow inbound SSH traffic from the SysOps administrator's IP address.
- D. Modify the instance security group to allow outbound SSH traffic to the SysOps administrator's IP address.

Answer: C

NEW QUESTION 26

- (Exam Topic 1)

An organization created an Amazon Elastic File System (Amazon EFS) volume with a file system ID of fs-85ba4Kc. and it is actively used by 10 Amazon EC2 hosts. The organization has become concerned that the file system is not encrypted. How can this be resolved?

- A. Enable encryption on each host's connection to the Amazon EFS volume. Each connection must be recreated for encryption to take effect.
- B. Enable encryption on the existing EFS volume by using the AWS Command Line Interface.
- C. Enable encryption on each host's local drive. Restart each host to encrypt the drive.
- D. Enable encryption on a newly created volume and copy all data from the original volume. Reconnect each host to the new volume.

Answer: D

Explanation:

<https://docs.aws.amazon.com/efs/latest/ug/encryption.html>

Amazon EFS supports two forms of encryption for file systems, encryption of data in transit and encryption at rest. You can enable encryption of data at rest when creating an Amazon EFS file system. You can enable encryption of data in transit when you mount the file system.

NEW QUESTION 28

- (Exam Topic 1)

A SysOps administrator is unable to authenticate an AWS CLI call to an AWS service. Which of the following is the cause of this issue?

- A. The IAM password is incorrect.
- B. The server certificate is missing.
- C. The SSH key pair is incorrect.
- D. There is no access key.

Answer: C

NEW QUESTION 31

- (Exam Topic 1)

A company has a stateless application that is hosted on a fleet of 10 Amazon EC2 On-Demand Instances in an Auto Scaling group. A minimum of 6 instances are needed to meet service requirements.

Which action will maintain uptime for the application MOST cost-effectively?

- A. Use a Spot Fleet with an On-Demand capacity of 6 instances.
- B. Update the Auto Scaling group with a minimum of 6 On-Demand Instances and a maximum of 10 On-Demand Instances.
- C. Update the Auto Scaling group with a minimum of 1 On-Demand Instance and a maximum of 6 On-Demand Instances.
- D. Use a Spot Fleet with a target capacity of 6 instances.

Answer: A

NEW QUESTION 33

- (Exam Topic 1)

A SysOps administrator is creating an Amazon EC2 Auto Scaling group in a new AWS account. After adding some instances, the SysOps administrator notices that the group has not reached the minimum number of instances. The SysOps administrator receives the following error message:

```
Launching a new EC2 instance. Status Reason: Your quota allows for 0 more running instance(s).  
You requested at least 1. Launching EC2 instance failed.
```

Which action will resolve this issue?

- A. Adjust the account spending limits for Amazon EC2 on the AWS Billing and Cost Management console
- B. Modify the EC2 quota for that AWS Region in the EC2 Settings section of the EC2 console.
- C. Request a quota Increase for the Instance type family by using Service Quotas on the AWS Management Console.
- D. Use the Rebalance action In the Auto Scaling group on the AWS Management Console.

Answer: C

NEW QUESTION 38

- (Exam Topic 1)

A SysOps administrator receives notification that an application that is running on Amazon EC2 instances has failed to authenticate to an Amazon RDS database. To troubleshoot, the SysOps administrator needs to investigate AWS Secrets Manager password rotation.

Which Amazon CloudWatch log will provide insight into the password rotation?

- A. AWS CloudTrail logs
- B. EC2 instance application logs
- C. AWS Lambda function logs
- D. RDS database logs

Answer: B

NEW QUESTION 41

- (Exam Topic 1)

A company's application currently uses an IAM role that allows all access to all AWS services. A SysOps administrator must ensure that the company's IAM policies allow only the permissions that the application requires.

How can the SysOps administrator create a policy to meet this requirement?

- A. Turn on AWS CloudTrail
- B. Generate a policy by using AWS Security Hub.
- C. Turn on Amazon EventBridge (Amazon CloudWatch Events). Generate a policy by using AWS Identity and Access Management Access Analyzer.
- D. Use the AWS CLI to run the get-generated-policy command in AWS Identity and Access Management Access Analyzer.
- E. Turn on AWS CloudTrail
- F. Generate a policy by using AWS Identity and Access Management Access Analyzer.

Answer: D

Explanation:

Generate a policy by using AWS Identity and Access Management Access Analyzer. AWS CloudTrail is a service that records all API calls made on your account. You can use this data to generate a policy with AWS Identity and Access Management Access Analyzer that only allows the permissions that the application requires. This will ensure that the application only has the necessary permissions and will protect the company from any unauthorized access.

<https://docs.aws.amazon.com/IAM/latest/UserGuide/what-is-access-analyzer.html#what-is-access-analyzer-poli>

NEW QUESTION 43

- (Exam Topic 1)

A Sysops administrator has created an Amazon EC2 instance using an AWS CloudFormation template in the us-east-1 Region. The administrator finds that this template has failed to create an EC2 instance in the us-west-2 Region. What is one cause for this failure?

- A. Resource tags defined in the CloudFormation template are specific to the us-east-1 Region.
- B. The Amazon Machine Image (AMI) ID referenced in the CloudFormation template could not be found in the us-west-2 Region.
- C. The cfn-init script did not run during resource provisioning in the us-west-2 Region.
- D. The IAM user was not created in the specified Region.

Answer: B

Explanation:

One possible cause for the failure of the CloudFormation template to create an EC2 instance in the us-west-2 Region is that the Amazon Machine Image (AMI) ID referenced in the template could not be found in the us-west-2 Region. This could be due to the fact that the AMI is not available in that region, or the credentials used to access the AMI were not configured properly. The other options (resource tags defined in the CloudFormation template are specific to the us-east-1 Region, the cfn-init script did not run during resource provisioning in the us-west-2 Region, and the IAM user was not created in the specified Region) are not valid causes for this failure.

NEW QUESTION 46

- (Exam Topic 1)

A SysOps administrator needs to delete an AWS CloudFormation stack that is no longer in use. The CloudFormation stack is in the DELETE_FAILED state. The SysOps administrator has validated the permissions that are required to delete the Cloud Formation stack.

- A. The configured timeout to delete the stack was too low for the delete operation to complete.
- B. The stack contains nested stacks that must be manually deleted fast.
- C. The stack was deployed with the -disable rollback option.
- D. There are additional resources associated with a security group in the stack
- E. There are Amazon S3 buckets that still contain objects in the stack.

Answer: DE

NEW QUESTION 48

- (Exam Topic 1)

A company has an application that customers use to search for records on a website. The application's data is stored in an Amazon Aurora DB cluster. The application's usage varies by season and by day of the week.

The website's popularity is increasing, and the website is experiencing slower performance because of increased load on the DB cluster during periods of peak activity. The application logs show that the performance issues occur when users are searching for information. The same search is rarely performed multiple times.

A SysOps administrator must improve the performance of the platform by using a solution that maximizes resource efficiency.

Which solution will meet these requirements?

- A. Deploy an Amazon ElastiCache for Redis cluster in front of the DB cluster
- B. Modify the application to check the cache before the application issues new queries to the database
- C. Add the results of any queries to the cache.
- D. Deploy an Aurora Replica for the DB cluster
- E. Modify the application to use the reader endpoint for search operation
- F. Use Aurora Auto Scaling to scale the number of replicas based on load
- G. Most Voted
- H. Use Provisioned IOPS on the storage volumes that support the DB cluster to improve performance sufficiently to support the peak load on the application.
- I. Increase the instance size in the DB cluster to a size that is sufficient to support the peak load on the application
- J. Use Aurora Auto Scaling to scale the instance size based on load.

Answer: B

Explanation:

https://docs.amazonaws.cn/en_us/AmazonRDS/latest/AuroraUserGuide/aurora-replicas-adding.html

NEW QUESTION 49

- (Exam Topic 1)

A company uploaded its website files to an Amazon S3 bucket that has S3 Versioning enabled. The company uses an Amazon CloudFront distribution with the S3 bucket as the origin. The company recently modified the files, but the object names remained the same. Users report that old content is still appearing on the website.

How should a SysOps administrator remediate this issue?

- A. Create a CloudFront invalidation, and add the path of the updated files.
- B. Create a CloudFront signed URL to update each object immediately.
- C. Configure an S3 origin access identity (OAI) to display only the updated files to users.
- D. Disable S3 Versioning on the S3 bucket so that the updated files can replace the old files.

Answer: A

NEW QUESTION 50

- (Exam Topic 1)

A SysOps administrator must configure a resilient tier of Amazon EC2 instances for a high performance computing (HPC) application. The HPC application requires minimum latency between nodes

Which actions should the SysOps administrator take to meet these requirements? (Select TWO.)

- A. Create an Amazon Elastic File System (Amazon EFS) file system. Mount the file system to the EC2 instances by using user data.
- B. Create a Multi-AZ Network Load Balancer in front of the EC2 instances.
- C. Place the EC2 instances in an Auto Scaling group within a single subnet.
- D. Launch the EC2 instances into a cluster placement group.
- E. Launch the EC2 instances into a partition placement group.

Answer: AD

NEW QUESTION 51

- (Exam Topic 1)

A SysOps administrator is building a process for sharing Amazon RDS database snapshots between different accounts associated with different business units within the same company. All data must be encrypted at rest.

How should the administrator implement this process?

- A. Write a script to download the encrypted snapshot, decrypt it using the AWS KMS encryption key used to encrypt the snapshot, then create a new volume in each account.
- B. Update the key policy to grant permission to the AWS KMS encryption key used to encrypt the snapshot with all relevant accounts, then share the snapshot with those accounts.
- C. Create an Amazon EC2 instance based on the snapshot, then save the instance's Amazon EBS volume as a snapshot and share it with the other account.
- D. Require each account owner to create a new volume from that snapshot and encrypt it.
- E. Create a new unencrypted RDS instance from the encrypted snapshot, connect to the instance using SSH/RDP.

F. export the database contents into a file, then share this file with the other accounts.

Answer: B

NEW QUESTION 56

- (Exam Topic 1)

A company uses Amazon Route 53 to manage the public DNS records for the domain example.com. The company deploys an Amazon CloudFront distribution to deliver static assets for a new corporate website. The company wants to create a subdomain that is named "static" and must route traffic for the subdomain to the CloudFront distribution.

How should a SysOps administrator create a new record for the subdomain in Route 53?

- A. Create a CNAME recor
- B. Enter static.cloudfront.net as the record nam
- C. Enter the CloudFront distribution's public IP address as the value.
- D. Create a CNAME recor
- E. Enter static.example.com as the record nam
- F. Enter the CloudFront distribution's private IP address as the value.
- G. Create an A recor
- H. Enter static.cloudfront.net as the record nam
- I. Enter the CloudFront distribution's ID as an alias target.
- J. Create an A recor
- K. Enter static.example.com as the record nam
- L. Enter the CloudFront distribution's domain name as an alias target.

Answer: D

Explanation:

<https://docs.aws.amazon.com/Route53/latest/DeveloperGuide/routing-to-cloudfront-distribution.html>

NEW QUESTION 60

- (Exam Topic 1)

A SysOps administrator is designing a solution for an Amazon RDS for PostgreSQL DB instance. Database credentials must be stored and rotated monthly. The applications that connect to the DB instance send

write-intensive traffic with variable client connections that sometimes increase significantly in a short period of time.

Which solution should a SysOps administrator choose to meet these requirements?

- A. Configure AWS Key Management Service (AWS KMS) to automatically rotate the keys for the DB instanc
- B. Use RDS Proxy to handle the increases in database connections.
- C. Configure AWS Key Management Service (AWS KMS) to automatically rotate the keys for the DB instanc
- D. Use RDS read replicas to handle the increases in database connections.
- E. Configure AWS Secrets Manager to automatically rotate the credentials for the DB instanc
- F. Use RDS Proxy to handle the increases in database connections.
- G. Configure AWS Secrets Manager to automatically rotate the credentials for the DB instanc
- H. Use RDS read replicas to handle the increases in database connections.

Answer: A

NEW QUESTION 62

- (Exam Topic 1)

A company wants to archive sensitive data on Amazon S3 Glacier. The company's regulatory and compliance requirements do not allow any modifications to the data by any account.

Which solution meets these requirements?

- A. Attach a vault lock policy to an S3 Glacier vault that contains the archived dat
- B. Use the lock ID to validate the vault lock policy after 24 hours.
- C. Attach a vault lock policy to an S3 Glacier vault that contains the archived dat
- D. Use the lock ID to validate the vault lock policy within 24 hours.
- E. Configure S3 Object Lock in governance mod
- F. Upload all files after 24 hours.
- G. Configure S3 Object Lock in governance mod
- H. Upload all files within 24 hours.

Answer: B

NEW QUESTION 63

- (Exam Topic 1)

A company's backend infrastructure contains an Amazon EC2 instance in a private subnet. The private subnet has a route to the internet through a NAT gateway in a public subnet. The instance must allow connectivity to a secure web server on the internet to retrieve data at regular intervals.

The client software times out with an error message that indicates that the client software could not establish the TCP connection.

What should a SysOps administrator do to resolve this error?

- A. Add an inbound rule to the security group for the EC2 instance with the following parameters: Type - HTTP, Source - 0.0.0.0/0.
- B. Add an inbound rule to the security group for the EC2 instance with the following parameters: Type - HTTPS, Source - 0.0.0.0/0.
- C. Add an outbound rule to the security group for the EC2 instance with the following parameters: Type - HTTP, Destination - 0.0.0.0/0.
- D. Add an outbound rule to the security group for the EC2 instance with the following parameters: Type - HTTP
- E. Destination - 0.0.0.0/0.

Answer: D

NEW QUESTION 65

- (Exam Topic 1)

A company's SysOps administrator needs to change the AWS Support plan for one of the company's AWS accounts. The account has multi-factor authentication (MFA) activated, and the MFA device is lost.

What should the SysOps administrator do to sign in?

- A. Sign in as a root user by using email and phone verification
- B. Set up a new MFA device
- C. Change the root user password.
- D. Sign in as an IAM user with administrator permission
- E. Resynchronize the MFA token by using the IAM console.
- F. Sign in as an IAM user with administrator permission
- G. Reset the MFA device for the root user by adding a new device.
- H. Use the forgot-password process to verify the email address
- I. Set up a new password and MFA device.

Answer: A

NEW QUESTION 69

- (Exam Topic 1)

A company runs hundreds of Amazon EC2 instances in a single AWS Region. Each EC2 instance has two attached 1 GiB General Purpose SSD (gp2) Amazon Elastic Block Store (Amazon EBS) volumes. A critical workload is using all the available IOPS capacity on the EBS volumes.

According to company policy, the company cannot change instance types or EBS volume types without completing lengthy acceptance tests to validate that the company's applications will function properly. A SysOps administrator needs to increase the I/O performance of the EBS volumes as quickly as possible.

Which action should the SysOps administrator take to meet these requirements?

- A. Increase the size of the 1 GiB EBS volumes.
- B. Add two additional elastic network interfaces on each EC2 instance.
- C. Turn on Transfer Acceleration on the EBS volumes in the Region.
- D. Add all the EC2 instances to a cluster placement group.

Answer: A

Explanation:

Increasing the size of the 1 GiB EBS volumes will increase the IOPS capacity of the volumes, which will improve the I/O performance of the EBS volumes. This option does not require any changes to the instance types or EBS volume types, so it can be done quickly without the need for lengthy acceptance tests to validate that the company's applications will function properly.

<https://docs.aws.amazon.com/AWSEC2/latest/UserGuide/requesting-ebs-volume-modifications.html>

NEW QUESTION 70

- (Exam Topic 1)

A company uses AWS CloudFormation templates to deploy cloud infrastructure. An analysis of all the company's templates shows that the company has declared the same components in multiple templates. A SysOps administrator needs to create dedicated templates that have their own parameters and conditions for these common components.

Which solution will meet this requirement?

- A. Develop a CloudFormation change set.
- B. Develop CloudFormation macros.
- C. Develop CloudFormation nested stacks.
- D. Develop CloudFormation stack sets.

Answer: C

NEW QUESTION 71

- (Exam Topic 1)

A global company handles a large amount of personally identifiable information (PII) through an internal web portal. The company's application runs in a corporate data center that is connected to AWS through an AWS Direct Connect connection. The application stores the PII in Amazon S3. According to a compliance requirement, traffic from the web portal to Amazon S3 must not travel across the internet.

What should a SysOps administrator do to meet the compliance requirement?

- A. Provision an interface VPC endpoint for Amazon S3. Modify the application to use the interface endpoint.
- B. Configure AWS Network Firewall to redirect traffic to the internal S3 address.
- C. Modify the application to use the S3 path-style endpoint.
- D. Set up a range of VPC network ACLs to redirect traffic to the internal S3 address.

Answer: B

NEW QUESTION 75

- (Exam Topic 1)

Application A runs on Amazon EC2 instances behind a Network Load Balancer (NLB). The EC2 instances are in an Auto Scaling group and are in the same subnet that is associated with the NLB. Other applications from an on-premises environment cannot communicate with Application A on port 8080.

To troubleshoot the issue, a SysOps administrator analyzes the flow logs. The flow logs include the following records:

```
2 123456789010 eni-1235b8ca123456789 192.168.0.13 172.31.16.139 59003 8080 1 4 336 1432917027 1432917142 ACCEPT OK
2 123456789010 eni-1235b8ca123456789 172.31.16.139 192.168.0.13 8080 59003 1 4 336 1432917094 1432917142 REJECT OK
```

What is the reason for the rejected traffic?

- A. The security group of the EC2 instances has no Allow rule for the traffic from the NLB.

- B. The security group of the NLB has no Allow rule for the traffic from the on-premises environment.
- C. The ACL of the on-premises environment does not allow traffic to the AWS environment.
- D. The network ACL that is associated with the subnet does not allow outbound traffic for the ephemeral port range.

Answer: A

NEW QUESTION 80

- (Exam Topic 1)

A company is storing backups in an Amazon S3 bucket. The backups must not be deleted for at least 3 months after the backups are created. What should a SysOps administrator do to meet this requirement?

- A. Configure an IAM policy that denies the s3:DeleteObject action for all user
- B. Three months after an object is written, remove the policy.
- C. Enable S3 Object Lock on a new S3 bucket in compliance mod
- D. Place all backups in the new S3 bucket with a retention period of 3 months.
- E. Enable S3 Versioning on the existing S3 bucke
- F. Configure S3 Lifecycle rules to protect the backups.
- G. Enable S3 Object Lock on a new S3 bucket in governance mod
- H. Place all backups in the new S3 bucket with a retention period of 3 months.

Answer: D

Explanation:

To meet the requirements of the workload, a SysOps administrator should enable S3 Object Lock on a new S3 bucket in governance mode and place all backups in the new S3 bucket with a retention period of 3 months.

This will ensure that the backups are not deleted for at least 3 months after they are created. The other solutions (configuring an IAM policy that denies the s3:DeleteObject action for all users, enabling S3 Object Lock on a new S3 bucket in compliance mode, or enabling S3 Versioning on the existing S3 bucket and configuring S3 Lifecycle rules to protect the backups) will not meet the requirements, as they do not provide a way to ensure that the backups are not deleted for at least 3 months after they are created.

NEW QUESTION 81

- (Exam Topic 1)

A development team recently deployed a new version of a web application to production. After the release, penetration testing revealed a cross-site scripting vulnerability that could expose user data. Which AWS service will mitigate this issue?

- A. AWS Shield Standard
- B. AWS WAF
- C. Elastic Load Balancing
- D. Amazon Cognito

Answer: A

NEW QUESTION 82

- (Exam Topic 1)

An application accesses data through a file system interface. The application runs on Amazon EC2 instances in multiple Availability Zones, all of which must share the same data. While the amount of data is currently small, the company anticipates that it will grow to tens of terabytes over the lifetime of the application. What is the MOST scalable storage solution to fulfill this requirement?

- A. Connect a large Amazon EBS volume to multiple instances and schedule snapshots.
- B. Deploy Amazon EFS in the VPC and create mount targets in multiple subnets.
- C. Launch an EC2 instance and share data using SMB/CIFS or NFS.
- D. Deploy an AWS Storage Gateway cached volume on Amazon EC2.

Answer: B

NEW QUESTION 87

- (Exam Topic 1)

A new website will run on Amazon EC2 instances behind an Application Load Balancer. Amazon Route 53 will be used to manage DNS records. What type of record should be set in Route 53 to point the website's apex domain name (for example company.com) to the Application Load Balancer?

- A. CNAME
- B. SOA
- C. TXT
- D. ALIAS

Answer: D

NEW QUESTION 89

- (Exam Topic 1)

A SysOps administrator is trying to set up an Amazon Route 53 domain name to route traffic to a website hosted on Amazon S3. The domain name of the website is www.anycompany.com and the S3 bucket name is anycompany-static. After the record set is set up in Route 53, the domain name www.anycompany.com does not seem to work, and the static website is not displayed in the browser. Which of the following is a cause of this?

- A. The S3 bucket must be configured with Amazon CloudFront first.
- B. The Route 53 record set must have an IAM role that allows access to the S3 bucket.
- C. The Route 53 record set must be in the same region as the S3 bucket.

D. The S3 bucket name must match the record set name in Route 53.

Answer: D

NEW QUESTION 92

- (Exam Topic 1)

A SysOps administrator has launched a large general purpose Amazon EC2 instance to regularly process large data files. The instance has an attached 1 TB General Purpose SSD (gp2) Amazon Elastic Block Store (Amazon EBS) volume. The instance also is EBS-optimized. To save costs, the SysOps administrator stops the instance each evening and restarts the instance each morning.

When data processing is active, Amazon CloudWatch metrics on the instance show a consistent 3.000 VolumeReadOps. The SysOps administrator must improve the I/O performance while ensuring data integrity.

Which action will meet these requirements?

- A. Change the instance type to a large, burstable, general purpose instance.
- B. Change the instance type to an extra large general purpose instance.
- C. Increase the EBS volume to a 2 TB General Purpose SSD (gp2) volume.
- D. Move the data that resides on the EBS volume to the instance store.

Answer: C

NEW QUESTION 96

- (Exam Topic 1)

A Sysops administrator needs to configure automatic rotation for Amazon RDS database credentials. The credentials must rotate every 30 days. The solution must integrate with Amazon RDS.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Store the credentials in AWS Systems Manager Parameter Store as a secure string
- B. Configure automatic rotation with a rotation interval of 30 days.
- C. Store the credentials in AWS Secrets Manager
- D. Configure automatic rotation with a rotation interval of 30 days.
- E. Store the credentials in a file in an Amazon S3 bucket
- F. Deploy an AWS Lambda function to automatically rotate the credentials every 30 days.
- G. Store the credentials in AWS Secrets Manager
- H. Deploy an AWS Lambda function to automatically rotate the credentials every 30 days.

Answer: B

Explanation:

Storing the credentials in AWS Secrets Manager and configuring automatic rotation with a rotation interval of 30 days is the most efficient way to meet the requirements with the least operational overhead. AWS Secrets Manager automatically rotates the credentials at the specified interval, so there is no need for an additional AWS Lambda function or manual rotation. Additionally, Secrets Manager is integrated with Amazon RDS, so the credentials can be easily used with the RDS database.

NEW QUESTION 98

- (Exam Topic 1)

A company has an Amazon CloudFront distribution that uses an Amazon S3 bucket as its origin. During a review of the access logs, the company determines that some requests are going directly to the S3 bucket by using the website hosting endpoint. A SysOps administrator must secure the S3 bucket to allow requests only from CloudFront.

What should the SysOps administrator do to meet this requirement?

- A. Create an origin access identity (OAI) in CloudFront
- B. Associate the OAI with the distribution
- C. Remove access to and from other principals in the S3 bucket policy
- D. Update the S3 bucket policy to allow access only from the OAI.
- E. Create an origin access identity (OAI) in CloudFront
- F. Associate the OAI with the distribution
- G. Update the S3 bucket policy to allow access only from the OAI
- H. Create a new origin, and specify the S3 bucket as the new origin
- I. Update the distribution behavior to use the new origin
- J. Remove the existing origin.
- K. Create an origin access identity (OAI) in CloudFront
- L. Associate the OAI with the distribution
- M. Update the S3 bucket policy to allow access only from the OAI
- N. Disable website hosting
- O. Create a new origin, and specify the S3 bucket as the new origin
- P. Update the distribution behavior to use the new origin
- Q. Remove the existing origin.
- R. Update the S3 bucket policy to allow access only from the CloudFront distribution
- S. Remove access to and from other principals in the S3 bucket policy
- T. Disable website hosting
- . Create a new origin, and specify the S3 bucket as the new origin
- . Update the distribution behavior to use the new origin
- . Remove the existing origin.

Answer: A

NEW QUESTION 100

- (Exam Topic 1)

A company uses an Amazon CloudFront distribution to deliver its website. Traffic logs for the website must be centrally stored and all data must be encrypted at

rest

Which solution will meet these requirements?

- A. Create an Amazon OpenSearch Service (Amazon ElastiSearch Service) domain with internet access and server-side encryption that uses the default AWS managed key Configure CloudFront to use the Amazon OpenSearch Service (Amazon Elasticsearch Service) domain as a log destination
- B. Create an Amazon OpenSearch Service (Amazon Elasticsearch Service) domain with VPC access and server-side encryption that uses AES-256 Configure CloudFront to use the Amazon OpenSearch Service (Amazon ElastiSearch Service) domain as a log destination
- C. Create an Amazon S3 bucket that is configured with default server side encryption that uses AES-256 Configure CloudFront to use the S3 bucket as a log destination
- D. Create an Amazon S3 bucket that is configured with no default encryption Enable encryption in the CloudFront distribution and use the S3 bucket as a log destination

Answer: C

NEW QUESTION 105

- (Exam Topic 1)

A company uses Amazon Elasticsearch Service (Amazon ES) to analyze sales and customer usage data. Members of the company's geographically dispersed sales team are traveling. They need to log in to Kibana by using their existing corporate credentials that are stored in Active Directory. The company has deployed Active Directory Federation Services (AD FS) to enable authentication to cloud services. Which solution will meet these requirements?

- A. Configure Active Directory as an authentication provider in Amazon E
- B. Add the Active Directory server's domain name to Amazon E
- C. Configure Kibana to use Amazon ES authentication.
- D. Deploy an Amazon Cognito user pool
- E. Configure Active Directory as an external identity provider for the user pool
- F. Enable Amazon Cognito authentication for Kibana on Amazon ES.
- G. Enable Active Directory user authentication in Kibana
- H. Create an IP-based custom domain access policy in Amazon ES that includes the Active Directory server's IP address.
- I. Establish a trust relationship with Kibana on the Active Directory server
- J. Enable Active Directory user authentication in Kibana
- K. Add the Active Directory server's IP address to Kibana.

Answer: B

Explanation:

<https://aws.amazon.com/blogs/security/how-to-enable-secure-access-to-kibana-using-aws-single-sign-on/> <https://docs.aws.amazon.com/elasticsearch-service/latest/developerguide/es-cognito-auth.html>

NEW QUESTION 108

- (Exam Topic 1)

A company is expanding globally and needs to back up data on Amazon Elastic Block Store (Amazon EBS) volumes to a different AWS Region. Most of the EBS volumes that store the data are encrypted, but some of the EBS volumes are unencrypted. The company needs the backup data from all the EBS volumes to be encrypted.

Which solution will meet these requirements with the LEAST management overhead?

- A. Configure a lifecycle policy in Amazon Data Lifecycle Manager (Amazon DLM) to create the EBS volume snapshots with cross-Region backups enabled
- B. Encrypt the snapshot copies by using AWS Key Management Service (AWS KMS).
- C. Create a point-in-time snapshot of the EBS volume
- D. When the snapshot status is COMPLETED, copy the snapshots to another Region and set the Encrypted parameter to False.
- E. Create a point-in-time snapshot of the EBS volume
- F. Copy the snapshots to an Amazon S3 bucket that uses server-side encryption
- G. Turn on S3 Cross-Region Replication on the S3 bucket.
- H. Schedule an AWS Lambda function with the Python runtime
- I. Configure the Lambda function to create the EBS volume snapshots, encrypt the unencrypted snapshots, and copy the snapshots to another Region.

Answer: A

Explanation:

Encrypt the snapshot copies by using AWS Key Management Service (AWS KMS). This solution will allow the company to automatically create encrypted snapshots of the EBS volumes and copy them to different AWS Regions with minimal effort.

NEW QUESTION 113

- (Exam Topic 1)

A company must migrate its applications to AWS. The company is using Chef recipes for configuration management. The company wants to continue to use the existing Chef recipes after the applications are migrated to AWS.

What is the MOST operationally efficient solution that meets these requirements?

- A. Use AWS CloudFormation to create an Amazon EC2 instance, install a Chef server, and add Chef recipes.
- B. Use AWS CloudFormation to create a stack and add layers for Chef recipes.
- C. Use AWS Elastic Beanstalk with the Docker platform to upload Chef recipes.
- D. Use AWS OpsWorks to create a stack and add layers with Chef recipes.

Answer: D

NEW QUESTION 114

- (Exam Topic 1)

A company needs to automatically monitor an AWS account for potential unauthorized AWS Management Console logins from multiple geographic locations.

Which solution will meet this requirement?

- A. Configure Amazon Cognito to detect any compromised IAM credentials.
- B. Set up Amazon Inspector
- C. Scan and monitor resources for unauthorized logins.
- D. Set up AWS Config
- E. Add the iam-policy-blacklisted-check managed rule to the account.
- F. Configure Amazon GuardDuty to monitor the UnauthorizedAccess:IAMUser/ConsoleLoginSuccess finding.

Answer: D

NEW QUESTION 115

- (Exam Topic 1)

A company is planning to host its stateful web-based applications on AWS. A SysOps administrator is using an Auto Scaling group of Amazon EC2 instances. The web applications will run 24 hours a day, 7 days a week throughout the year. The company must be able to change the instance type within the same instance family later in the year based on the traffic and usage patterns.

Which EC2 instance purchasing option will meet these requirements MOST cost-effectively?

- A. Convertible Reserved Instances
- B. On-Demand instances
- C. Spot instances
- D. Standard Reserved instances

Answer: A

Explanation:

<https://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ri-convertible-exchange.html>

NEW QUESTION 120

- (Exam Topic 1)

A company needs to ensure strict adherence to a budget for 25 applications deployed on AWS. Separate teams are responsible for storage, compute, and database costs. A SysOps administrator must implement an automated solution to alert each team when their projected spend will exceed a quarterly amount that has been set by the finance department. The solution cannot add additional compute, storage, or database costs.

- A. Configure AWS Cost and Usage Reports to send a daily report to an Amazon S3 bucket.
- B. Create an AWS Lambda function that will evaluate spend by service and notify each team by using Amazon Simple Notification Service (Amazon SNS) notification.
- C. Invoke the Lambda function when a report is placed in the S3 bucket.
- D. Configure AWS Cost and Usage Reports to send a daily report to an Amazon S3 bucket.
- E. Create a rule in Amazon EventBridge (Amazon CloudWatch Events) to evaluate the spend by service and notify each team by using Amazon Simple Queue Service (Amazon SQS) when the cost threshold is exceeded.
- F. Use AWS Budgets to create one cost budget and select each of the services in use. Specify the budget amount defined by the finance department along with the forecasted cost threshold. Enter the appropriate email recipients for the budget.
- G. Use AWS Budgets to create a cost budget for each team, filtering by the services they own.
- H. Specify the budget amount defined by the finance department along with a forecasted cost threshold. Enter the appropriate email recipients for each budget.

Answer: D

NEW QUESTION 122

- (Exam Topic 1)

A data storage company provides a service that gives users the ability to upload and download files as needed. The files are stored in Amazon S3 Standard and must be immediately retrievable for 1 year. Users access files frequently during the first 30 days after the files are stored. Users rarely access files after 30 days. The company's SysOps administrator must use S3 Lifecycle policies to implement a solution that maintains object availability and minimizes cost.

Which solution will meet these requirements?

- A. Move objects to S3 Glacier after 30 days.
- B. Move objects to S3 One Zone-Infrequent Access (S3 One Zone-IA) after 30 days.
- C. Move objects to S3 Standard-Infrequent Access (S3 Standard-IA) after 30 days.
- D. Move objects to S3 Standard-Infrequent Access (S3 Standard-IA) immediately.

Answer: C

Explanation:

<https://aws.amazon.com/s3/storage-classes/>

NEW QUESTION 125

- (Exam Topic 1)

A SysOps Administrator is managing a web application that runs on Amazon EC2 instances behind an Application Load Balancer (ALB). The instances run in an EC2 Auto Scaling group. The administrator wants to set an alarm for when all target instances associated with the ALB are unhealthy.

Which condition should be used with the alarm?

- A. AWS/ApplicationELB HealthyHostCount <= 0
- B. AWS/ApplicationELB UnhealthyHostCount >= 1
- C. AWS/EC2 StatusCheckFailed <= 0
- D. AWS/EC2 StatusCheckFailed >= 1

Answer: A

Explanation:

<https://docs.aws.amazon.com/elasticloadbalancing/latest/application/load-balancer-cloudwatch-metrics.html>

NEW QUESTION 126

- (Exam Topic 1)

A company has attached the following policy to an IAM user:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "rds:Describe*",
      "Resource": "*"
    },
    {
      "Effect": "Allow",
      "Action": "ec2:*",
      "Resource": "*",
      "Condition": {
        "StringEquals": {
          "ec2:Region": "us-east-1"
        }
      }
    },
    {
      "Effect": "Deny",
      "NotAction": [
        "ec2:*",
        "s3:GetObject"
      ],
      "Resource": "*"
    }
  ]
}
```

Which of the following actions are allowed for the IAM user?

- A. Amazon RDS DescribeDBInstances action in the us-east-1 Region
- B. Amazon S3 Putobject operation in a bucket named testbucket
- C. Amazon EC2 Describe Instances action in the us-east-1 Region
- D. Amazon EC2 AttachNetworkinterface action in the eu-west-1 Region

Answer: C

NEW QUESTION 130

- (Exam Topic 1)

A SysOps administrator is required to monitor free space on Amazon EBS volumes attached to Microsoft Windows-based Amazon EC2 instances within a company's account. The administrator must be alerted to potential issues.

What should the administrator do to receive email alerts before low storage space affects EC2 instance performance?

- A. Use built-in Amazon CloudWatch metrics, and configure CloudWatch alarms and an Amazon SNS topic for email notifications
- B. Use AWS CloudTrail logs and configure the trail to send notifications to an Amazon SNS topic.
- C. Use the Amazon CloudWatch agent to send disk space metrics, then set up CloudWatch alarms using an Amazon SNS topic.
- D. Use AWS Trusted Advisor and enable email notification alerts for EC2 disk space

Answer: C

NEW QUESTION 135

- (Exam Topic 1)

A SysOps administrator is using AWS Systems Manager Patch Manager to patch a fleet of Amazon EC2 instances. The SysOps administrator has configured a patch baseline and a maintenance window. The SysOps administrator also has used an instance tag to identify which instances to patch. The SysOps administrator must give Systems Manager the ability to access the EC2 instances. Which additional action must the SysOps administrator perform to meet this requirement?

- A. Add an inbound rule to the instances' security group.
- B. Attach an IAM instance profile with access to Systems Manager to the instances.
- C. Create a Systems Manager activation Then activate the fleet of instances.
- D. Manually specify the instances to patch Instead of using tag-based selection.

Answer: A

NEW QUESTION 136

- (Exam Topic 1)

A SysOps administrator is responsible for a company's security groups. The company wants to maintain a documented trail of any changes that are made to the security groups. The SysOps administrator must receive notification whenever the security groups change. Which solution will meet these requirements?

- A. Set up Amazon Detective to record security group change
- B. Specify an Amazon CloudWatch Logs log group to store configuration history log
- C. Create an Amazon Simple Queue Service (Amazon SQS) queue for notifications about configuration change
- D. Subscribe the SysOps administrator's email address to the SQS queue.
- E. Set up AWS Systems Manager Change Manager to record security group change
- F. Specify an Amazon CloudWatch Logs log group to store configuration history log
- G. Create an Amazon Simple Notification Service (Amazon SNS) topic for notifications about configuration change
- H. Subscribe the SysOps administrator's email address to the SNS topic.
- I. Set up AWS Config to record security group change
- J. Specify an Amazon S3 bucket as the location for configuration snapshots and history file
- K. Create an Amazon Simple Notification Service (Amazon SNS) topic for notifications about configuration change
- L. Subscribe the SysOps administrator's email address to the SNS topic.
- M. Set up Amazon Detective to record security group change
- N. Specify an Amazon S3 bucket as the location for configuration snapshots and history file
- O. Create an Amazon Simple Notification Service (Amazon SNS) topic for notifications about configuration change
- P. Subscribe the SysOps administrator's email address to the SNS topic.

Answer: D

NEW QUESTION 139

- (Exam Topic 1)

A manufacturing company uses an Amazon RDS DB instance to store inventory of all stock items. The company maintains several AWS Lambda functions that interact with the database to add, update, and delete items. The Lambda functions use hardcoded credentials to connect to the database.

A SysOps administrator must ensure that the database credentials are never stored in plaintext and that the password is rotated every 30 days.

Which solution will meet these requirements in the MOST operationally efficient manner?

- A. Store the database password as an environment variable for each Lambda function
- B. Create a new Lambda function that is named PasswordRotat
- C. Use Amazon EventBridge (Amazon CloudWatch Events) to schedule the PasswordRotate function every 30 days to change the database password and update the environment variable for each Lambda function.
- D. Use AWS Key Management Service (AWS KMS) to encrypt the database password and to store the encrypted password as an environment variable for each Lambda function
- E. Grant each Lambda function access to the KMS key so that the database password can be decrypted when require
- F. Create a new Lambda function that is named PasswordRotate to change the password every 30 days.
- G. Use AWS Secrets Manager to store credentials for the databases
- H. Create a Secrets Manager secret, and select the database so that Secrets Manager will use a Lambda function to update the database password automatically
- I. Specify an automatic rotation schedule of 30 day
- J. Update each Lambda function to access the database password from SecretsManager.
- K. Use AWS Systems Manager Parameter Store to create a secure string to store credentials for the databases
- L. Create a new Lambda function called PasswordRotat
- M. Use Amazon EventBridge (Amazon CloudWatch Events) to schedule the PasswordRotate function every 30 days to change the database password and to update the secret within Parameter Store
- N. Update each Lambda function to access the database password from Parameter Store.

Answer: C

Explanation:

When you choose to enable rotation, Secrets Manager supports the following Amazon Relational Database Service (Amazon RDS) databases with AWS written and tested Lambda rotation function templates, and full configuration of the rotation process:

Amazon Aurora on Amazon RDS MySQL on Amazon RDS PostgreSQL on Amazon RDS Oracle on Amazon RDS MariaDB on Amazon RDS

Microsoft SQL Server on Amazon RDS <https://docs.aws.amazon.com/secretsmanager/latest/userguide/intro.html>

NEW QUESTION 142

- (Exam Topic 1)

A company's SysOps administrator deploys a public Network Load Balancer (NLB) in front of the company's web application. The web application does not use any Elastic IP addresses. Users must access the web application by using the company's domain name. The SysOps administrator needs to configure Amazon Route 53 to route traffic to the NLB.

Which solution will meet these requirements MOST cost-effectively?

- A. Create a Route 53 AAAA record for the NLB.

- B. Create a Route 53 alias record for the NLB.
- C. Create a Route 53 CAA record for the NLB.
- D. Create a Route 53 CNAME record for the NLB.

Answer: B

NEW QUESTION 143

- (Exam Topic 1)

A company has an initiative to reduce costs associated with Amazon EC2 and AWS Lambda. Which action should a SysOps administrator take to meet these requirements?

- A. Analyze the AWS Cost and Usage Report by using Amazon Athena to identify cost savings.
- B. Create an AWS Budgets alert to alarm when account spend reaches 80% of the budget.
- C. Purchase Reserved Instances through the Amazon EC2 console.
- D. Use AWS Compute Optimizer and take action on the provided recommendations.

Answer: D

NEW QUESTION 147

- (Exam Topic 1)

A new application runs on Amazon EC2 instances and accesses data in an Amazon RDS database instance. When fully deployed in production, the application fails. The database can be queried from a console on a bastion host. When looking at the web server logs, the following error is repeated multiple times:

*** Error Establishing a Database Connection

Which of the following may be causes of the connectivity problems? (Select TWO.)

- A. The security group for the database does not have the appropriate egress rule from the database to the web server.
- B. The certificate used by the web server is not trusted by the RDS instance.
- C. The security group for the database does not have the appropriate ingress rule from the web server to the database.
- D. The port used by the application developer does not match the port specified in the RDS configuration.
- E. The database is still being created and is not available for connectivity.

Answer: CD

NEW QUESTION 148

- (Exam Topic 1)

A software development company has multiple developers who work on the same product. Each developer must have their own development environment, and these development environments must be identical. Each development environment consists of Amazon EC2 instances and an Amazon RDS DB instance. The development environments should be created only when necessary, and they must be terminated each night to minimize costs.

What is the MOST operationally efficient solution that meets these requirements?

- A. Provide developers with access to the same AWS CloudFormation template so that they can provision their development environment when necessary.
- B. Schedule a nightly cron job on each development instance to stop all running processes to reduce CPU utilization to nearly zero.
- C. Provide developers with access to the same AWS CloudFormation template so that they can provision their development environment when necessary.
- D. Schedule a nightly Amazon EventBridge (Amazon CloudWatch Events) rule to invoke an AWS Lambda function to delete the AWS CloudFormation stacks.
- E. Provide developers with CLI commands so that they can provision their own development environment when necessary.
- F. Schedule a nightly Amazon EventBridge (Amazon CloudWatch Events) rule to invoke an AWS Lambda function to terminate all EC2 instances and the DB instance.
- G. Provide developers with CLI commands so that they can provision their own development environment when necessary.
- H. Schedule a nightly Amazon EventBridge (Amazon CloudWatch Events) rule to cause AWS CloudFormation to delete all of the development environment resources.

Answer: B

NEW QUESTION 151

- (Exam Topic 1)

A company runs an application on an Amazon EC2 instance. A SysOps administrator creates an Auto Scaling group and an Application Load Balancer (ALB) to handle an increase in demand. However, the EC2 instances are failing the health check.

What should the SysOps administrator do to troubleshoot this issue?

- A. Verify that the Auto Scaling group is configured to use all AWS Regions.
- B. Verify that the application is running on the protocol and the port that the listener is expecting.
- C. Verify the listener priority in the ALB. Change the priority if necessary.
- D. Verify the maximum number of instances in the Auto Scaling group. Change the number if necessary.

Answer: B

NEW QUESTION 153

- (Exam Topic 1)

A company has a VPC with public and private subnets. An Amazon EC2-based application resides in the private subnets and needs to process raw .csv files stored in an Amazon S3 bucket. A SysOps administrator has set up the correct IAM role with the required permissions for the application to access the S3 bucket, but the application is unable to communicate with the S3 bucket.

Which action will solve this problem while adhering to least privilege access?

- A. Add a bucket policy to the S3 bucket permitting access from the IAM role.
- B. Attach an S3 gateway endpoint to the VPC.
- C. Configure the route table for the private subnet.
- D. Configure the route table to allow the instances on the private subnet access through the internet gateway.
- E. Create a NAT gateway in a private subnet and configure the route table for the private subnets.

Answer: B

Explanation:

Technology to use is a VPC endpoint - "A VPC endpoint enables private connections between your VPC and supported AWS services and VPC endpoint services powered by AWS PrivateLink. AWS PrivateLink is a technology that enables you to privately access services by using private IP addresses. Traffic between your VPC and the other service does not leave the Amazon network." S3 is an example of a gateway endpoint. We want to see services in AWS while not leaving the VPC.

NEW QUESTION 158

- (Exam Topic 1)

A company uses AWS Organizations. A SysOps administrator wants to use AWS Compute Optimizer and AWS tag policies in the management account to govern all member accounts in the billing family. The SysOps administrator navigates to the AWS Organizations console but cannot activate tag policies through the management account.

What could be the reason for this issue?

- A. All features have not been enabled in the organization.
- B. Consolidated billing has not been enabled.
- C. The member accounts do not have tags enabled for cost allocation.
- D. The member accounts have not manually enabled trusted access for Compute Optimizer.

Answer: C

NEW QUESTION 161

- (Exam Topic 1)

A company has an internal web application that runs on Amazon EC2 instances behind an Application Load Balancer. The instances run in an Amazon EC2 Auto Scaling group in a single Availability Zone. A SysOps administrator must make the application highly available.

Which action should the SysOps administrator take to meet this requirement?

- A. Increase the maximum number of instances in the Auto Scaling group to meet the capacity that is required at peak usage.
- B. Increase the minimum number of instances in the Auto Scaling group to meet the capacity that is required at peak usage.
- C. Update the Auto Scaling group to launch new instances in a second Availability Zone in the same AWS Region.
- D. Update the Auto Scaling group to launch new instances in an Availability Zone in a second AWS Region.

Answer: C

Explanation:

"An Auto Scaling group can contain EC2 instances in one or more Availability Zones within the same Region. However, Auto Scaling groups cannot span multiple Regions". As stated in <https://docs.aws.amazon.com/autoscaling/ec2/userguide/auto-scaling-benefits.htm>

NEW QUESTION 163

- (Exam Topic 1)

A SysOps administrator configuring AWS Client VPN to connect users on a corporate network to AWS resources that are running in a VPC. According to compliance requirements, only traffic that is destined for the VPC can travel across the VPN tunnel.

How should the SysOps administrator configure Client VPN to meet these requirements?

- A. Associate the Client VPN endpoint with a private subnet that has an internet route through a NAT gateway.
- B. On the Client VPN endpoint, turn on the split-tunnel option.
- C. On the Client VPN endpoint, specify DNS server IP addresses.
- D. Select a private certificate to use as the identity certificate for the VPN client.

Answer: C

NEW QUESTION 168

- (Exam Topic 1)

A company has an Auto Scaling group of Amazon EC2 instances that scale based on average CPU utilization. The Auto Scaling group events log indicates an `InsufficientInstanceCapacity` error.

Which actions should a SysOps administrator take to remediate this issue? (Select TWO.)

- A. Change the instance type that the company is using.
- B. Configure the Auto Scaling group in different Availability Zones.
- C. Configure the Auto Scaling group to use different Amazon Elastic Block Store (Amazon EBS) volume sizes.
- D. Increase the maximum size of the Auto Scaling group.
- E. Request an increase in the instance service quota.

Answer: AB

NEW QUESTION 173

- (Exam Topic 1)

A SysOps administrator creates an AWS CloudFormation template to define an application stack that can be deployed in multiple AWS Regions.

The SysOps administrator also creates an Amazon CloudWatch dashboard by using the AWS Management Console. Each deployment of the application requires its own CloudWatch dashboard.

How can the SysOps administrator automate the creation of the CloudWatch dashboard each time the application is deployed?

- A. Create a script by using the AWS CLI to run the `aws cloudformation put-dashboard` command with the name of the dashboard.
- B. Run the command each time a new CloudFormation stack is created.
- C. Export the existing CloudWatch dashboard as JSON.
- D. Update the CloudFormation template to define an `AWS::CloudWatch::Dashboard` resource.
- E. Include the exported JSON in the resource's `DashboardBody` property.

- F. Update the CloudFormation template to define an resource
- G. Use the intrinsic Ref function to reference the ID of the existing CloudWatch dashboard.
- H. Update the CloudFormation template to define an AWS::CloudWatch::Dashboard resource
- I. Specify the name of the existing dashboard in the DashboardName property.

Answer: B

Explanation:

You can only use the Intrinsic Ref function to reference a resource that is being created at the same time as the current CloudFormation template. The question states that the CloudWatch dashboard was previously created using the AWS Management Console, so there is no ID to reference the existing CloudWatch dashboard in the CloudFormation template. You would need to export the existing CloudWatch dashboard as JSON, then use the DashboardBody property in the CloudFormation template to replicate it upon each deployment
(<https://docs.aws.amazon.com/AmazonCloudWatch/latest/APIReference/CloudWatch-Dashboard-Body-Structu>)

NEW QUESTION 176

- (Exam Topic 1)

A company hosts a website on multiple Amazon EC2 instances that run in an Auto Scaling group. Users are reporting slow responses during peak times between 6 PM and 11 PM every weekend. A SysOps administrator must implement a solution to improve performance during these peak times. What is the MOST operationally efficient solution that meets these requirements?

- A. Create a scheduled Amazon EventBridge (Amazon CloudWatch Events) rule to invoke an AWS Lambda function to increase the desired capacity before peak times.
- B. Configure a scheduled scaling action with a recurrence option to change the desired capacity before and after peak times.
- C. Create a target tracking scaling policy to add more instances when memory utilization is above 70%.
- D. Configure the cooldown period for the Auto Scaling group to modify desired capacity before and after peak times.

Answer: B

Explanation:

"Scheduled scaling helps you to set up your own scaling schedule according to predictable load changes. For example, let's say that every week the traffic to your web application starts to increase on Wednesday, remains high on Thursday, and starts to decrease on Friday. You can configure a schedule for Amazon EC2 Auto Scaling to increase capacity on Wednesday and decrease capacity on Friday." https://docs.aws.amazon.com/autoscaling/ec2/userguide/schedule_time.html

NEW QUESTION 178

- (Exam Topic 1)

A company is deploying a third-party unit testing solution that is delivered as an Amazon EC2 Amazon Machine Image (AMI). All system configuration data is stored in Amazon DynamoDB. The testing results are stored in Amazon S3.

A minimum of three EC2 instances are required to operate the product. The company's testing team wants to use an additional three EC2 Instances when the Spot Instance prices are at a certain threshold. A SysOps administrator must implement a highly available solution that provides this functionality. Which solution will meet these requirements with the LEAST operational overhead?

- A. Define an Amazon EC2 Auto Scaling group by using a launch configuration
- B. Use the provided AMI in the launch configuration
- C. Configure three On-Demand Instances and three Spot Instance
- D. Configure a maximum Spot Instance price in the launch configuration.
- E. Define an Amazon EC2 Auto Scaling group by using a launch template
- F. Use the provided AMI in the launch template
- G. Configure three On-Demand Instances and three Spot Instance
- H. Configure a maximum Spot Instance price in the launch template.
- I. Define two Amazon EC2 Auto Scaling groups by using launch configuration
- J. Use the provided AMI in the launch configuration
- K. Configure three On-Demand Instances for one Auto Scaling group
- L. Configure three Spot Instances for the other Auto Scaling group
- M. Configure a maximum Spot Instance price in the launch configuration for the Auto Scaling group that has Spot Instances.
- N. Define two Amazon EC2 Auto Scaling groups by using launch template
- O. Use the provided AMI in the launch template
- P. Configure three On-Demand Instances for one Auto Scaling group
- Q. Configure three Spot Instances for the other Auto Scaling group
- R. Configure a maximum Spot Instance price in the launch template for the Auto Scaling group that has Spot Instances.

Answer: A

Explanation:

- > <https://docs.aws.amazon.com/autoscaling/ec2/userguide/LaunchTemplates.html>
- > <https://docs.aws.amazon.com/autoscaling/ec2/userguide/LaunchConfiguration.html>

NEW QUESTION 179

- (Exam Topic 1)

A company needs to restrict access to an Amazon S3 bucket to Amazon EC2 instances in a VPC only. All traffic must be over the AWS private network. What actions should the SysOps administrator take to meet these requirements?

- A. Create a VPC endpoint for the S3 bucket, and create an IAM policy that conditionally limits all S3 actions on the bucket to the VPC endpoint as the source.
- B. Create a VPC endpoint for the S3 bucket, and create an S3 bucket policy that conditionally limits all S3 actions on the bucket to the VPC endpoint as the source.
- C. Create a service-linked role for Amazon EC2 that allows the EC2 instances to interact directly with Amazon S3, and attach an IAM policy to the role that allows the EC2 instances full access to the S3 bucket.
- D. Create a NAT gateway in the VPC, and modify the VPC route table to route all traffic destined for Amazon S3 through the NAT gateway.

Answer: B

Explanation:

While IAM policy (letter A) also can be used, it does not enforce everyone. The only option that enforces everyone is policy configured directly in the bucket S3.

NEW QUESTION 182

- (Exam Topic 1)

A company hosts an application on an Amazon EC2 instance in a single AWS Region. The application requires support for non-HTTP TCP traffic and HTTP traffic. The company wants to deliver content with low latency by leveraging the AWS network. The company also wants to implement an Auto Scaling group with an Elastic Load Balancer.

How should a SysOps administrator meet these requirements?

- A. Create an Auto Scaling group with an Application Load Balancer (ALB). Add an Amazon CloudFront distribution with the ALB as the origin.
- B. Create an Auto Scaling group with an Application Load Balancer (ALB). Add an accelerator with AWS Global Accelerator with the ALB as an endpoint.
- C. Create an Auto Scaling group with a Network Load Balancer (NLB). Add an Amazon CloudFront distribution with the NLB as the origin.
- D. Create an Auto Scaling group with a Network Load Balancer (NLB). Add an accelerator with AWS Global Accelerator with the NLB as an endpoint.

Answer: D

Explanation:

AWS Global Accelerator and Amazon CloudFront are separate services that use the AWS global network and its edge locations around the world. CloudFront improves performance for both cacheable content (such as images and videos) and dynamic content (such as API acceleration and dynamic site delivery). Global Accelerator improves performance for a wide range of applications over TCP or UDP by proxying packets at the edge to applications running in one or more AWS Regions. Global Accelerator is a good fit for non-HTTP use cases, such as gaming (UDP), IoT (MQTT), or Voice over IP, as well as for HTTP use cases that specifically require static IP addresses or deterministic, fast regional failover. Both services integrate with AWS Shield for DDoS protection.

<https://medium.com/awesome-cloud/aws-difference-between-application-load-balancer-and-network-load-balancer> https://aws.amazon.com/global-accelerator/faqs/?nc1=h_ls

NEW QUESTION 183

- (Exam Topic 2)

You need to update an existing AWS CloudFormation stack. If needed, a copy to the CloudFormation template is available in an Amazon S3 bucket named cloudformation-bucket

- * 1. Use the us-east-2 Region for all resources.
- * 2. Unless specified below, use the default configuration settings.
- * 3. update the Amazon EC2 instance named DevInstance by making the following changes to the stack named 1700182:
 - * a) Change the EC2 instance type to us-east-t2.nano.
 - * b) Allow SSH to connect to the EC2 instance from the IP address range 192.168.100.0/30.
 - * c) Replace the instance profile IAM role with IamRoleB.
- * 4. Deploy the changes by updating the stack using the CFServiceR01e role.
- * 5. Edit the stack options to prevent accidental deletion.
- * 6. Using the output from the stack, enter the value of the ProdInstanceID in the text box below:

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Here are the steps to update an existing AWS CloudFormation stack:

- Log in to the AWS Management Console and navigate to the CloudFormation service in the us-east-2 Region.
- Find the existing stack named 1700182 and click on it.
- Click on the "Update" button.
- Choose "Replace current template" and upload the updated CloudFormation template from the Amazon S3 bucket named "cloudformation-bucket"
- In the "Parameter" section, update the EC2 instance type to us-east-t2.nano and add the IP address range 192.168.100.0/30 for SSH access.
- Replace the instance profile IAM role with IamRoleB.
- In the "Capabilities" section, check the checkbox for "IAM Resources"
- Choose the role CFServiceR01e and click on "Update Stack"
- Wait for the stack to be updated.
- Once the update is complete, navigate to the stack and click on the "Stack options" button, and select "Prevent updates to prevent accidental deletion"
- To get the value of the ProdInstanceID, navigate to the "Outputs" tab in the CloudFormation stack and find the key "ProdInstanceID". The value corresponding to it is the value that you need to enter in the text box below.

Note:

- You can use AWS CloudFormation to update an existing stack.

You can use the AWS CloudFormation service role to deploy updates.

You can refer to the AWS CloudFormation documentation for more information on how to update and manage stacks: <https://aws.amazon.com/cloudformation/>

NEW QUESTION 184

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

SOA-C02 Practice Exam Features:

- * SOA-C02 Questions and Answers Updated Frequently
- * SOA-C02 Practice Questions Verified by Expert Senior Certified Staff
- * SOA-C02 Most Realistic Questions that Guarantee you a Pass on Your First Try
- * SOA-C02 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The SOA-C02 Practice Test Here](#)