



Amazon-Web-Services

Exam Questions ANS-C01

AWS Certified Advanced Networking Specialty Exam

About ExamBible

Your Partner of IT Exam

Found in 1998

ExamBible is a company specialized on providing high quality IT exam practice study materials, especially Cisco CCNA, CCDA, CCNP, CCIE, Checkpoint CCSE, CompTIA A+, Network+ certification practice exams and so on. We guarantee that the candidates will not only pass any IT exam at the first attempt but also get profound understanding about the certificates they have got. There are so many alike companies in this industry, however, ExamBible has its unique advantages that other companies could not achieve.

Our Advances

* 99.9% Uptime

All examinations will be up to date.

* 24/7 Quality Support

We will provide service round the clock.

* 100% Pass Rate

Our guarantee that you will pass the exam.

* Unique Gurantee

If you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

NEW QUESTION 1

A company is using custom DNS servers that run BIND for name resolution in its VPCs. The VPCs are deployed across multiple AWS accounts that are part of the same organization in AWS Organizations. All the VPCs are connected to a transit gateway. The BIND servers are running in a central VPC and are configured to forward all queries for an on-premises DNS domain to DNS servers that are hosted in an on-premises data center. To ensure that all the VPCs use the custom DNS servers, a network engineer has configured a VPC DHCP options set in all the VPCs that specifies the custom DNS servers to be used as domain name servers.

Multiple development teams in the company want to use Amazon Elastic File System (Amazon EFS). A development team has created a new EFS file system but cannot mount the file system to one of its Amazon EC2 instances. The network engineer discovers that the EC2 instance cannot resolve the IP address for the EFS mount point `fs-33444567d.efs.us-east-1.amazonaws.com`. The network engineer needs to implement a solution so that development teams throughout the organization can mount EFS file systems.

Which combination of steps will meet these requirements? (Choose two.)

- A. Configure the BIND DNS servers in the central VPC to forward queries `forefs.us-east-1.amazonaws.com` to the Amazon provided DNS server (169.254.169.253).
- B. Create an Amazon Route 53 Resolver outbound endpoint in the central VP
- C. Update all the VPC DHCP options sets to use AmazonProvidedDNS for name resolution.
- D. Create an Amazon Route 53 Resolver inbound endpoint in the central VPC Update all the VPC DHCP options sets to use the Route 53 Resolver inbound endpoint in the central VPC for name resolution.
- E. Create an Amazon Route 53 Resolver rule to forward queries for the on-premises domain to the on-premises DNS server
- F. Share the rule with the organization by using AWS Resource Access Manager (AWS RAM). Associate the rule with all the VPCs.
- G. Create an Amazon Route 53 private hosted zone for the `efs.us-east-1.amazonaws.com` domain. Associate the private hosted zone with the VPC where the EC2 instance is deployed
- H. Create an A record for `fs-33444567d.efs.us-east-1.amazonaws.com` in the private hosted zone
- I. Configure the A record to return the mount target of the EFS mount point.

Answer: BD

Explanation:

Option B suggests using Amazon Route 53 Resolver outbound endpoint, which would replace the existing BIND DNS servers with the AmazonProvidedDNS for name resolution. However, the scenario specifically mentions that the company is using custom DNS servers that run BIND for name resolution in its VPCs, so this solution would not work. Option D suggests creating a Route 53 Resolver rule to forward queries for the on-premises domain to the on-premises DNS servers, which would not address the issue of resolving the EFS mount point. The problem is not with resolving queries for the on-premises domain, but rather with resolving the IP address for the EFS mount point.

NEW QUESTION 2

An IoT company sells hardware sensor modules that periodically send out temperature, humidity, pressure, and location data through the MQTT messaging protocol. The hardware sensor modules send this data to the company's on-premises MQTT brokers that run on Linux servers behind a load balancer. The hardware sensor modules have been hardcoded with public IP addresses to reach the brokers.

The company is growing and is acquiring customers across the world. The existing solution can no longer scale and is introducing additional latency because of the company's global presence. As a result, the company decides to migrate its entire infrastructure from on premises to the AWS Cloud. The company needs to migrate without reconfiguring the hardware sensor modules that are already deployed across the world. The solution also must minimize latency.

The company migrates the MQTT brokers to run on Amazon EC2 instances. What should the company do next to meet these requirements?

- A. Place the EC2 instances behind a Network Load Balancer (NLB). Configure TCP listener
- B. Use Bring Your Own IP (BYOIP) from the on-premises network with the NLB.
- C. Place the EC2 instances behind a Network Load Balancer (NLB). Configure TCP listener
- D. Create an AWS Global Accelerator accelerator in front of the NLB Use Bring Your Own IP (BYOIP) from the on-premises network with Global Accelerator.
- E. Place the EC2 instances behind an Application Load Balancer (ALB). Configure TCP listener
- F. Create an AWS Global Accelerator accelerator in front of the AL
- G. Use Bring Your Own IP (BYOIP) from the on-premises network with Global Accelerator
- H. Place the EC2 instances behind an Amazon CloudFront distributio
- I. Use Bring Your Own IP (BYOIP) from the on-premises network with CloudFront.

Answer: B

NEW QUESTION 3

A company has an AWS Site-to-Site VPN connection between its existing VPC and on-premises network. The default DHCP options set is associated with the VPC. The company has an application that is running on an Amazon Linux 2 Amazon EC2 instance in the VPC. The application must retrieve an Amazon RDS database secret that is stored in AWS Secrets Manager through a private VPC endpoint. An on-premises application provides internal RESTful API service that can be reached by URL (`https://api.example.internal`). Two on-premises Windows DNS servers provide internal DNS resolution.

The application on the EC2 instance needs to call the internal API service that is deployed in the on-premises environment. When the application on the EC2 instance attempts to call the internal API service by referring to the hostname that is assigned to the service, the call fails. When a network engineer tests the API service call from the same EC2 instance by using the API service's IP address, the call is successful.

What should the network engineer do to resolve this issue and prevent the same problem from affecting other resources in the VPC?

- A. Create a new DHCP options set that specifies the on-premises Windows DNS server
- B. Associate the new DHCP options set with the existing VP
- C. Reboot the Amazon Linux 2 EC2 instance.
- D. Create an Amazon Route 53 Resolver rule
- E. Associate the rule with the VP
- F. Configure the rule to forward DNS queries to the on-premises Windows DNS servers if the domain name matches `example.internal`.
- G. Modify the local host file in the Amazon Linux 2 EC2 instance in the VPC Map the service domain name (`api.example.internal`) to the IP address of the internal API service.
- H. Modify the local `/etc/resolv.conf` file in the Amazon Linux 2 EC2 instance in the VP
- I. Change the IP addresses of the name servers in the file to the IP addresses of the company's on-premises Windows DNS servers.

Answer: B

Explanation:

Creating an Amazon Route 53 Resolver rule and associating it with the VPC would enable forwarding of DNS queries for a specified domain name (example.internal) to a specified IP address (the on-premises Windows DNS servers)³. This would allow EC2 instances in the VPC to resolve the internal API service by using its hostname. Configuring the rule to forward DNS queries only if the domain name matches example.internal would also allow EC2 instances to use the Amazon Route 53 Resolver server for other DNS queries, such as those for AWS services through private VPC endpoints².

NEW QUESTION 4

A network engineer must develop an AWS CloudFormation template that can create a virtual private gateway, a customer gateway, a VPN connection, and static routes in a route table. During testing of the template, the network engineer notes that the CloudFormation template has encountered an error and is rolling back. What should the network engineer do to resolve the error?

- A. Change the order of resource creation in the CloudFormation template.
- B. Add the DependsOn attribute to the resource declaration for the virtual private gateway
- C. Specify the route table entry resource.
- D. Add a wait condition in the template to wait for the creation of the virtual private gateway.
- E. Add the DependsOn attribute to the resource declaration for the route table entry
- F. Specify the virtual private gateway resource.

Answer: D

NEW QUESTION 5

A company is planning to use Amazon S3 to archive financial data. The data is currently stored in an on-premises data center. The company uses AWS Direct Connect with a Direct Connect gateway and a transit gateway to connect to the on-premises data center. The data cannot be transported over the public internet and must be encrypted in transit. Which solution will meet these requirements?

- A. Create a Direct Connect public VIF
- B. Set up an IPsec VPN connection over the public VIF to access Amazon S3. Use HTTPS for communication.
- C. Create an IPsec VPN connection over the transit VIF
- D. Create a VPC and attach the VPC to the transit gateway
- E. In the VPC, provision an interface VPC endpoint for Amazon S3. Use HTTPS for communication.
- F. Create a VPC and attach the VPC to the transit gateway
- G. In the VPC, provision an interface VPC endpoint for Amazon S3. Use HTTPS for communication.
- H. Create a Direct Connect public VIF
- I. Set up an IPsec VPN connection over the public VIF to the transit gateway
- J. Create an attachment for Amazon S3. Use HTTPS for communication.

Answer: B

Explanation:

<https://docs.aws.amazon.com/vpn/latest/s2svpn/private-ip-dx.html>

An IPsec VPN connection over the transit VIF can encrypt traffic between the on-premises network and AWS without using public IP addresses or the internet². A VPC endpoint for Amazon S3 can enable private access to S3 buckets within the same region. HTTPS can provide additional encryption for communication.

NEW QUESTION 6

An insurance company is planning the migration of workloads from its on-premises data center to the AWS Cloud. The company requires end-to-end domain name resolution. Bi-directional DNS resolution between AWS and the existing on-premises environments must be established. The workloads will be migrated into multiple VPCs. The workloads also have dependencies on each other, and not all the workloads will be migrated at the same time. Which solution meets these requirements?

- A. Configure a private hosted zone for each application VPC, and create the requisite record
- B. Create a set of Amazon Route 53 Resolver inbound and outbound endpoints in an egress VPC
- C. Define Route 53 Resolver rules to forward requests for the on-premises domains to the on-premises DNS resolver
- D. Associate the application VPC private hosted zones with the egress VPC, and share the Route 53 Resolver rules with the application accounts by using AWS Resource Access Manager
- E. Configure the on-premises DNS servers to forward the cloud domains to the Route 53 inbound endpoints.
- F. Configure a public hosted zone for each application VPC, and create the requisite record
- G. Create a set of Amazon Route 53 Resolver inbound and outbound endpoints in an egress VPC
- H. Define Route 53 Resolver rules to forward requests for the on-premises domains to the on-premises DNS resolver
- I. Associate the application VPC private hosted zones with the egress VPC
- J. and share the Route 53 Resolver rules with the application accounts by using AWS Resource Access Manager
- K. Configure the on-premises DNS servers to forward the cloud domains to the Route 53 inbound endpoints.
- L. Configure a private hosted zone for each application VPC, and create the requisite record
- M. Create a set of Amazon Route 53 Resolver inbound and outbound endpoints in an egress VPC. Define Route 53 Resolver rules to forward requests for the on-premises domains to the on-premises DNS resolver
- N. Associate the application VPC private hosted zones with the egress VPC and share the Route 53 Resolver rules with the application accounts by using AWS Resource Access Manager

Answer: A

Explanation:

Creating a private hosted zone for each application VPC and creating the requisite records would enable end-to-end domain name resolution for the resources. Creating a set of Amazon Route 53 Resolver inbound and outbound endpoints in an egress VPC would enable bi-directional DNS resolution between AWS and the existing on-premises environments. Defining Route 53 Resolver rules to forward requests for the on-premises domains to the on-premises DNS resolver would enable DNS queries from AWS resources to on-premises resources. Associating the application VPC private hosted zones with the egress VPC and sharing the Route 53 Resolver rules with the application accounts by using AWS Resource Access Manager would enable DNS queries among different VPCs and accounts. Configuring the on-premises DNS servers to forward the cloud domains to the Route 53 inbound endpoints would enable DNS queries from on-premises resources to AWS resources¹.

NEW QUESTION 7

Your organization has a newly installed 1-Gbps AWS Direct Connect connection. You order the cross-connect from the Direct Connect location provider to the port

on your router in the same facility. To enable the use of your first virtual interface, your router must be configured appropriately.
What are the minimum requirements for your router?

- A. 1-Gbps Multi Mode Fiber Interface, 802.1Q VLAN, Peer IP Address, BGP Session with MD5.
- B. 1-Gbps Single Mode Fiber Interface, 802.1Q VLAN, Peer IP Address, BGP Session with MD5.
- C. IPsec Parameters, Pre-Shared key, Peer IP Address, BGP Session with MD5
- D. BGP Session with MD5, 802.1Q VLAN, Route-Map, Prefix List, IPsec encrypted GRE Tunnel

Answer: B

NEW QUESTION 8

A customer has set up multiple VPCs for Dev, Test, Prod, and Management. You need to set up AWS Direct Connect to enable data flow from on-premises to each VPC. The customer has monitoring software running in the Management VPC that collects metrics from the instances in all the other VPCs. Due to budget requirements, data transfer charges should be kept at minimum.

Which design should be recommended?

- A. Create a total of four private VIFs, one for each VPC owned by the customer, and route traffic between VPCs using the Direct Connect link.
- B. Create a private VIF to the Management VPC, and peer this VPC to all other VPCs.
- C. Create a private VIF to the Management VPC, and peer this VPC to all other VPCs, enable source/destination NAT in the Management VPC.
- D. Create a total of four private VIFs, and enable VPC peering between all VPCs.

Answer: D

Explanation:

- creating VPC peering is free of charge - traffic costs ~0.01€/GB for VPC peering (IN + OUT) and ~0.02€/GB for direct connect (OUT only). As the communication involved in monitoring will never have IN == OUT, then $0.01 * (IN + OUT)$ will always be lower than $0.02 * OUT$, ergo VPC peering will be cheaper

NEW QUESTION 9

A network engineer needs to update a company's hybrid network to support IPv6 for the upcoming release of a new application. The application is hosted in a VPC in the AWS Cloud. The company's current AWS infrastructure includes VPCs that are connected by a transit gateway. The transit gateway is connected to the on-premises network by AWS Direct Connect and AWS Site-to-Site VPN. The company's on-premises devices have been updated to support the new IPv6 requirements.

The company has enabled IPv6 for the existing VPC by assigning a new IPv6 CIDR block to the VPC and by assigning IPv6 to the subnets for dual-stack support. The company has launched new Amazon EC2 instances for the new application in the updated subnets.

When updating the hybrid network to support IPv6 the network engineer must avoid making any changes to the current infrastructure. The network engineer also must block direct access to the instances' new IPv6 addresses from the internet. However, the network engineer must allow outbound internet access from the instances.

What is the MOST operationally efficient solution that meets these requirements?

- A. Update the Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- B. Create a new VPN connection that supports IPv6 connectivity
- C. Add an egress-only internet gateway
- D. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices
- E. Update the Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- F. Update the existing VPN connection to support IPv6 connectivity
- G. Add an egress-only internet gateway
- H. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices.
- I. Create a Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- J. Create a new VPN connection that supports IPv6 connectivity
- K. Add an egress-only internet gateway
- L. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices.
- M. Create a Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- N. Create a new VPN connection that supports IPv6 connectivity
- O. Add a NAT gateway
- P. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices.

Answer: B

NEW QUESTION 10

A company uses a 1 Gbps AWS Direct Connect connection to connect its AWS environment to its on-premises data center. The connection provides employees with access to an application VPC that is hosted on AWS. Many remote employees use a company-provided VPN to connect to the data center. These employees are reporting slowness when they access the application during business hours. On-premises users have started to report similar slowness while they are in the office.

The company plans to build an additional application on AWS. On-site and remote employees will use the additional application. After the deployment of this additional application, the company will need 20% more bandwidth than the company currently uses. With the increased usage, the company wants to add resiliency to the AWS connectivity. A network engineer must review the current implementation and must make improvements within a limited budget.

What should the network engineer do to meet these requirements MOST cost-effectively?

- A. Set up a new 1 Gbps Direct Connect dedicated connection to accommodate the additional traffic load from remote employees and the additional application
- B. Create a link aggregation group (LAG).
- C. Deploy an AWS Site-to-Site VPN connection to the application VPC
- D. Configure the on-premises routing for the remote employees to connect to the Site-to-Site VPN connection.
- E. Deploy Amazon Workspaces into the application VPC and instruct the remote employees to connect to Workspaces.
- F. Replace the existing 1 Gbps Direct Connect connection with two new 2 Gbps Direct Connect hosted connections
- G. Create an AWS Client VPN endpoint in the application VPC
- H. Instruct the remote employees to connect to the Client VPN endpoint.

Answer: A

Explanation:

Setting up a new 1 Gbps Direct Connect dedicated connection to accommodate the additional trafficload from remote employees and the additional application would provide more bandwidth and lower latency than a VPN connection over the public internet1. Creating a link aggregation group (LAG) with the existing and new Direct Connect connections would provide resiliency and redundancy for the AWS connectivity2.

NEW QUESTION 10

A company is building its website on AWS in a single VPC. The VPC has public subnets and private subnets in two Availability Zones. The website has static content such as images. The company is using Amazon S3 to store the content.

The company has deployed a fleet of Amazon EC2 instances as web servers in a private subnet. The EC2 instances are in an Auto Scaling group behind an Application Load Balancer. The EC2 instances will serve traffic, and they must pull content from an S3 bucket to render the webpages. The company is using AWS Direct Connect with a public VIF for on-premises connectivity to the S3 bucket.

A network engineer notices that traffic between the EC2 instances and Amazon S3 is routing through a NAT gateway. As traffic increases, the company's costs are increasing. The network engineer needs to change the connectivity to reduce the NAT gateway costs that result from the traffic between the EC2 instances and Amazon S3.

Which solution will meet these requirements?

- A. Create a Direct Connect private VIF
- B. Migrate the traffic from the public VIF to the private VIF.
- C. Create an AWS Site-to-Site VPN tunnel over the existing public VIF.
- D. Implement interface VPC endpoints for Amazon S3. Update the VPC route table.
- E. Implement gateway VPC endpoints for Amazon S3. Update the VPC route table.

Answer: D

NEW QUESTION 14

An AWS CloudFormation template is being used to create a VPC peering connection between two existing operational VPCs, each belonging to a different AWS account. All necessary components in the 'Remote' (receiving) account are already in place.

The template below creates the VPC peering connection in the Originating account. It contains these components:

AWSTemplateFormatVersion: 2010-09-09 Parameters:

OriginatingVPCId: Type: String RemoteVPCId: Type: String

RemoteVPCAccountId: Type: String Resources:

newVPCPeeringConnection:

Type: 'AWS::EC2::VPCPeeringConnection'

Properties:

VpcId: !Ref OriginatingVPCId PeerVpcId: !Ref RemoteVPCId PeerOwnerId: !Ref RemoteVPCAccountId

Which additional AWS CloudFormation components are necessary in the Originating account to create an operational cross-account VPC peering connection with AWS CloudFormation? (Select two.)

- A. Resources:NewEC2SecurityGroup:Type: AWS::EC2::SecurityGroup
- B. Resources:NetworkInterfaceToRemoteVPC:Type: "AWS::EC2::NetworkInterface"
- C. Resources:newEC2Route:Type: AWS::EC2::Route
- D. Resources:VPCGatewayToRemoteVPC:Type: "AWS::EC2::VPCGatewayAttachment"
- E. Resources:newVPCPeeringConnection:Type: 'AWS::EC2::VPCPeeringConnection'PeerRoleArn: !Ref PeerRoleArn

Answer: CE

Explanation:

https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/AWS_EC2.html

NEW QUESTION 16

A company has created three VPCs: a production VPC, a nonproduction VPC, and a shared services VPC. The production VPC and the nonproduction VPC must each have communication with the shared services VPC. There must be no communication between the production VPC and the nonproduction VPC. A transit gateway is deployed to facilitate communication between VPCs.

Which route table configurations on the transit gateway will meet these requirements?

- A. Configure a route table with the production and nonproduction VPC attachments associated with propagated routes for only the shared services VPC
- B. Create an additional route table with only the shared services VPC attachment associated with propagated routes from the production and nonproduction VPCs.
- C. Configure a route table with the production and nonproduction VPC attachments associated with propagated routes for each VPC
- D. Create an additional route table with only the shared services VPC attachment associated with propagated routes from each VPC.
- E. Configure a route table with all the VPC attachments associated with propagated routes for only the shared services VPC
- F. Create an additional route table with only the shared services VPC attachment associated with propagated routes from the production and nonproduction VPCs.
- G. Configure a route table with the production and nonproduction VPC attachments associated with propagated routes disabled
- H. Create an additional route table with only the shared services VPC attachment associated with propagated routes from the production and nonproduction VPCs.

Answer: A

NEW QUESTION 20

A company is using a NAT gateway to allow internet connectivity for private subnets in a VPC in the us-west-2 Region. After a security audit, the company needs to remove the NAT gateway.

In the private subnets, the company has resources that use the unified Amazon CloudWatch agent. A network engineer must create a solution to ensure that the unified CloudWatch agent continues to work after the removal of the NAT gateway.

Which combination of steps should the network engineer take to meet these requirements? (Choose three.)

- A. Validate that private DNS is enabled on the VPC by setting the enableDnsHostnames VPC attribute and the enableDnsSupport VPC attribute to true.
- B. Create a new security group with an entry to allow outbound traffic that uses the TCP protocol on port 443 to destination 0.0.0.0/0
- C. Create a new security group with entries to allow inbound traffic that uses the TCP protocol on port 443 from the IP prefixes of the private subnets.
- D. Create the following interface VPC endpoints in the VPC: com.amazonaws.us-west-2.logs and com.amazonaws.us-west-2.monitoring
- E. Associate the new security group with the endpoint network interfaces.
- F. Create the following interface VPC endpoint in the VPC: com.amazonaws.us-west-2.cloudwatch.Associate the new security group with the endpoint network

interfaces.

G. Associate the VPC endpoint or endpoints with route tables that the private subnets use.

Answer: BDF

NEW QUESTION 25

A company is using an AWS Site-to-Site VPN connection from the company's on-premises data center to a virtual private gateway in the AWS Cloud. Because of congestion, the company is experiencing availability and performance issues as traffic travels across the internet before the traffic reaches AWS. A network engineer must reduce these issues for the connection as quickly as possible with minimum administration effort.

Which solution will meet these requirements?

- A. Edit the existing Site-to-Site VPN connection by enabling acceleration
- B. Stop and start the VPN service on the customer gateway for the new setting to take effect.
- C. Configure a transit gateway in the same AWS Region as the existing virtual private gateway
- D. Create a new accelerated Site-to-Site VPN connection
- E. Connect the new connection to the transit gateway by using a VPN attachment
- F. Update the customer gateway device to use the new Site-to-Site VPN connection
- G. Delete the existing Site-to-Site VPN connection
- H. Create a new accelerated Site-to-Site VPN connection
- I. Connect the new Site-to-Site VPN connection to the existing virtual private gateway
- J. Update the customer gateway device to use the new Site-to-Site VPN connection
- K. Delete the existing Site-to-Site VPN connection.
- L. Create a new AWS Direct Connect connection with a private VIF between the on-premises data center and the AWS Cloud
- M. Update the customer gateway device to use the new Direct Connect connection
- N. Delete the existing Site-to-Site VPN connection.

Answer: B

NEW QUESTION 30

A company has two on-premises data center locations. There is a company-managed router at each data center. Each data center has a dedicated AWS Direct Connect connection to a Direct Connect gateway through a private virtual interface. The router for the first location is advertising 110 routes to the Direct Connect gateway by using BGP, and the router for the second location is advertising 60 routes to the Direct Connect gateway by using BGP. The Direct Connect gateway is attached to a company VPC through a virtual private gateway.

A network engineer receives reports that resources in the VPC are not reachable from various locations in either data center. The network engineer checks the VPC route table and sees that the routes from the first data center location are not being populated into the route table. The network engineer must resolve this issue in the most operationally efficient manner.

What should the network engineer do to meet these requirements?

- A. Remove the Direct Connect gateway, and create a new private virtual interface from each company router to the virtual private gateway of the VPC.
- B. Change the router configurations to summarize the advertised routes.
- C. Open a support ticket to increase the quota on advertised routes to the VPC route table.
- D. Create an AWS Transit Gateway
- E. Attach the transit gateway to the VPC, and connect the Direct Connect gateway to the transit gateway.

Answer: B

Explanation:

"If you advertise more than 100 routes each for IPv4 and IPv6 over the BGP session, the BGP session will go into an idle state with the BGP session DOWN." <https://docs.aws.amazon.com/directconnect/latest/UserGuide/limits.html>

NEW QUESTION 32

A company has deployed its AWS environment in a single AWS Region. The environment consists of a few hundred application VPCs, a shared services VPC, and a VPN connection to the company's on-premises environment. A network engineer needs to implement a transit gateway with the following requirements:

- Application VPCs must be isolated from each other.
 - Bidirectional communication must be allowed between the application VPCs and the on-premises network.
 - Bidirectional communication must be allowed between the application VPCs and the shared services VPC. The network engineer creates the transit gateway with options disabled for default route table association and default route table propagation. The network engineer also creates the VPN attachment for the on-premises network and creates the VPC attachments for the application VPCs and the shared services VPC.
- The network engineer must meet all the requirements for the transit gateway by designing a solution that needs the least number of transit gateway route tables. Which combination of actions should the network engineer perform to accomplish this goal? (Choose two.)

- A. Configure a separate transit gateway route table for on-premise
- B. Associate the VPN attachment with this transit gateway route table
- C. Propagate all application VPC attachments to this transit gateway route table.
- D. Configure a separate transit gateway route table for each application VPC
- E. Associate each application VPC attachment with its respective transit gateway route table
- F. Propagate the shared services VPC attachment and the VPN attachment to this transit gateway route table.
- G. Configure a separate transit gateway route table for all application VPCs
- H. Associate all application VPCs with this transit gateway route table
- I. Propagate the shared services VPC attachment and the VPN attachment to this transit gateway route table.
- J. Configure a separate transit gateway route table for the shared services VPC
- K. Associate the shared services VPC attachment with this transit gateway route table
- L. Propagate all application VPC attachments to this transit gateway route table.
- M. Configure a separate transit gateway route table for on-premises and the shared services VPC
- N. Associate the VPN attachment and the shared services VPC attachment with this transit gateway route table
- O. Propagate all application VPC attachments to this transit gateway route table.

Answer: BD

NEW QUESTION 34

A company has a global network and is using transit gateways to connect AWS Regions together. The company finds that two Amazon EC2 instances in different Regions are unable to communicate with each other. A network engineer needs to troubleshoot this connectivity issue. What should the network engineer do to meet this requirement?

- A. Use AWS Network Manager Route Analyzer to analyze routes in the transit gateway route tables and in the VPC route table
- B. Use VPC flow logs to analyze the IP traffic that security group rules and network ACL rules accept or reject in the VPC.
- C. Use AWS Network Manager Route Analyzer to analyze routes in the transit gateway route tables. Verify that the VPC route tables are correct
- D. Use AWS Firewall Manager to analyze the IP traffic that security group rules and network ACL rules accept or reject in the VPC.
- E. Use AWS Network Manager Route Analyzer to analyze routes in the transit gateway route tables. Verify that the VPC route tables are correct
- F. Use VPC flow logs to analyze the IP traffic that security group rules and network ACL rules accept or reject in the VPC.
- G. Use VPC Reachability Analyzer to analyze routes in the transit gateway route table
- H. Verify that the VPC route tables are correct
- I. Use VPC flow logs to analyze the IP traffic that security group rules and network ACL rules accept or reject in the VPC.

Answer: C

Explanation:

Using AWS Network Manager Route Analyzer to analyze routes in the transit gateway route tables would enable identification of routing issues between VPCs and transit gateways¹. Verifying that the VPC route tables are correct would enable identification of routing issues within a VPC. Using VPC flow logs to analyze the IP traffic that security group rules and network ACL rules accept or reject in the VPC would enable identification of traffic filtering issues within a VPC². Additionally, using VPC Reachability Analyzer to analyze routes in the transit gateway route tables would enable identification of routing issues between transit gateways in different Regions. VPC Reachability Analyzer is a configuration analysis tool that enables connectivity testing between a source resource and a destination resource in your VPCs.

NEW QUESTION 38

A company is deploying a new application in the AWS Cloud. The company wants a highly available web server that will sit behind an Elastic Load Balancer. The load balancer will route requests to multiple target groups based on the URL in the request. All traffic must use HTTPS. TLS processing must be offloaded to the load balancer. The web server must know the user's IP address so that the company can keep accurate logs for security purposes. Which solution will meet these requirements?

- A. Deploy an Application Load Balancer with an HTTPS listener
- B. Use path-based routing rules to forward the traffic to the correct target group
- C. Include the X-Forwarded-For request header with traffic to the targets.
- D. Deploy an Application Load Balancer with an HTTPS listener for each domain
- E. Use host-based routing rules to forward the traffic to the correct target group for each domain
- F. Include the X-Forwarded-For request header with traffic to the targets.
- G. Deploy a Network Load Balancer with a TLS listener
- H. Use path-based routing rules to forward the traffic to the correct target group
- I. Configure client IP address preservation for traffic to the targets.
- J. Deploy a Network Load Balancer with a TLS listener for each domain
- K. Use host-based routing rules to forward the traffic to the correct target group for each domain
- L. Configure client IP address preservation for traffic to the targets.

Answer: A

Explanation:

An Application Load Balancer (ALB) can be used to route traffic to multiple target groups based on the URL in the request. The ALB can be configured with an HTTPS listener to ensure all traffic uses HTTPS. TLS processing can be offloaded to the ALB, which reduces the load on the web server. Path-based routing rules can be used to route traffic to the correct target group based on the URL in the request. The X-Forwarded-For request header can be included with traffic to the targets, which will allow the web server to know the user's IP address and keep accurate logs for security purposes.

NEW QUESTION 43

A company's network engineer builds and tests network designs for VPCs in a development account. The company needs to monitor the changes that are made to network resources and must ensure strict compliance with network security policies. The company also needs access to the historical configurations of network resources.

Which solution will meet these requirements?

- A. Create an Amazon EventBridge (Amazon CloudWatch Events) rule with a custom pattern to monitor the account for change
- B. Configure the rule to invoke an AWS Lambda function to identify noncompliant resource
- C. Update an Amazon DynamoDB table with the changes that are identified.
- D. Create custom metrics from Amazon CloudWatch log
- E. Use the metrics to invoke an AWS Lambda function to identify noncompliant resource
- F. Update an Amazon DynamoDB table with the changes that are identified.
- G. Record the current state of network resources by using AWS Config
- H. Create rules that reflect the desired configuration setting
- I. Set remediation for noncompliant resources.
- J. Record the current state of network resources by using AWS Systems Manager Inventory
- K. Use Systems Manager State Manager to enforce the desired configuration settings and to carry out remediation for noncompliant resources.

Answer: C

Explanation:

Recording the current state of network resources by using AWS Config would enable auditing and assessment of resource configurations and compliance³. Creating rules that reflect the desired configuration settings would enable evaluation of whether the network resources comply with network security policies³. Setting remediation for noncompliant resources would enable automatic correction of undesired configurations³.

NEW QUESTION 44

A company uses a 4 Gbps AWS Direct Connect dedicated connection with a link aggregation group (LAG) bundle to connect to five VPCs that are deployed in the us-east-1 Region. Each VPC serves a different business unit and uses its own private VIF for connectivity to the on-premises environment. Users are reporting

slowness when they access resources that are hosted on AWS.

A network engineer finds that there are sudden increases in throughput and that the Direct Connect connection becomes saturated at the same time for about an hour each business day. The company wants to know which business unit is causing the sudden increase in throughput. The network engineer must find out this information and implement a solution to resolve the problem.

Which solution will meet these requirements?

- A. Review the Amazon CloudWatch metrics for VirtualInterfaceBpsEgress and VirtualInterfaceBpsIngress to determine which VIF is sending the highest throughput during the period in which slowness is observed
- B. Create a new 10 Gbps dedicated connection
- C. Shift traffic from the existing dedicated connection to the new dedicated connection.
- D. Review the Amazon CloudWatch metrics for VirtualInterfaceBpsEgress and VirtualInterfaceBpsIngress to determine which VIF is sending the highest throughput during the period in which slowness is observed
- E. Upgrade the bandwidth of the existing dedicated connection to 10 Gbps.
- F. Review the Amazon CloudWatch metrics for ConnectionBpsIngress and ConnectionPpsEgress to determine which VIF is sending the highest throughput during the period in which slowness is observed
- G. Upgrade the existing dedicated connection to a 5 Gbps hosted connection.
- H. Review the Amazon CloudWatch metrics for ConnectionBpsIngress and ConnectionPpsEgress to determine which VIF is sending the highest throughput during the period in which slowness is observed. Create a new 10 Gbps dedicated connection
- I. Shift traffic from the existing dedicated connection to the new dedicated connection.

Answer: A

Explanation:

To meet the requirements of finding out which business unit is causing the sudden increase in throughput and resolving the problem, the network engineer should review the Amazon CloudWatch metrics for VirtualInterfaceBpsEgress and VirtualInterfaceBpsIngress to determine which VIF is sending the highest throughput during the period in which slowness is observed (Option B). After identifying the VIF that is causing the issue, they can upgrade the bandwidth of the existing dedicated connection to 10 Gbps to resolve the problem (Option B).

NEW QUESTION 45

A company is developing an application in which IoT devices will report measurements to the AWS Cloud. The application will have millions of end users. The company observes that the IoT devices cannot support DNS resolution. The company needs to implement an Amazon EC2 Auto Scaling solution so that the IoT devices can connect to an application endpoint without using DNS.

Which solution will meet these requirements MOST cost-effectively?

- A. Use an Application Load Balancer (ALB)-type target group for a Network Load Balancer (NLB). Create an EC2 Auto Scaling group
- B. Attach the Auto Scaling group to the ALB
- C. Set up the IoT devices to connect to the IP addresses of the NLB.
- D. Use an AWS Global Accelerator accelerator with an Application Load Balancer (ALB) endpoint
- E. Create an EC2 Auto Scaling group
- F. Attach the Auto Scaling group to the ALB. Set up the IoT devices to connect to the IP addresses of the accelerator.
- G. Use a Network Load Balancer (NLB). Create an EC2 Auto Scaling group
- H. Attach the Auto Scaling group to the NLB
- I. Set up the IoT devices to connect to the IP addresses of the NLB.
- J. Use an AWS Global Accelerator accelerator with a Network Load Balancer (NLB) endpoint
- K. Create an EC2 Auto Scaling group
- L. Attach the Auto Scaling group to the NLB
- M. Set up the IoT devices to connect to the IP addresses of the accelerator.

Answer: D

Explanation:

AWS Global Accelerator can provide static IP addresses that the IoT devices can connect to without using DNS. It can also route traffic over the AWS global network and improve performance and availability for the IoT devices. An NLB can provide end-to-end encryption for HTTPS traffic by using TLS as a target group protocol and terminating SSL connections at the load balancer level. An NLB can also support session affinity (sticky sessions) with TCP connections.

NEW QUESTION 46

A company's AWS architecture consists of several VPCs. The VPCs include a shared services VPC and several application VPCs. The company has established network connectivity from all VPCs to the on-premises DNS servers.

Applications that are deployed in the application VPCs must be able to resolve DNS for internally hosted domains on premises. The applications also must be able to resolve local VPC domain names and domains that are hosted in Amazon Route 53 private hosted zones.

What should a network engineer do to meet these requirements?

- A. Create a new Route 53 Resolver inbound endpoint in the shared services VPC
- B. Create forwarding rules for the on-premises hosted domain
- C. Associate the rules with the new Resolver endpoint and each application VPC
- D. Update each application VPC's DHCP configuration to point DNS resolution to the new Resolver endpoint.
- E. Create a new Route 53 Resolver outbound endpoint in the shared services VPC
- F. Create forwarding rules for the on-premises hosted domain
- G. Associate the rules with the new Resolver endpoint and each application VPC.
- H. Create a new Route 53 Resolver outbound endpoint in the shared services VPC. Create forwarding rules for the on-premises hosted domain
- I. Associate the rules with the new Resolver endpoint and each application VPC. Update each application VPC's DHCP configuration to point DNS resolution to the new Resolver endpoint.
- J. Create a new Route 53 Resolver inbound endpoint in the shared services VPC
- K. Create forwarding rules for the on-premises hosted domain
- L. Associate the rules with the new Resolver endpoint and each application VPC.

Answer: B

Explanation:

Creating a new Route 53 Resolver outbound endpoint in the shared services VPC would enable forwarding of DNS queries from the VPC to on-premises.

Creating forwarding rules for the on-premises hosted domains would enable specifying which domain names are forwarded to the on-premises DNS servers2. Associating the rules with the new Resolver endpoint and each application VPC would enable applying the rules to the VPCs2. This solution would not affect the default DNS resolution behavior of Route 53 Resolver for local VPC domain names and domains that are hosted in Route 53 private hosted zones3.

NEW QUESTION 48

A security team is performing an audit of a company's AWS deployment. The security team is concerned that two applications might be accessing resources that should be blocked by network ACLs and security groups. The applications are deployed across two Amazon Elastic Kubernetes Service (Amazon EKS) clusters that use the Amazon VPC Container Network Interface (CNI) plugin for Kubernetes. The clusters are in separate subnets within the same VPC and have a Cluster Autoscaler configured.

The security team needs to determine which POD IP addresses are communicating with which services throughout the VPC. The security team wants to limit the number of flow logs and wants to examine the traffic from only the two applications.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create VPC flow logs in the default forma
- B. Create a filter to gather flow logs only from the EKS nodes.Include the srcaddr field and the dstaddr field in the flow logs.
- C. Create VPC flow logs in a custom forma
- D. Set the EKS nodes as the resource Include the pkt-srcaddr field and the pkt-dstaddr field in the flow logs.
- E. Create VPC flow logs in a custom forma
- F. Set the application subnets as resource
- G. Include the pkt-srcaddr field and the pkt-dstaddr field in the flow logs.
- H. Create VPC flow logs in a custom forma
- I. Create a filter to gather flow logs only from the EKS nodes.Include the pkt-srcaddr field and the pkt-dstaddr field in the flow logs.

Answer: D

NEW QUESTION 52

An Australian ecommerce company hosts all of its services in the AWS Cloud and wants to expand its customer base to the United States (US). The company is targeting the western US for the expansion.

The company's existing AWS architecture consists of four AWS accounts with multiple VPCs deployed in the ap-southeast-2 Region. All VPCs are attached to a transit gateway in ap-southeast-2. There are dedicated VPCs for each application service. The company also has VPCs for centralized security features such as proxies, firewalls, and logging.

The company plans to duplicate the infrastructure from ap-southeast-2 to the us-west-1 Region. A network engineer must establish connectivity between the various applications in the two Regions. The solution must maximize bandwidth, minimize latency and minimize operational overhead.

Which solution will meet these requirements?

- A. Create VPN attachments between the two transit gateway
- B. Configure the VPN attachments to use BGP routing between the two transit gateways.
- C. Peer the transit gateways in each Regio
- D. Configure routing between the two transit gateways for each Region's IP addresses.
- E. Create a VPN server in a VPC in each Regio
- F. Update the routing to point to the VPN servers for the IP addresses in alternate Regions.
- G. Attach the VPCs in us-west-1 to the transit gateway in ap-southeast-2.

Answer: B

Explanation:

Peering the transit gateways in each region would establish a private network connection between the two regions, allowing the company to route traffic between the VPCs in different regions without going over the public internet. This would help minimize latency and maximize bandwidth while reducing the operational overhead of managing multiple VPN connections.

NEW QUESTION 57

A retail company is running its service on AWS. The company's architecture includes Application Load Balancers (ALBs) in public subnets. The ALB target groups are configured to send traffic to backend Amazon EC2 instances in private subnets. These backend EC2 instances can call externally hosted services over the internet by using a NAT gateway.

The company has noticed in its billing that NAT gateway usage has increased significantly. A network engineer needs to find out the source of this increased usage.

Which options can the network engineer use to investigate the traffic through the NAT gateway? (Choose two.)

- A. Enable VPC flow logs on the NAT gateway's elastic network interfac
- B. Publish the logs to a log group in Amazon CloudWatch Log
- C. Use CloudWatch Logs Insights to query and analyze the logs.
- D. Enable NAT gateway access log
- E. Publish the logs to a log group in Amazon CloudWatch Log
- F. Use CloudWatch Logs Insights to query and analyze the logs.
- G. Configure Traffic Mirroring on the NAT gateway's elastic network interfac
- H. Send the traffic to an additional EC2 instanc
- I. Use tools such as tcpdump and Wireshark to query and analyze the mirrored traffic.
- J. Enable VPC flow logs on the NAT gateway's elastic network interfac
- K. Publish the logs to an Amazon S3 bucke
- L. Create a custom table for the S3 bucket in Amazon Athena to describe the log structur
- M. Use Athena to query and analyze the logs.
- N. Enable NAT gateway access log
- O. Publish the logs to an Amazon S3 bucke
- P. Create a custom table for the S3 bucket in Amazon Athena to describe the log structur
- Q. Use Athena to query and analyze the logs.

Answer: AD

Explanation:

To investigate the increased usage of a NAT gateway in a VPC architecture with ALBs and backend EC2 instances, a network engineer can use the following

options:

➤ Enable VPC flow logs on the NAT gateway's elastic network interface and publish the logs to a log group in Amazon CloudWatch Logs. Use CloudWatch Logs Insights to query and analyze the logs.

(Option A)

➤ Enable VPC flow logs on the NAT gateway's elastic network interface and publish the logs to an Amazon S3 bucket. Create a custom table for the S3 bucket in Amazon Athena to describe the log structure and use Athena to query and analyze the logs. (Option D)

These options allow for detailed analysis of traffic through the NAT gateway to identify the source of increased usage.

NEW QUESTION 61

An ecommerce company is hosting a web application on Amazon EC2 instances to handle continuously changing customer demand. The EC2 instances are part of an Auto Scaling group. The company wants to implement a solution to distribute traffic from customers to the EC2 instances. The company must encrypt all traffic at all stages between the customers and the application servers. No decryption at intermediate points is allowed.

Which solution will meet these requirements?

- A. Create an Application Load Balancer (ALB). Add an HTTPS listener to the AL
- B. Configure the Auto Scaling group to register instances with the ALB's target group.
- C. Create an Amazon CloudFront distributio
- D. Configure the distribution with a custom SSL/TLS certificat
- E. Set the Auto Scaling group as the distribution's origin.
- F. Create a Network Load Balancer (NLB). Add a TCP listener to the NL
- G. Configure the Auto Scaling group to register instances with the NLB's target group.
- H. Create a Gateway Load Balancer (GLB). Configure the Auto Scaling group to register instances with the GLB's target group.

Answer: C

Explanation:

To distribute traffic from customers to EC2 instances in an Auto Scaling group and encrypt all traffic at all stages between the customers and the application servers without decryption at intermediate points, the company should create a Network Load Balancer (NLB) with a TCP listener and configure the Auto Scaling group to register instances with the NLB's target group (Option C). This solution allows for end-to-end encryption of traffic without decryption at intermediate points.

NEW QUESTION 62

.....

Relate Links

100% Pass Your ANS-C01 Exam with ExamBible Prep Materials

<https://www.exambible.com/ANS-C01-exam/>

Contact us

We are proud of our high-quality customer service, which serves you around the clock 24/7.

Viste - <https://www.exambible.com/>